

285. Inorder Successor in BST

[Add to List](#)[Question](#)[Editorial Solution](#)[My Submissions \(/problems/inorder-successor-in-bst/submissions/\)](/problems/inorder-successor-in-bst/submissions/)

Total Accepted: **24054** Total Submissions: **66522** Difficulty: **Medium** Contributors: **Admin**

Given a binary search tree and a node in it, find the in-order successor of that node in the BST.

Note: If the given node has no in-order successor in the tree, return `null`.

[Hide Company Tags](#)[Pocket Gems \(/company/pocket-gems/\)](/company/pocket-gems/)[Microsoft \(/company/microsoft/\)](/company/microsoft/)[Facebook \(/company/facebook/\)](/company/facebook/)[Hide Tags](#)[Tree \(/tag/tree/\)](/tag/tree/)[Hide Similar Problems](#)[\(M\) Binary Tree Inorder Traversal \(/problems/binary-tree-inorder-traversal/\)](/problems/binary-tree-inorder-traversal/)[\(M\) Binary Search Tree Iterator \(/problems/binary-search-tree-iterator/\)](/problems/binary-search-tree-iterator/)

Have you met this question in a real interview?

[Discuss \(https://discuss.leetcode.com/category/355\)](https://discuss.leetcode.com/category/355)[Top Solutions](#)[Pick One \(/problems/random-one-question/\)](/problems/random-one-question/)[C++](#)

```
1 /**
2  * Definition for a binary tree node.
3  * struct TreeNode {
4  *     int val;
5  *     TreeNode *left;
6  *     TreeNode *right;
7  *     TreeNode(int x) : val(x), left(NULL), right(NULL) {}
8  * };
9  */
10
11 //works for general Binary Tree not restricted to BST
12 class Solution {
13 public:
14     TreeNode* inorderSuccessor(TreeNode* root, TreeNode* p) {
15         if(p==NULL) return NULL;
16         if(p->right!=NULL) {
17             TreeNode* tmp = p->right;
18             while(tmp->left!=NULL) tmp=tmp->left;
19             return tmp;
20         }
21         TreeNode* res = helper(root,p);
22         if(res==p)
23             return NULL;
24         else
25             return res;
26     }
27 private:
28     TreeNode* helper(TreeNode* root, TreeNode* p){
29         if(root==NULL) return NULL;
30         if(root==p) return p;
31
32         TreeNode* left = helper(root->left,p);
33         if(left==p) return root;
34         if(left!=NULL) return left;
35         TreeNode* right = helper(root->right,p);
36         if(right==p) return p;
37         if(right!=NULL) return right;
38         return NULL;
39     }
40 };
```

[Submit Solution](#)

[Frequently Asked Questions \(/faq/\)](/faq/) | [Terms of Service \(/tos/\)](/tos/)

[Privacy](#)[✉ Send Feedback \(mailto:admin@leetcode.com?subject=Feedback\)](mailto:admin@leetcode.com?subject=Feedback)

Copyright © 2017 LeetCode

[Notes](#)