

78. Subsets

[Add to List ▾](#)[Question](#)[Editorial Solution](#)[My Submissions \(/problems/subsets/submissions/\)](#)

Total Accepted: **138542** Total Submissions: **374399** Difficulty: **Medium** Contributors: **Admin**

Given a set of **distinct** integers, *nums*, return all possible subsets.

Note: The solution set must not contain duplicate subsets.

For example,

If *nums* = [1,2,3] , a solution is:

```
[
  [3],
  [1],
  [2],
  [1,2,3],
  [1,3],
  [2,3],
  [1,2],
  []
]
```

[Notes](#)

Hide Company Tags [Amazon \(/company/amazon/\)](#) [Uber \(/company/uber/\)](#) [Facebook \(/company/facebook/\)](#)

Hide Tags [Array \(/tag/array/\)](#) [Backtracking \(/tag/backtracking/\)](#) [Bit Manipulation \(/tag/bit-manipulation/\)](#)

Hide Similar Problems [\(M\) Generalized Abbreviation \(/problems/generalized-abbreviation/\)](#)

Have you met this question in a real interview?

[Discuss \(https://discuss.leetcode.com/category/86\)](https://discuss.leetcode.com/category/86)[Top Solutions](#)[Pick One \(/problems/random-one-question/\)](#)

C++ ▾



```
1 class Solution {
2 public:
3     vector<vector<int>> subsets(vector<int>& nums) {
4         sort(nums.begin(),nums.end());
5
6         vector<int> s;
7         vector<vector<int>> result(1,s);
8         int n = nums.size(),j;
9
10        for(int i = 0 ; i+1<1<n;i++)
11        {
12            for(j = 0; (i>>j)&1;j++) s.pop_back();
13            s.push_back(nums[n - j - 1]);
14            result.push_back(s);
15        }
16
17        return result;
18    }
19 };
```

Custom Testcase ☐

Contribute Testcase

[Run Code](#)[Submit Solution](#)

[Frequently Asked Questions \(/faq/\)](#) | [Terms of Service \(/tos/\)](#)

[Privacy](#)

Copyright © 2017 LeetCode