


## 235. Lowest Common Ancestor of a Binary Search Tree

[Add to List](#)[Question](#)[Editorial Solution](#)[My Submissions \(/problems/lowest-common-ancestor-of-a-binary-search-tree/submissions/\)](/problems/lowest-common-ancestor-of-a-binary-search-tree/submissions/)

Total Accepted: **116088** Total Submissions: **304225** Difficulty: **Easy** Contributors: **Admin**

Given a binary search tree (BST), find the lowest common ancestor (LCA) of two given nodes in the BST.

According to the definition of LCA on Wikipedia ([https://en.wikipedia.org/wiki/Lowest\\_common\\_ancestor](https://en.wikipedia.org/wiki/Lowest_common_ancestor)): “The lowest common ancestor is defined between two nodes  $v$  and  $w$  as the lowest node in  $T$  that has both  $v$  and  $w$  as descendants (where we allow **a node to be a descendant of itself**).”



For example, the lowest common ancestor (LCA) of nodes 2 and 8 is 6. Another example is LCA of nodes 2 and 4 is 2, since a node can be a descendant of itself according to the LCA definition.

[Hide Company Tags](#)[Amazon \(/company/amazon/\)](/company/amazon/)[Microsoft \(/company/microsoft/\)](/company/microsoft/)[Facebook \(/company/facebook/\)](/company/facebook/)[Twitter \(/company/twitter/\)](/company/twitter/)[Hide Tags](#)[Tree \(/tag/tree/\)](/tag/tree/)[Hide Similar Problems](#)[\(M\) Lowest Common Ancestor of a Binary Tree \(/problems/lowest-common-ancestor-of-a-binary-tree/\)](/problems/lowest-common-ancestor-of-a-binary-tree/)

Have you met this question in a real interview?

[Discuss \(https://discuss.leetcode.com/category/291\)](https://discuss.leetcode.com/category/291)[Top Solutions](#)[Pick One \(/problems/random-one-question/\)](/problems/random-one-question/)[Notes](#)[C++](#)

```
1 /**
2  * Definition for a binary tree node.
3  * struct TreeNode {
4  *     int val;
5  *     TreeNode *left;
6  *     TreeNode *right;
7  *     TreeNode(int x) : val(x), left(NULL), right(NULL) {}
8  * };
9  */
10 class Solution {
11 public:
12     TreeNode* lowestCommonAncestor(TreeNode* root, TreeNode* p, TreeNode* q) {
13         if(p==NULL) return q;
14         if(q==NULL) return p;
15         while(root!=NULL&&root!=p&&root!=q){
16             if(root->val>p->val&&root->val>q->val) root = root->left;
17             else if(root->val<p->val&&root->val<q->val) root = root->right;
18             else break;
19         }
20         return root;
21     }
22 };
```

[Submit Solution](#)[Frequently Asked Questions \(/faq/\)](/faq/) | [Terms of Service \(/tos/\)](/tos/)[Privacy](#)

Copyright © 2017 LeetCode