

19. Remove Nth Node From End of List

[Add to List](#)[Question](#)[Editorial Solution](#)[My Submissions \(/problems/remove-nth-node-from-end-of-list/submissions/\)](/problems/remove-nth-node-from-end-of-list/submissions/)

Total Accepted: **155329** Total Submissions: **482413** Difficulty: **Easy** Contributors: **Admin**

Given a linked list, remove the n^{th} node from the end of list and return its head.

For example,

Given linked list: **1->2->3->4->5**, and $n = 2$.

After removing the second node from the end, the linked list becomes **1->2->3->5**.

Note:

Given n will always be valid.

Try to do this in one pass.

[Subscribe \(/subscribe/\)](/subscribe/) to see which companies asked this question

[Show Tags](#)

Have you met this question in a real interview?

[Discuss \(https://discuss.leetcode.com/category/27\)](https://discuss.leetcode.com/category/27)[Top Solutions](#)[Pick One \(/problems/random-one-question/\)](/problems/random-one-question/)

C++



```
1 /**
2  * Definition for singly-linked list.
3  * struct ListNode {
4  *     int val;
5  *     ListNode *next;
6  *     ListNode(int x) : val(x), next(NULL) {}
7  * };
8  */
9 class Solution {
10 public:
11     ListNode* removeNthFromEnd(ListNode* head, int n) {
12         int length = 0;
13         if(head==NULL) return NULL;
14         ListNode* slow = new ListNode(0);
15         ListNode* prehead = slow;
16         slow->next = head;
17         ListNode* fast = head;
18         int i=0;
19         while(i<n&&fast!=NULL){
20             fast=fast->next;
21             i++;
22         }
23         if(i<n)
24             return head;
25         while(fast!=NULL){
26             slow = slow->next;
27             fast = fast->next;
28         }
29         slow->next = slow->next->next;
30         return prehead->next;
31     }
32 }
33 ;
```

Custom Testcase ☐

Contribute Testcase

[Run Code](#)[Submit Solution](#)