

46. Permutations

[Add to List ▾](#)[Question](#)[Editorial Solution](#)[My Submissions \(/problems/permutations/submissions/\)](#)

Total Accepted: **142717** Total Submissions: **350690** Difficulty: **Medium** Contributors: **Admin**

Given a collection of **distinct** numbers, return all possible permutations.

For example,

[1,2,3] have the following permutations:

```
[
  [1,2,3],
  [1,3,2],
  [2,1,3],
  [2,3,1],
  [3,1,2],
  [3,2,1]
]
```

[Hide Company Tags](#)[LinkedIn \(/company/linkedin/\)](#)[Microsoft \(/company/microsoft/\)](#)[Hide Tags](#)[Backtracking \(/tag/backtracking/\)](#)[Hide Similar Problems](#)[\(M\) Next Permutation \(/problems/next-permutation/\)](#)[\(M\) Permutations II \(/problems/permutations-ii/\)](#)[\(M\) Permutation Sequence \(/problems/permutation-sequence/\)](#)[\(M\) Combinations \(/problems/combinations/\)](#)

Have you met this question in a real interview? [Yes](#) [No](#)

[Discuss \(https://discuss.leetcode.com/category/54\)](https://discuss.leetcode.com/category/54)[Top Solutions](#)[Pick One \(/problems/random-one-question/\)](#)[C++](#)

```
1 class Solution {
2     // lexicographic algorithms could handle same elements
3 public:
4     vector<vector<int>> permute(vector<int>& nums) {
5         sort(nums.begin(),nums.end());
6         vector<vector<int>> res;
7         res.push_back(nums);
8         int n = nums.size();
9         if(n==1) return res;
10        int j,l,k;
11        while(true){
12            //step 1a: set j to 2nd last
13            j = n-2;
14            //step 1b: search for first j satisfy n_j < n_{j+1}
15            while(j>=0&&nums[j]>=nums[j+1]) j--;
16            //step 1c: if j<0 terminate algorithm;
17            if(j<0) break;
18            //step 2a: set l to last one
19            l = n-1;
20            //step 2b: find first l which n_l > n_j
21            while(nums[j]>=nums[l]) l--;
22            //step 3: swap n_j and n_l;
23            swap(nums[j],nums[l]);
24            //step 4: start from j+1 reverse subarray j+1 to n-1;
25            for(k=j+1,l=n-1;k<l;k++,l--){
26                swap(nums[k],nums[l]);
27            }
28            res.push_back(nums);
29        }
30        return res;
31    }
32 };
```

[Custom Testcase](#) ☐

[Contribute Testcase](#)

[Run Code](#)[Submit Solution](#)