Total Accepted: 100489 Total Submissions: 322841 Difficulty: Medium Contributors: Admin

Given a linked list, return the node where the cycle begins. If there is no cycle, return $\ \ \text{null}\ .$

Note: Do not modify the linked list.

Follow up:

Can you solve it without using extra space?

Subscribe (/subscribe/) to see which companies asked this question

Hide Tags Linked List (/tag/linked-list) Two Pointers (/tag/two-pointers/)

Hide Similar Problems (E) Linked List Cycle (/problems/linked-list-cycle/) (H) Find the Duplicate Number (/problems/find-the-duplicate-number/)

Have you met this question in a real interview? Yes No

Discuss (https://discuss.leetcode.com/category/150)

Top Solutions

Pick One (/problems/random-one-question/)

```
C++
                           C
                                 </>
  1
      * Definition for singly-linked list.
  2
  3
      * struct ListNode {
  4
            int val;
  5
            ListNode *next;
            ListNode(int x) : val(x), next(NULL) {}
  6
     * };
  7
     */
  8
 9
     class Solution {
 10
     public:
 11
         ListNode *detectCycle(ListNode *head) {
 12
             ListNode* slow=head;
             ListNode* fast=head;
 13
 14
             while(fast!=NULL){
 15
 16
                 if(fast->next==NULL)
 17
                     return NULL;
 18
                 fast = fast->next->next;
 19
                 slow = slow->next;
 20
                 if(fast==slow) break;
             }
 21
 22
             if(fast==NULL)
 23
 24
                 return NULL;
 25
             slow = head;
             while(slow!=fast){
 26
 27
                 slow = slow->next;
 28
                 fast = fast->next;
 29
 30
             return slow;
 31
         }
 32 };
```

Submit Solution