

46. Permutations

[Add to List ▾](#)[Question](#)[Editorial Solution](#)[My Submissions \(/problems/permutations/submissions/\)](#)

Total Accepted: **142729** Total Submissions: **350707** Difficulty: **Medium** Contributors: **Admin**

Given a collection of **distinct** numbers, return all possible permutations.

For example,

[1, 2, 3] have the following permutations:

```
[
  [1,2,3],
  [1,3,2],
  [2,1,3],
  [2,3,1],
  [3,1,2],
  [3,2,1]
]
```

[Notes](#)[Show Company Tags](#)[Show Tags](#)[Show Similar Problems](#)

Have you met this question in a real interview? ☐ Yes ☐ No

[Discuss \(https://discuss.leetcode.com/category/54\)](https://discuss.leetcode.com/category/54)[Top Solutions](#)[Pick One \(/problems/random-one-question/\)](/problems/random-one-question/)

C++ ▾



```
1 class Solution {
2     // recursive
3 public:
4     vector<vector<int>> permute(vector<int>& nums) {
5         vector<vector<int>> res;
6         helper(res,nums,0);
7         return res;
8     }
9     void helper(vector<vector<int>>& res,vector<int>& nums,int begin ){
10        if(begin==nums.size()) {
11            res.push_back(nums);
12            return;
13        }
14        for(int i=begin;i<nums.size();i++){
15            swap(nums[begin],nums[i]);
16            helper(res,nums,begin+1);
17            swap(nums[begin],nums[i]);
18        }
19    }
20 };
```

Custom Testcase ☐

Contribute Testcase

[Run Code](#)[Submit Solution](#)

[Frequently Asked Questions \(/faq/\)](#) | [Terms of Service \(/tos/\)](#)

[Privacy](#)

Copyright © 2017 LeetCode

Send Feedback (mailto:admin@leetcode.com?subject=Feedback)