What user are you logged in as by default?

The root user.

If you start and then exit an interactive container, and then use the docker run command again, is it the same container? How can you tell?

They are not the same container as running “docker ps -a” gives two containers with separate ID’s.

CONTAINER ID IMAGE COMMAND

e11dc55eae7f ubuntu:22.04 "/bin/bash"

cffe6ddd8899 ubuntu:22.04 "/bin/bash"

43074b8b5b40 hello-world "/hello"

Run the image you just built. What do you observe?

The container starts up directly into the interactive Python session rather than a bash shell terminal. This is because we specified Python as the default command in CMD.

Paste the output of docker images

$ docker images

IMAGE	ID	DISK USAGE	CONTENT SIZE	EXTRA
hello-world:latest	cf1b20a0c89a	25.9kB	9.49kB	
myfortune:latest	855de43132fa	259MB	86.3MB	U
mypython:latest	03fbdda6b202	299MB	95.7MB	U
ubuntu:22.04	74b12b11ffa5	120MB	32.1MB	

Why are there so few processes compared with your VM?

ps aux

USER PID %CPU %MEM VSZ RSS TTY STAT START TIME COMMAND

root 1 0.0 0.0 6208 4600 ? Ss 09:55 0:00 httpd -DFOREGROUND

www-data 8 0.0 0.0 1997392 4012 ? Sl 09:55 0:00 httpd -DFOREGROUND

www-data 9 0.0 0.0 1997392 4012 ? Sl 09:55 0:00 httpd -DFOREGROUND

www-data 15 0.0 0.0 1997448 4268 ? Sl 09:55 0:00 httpd -DFOREGROUND

root 92 0.0 0.0 4320 3584 pts/0 Ss 09:57 0:00 /bin/bash

```
root       221  0.0  0.0   6392  3584 pts/0    R+   09:58   0:00 ps aux
```

A Docker container runs an isolated application rather than a complete operating system like a virtual machine does. The Apache container only needs the processes required to run it. The Apache container and all other containers share the host's Linux kernel.

This is why containers are more lightweight than virtual machines.

All request files have been pushed to the repo.