

ArrayList and Lists

© A+ Computer Science - www.apluscompsci.com

What is a list?

© A+ Computer Science - www.apluscompsci.com



© A+ Computer Science - www.apluscompsci.com

What is an ArrayList?

© A+ Computer Science - www.apluscompsci.com

ArrayList

ArrayList is a class that houses an array.

An ArrayList can store any type.

All ArrayLists store the first reference at spot / index position 0.

© A+ Computer Science - www.apluscompsci.com

ArrayList can store a reference to any type of Object.
ArrayList was built using an array[] of object references.

What is an array?

```
int[] nums = new int[10];    //Java int array
```

	0	1	2	3	4	5	6	7	8	9
nums	0	0	0	0	0	0	0	0	0	0

An array is a group of items all of the same type which are accessed through a single identifier.

© A+ Computer Science - www.apluscompsci.com

ArrayList References

ArrayList list;

list
null



null

nothing

list is a reference to an ArrayList.

© A+ Computer Science - www.apluscompsci.com

A reference variable is used to store the location of an Object. In most situations, a reference stores the actual memory address of an Object.

`list` stores the location / memory address of an ArrayList.

ArrayList Instantiation

```
new ArrayList();
```

0x213


```
[]
```

ArrayLists are Objects.

© A+ Computer Science - www.apluscompsci.com

ArrayList

```
ArrayList list = new ArrayList();
```



list is a reference to an ArrayList.

© A+ Computer Science - www.apluscompsci.com

A reference variable is used to store the location of an Object. In most situations, a reference stores the actual memory address of an Object.

`list` stores the location / memory address of an ArrayList.

Open objects.java

© A+ Computer Science - www.apluscompsci.com

Generic ArrayLists

© A+ Computer Science - www.apluscompsci.com

ArrayList

```
ArrayList<String> words;  
words = new ArrayList<String>();  
  
List<Double> decNums;  
decnums = new ArrayList<Double>();
```

© A+ Computer Science - www.apluscompsci.com

In the example above, words can only store String references. decNums can only store Double references.

Java knows the exact type of reference in both ArrayLists; thus, there is no need for casting when accessing class specific methods.

```
words.add("Hello");  
out.println(words.get(0).charAt(0));
```

ArrayList

```
ArrayList<Long> bigStuff;  
bigStuff = new ArrayList<Long>();
```

```
List<It> itList;  
itList = new ArrayList<It>();
```

© A+ Computer Science - www.apluscompsci.com

In the example above, words can only store String references. decNums can only store Double references.

Java knows the exact type of reference in both ArrayLists; thus, there is no need for casting when accessing class specific methods.

```
itList.add(new It(34.21));  
out.println(itList.get(0).getIt());
```

ArrayList

```
List<String> ray;  
ray = new ArrayList<String>();  
ray.add("hello");  
ray.add("whoot");  
ray.add("contests");  
out.println(ray.get(0).charAt(0));  
out.println(ray.get(2).charAt(0));
```

OUTPUT

h
c

ray stores String references.

© A+ Computer Science - www.apluscompsci.com

In the example above, ray is an ArrayList that stores String references. Casting would not be required to call non-Object methods on ray.

```
ray.add(0, "hello");  
ray.add(1, "chicken");
```

```
out.println(ray.get(0).charAt(0));  
out.println(ray.get(1).charAt(5));
```

Open generics.java

© A+ Computer Science - www.apluscompsci.com

ArrayList

Methods

© A+ Computer Science - www.apluscompsci.com

ArrayList

frequently used methods

Name	Use
add(item)	adds item to the end of the list
add(spot,item)	adds item at spot – shifts items up->
set(spot,item)	put item at spot $z[\text{spot}] = \text{item}$
get(spot)	returns the item at spot return $z[\text{spot}]$
size()	returns the # of items in the list
remove()	removes an item from the list
clear()	removes all items from the list

```
import java.util.ArrayList;
```

© A+ Computer Science - www.apluscompsci.com

add() one

```
ArrayList<String> words;  
words = new ArrayList<String>();
```

```
words.add("it");  
words.add("is");  
words.add(0,"a");  
words.add(1,"lie");  
out.println(words);
```

OUTPUT

```
[a, lie, it, is]
```

© A+ Computer Science - www.apluscompsci.com

The `add(item)` method adds the new item to the end of the `ArrayList`.

The `add(spot, item)` method adds the new item at the spot specified.

All other existing items are shifted toward the end of the `ArrayList`.

The `add` method does not override existing values.

add() two

```
List<Integer> nums;  
nums = new ArrayList<Integer>();
```

```
nums.add(34);  
nums.add(0,99);  
nums.add(21);  
nums.add(0,11);  
out.println(nums);
```

OUTPUT

```
[11, 99, 34, 21]
```

© A+ Computer Science - www.apluscompsci.com

The `add(item)` method adds the new item to the end of the `ArrayList`.

The `add(spot, item)` method adds the new item at the spot specified.

All other existing items are shifted toward the end of the `ArrayList`.

The `add` method does not override existing values.

Open
addone.java
addtwo.java

© A+ Computer Science - www.apluscompsci.com

set()

```
ArrayList<Integer> ray;  
ray = new ArrayList<Integer>();  
ray.add(23);  
ray.add(11);  
ray.set(0,66);  
ray.add(53);  
ray.set(1,93);  
ray.add(22);  
out.println(ray);
```

OUTPUT

[66, 93, 53, 22]

© A+ Computer Science - www.apluscompsci.com

The `add(item)` method adds the new item to the end of the `ArrayList`.

The `set(spot, item)` method replaces the reference at `spot` with the new item.

The location / address of item is placed in `spot`.

You cannot set a location to a value if the location does not already exist.

This will result in an index out of bounds exception.

set()

```
List<Integer> ray;  
ray = new ArrayList<Integer>();  
ray.add(23);  
ray.add(0, 11);  
ray.set(5,66);  
out.println(ray);
```

OUTPUT

Runtime exception

© A+ Computer Science - www.apluscompsci.com

The `add(item)` method adds the new item to the end of the `ArrayList`.

The `set(spot, item)` method replaces the reference at `spot` with the new item.

The location / address of item is placed in `spot`.

You cannot set a location to a value if the location does not already exist.

This will result in an index out of bounds exception.

get()

```
ArrayList<Integer> ray;  
ray = new ArrayList<Integer>();  
ray.add(23);  
ray.add(11);  
ray.add(12);  
ray.add(65);
```

OUTPUT

23

65

```
out.println(ray.get(0));  
out.println(ray.get(3));
```

.get(spot) returns the reference stored at spot!

© A+ Computer Science - www.apluscompsci.com

The get(spot) method returns the reference stored at spot.

get()

```
List<Integer> ray;  
ray = new ArrayList<Integer>();  
ray.add(23);  
ray.add(11);  
ray.add(12);  
ray.add(65);  
  
for(int i=0; i<ray.size(); i++)  
    out.println(ray.get(i));
```

OUTPUT

```
23  
11  
12  
65
```

.get(spot) returns the reference stored at spot!

© A+ Computer Science - www.apluscompsci.com

The get(spot) method returns the reference stored at spot.

Open
set.java
get.java

© A+ Computer Science - www.apluscompsci.com

Processing a list using loops

© A+ Computer Science - www.apluscompsci.com

Traditional for loop

```
for (int i=0; i<ray.size(); i++)  
{  
    out.println(ray.get(i));  
}
```

**.size() returns the number of
elements/items/spots/boxes or
whatever you want to call them.**

© A+ Computer Science - www.apluscompsci.com

The `size()` method returns the number of items in the `ArrayList`. If the `ArrayList` is storing seven references, `size()` would return a 7.

for each loop

```
List<Integer> ray;  
ray = new ArrayList<Integer>();
```

```
ray.add(23);  
ray.add(11);  
ray.add(53);
```

```
for(int num : ray){  
    out.println(num);  
}
```

OUTPUT

```
23  
11  
53
```

© A+ Computer Science - www.apluscompsci.com

The new for loop is great to print out Arrays and Collections. The new for loop extracts an item from ray each time it iterates. The new for loop is an iterator based loop. Once the loop reaches the end of ray, it stops iterating.

Open foreachloopone.java

© A+ Computer Science - www.apluscompsci.com

remove methods

© A+ Computer Science - www.apluscompsci.com

remove() one

```
ArrayList<String> ray;  
ray = new ArrayList<String>();
```

```
ray.add("a");  
ray.add("b");  
ray.remove(0);  
ray.add("c");  
ray.add("d");  
ray.remove(0);  
out.println(ray);
```

OUTPUT

[c, d]

© A+ Computer Science - www.apluscompsci.com

The remove method will remove the item at the specified spot / location or the specified value. When an item is removed, all items above the removed item are shifted down toward the front of the ArrayList. All items are shifted to the left.

[a, b] becomes [b]

[b, c, d] becomes [c, d]

remove() two

```
List<String> ray;  
ray = new ArrayList<String>();
```

```
ray.add("a");  
ray.add("b");  
ray.remove("a");  
ray.add("c");  
ray.add("d");  
ray.remove("d");  
out.println(ray);
```

OUTPUT

[b, c]

© A+ Computer Science - www.apluscompsci.com

The remove method will remove the item at the specified spot / location or the specified value. When an item is removed, all items above the removed item are shifted down toward the front of the ArrayList. All items are shifted to the left.

[a, b] becomes [b]

[b, c, d] becomes [b, c]

Open
removeone.java
removetwo.java

© A+ Computer Science - www.apluscompsci.com

Removing Multiple Items

© A+ Computer Science - www.apluscompsci.com

Removing multiple items

```
spot = list size – 1  
while( spot is >=0 )  
{  
    if ( this item is a match )  
        remove this item from the list  
        subtract 1 from spot  
}
```

© A+ Computer Science - www.apluscompsci.com

In order to remove multiple values from an ArrayList, a loop must be used.

The loop will need an if statement to identify the items to remove.

Keep in mind that the ArrayList shrinks when items are removed.

The items in the ArrayList shift down towards spot 0.

The loop must start at size()-1 and go down in order to account for the shift.

Removing multiple items

```
spot = list.size() - 1
while( spot >= 0 )
{
    if ( list.get(spot).equals( value ) )
        list.remove( spot );
    spot = spot - 1
}
```

© A+ Computer Science - www.apluscompsci.com

In order to remove multiple values from an ArrayList, a loop must be used.

The loop will need an if statement to identify the items to remove.

Keep in mind that the ArrayList shrinks when items are removed.

The items in the ArrayList shift down towards spot 0.

The loop must start at size()-1 and go down in order to account for the shift.

Open

removeall.java

Complete the code

© A+ Computer Science - www.apluscompsci.com

clear()

```
ArrayList<String> ray;  
ray = new ArrayList<String>();
```

```
ray.add("a");  
ray.add("x");  
ray.clear();  
ray.add("t");  
ray.add("w");  
out.println(ray);
```

OUTPUT

[t, w]

© A+ Computer Science - www.apluscompsci.com

The `clear()` method removes all items from the `ArrayList`.

The `ArrayList` becomes an `[]` empty `ArrayList` with a `size()` of 0.

The `clear()` method essentially performs the same operation as instantiating a new `ArrayList`.

Open clear.java

© A+ Computer Science - www.apluscompsci.com

Collections

class

© A+ Computer Science - www.apluscompsci.com

Collections

frequently used methods

Name	Use
sort(x)	puts all items in x in ascending order
binarySearch(x,y)	checks x for the location of y
fill(x,y)	fills all spots in x with value y
rotate(x,y)	shifts items in x left or right y locations
reverse(x)	reverses the order of the items in x

```
import java.util.Collections;
```

© A+ Computer Science - www.apluscompsci.com

Collections

```
ArrayList<Integer> ray;  
ray = new ArrayList<Integer>();
```

```
ray.add(23);  
ray.add(11);  
ray.add(66);  
ray.add(53);  
Collections.sort(ray);  
out.println(ray);  
out.println(Collections.binarySearch(ray,677));  
out.println(Collections.binarySearch(ray,66));
```

OUTPUT

[11, 23, 53, 66]

-5

3

© A+ Computer Science - www.apluscompsci.com

`Collections.sort()` will put all items in natural ascending order.

`Collectoins.binarySearch()` will locate an item. If the item does not exist, `binarySearch()` will return $-1 + -(\text{where the value would be if it was there})$.

-3 is $-1 + -2$ (2 is the spot where the item would be)

Collections

```
ArrayList<Integer> ray;  
ray = ArrayList<Integer>();
```

```
ray.add(23);  
ray.add(11);  
ray.add(53);  
out.println(ray);  
rotate(ray,2);  
out.println(ray);  
rotate(ray,2);  
reverse(ray);  
out.println(ray);
```

OUTPUT

```
[23, 11, 53]  
[11, 53, 23]  
[11, 23, 53]
```

© A+ Computer Science - www.apluscompsci.com

`Collections.rotate()` rotates items to the right or to the left a specified number of spots / positions. A negative number rotates to the left and a positive number rotates to the right.

`Collections.reverse()` reverses the order of all items.

Collections

```
ArrayList<Integer> ray;  
ray = new ArrayList<Integer>();  
ray.add(0);  
ray.add(0);  
ray.add(0);  
out.println(ray);
```

OUTPUT

```
[0, 0, 0]  
[33, 33, 33]
```

```
Collections.fill(ray,33);  
out.println(ray);
```

© A+ Computer Science - www.apluscompsci.com

Collections.fill() will fill in all spots with a specified value.

Open
binarysearch.java
rotate.java
fill.java

© A+ Computer Science - www.apluscompsci.com

search methods

© A+ Computer Science - www.apluscompsci.com

ArrayList
frequently used methods

Name	Use
<code>contains(x)</code>	checks if the list contains x
<code>indexOf(x)</code>	checks the list for the location of x

© A+ Computer Science - www.apluscompsci.com

```
ArrayList<Integer> ray;  
ray = new ArrayList<Integer>();
```

```
ray.add(23);  
ray.add(11);  
ray.add(66);  
ray.add(53);
```

```
out.println(ray);  
out.println(ray.indexOf(21));  
out.println(ray.indexOf(66));
```

```
out.println(ray);  
out.println(ray.contains(21));  
out.println(ray.contains(66));
```

OUTPUT

[23, 11, 66, 53]

-1

2

[23, 11, 66, 53]

false

true

© A+ Computer Science - www.apluscompsci.com

Open search.java

© A+ Computer Science - www.apluscompsci.com

Java Collections


© A+ Computer Science - www.apluscompsci.com

Java Interfaces

**The following are important
interfaces included in the
Java language ::**

Collection List


© A+ Computer Science - www.apluscompsci.com



This Collections hierarchy chart is very important. It is a must to know which classes implement which interfaces and which interfaces extend which interfaces.

The Collection Interface

The Collection interface is the parent of List and Set. The Collection interface has many methods listed including add(), clear(), remove(), and size().




others not shown

© A+ Computer Science - www.apluscompsci.com

The List Interface

The List interface extends the Collection interface. The List interface adds in the get() method as well as several others.



© A+ Computer Science - www.apluscompsci.com

ArrayList

ArrayList is a descendant of List and Collection, but because List and Collection are interfaces, you cannot instantiate them.

Collection bad = new Collection(); //illegal

List ray = new ArrayList(); //legal

ArrayList list = new ArrayList(); //legal

ray and list store Object references.

© A+ Computer Science - www.apluscompsci.com

In the example above, ray is an ArrayList that stores Object references. In order to call non-Object methods on a spot in ray, casting would be required.

```
ray.add(0, "hello");
```

```
out.println(((String) ray.get(0)).charAt(0));
```

Work on Lab 16

© A+ Computer Science - www.apluscompsci.com