

Lecture 6: Backpropagation

Waitlist update

Over the past few days everyone on the waitlist got an override!


Reminder: A2

Due Monday, 9/30, 11:59pm


Last time: Neural Networks

From linear classifiers to
fully-connected networks


$$f = W_2 \max(0, W_1 x)$$




Space Warping



Universal Approximation



Nonconvex



Problem: How to compute gradients?

$$s = f(x; W_1, W_2) = W_2 \max(0, W_1 x) \quad \text{Nonlinear score function}$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1) \quad \text{SVM Loss on predictions}$$

$$R(W) = \sum_k W_k^2 \quad \text{Regularization}$$

$$L = \frac{1}{N} \sum_{i=1}^N L_i + \lambda R(W_1) + \lambda R(W_2) \quad \text{Total loss: data loss + regularization}$$

If we can compute $\frac{\partial L}{\partial W_1}, \frac{\partial L}{\partial W_2}$ we can learn W_1 and W_2

(Bad) Idea: Derive $\nabla_W L$ on paper

$$s = f(x; W) = Wx$$

$$L_i = \sum_{j \neq y_i} \max(0, s_j - s_{y_i} + 1)$$

$$= \sum_{j \neq y_i} \max(0, W_{j,:} \cdot x + W_{y_i,:} \cdot x + 1)$$

$$L = \frac{1}{N} \sum_{i=1}^N L_i + \lambda \sum_k W_k^2$$

$$= \frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, W_{j,:} \cdot x + W_{y_i,:} \cdot x + 1) + \lambda \sum_k W_k^2$$


$$\nabla_W L = \nabla_W \left(\frac{1}{N} \sum_{i=1}^N \sum_{j \neq y_i} \max(0, W_{j,:} \cdot x + W_{y_i,:} \cdot x + 1) + \lambda \sum_k W_k^2 \right)$$

Problem: Very tedious: Lots of matrix calculus, need lots of paper

Problem: What if we want to change loss? E.g. use softmax instead of SVM? Need to re-derive from scratch. Not modular!

Problem: Not feasible for very complex models!

Better Idea: Computational Graphs




Deep Network (AlexNet)

input image

weights

loss



Neural Turing Machine

input image

loss





Figure reproduced with permission from a [Twitter post](#) by Andrej Karpathy.

Neural Turing Machine




Graves et al, arXiv 2014

Figure reproduced with permission from a [Twitter post](#) by Andrej Karpathy.

Backpropagation: Simple Example


$$f(x, y, z) = (x + y)z$$



Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$




Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$

1. Forward pass: Compute outputs


$$q = x + y \quad f = qz$$



Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$



1. Forward pass: Compute outputs

$$q = x + y \quad f = qz$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$

Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$


e.g. $x = -2, y = 5, z = -4$

1. Forward pass: Compute outputs

$$q = x + y \quad f = qz$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial f}$$

Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$


e.g. $x = -2, y = 5, z = -4$

1. Forward pass: Compute outputs

$$q = x + y \quad f = qz$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial f}$$

Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$

e.g. $x = -2, y = 5, z = -4$


1. Forward pass: Compute outputs

$$q = x + y$$

$$f = qz$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial z}$$

Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$


e.g. $x = -2, y = 5, z = -4$

1. Forward pass: Compute outputs

$$q = x + y \quad \boxed{f = qz}$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\boxed{\frac{\partial f}{\partial z} = q}$$

Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$


e.g. $x = -2, y = 5, z = -4$

1. Forward pass: Compute outputs

$$q = x + y \quad f = qz$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$


e.g. $x = -2, y = 5, z = -4$

1. **Forward pass:** Compute outputs

$$q = x + y \quad \boxed{f = qz}$$

2. **Backward pass:** Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\boxed{\frac{\partial f}{\partial q} = z}$$

Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$


e.g. $x = -2, y = 5, z = -4$

1. Forward pass: Compute outputs

$$q = x + y \quad f = qz$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



$$\frac{\partial f}{\partial y}$$

Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$


e.g. $x = -2, y = 5, z = -4$

1. Forward pass: Compute outputs

$$q = x + y \quad f = qz$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Chain Rule

$$\frac{\partial f}{\partial y} = \frac{\partial q}{\partial y} \frac{\partial f}{\partial q}$$

Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$


e.g. $x = -2, y = 5, z = -4$

1. Forward pass: Compute outputs

$$q = x + y \quad f = qz$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Chain Rule

$$\frac{\partial f}{\partial y} = \frac{\partial q}{\partial y} \frac{\partial f}{\partial q}$$

$$\frac{\partial q}{\partial y} = 1$$

Downstream
Gradient

Local
Gradient

Upstream
Gradient

Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$


e.g. $x = -2, y = 5, z = -4$

1. Forward pass: Compute outputs

$$q = x + y \quad f = qz$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Chain Rule

$$\frac{\partial f}{\partial y} = \frac{\partial q}{\partial y} \frac{\partial f}{\partial q}$$

$$\frac{\partial q}{\partial y} = 1$$

Downstream
Gradient

Local
Gradient

Upstream
Gradient

Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$


e.g. $x = -2, y = 5, z = -4$

1. Forward pass: Compute outputs

$$q = x + y \quad f = qz$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Chain Rule

$$\frac{\partial f}{\partial x} = \frac{\partial q}{\partial x} \frac{\partial f}{\partial q}$$

$$\frac{\partial q}{\partial x} = 1$$

Downstream
Gradient

Local
Gradient

Upstream
Gradient

Backpropagation: Simple Example

$$f(x, y, z) = (x + y)z$$


e.g. $x = -2, y = 5, z = -4$

1. Forward pass: Compute outputs

$$q = x + y \quad f = qz$$

2. Backward pass: Compute derivatives

Want: $\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y}, \frac{\partial f}{\partial z}$



Chain Rule


$$\frac{\partial f}{\partial x} = \frac{\partial q}{\partial x} \frac{\partial f}{\partial q}$$


$$\frac{\partial q}{\partial x} = 1$$


Downstream
Gradient


Local
Gradient


Upstream
Gradient













Another Example $f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$



Another Example

$$f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}}$$


Forward pass: Compute outputs



Another Example

$$f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$


Backward pass: Compute gradients



Another Example

$$f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$


Backward pass: Compute gradients



Another Example

$$f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$


Backward pass: Compute gradients



Another Example

$$f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$


Backward pass: Compute gradients



Another Example


$$f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$

Backward pass: Compute gradients




Another Example $f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}}$

Backward pass: Compute gradients



Another Example $f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$


Backward pass: Compute gradients



Another Example

$$f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$


Backward pass: Compute gradients



Another Example

$$f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2x_2)}}$$


Backward pass: Compute gradients



Another Example


$$f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}} = \sigma(w_0x_0 + w_1x_1 + w_2)$$

Backward pass: Compute gradients



$$\sigma(x) = \frac{1}{1 + e^{-x}}$$


Computational graph is not unique: we can use primitives that have simple local gradients



Another Example


$$f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}} = \sigma(w_0x_0 + w_1x_1 + w_2)$$

Backward pass: Compute gradients



$$\sigma(x) = \frac{1}{1 + e^{-x}}$$

Computational graph is not unique: we can use primitives that have simple local gradients




Sigmoid local gradient:

$$\frac{\partial}{\partial x} [\sigma(x)] = \frac{e^{-x}}{(1 + e^{-x})^2} = \left(\frac{1 + e^{-x} - 1}{1 + e^{-x}} \right) \left(\frac{1}{1 + e^{-x}} \right) = (1 - \sigma(x))\sigma(x)$$

Another Example


$$f(x, w) = \frac{1}{1 + e^{-(w_0x_0 + w_1x_1 + w_2)}} = \sigma(w_0x_0 + w_1x_1 + w_2)$$

Backward pass: Compute gradients



$$\sigma(x) = \frac{1}{1 + e^{-x}}$$

Computational graph is not unique: we can use primitives that have simple local gradients




$$\begin{aligned} [\text{Downstream}] &= [\text{Local}] * [\text{Upstream}] \\ &= (1 - 0.73) * 0.73 * 1.0 = 0.2 \end{aligned}$$

Sigmoid local gradient:

$$\frac{\partial}{\partial x} [\sigma(x)] = \frac{e^{-x}}{(1 + e^{-x})^2} = \left(\frac{1 + e^{-x} - 1}{1 + e^{-x}} \right) \left(\frac{1}{1 + e^{-x}} \right) = (1 - \sigma(x))\sigma(x)$$


Patterns in Gradient Flow

add gate: gradient distributor




Patterns in Gradient Flow

add gate: gradient distributor




copy gate: gradient adder




Patterns in Gradient Flow


add gate: gradient distributor



mul gate: “swap multiplier”




copy gate: gradient adder




Patterns in Gradient Flow


add gate: gradient distributor




mul gate: “swap multiplier”



copy gate: gradient adder



max gate: gradient router



Backprop Implementation: "Flat" gradient code:

Forward pass:
Compute output

```
def f(w0, x0, w1, x1, w2):
```


```
    s0 = w0 * x0
```

```
    s1 = w1 * x1
```

```
    s2 = s0 + s1
```

```
    s3 = s2 + w2
```

```
    L = sigmoid(s3)
```




Backprop Implementation: "Flat" gradient code:

Forward pass:
Compute output

```
def f(w0, x0, w1, x1, w2):
```

```
    s0 = w0 * x0  
    s1 = w1 * x1  
    s2 = s0 + s1  
    s3 = s2 + w2  
    L = sigmoid(s3)
```




Backward pass:
Compute grads

```
    grad_L = 1.0  
    grad_s3 = grad_L * (1 - L) * L  
    grad_w2 = grad_s3  
    grad_s2 = grad_s3  
    grad_s0 = grad_s2  
    grad_s1 = grad_s2  
    grad_w1 = grad_s1 * x1  
    grad_x1 = grad_s1 * w1  
    grad_w0 = grad_s0 * x0  
    grad_x0 = grad_s0 * w0
```

Backprop Implementation: "Flat" gradient code:

Forward pass:
Compute output



Base case

```
def f(w0, x0, w1, x1, w2):
```

```
    s0 = w0 * x0
```

```
    s1 = w1 * x1
```

```
    s2 = s0 + s1
```

```
    s3 = s2 + w2
```

```
    L = sigmoid(s3)
```

```
    grad_L = 1.0
```

```
    grad_s3 = grad_L * (1 - L) * L
```

```
    grad_w2 = grad_s3
```

```
    grad_s2 = grad_s3
```

```
    grad_s0 = grad_s2
```

```
    grad_s1 = grad_s2
```

```
    grad_w1 = grad_s1 * x1
```


```
    grad_x1 = grad_s1 * w1
```

```
    grad_w0 = grad_s0 * x0
```

```
    grad_x0 = grad_s0 * w0
```

Backprop Implementation: "Flat" gradient code:

Forward pass:
Compute output



Sigmoid

```
def f(w0, x0, w1, x1, w2):
```

```
    s0 = w0 * x0
```

```
    s1 = w1 * x1
```

```
    s2 = s0 + s1
```

```
    s3 = s2 + w2
```

```
    L = sigmoid(s3)
```

```
    grad_L = 1.0
```

```
    grad_s3 = grad_L * (1 - L) * L
```

```
    grad_w2 = grad_s3
```

```
    grad_s2 = grad_s3
```

```
    grad_s0 = grad_s2
```

```
    grad_s1 = grad_s2
```

```
    grad_w1 = grad_s1 * x1
```


```
    grad_x1 = grad_s1 * w1
```

```
    grad_w0 = grad_s0 * x0
```

```
    grad_x0 = grad_s0 * w0
```

Backprop Implementation: "Flat" gradient code:

Forward pass:
Compute output



```
def f(w0, x0, w1, x1, w2):
```

```
    s0 = w0 * x0
```

```
    s1 = w1 * x1
```

```
    s2 = s0 + s1
```

```
    s3 = s2 + w2
```

```
    L = sigmoid(s3)
```

```
    grad_L = 1.0
```

```
    grad_s3 = grad_L * (1 - L) * L
```

```
    grad_w2 = grad_s3
```

```
    grad_s2 = grad_s3
```

```
    grad_s0 = grad_s2
```

```
    grad_s1 = grad_s2
```

```
    grad_w1 = grad_s1 * x1
```

```
    grad_x1 = grad_s1 * w1
```


```
    grad_w0 = grad_s0 * x0
```

```
    grad_x0 = grad_s0 * w0
```

Add

Backprop Implementation: "Flat" gradient code:

Forward pass:
Compute output



```
def f(w0, x0, w1, x1, w2):
```

```
    s0 = w0 * x0
```

```
    s1 = w1 * x1
```

```
    s2 = s0 + s1
```

```
    s3 = s2 + w2
```

```
    L = sigmoid(s3)
```

```
grad_L = 1.0
```

```
grad_s3 = grad_L * (1 - L) * L
```

```
grad_w2 = grad_s3
```

```
grad_s2 = grad_s3
```

```
grad_s0 = grad_s2
```

```
grad_s1 = grad_s2
```

```
grad_w1 = grad_s1 * x1
```

```
grad_x1 = grad_s1 * w1
```


```
grad_w0 = grad_s0 * x0
```

```
grad_x0 = grad_s0 * w0
```

Add

Backprop Implementation: "Flat" gradient code:

Forward pass:
Compute output



```
def f(w0, x0, w1, x1, w2):
```

```
    s0 = w0 * x0
```

```
    s1 = w1 * x1
```

```
    s2 = s0 + s1
```

```
    s3 = s2 + w2
```

```
    L = sigmoid(s3)
```

```
grad_L = 1.0
```

```
grad_s3 = grad_L * (1 - L) * L
```

```
grad_w2 = grad_s3
```

```
grad_s2 = grad_s3
```

```
grad_s0 = grad_s2
```

```
grad_s1 = grad_s2
```

```
grad_w1 = grad_s1 * x1
```

```
grad_x1 = grad_s1 * w1
```


```
grad_w0 = grad_s0 * x0
```

```
grad_x0 = grad_s0 * w0
```

Multiply

Backprop Implementation: "Flat" gradient code:

Forward pass:
Compute output



```
def f(w0, x0, w1, x1, w2):
```

```
    s0 = w0 * x0
```

```
    s1 = w1 * x1
```

```
    s2 = s0 + s1
```

```
    s3 = s2 + w2
```

```
    L = sigmoid(s3)
```

```
grad_L = 1.0
```

```
grad_s3 = grad_L * (1 - L) * L
```

```
grad_w2 = grad_s3
```

```
grad_s2 = grad_s3
```

```
grad_s0 = grad_s2
```

```
grad_s1 = grad_s2
```

```
grad_w1 = grad_s1 * x1
```

```
grad_x1 = grad_s1 * w1
```

```
grad_w0 = grad_s0 * x0
```

```
grad_x0 = grad_s0 * w0
```

Multiply


“Flat” Backprop: Do this for Assignment 2!

Your gradient code should look like a “reversed version” of your forward pass!

E.g. for the SVM:

```
# receive W (weights), X (data)
# forward pass (we have 8 lines)
scores = #...
margins = #...
data_loss = #...
reg_loss = #...
loss = data_loss + reg_loss

# backward pass (we have 5 lines)
dmargins = # ... (optionally, we go direct to dscores)
dscores = #...
dW = #...
```



“Flat” Backprop: Do this for Assignment 2!


Your gradient code should look like a “reversed version” of your forward pass!

E.g. for two-layer neural net:

```
# receive W1,W2,b1,b2 (weights/biases), X (data)
# forward pass:
h1 = #... function of X,W1,b1
scores = #... function of h1,W2,b2
loss = #... (several lines of code to evaluate Softmax loss)
# backward pass:
dscores = #...
dh1,dW2,db2 = #...
dW1,db1 = #...
```


Backprop Implementation: Modular API

Graph (or Net) object *(rough pseudo code)*



```
class ComputationalGraph(object):  
    #...  
    def forward(inputs):  
        # 1. [pass inputs to input gates...]  
        # 2. forward the computational graph:  
        for gate in self.graph.nodes_topologically_sorted():  
            gate.forward()  
        return loss # the final gate in the graph outputs the loss  
    def backward():  
        for gate in reversed(self.graph.nodes_topologically_sorted()):  
            gate.backward() # little piece of backprop (chain rule applied)  
        return inputs_gradients
```

Example: PyTorch Autograd Functions



(x,y,z are scalars)


```
class Multiply(torch.autograd.Function):  
    @staticmethod  
    def forward(ctx, x, y):  
        ctx.save_for_backward(x, y)  
        z = x * y  
        return z  
    @staticmethod  
    def backward(ctx, grad_z):  
        x, y = ctx.saved_tensors  
        grad_x = y * grad_z    # dz/dx * dL/dz  
        grad_y = x * grad_z    # dz/dy * dL/dz  
        return grad_x, grad_y
```

Need to stash some
values for use in
backward

Upstream
gradient

Multiply upstream
and local gradients

Example: PyTorch operators



pytorch / pytorch		
Watch 1,221 Unstar 26,770 Fork 6,340		
Code Issues 2,286 Pull requests 561 Projects 4 Wiki Insights		
Tree: 517c7c9861 pytorch / aten / src / THNN / generic /		
ezyang and facebook-github-bot Canonicalize all includes in PyTorch. (#14849) Latest commit 517c7c9 on Dec 8, 2018		
AbsCriterion.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
BCECriterion.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
ClassNLLCriterion.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
Col2Im.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
ELU.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
FeatureLPPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
GatedLinearUnit.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
HardTanh.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
Im2Col.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
IndexLinear.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
LeakyReLU.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
LogSigmoid.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
MSECriterion.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
MultiLabelMarginCriterion.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
MultiMarginCriterion.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
RRReLU.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
Sigmoid.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SmoothL1Criterion.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SoftMarginCriterion.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SoftPlus.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SoftShrink.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SparseLinear.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialAdaptiveAveragePooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialAdaptiveMaxPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialAveragePooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago

SpatialClassNLLCriterion.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialConvolutionMM.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialDilatedConvolution.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialDilatedMaxPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialFractionalMaxPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialFullDilatedConvolution.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialMaxUnpooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialReflectionPadding.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialReplicationPadding.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialUpSamplingBilinear.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
SpatialUpSamplingNearest.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
THNN.h	Canonicalize all includes in PyTorch. (#14849)	4 months ago
Tanh.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
TemporalReflectionPadding.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
TemporalReplicationPadding.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
TemporalRowConvolution.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
TemporalUpSamplingLinear.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
TemporalUpSamplingNearest.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricAdaptiveAveragePoolin...	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricAdaptiveMaxPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricAveragePooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricConvolutionMM.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricDilatedConvolution.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricDilatedMaxPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricFractionalMaxPooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricFullDilatedConvolution.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricMaxUnpooling.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricReplicationPadding.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricUpSamplingNearest.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
VolumetricUpSamplingTrilinear.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago
linear_upsampling.h	Implement nn.functional.interpolate based on upsample. (#8591)	9 months ago
pooling_shape.h	Use integer math to compute output size of pooling operations (#14405)	4 months ago
unfold.c	Canonicalize all includes in PyTorch. (#14849)	4 months ago

PyTorch sigmoid layer

```
1  #ifndef TH_GENERIC_FILE
2  #define TH_GENERIC_FILE "THNN/generic/Sigmoid.c"
3  #else
4
5  void THNN_(Sigmoid_updateOutput)(
6      THNNState *state,
7      THTensor *input,
8      THTensor *output)
9  {
10     THTensor_(sigmoid)(output, input);
11 }
12
13 void THNN_(Sigmoid_updateGradInput)(
14     THNNState *state,
15     THTensor *gradOutput,
16     THTensor *gradInput,
17     THTensor *output)
18 {
19     THNN_CHECK_NELEMENT(output, gradOutput);
20     THTensor_(resizeAs)(gradInput, output);
21     TH_TENSOR_APPLY3(scalar_t, gradInput, scalar_t, gradOutput, scalar_t, output,
22         scalar_t z = *output_data;
23         *gradInput_data = *gradOutput_data * (1. - z) * z;
24     );
25 }
26
27 #endif
```

[Source](#)

PyTorch sigmoid layer

```
1 #ifndef TH_GENERIC_FILE
2 #define TH_GENERIC_FILE "THNN/generic/Sigmoid.c"
3 #else
4
5 void THNN_(Sigmoid_updateOutput)(
6     THNNState *state,
7     THTensor *input,
8     THTensor *output)
9 {
10     THTensor_(sigmoid)(output, input);
11 }
12
13 void THNN_(Sigmoid_updateGradInput)(
14     THNNState *state,
15     THTensor *gradOutput,
16     THTensor *gradInput,
17     THTensor *output)
18 {
19     THNN_CHECK_NELEMENT(output, gradOutput);
20     THTensor_(resizeAs)(gradInput, output);
21     TH_TENSOR_APPLY3(scalar_t, gradInput, scalar_t, gradOutput, scalar_t, output,
22         scalar_t z = *output_data;
23         *gradInput_data = *gradOutput_data * (1. - z) * z;
24     );
25 }
26
27 #endif
```

Forward

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$

[Source](#)

PyTorch sigmoid layer

```
1 #ifndef TH_GENERIC_FILE
2 #define TH_GENERIC_FILE "THNN/generic/Sigmoid.c"
3 #else
```

```
4
5 void THNN_(Sigmoid_updateOutput)(
6     THNNState *state,
7     THTensor *input,
8     THTensor *output)
9 {
10     THTensor_(sigmoid)(output, input);
11 }
```

Forward

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$

```
12
13 void THNN_(Sigmoid_updateGradInput)(
14     THNNState *state,
15     THTensor *gradOutput,
16     THTensor *gradInput,
17     THTensor *output)
18 {
19     THNN_CHECK_NELEMENT(output, gradOutput);
20     THTensor_(resizeAs)(gradInput, output);
21     TH_TENSOR_APPLY3(scalar_t, gradInput, scalar_t, gradOutput, scalar_t, output,
22         scalar_t z = *output_data;
23         *gradInput_data = *gradOutput_data * (1. - z) * z;
24     );
25 }
26
27 #endif
```

```
static void sigmoid_kernel(TensorIterator& iter) {
    AT_DISPATCH_FLOATING_TYPES(iter.dtype(), "sigmoid_cpu", [&]() {
        unary_kernel_vec(
            iter,
            [=](scalar_t a) -> scalar_t { return (1 / (1 + std::exp((-a)))); },
            [=](Vec256<scalar_t> a) {
                a = Vec256<scalar_t>((scalar_t)(0)) - a;
                a = a.exp();
                a = Vec256<scalar_t>((scalar_t)(1)) + a;
                a = a.reciprocal();
                return a;
            });
    });
}
```

Forward actually defined [elsewhere...](#)

```
return (1 / (1 + std::exp((-a))));
```

[Source](#)

PyTorch sigmoid layer

```
1 #ifndef TH_GENERIC_FILE
2 #define TH_GENERIC_FILE "THNN/generic/Sigmoid.c"
3 #else
```

```
5 void THNN_(Sigmoid_updateOutput)(
6     THNNState *state,
7     THTensor *input,
8     THTensor *output)
9 {
10     THTensor_(sigmoid)(output, input);
11 }
```

Forward

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$

```
13 void THNN_(Sigmoid_updateGradInput)(
14     THNNState *state,
15     THTensor *gradOutput,
16     THTensor *gradInput,
17     THTensor *output)
18 {
19     THNN_CHECK_NELEMENT(output, gradOutput);
20     THTensor_(resizeAs)(gradInput, output);
21     TH_TENSOR_APPLY3(scalar_t, gradInput, scalar_t, gradOutput, scalar_t, output,
22         scalar_t z = *output_data;
23         *gradInput_data = *gradOutput_data * (1. - z) * z;
24     );
25 }
```

Backward

$$(1 - \sigma(x)) \sigma(x)$$

[Source](#)

So far: backprop with scalars

What about vector-valued functions?

Recap: Vector Derivatives

$$x \in \mathbb{R}, y \in \mathbb{R}$$

Regular derivative:

$$\frac{\partial y}{\partial x} \in \mathbb{R}$$

If x changes by a small amount, how much will y change?

Recap: Vector Derivatives

$$x \in \mathbb{R}, y \in \mathbb{R}$$

Regular derivative:

$$\frac{\partial y}{\partial x} \in \mathbb{R}$$

If x changes by a small amount, how much will y change?

$$x \in \mathbb{R}^N, y \in \mathbb{R}$$

Derivative is **Gradient**:

$$\frac{\partial y}{\partial x} \in \mathbb{R}^N \quad \left(\frac{\partial y}{\partial x} \right)_n = \frac{\partial y}{\partial x_n}$$

For each element of x , if it changes by a small amount then how much will y change?

Recap: Vector Derivatives

$$x \in \mathbb{R}, y \in \mathbb{R}$$

Regular derivative:

$$\frac{\partial y}{\partial x} \in \mathbb{R}$$

If x changes by a small amount, how much will y change?

$$x \in \mathbb{R}^N, y \in \mathbb{R}$$

Derivative is **Gradient**:

$$\frac{\partial y}{\partial x} \in \mathbb{R}^N \quad \left(\frac{\partial y}{\partial x} \right)_n = \frac{\partial y}{\partial x_n}$$

For each element of x , if it changes by a small amount then how much will y change?


$$x \in \mathbb{R}^N, y \in \mathbb{R}^M$$

Derivative is **Jacobian**:


$$\frac{\partial y}{\partial x} \in \mathbb{R}^{N \times M} \quad \left(\frac{\partial y}{\partial x} \right)_{n,m} = \frac{\partial y_m}{\partial x_n}$$

For each element of x , if it changes by a small amount then how much will each element of y change?


Backprop with Vectors




Backprop with Vectors



Backprop with Vectors




Backprop with Vectors



Backprop with Vectors

4D input x:

$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$




$$f(x) = \max(0, x)$$

(elementwise)

4D output y:


$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$



Backprop with Vectors

4D input x:

$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$




$$f(x) = \max(0, x)$$

(elementwise)


4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$



4D dL/dy :

$\begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$




Upstream
gradient

Backprop with Vectors

4D input x:

$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$




$$f(x) = \max(0, x)$$

(elementwise)

4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$




Jacobian dy/dx

$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix}$

4D dL/dy :

$\begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$


Upstream
gradient



Backprop with Vectors

4D input x:

$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$




$$f(x) = \max(0, x)$$

(elementwise)

4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$



$\begin{bmatrix} dy/dx \end{bmatrix} \begin{bmatrix} dL/dy \end{bmatrix}$

$\begin{bmatrix} 1 & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} 4 \end{bmatrix}$

$\begin{bmatrix} 0 & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} -1 \end{bmatrix}$

$\begin{bmatrix} 0 & 0 & 1 & 0 \end{bmatrix} \begin{bmatrix} 5 \end{bmatrix}$

$\begin{bmatrix} 0 & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} 9 \end{bmatrix}$



4D dL/dy:

$\begin{bmatrix} 4 \end{bmatrix}$

$\begin{bmatrix} -1 \end{bmatrix}$

$\begin{bmatrix} 5 \end{bmatrix}$

$\begin{bmatrix} 9 \end{bmatrix}$




Upstream
gradient

Backprop with Vectors

4D input x:


$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$



$f(x) = \max(0, x)$
(*elementwise*)


4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$



4D dL/dx:

$\begin{bmatrix} 4 \\ 0 \\ 5 \\ 0 \end{bmatrix}$




$\begin{bmatrix} dy/dx & dL/dy \end{bmatrix}$

$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$

4D dL/dy:

$\begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$




Upstream
gradient

Backprop with Vectors

Jacobian is **sparse**: off-diagonal entries all zero! Never **explicitly** form Jacobian; instead use **implicit** multiplication

4D input x:


$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$



$$f(x) = \max(0, x) \\ (\textit{elementwise})$$


4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$



4D dL/dx:

$\begin{bmatrix} 4 \\ 0 \\ 5 \\ 0 \end{bmatrix}$




$\begin{bmatrix} dy/dx & dL/dy \end{bmatrix}$

$\begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 0 \end{bmatrix} \begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$

4D dL/dy:

$\begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$




Upstream
gradient

Backprop with Vectors

Jacobian is **sparse**: off-diagonal entries all zero! Never **explicitly** form Jacobian; instead use **implicit** multiplication

4D input x:


$\begin{bmatrix} 1 \\ -2 \\ 3 \\ -1 \end{bmatrix}$



$$f(x) = \max(0, x) \\ (\text{elementwise})$$

4D output y:

$\begin{bmatrix} 1 \\ 0 \\ 3 \\ 0 \end{bmatrix}$



4D dL/dx:

$\begin{bmatrix} 4 \\ 0 \\ 5 \\ 0 \end{bmatrix}$




$[dy/dx] [dL/dy]$

$$\left(\frac{\partial L}{\partial x} \right)_i = \begin{cases} \left(\frac{\partial L}{\partial y} \right)_i & \text{if } x_i > 0 \\ 0 & \text{otherwise} \end{cases}$$


4D dL/dy:

$\begin{bmatrix} 4 \\ -1 \\ 5 \\ 9 \end{bmatrix}$



Upstream
gradient


Backprop with Matrices (or Tensors):



Backprop with Matrices (or Tensors):

Loss L still a scalar!


dL/dx always has the same shape as x !



Backprop with Matrices (or Tensors):

Loss L still a scalar!


dL/dx always has the same shape as x !



Backprop with Matrices (or Tensors):

Loss L still a scalar!


dL/dx always has the same shape as x !




Backprop with Matrices (or Tensors):

Loss L still a scalar!


dL/dx always has the same shape as x !




Example: Matrix Multiplication



Example: Matrix Multiplication



Example: Matrix Multiplication




For a neural net we may have


$N=64, D=M=4096$

Each Jacobian takes 256 GB of memory! Must work with them implicitly!


Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication




Example: Matrix Multiplication



Example: Matrix Multiplication



Example: Matrix Multiplication



$$dL/dx = (dL/dy) w^T$$


$[N \times D] \quad [N \times M] \quad [M \times D]$

$$dL/dw = x^T (dL/dy)$$

$[D \times M] \quad [D \times N] \quad [N \times M]$


Easy way to remember:
It's the only way the
shapes work out!

Backpropagation: Another View



Chain rule $\frac{\partial L}{\partial x_0} = \left(\frac{\partial x_1}{\partial x_0} \right) \left(\frac{\partial x_2}{\partial x_1} \right) \left(\frac{\partial x_3}{\partial x_2} \right) \left(\frac{\partial L}{\partial x_3} \right)$


Backpropagation: Another View




Matrix multiplication is **associative**: we can compute products in any order

$$\text{Chain rule } \frac{\partial L}{\partial x_0} = \underbrace{\left(\frac{\partial x_1}{\partial x_0} \right)}_{D_0 \times D_1} \underbrace{\left(\frac{\partial x_2}{\partial x_1} \right)}_{D_1 \times D_2} \underbrace{\left(\frac{\partial x_3}{\partial x_2} \right)}_{D_2 \times D_3} \underbrace{\left(\frac{\partial L}{\partial x_3} \right)}_{D_3}$$

Reverse-Mode Automatic Differentiation



Matrix multiplication is **associative**: we can compute products in any order
Computing products right-to-left avoids matrix-matrix products; only needs matrix-vector




Chain rule

$$\frac{\partial L}{\partial x_0} = \left(\frac{\partial x_1}{\partial x_0} \right) \left(\frac{\partial x_2}{\partial x_1} \right) \left(\frac{\partial x_3}{\partial x_2} \right) \left(\frac{\partial L}{\partial x_3} \right)$$

$D_0 \times D_1$ $D_1 \times D_2$ $D_2 \times D_3$ D_3

Reverse-Mode Automatic Differentiation



Matrix multiplication is **associative**: we can compute products in any order
 Computing products right-to-left avoids matrix-matrix products; only needs matrix-vector


Chain rule $\frac{\partial L}{\partial x_0} = \left(\frac{\partial x_1}{\partial x_0} \right) \left(\frac{\partial x_2}{\partial x_1} \right) \left(\frac{\partial x_3}{\partial x_2} \right) \left(\frac{\partial L}{\partial x_3} \right)$

$D_0 \times D_1$ $D_1 \times D_2$ $D_2 \times D_3$ D_3

What if we want grads of scalar input w/respect to vector outputs?

Compute grad of scalar output w/respect to all vector inputs


Forward-Mode Automatic Differentiation




Chain rule $\frac{\partial x_3}{\partial a} = \left(\frac{\partial x_0}{\partial a} \right) \left(\frac{\partial x_1}{\partial x_0} \right) \left(\frac{\partial x_2}{\partial x_1} \right) \left(\frac{\partial x_3}{\partial x_2} \right)$

$$\begin{array}{cccc} D_0 & D_0 \times D_1 & D_1 \times D_2 & D_2 \times D_3 \end{array}$$


Forward-Mode Automatic Differentiation



Computing products left-to-right avoids matrix-matrix products; only needs matrix-vector


$$\text{Chain rule } \frac{\partial x_3}{\partial a} = \underbrace{\left(\frac{\partial x_0}{\partial a} \right)}_{D_0} \underbrace{\left(\frac{\partial x_1}{\partial x_0} \right)}_{D_0 \times D_1} \underbrace{\left(\frac{\partial x_2}{\partial x_1} \right)}_{D_1 \times D_2} \underbrace{\left(\frac{\partial x_3}{\partial x_2} \right)}_{D_2 \times D_3}$$

Forward-Mode Automatic Differentiation



Computing products left-to-right avoids matrix-matrix products; only needs matrix-vector


Not implemented in PyTorch / TensorFlow =(

Chain rule $\frac{\partial x_3}{\partial a} =$

$$\begin{matrix} \xrightarrow{\hspace{10cm}} \\ \left(\frac{\partial x_0}{\partial a} \right) & \left(\frac{\partial x_1}{\partial x_0} \right) & \left(\frac{\partial x_2}{\partial x_1} \right) & \left(\frac{\partial x_3}{\partial x_2} \right) \\ D_0 & D_0 \times D_1 & D_1 \times D_2 & D_2 \times D_3 \end{matrix}$$

But you can implement forward-mode AD using [two calls to reverse-mode AD!](#) (Inefficient but elegant)


Backprop: Higher-Order Derivatives



$$\frac{\partial^2 L}{\partial x_0^2}$$

Hessian matrix
H of second
derivatives.
 $D_0 \times D_0$

Backprop: Higher-Order Derivatives



Hessian / vector multiply

$$\frac{\partial^2 L}{\partial x_0^2}$$


Hessian matrix
H of second
derivatives.

$D_0 \times D_0$

$$\frac{\partial^2 L}{\partial x_0^2} v$$

$D_0 \times D_0 \quad D_0$

Backprop: Higher-Order Derivatives



Hessian / vector multiply

$$\frac{\partial^2 L}{\partial x_0^2}$$

Hessian matrix
H of second
derivatives.


$D_0 \times D_0$

$$\frac{\partial^2 L}{\partial x_0^2} v = \frac{\partial}{\partial x_0} \left[\frac{\partial L}{\partial x_0} \cdot v \right]$$

(if v doesn't
depend on x_0)

$D_0 \times D_0 \quad D_0$

Backprop: Higher-Order Derivatives



Hessian / vector multiply

$$\frac{\partial^2 L}{\partial x_0^2}$$

Hessian matrix
H of second derivatives.


$D_0 \times D_0$

$$\frac{\partial^2 L}{\partial x_0^2} v = \frac{\partial}{\partial x_0} \left[\frac{\partial L}{\partial x_0} \cdot v \right]$$

(if v doesn't depend on x_0)

$D_0 \times D_0 \quad D_0$

Backprop: Higher-Order Derivatives



Hessian / vector multiply

$$\frac{\partial^2 L}{\partial x_0^2}$$

Hessian matrix
H of second derivatives.


$D_0 \times D_0$

$$\frac{\partial^2 L}{\partial x_0^2} v = \frac{\partial}{\partial x_0} \left[\frac{\partial L}{\partial x_0} \cdot v \right]$$

(if v doesn't depend on x_0)

$D_0 \times D_0 \quad D_0$

Backprop: Higher-Order Derivatives



Hessian / vector multiply

$$\frac{\partial^2 L}{\partial x_0^2}$$

Hessian matrix
H of second derivatives.


$D_0 \times D_0$

$$\frac{\partial^2 L}{\partial x_0^2} v = \frac{\partial}{\partial x_0} \left[\frac{\partial L}{\partial x_0} \cdot v \right]$$

(if v doesn't depend on x_0)

$D_0 \times D_0 \quad D_0$

Backprop: Higher-Order Derivatives




Example: Regularization to penalize the norm of the gradient

$$R(W) = \left\| \frac{\partial L}{\partial W} \right\|_2^2 = \left(\frac{\partial L}{\partial W} \right) \cdot \left(\frac{\partial L}{\partial W} \right) \quad \frac{\partial}{\partial x_0} [R(W)] = 2 \left(\frac{\partial^2 L}{\partial x_0^2} \right) \left(\frac{\partial L}{\partial x_0} \right)$$

Summary


Represent complex expressions as **computational graphs**



Forward pass computes outputs

Backward pass computes gradients

During the backward pass, each node in the graph receives **upstream gradients** and multiplies them by **local gradients** to compute **downstream gradients**



Summary

Backprop can be implemented with “flat” code where the backward pass looks like forward pass reversed (Use this for A2!)


```
def f(w0, x0, w1, x1, w2):
    s0 = w0 * x0
    s1 = w1 * x1
    s2 = s0 + s1
    s3 = s2 + w2
    L = sigmoid(s3)

    grad_L = 1.0
    grad_s3 = grad_L * (1 - L) * L
    grad_w2 = grad_s3
    grad_s2 = grad_s3
    grad_s0 = grad_s2
    grad_s1 = grad_s2
    grad_w1 = grad_s1 * x1
    grad_x1 = grad_s1 * w1
    grad_w0 = grad_s0 * x0
    grad_x0 = grad_s0 * w0
```


Backprop can be implemented with a modular API, as a set of paired forward/backward functions (We will do this on A3!)

```
class Multiply(torch.autograd.Function):
    @staticmethod
    def forward(ctx, x, y):
        ctx.save_for_backward(x, y)
        z = x * y
        return z
    @staticmethod
    def backward(ctx, grad_z):
        x, y = ctx.saved_tensors
        grad_x = y * grad_z    # dz/dx * dL/dz
        grad_y = x * grad_z    # dz/dy * dL/dz
        return grad_x, grad_y
```


$$f(x, W) = Wx$$



$$f = W_2 \max(0, W_1 x)$$



Stretch pixels into column



Input image
(2, 2)

Problem: So far our classifiers don't respect the spatial structure of images!

56
231
24
2

(4,)

Next time:

Convolutional Neural Networks