

Lecture 9: Hardware and Software

Assignment 3 Released

We released Assignment 3 last night

We had a few hotfixes today;
check Piazza for details

Modular backprop API

Fully-connected networks

Dropout

Convolutional Networks

Batch Normalization

Due **Monday, October 14, 11:59pm**

Remember to [validate your submission](#)

Deep Learning Hardware

Inside a computer



This image copyright 2017, Justin Johnson

Inside a computer

GPU: “Graphics Processing Unit”



[This image](#) is in the public domain



This image copyright 2017, Justin Johnson

Inside a computer

CPU: “Central Processing Unit”



[This image](#) is licensed under [CC-BY 2.0](#)

GPU: “Graphics Processing Unit”



[This image](#) is in the public domain



This image copyright 2017, Justin Johnson

NVIDIA

vs


AMD

NVIDIA

vs

AMD

GigaFLOPs per Dollar




CPU vs GPU

	Cores	Clock Speed (GHz)	Memory	Price	TFLOP/sec
CPU Ryzen 9 3950X	16 (32 threads with hyperthreading)	3.5 (4.7 boost)	System RAM	\$749	~4.8 FP32
GPU NVIDIA Titan RTX	4608	1.35 (1.77 boost)	24 GB GDDR6	\$2499	~16.3 FP32

CPU: Fewer cores, but each core is much faster and much more capable; great at sequential tasks


GPU: More cores, but each core is much slower and “dumber”; great for parallel tasks

Inside a GPU: RTX Titan



Inside a GPU: RTX Titan


12x 2GB
memory
modules




Inside a GPU: RTX Titan

12x 2GB
memory
modules

Processor





Inside a GPU: RTX Titan




Inside a GPU: RTX Titan

72 Streaming
multiprocessors
(SMs)



Inside a GPU: RTX Titan


72 Streaming
multiprocessors (SMs)



Inside a GPU: RTX Titan

72 Streaming
multiprocessors (SMs)

64 FP32 cores
per SM




Inside a GPU: RTX Titan

$(72 \text{ SM}) * (64 \text{ FP32 core per SM}) * (2 \text{ FLOP/cycle})$
 $* (1.77 \text{ Gcycle/sec}) = \mathbf{16.3 \text{ TFLOP/sec}}$

72 Streaming
multiprocessors (SMs)

64 FP32 cores
per SM




Inside a GPU: RTX Titan

$(72 \text{ SM}) * (64 \text{ FP32 core per SM}) * (2 \text{ FLOP/cycle})$
 $* (1.77 \text{ Gcycle/sec}) = \mathbf{16.3 \text{ TFLOP/sec}}$

Tensor cores use **mixed precision**: Multiplication is done in FP16, and addition is done in FP32

72 Streaming multiprocessors (SMs)



64 FP32 cores
per SM

8 Tensor Core
per SM

Tensor core:
Special
hardware!

Let A,B,C be
4x4 matrices;
computes $AB+C$
in one clock
cycle!
(128 FLOP)

Inside a GPU: RTX Titan

$(72 \text{ SM}) * (64 \text{ FP32 core per SM}) * (2 \text{ FLOP/cycle})$
 $* (1.77 \text{ Gcycle/sec}) = \mathbf{16.3 \text{ TFLOP/sec}}$

$(72 \text{ SM}) * (8 \text{ tensor core per SM})$
 $* (128 \text{ FLOP/cycle}) * (1.77 \text{ Gcycle/sec})$
 $= \mathbf{130 \text{ TFLOP/sec!}}$


72 Streaming
multiprocessors (SMs)

64 FP32 cores
per SM

8 Tensor Core
per SM

Tensor core:
Special
hardware!

Let A,B,C be
4x4 matrices;
computes $AB+C$
in one clock
cycle!
(128 FLOP)




CPU vs GPU

	Cores	Clock Speed (GHz)	Memory	Price	TFLOP/sec
CPU Ryzen 9 3950X	16 (32 threads with hyperthreading)	3.5 (4.7 boost)	System RAM	\$749	~4.8 FP32
GPU NVIDIA Titan RTX	4608	1.35 (1.77 boost)	24 GB GDDR6	\$2499	~16.3 FP32 ~ 130 with Tensor Cores

CPU: Fewer cores, but each core is much faster and much more capable; great at sequential tasks


GPU: More cores, but each core is much slower and “dumber”; great for parallel tasks

GigaFLOPs per Dollar




Example: Matrix Multiplication

$A \times B$




$B \times C$



=

$A \times C$



Perfect for GPUs! All output elements are independent, can be trivially parallelized

Programming GPUs

- CUDA (NVIDIA only)
 - Write C-like code that runs directly on the GPU
 - NVIDIA provides optimized APIs: cuBLAS, cuFFT, cuDNN, etc
- OpenCL
 - Similar to CUDA, but runs on anything
 - Usually slower on NVIDIA hardware
- EECS 598.009: Applied GPU Programming

Scaling up: Typically 8 GPUs per server



NVIDIA DGX-1: 8x V100 GPUs

Google Tensor Processing Units (TPU)



Special hardware for matrix multiplication, similar to NVIDIA Tensor Cores; also runs in mixed precision (bfloat16)

Cloud TPU v2


180 TFLOPs

64 GB HBM memory

\$4.50 / hour

(free on Colab!)

Google Tensor Processing Units (TPU)



Cloud TPU v2

180 TFLOPs

64 GB HBM memory

\$4.50 / hour

(free on Colab!)




Cloud TPU v2 Pod

64 TPU-v2

11.5 PFLOPs

\$384 / hour

Google Tensor Processing Units (TPU)



Cloud TPU v3


420 TFLOPs

128 GB HBM memory

\$8 / hour

[TPU-v3 image](#) is released under a [CC-SA 4.0 International](#) license

Google Tensor Processing Units (TPU)



Cloud TPU v3

420 TFLOPs

128 GB HBM memory

\$8 / hour



Cloud TPU v3 Pod

256 TPU-v3

107 PFLOPs

TPU-v3 image is released under a [CC-SA 4.0 International](#) license


Google Tensor Processing Units (TPU)

In order to use TPUs, you have to use TensorFlow

Google Tensor Processing Units (TPU)

In order to use TPUs, you have to use TensorFlow

... For now!



Add XLA / TPU device type, backend type and type id
(#16585) #16763

Deep Learning Software

A zoo of frameworks!

Caffe
(UC Berkeley)



Caffe2
(Facebook)

Torch
(NYU / Facebook)



PyTorch
(Facebook)

Theano
(U Montreal)



TensorFlow
(Google)

PaddlePaddle
(Baidu)

MXNet
(Amazon)


Developed by U Washington, CMU, MIT, Hong Kong U, etc but main framework of choice at AWS

Chainer


CNTK
(Microsoft)

JAX
(Google)

A zoo of frameworks!



Recall: Computational Graphs



The point of deep learning frameworks

1. Allow rapid prototyping of new ideas
2. Automatically compute gradients for you
3. Run it all efficiently on GPU (or TPU)

PyTorch

PyTorch: Versions

For this class we are using **PyTorch version 1.2**
(Released August 2019)

Be careful if you are looking at older PyTorch code –
the API changed a lot before 1.0
(0.3 to 0.4 had big changes!)

PyTorch: Fundamental Concepts

Tensor: Like a numpy array, but can run on GPU

Autograd: Package for building computational graphs out of Tensors, and automatically computing gradients

Module: A neural network layer; may store state or learnable weights

PyTorch: Fundamental Concepts

Tensor: Like a numpy array, but can run on GPU **A1, A2, A3**

Autograd: Package for building computational graphs out of Tensors, and automatically computing gradients

Module: A neural network layer; may store state or learnable weights

A4, A5, A6

PyTorch: Tensors

Running example: Train a two-layer ReLU network on random data with L2 loss

```
import torch

device = torch.device('cpu')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)

learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```

PyTorch: Tensors

Create random tensors
for data and weights

```
import torch

device = torch.device('cpu')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)

learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```

PyTorch: Tensors

Forward pass: compute predictions and loss

```
import torch

device = torch.device('cpu')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)


learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```


PyTorch: Tensors

Backward pass: manually
compute gradients



```
import torch

device = torch.device('cpu')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)

learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```

PyTorch: Tensors

Gradient descent
step on weights

```
import torch

device = torch.device('cpu')

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in, device=device)
y = torch.randn(N, D_out, device=device)
w1 = torch.randn(D_in, H, device=device)
w2 = torch.randn(H, D_out, device=device)

learning_rate = 1e-6
for t in range(500):
    h = x.mm(w1)
    h_relu = h.clamp(min=0)
    y_pred = h_relu.mm(w2)
    loss = (y_pred - y).pow(2).sum()

    grad_y_pred = 2.0 * (y_pred - y)
    grad_w2 = h_relu.t().mm(grad_y_pred)
    grad_h_relu = grad_y_pred.mm(w2.t())
    grad_h = grad_h_relu.clone()
    grad_h[h < 0] = 0
    grad_w1 = x.t().mm(grad_h)

    w1 -= learning_rate * grad_w1
    w2 -= learning_rate * grad_w2
```

PyTorch: Tensors

To run on GPU, just use a different device!

```
import torch
```

```
device = torch.device('cuda:0')
```

```
N, D_in, H, D_out = 64, 1000, 100, 10
```

```
x = torch.randn(N, D_in, device=device)
```

```
y = torch.randn(N, D_out, device=device)
```

```
w1 = torch.randn(D_in, H, device=device)
```

```
w2 = torch.randn(H, D_out, device=device)
```

```
learning_rate = 1e-6
```

```
for t in range(500):
```

```
    h = x.mm(w1)
```

```
    h_relu = h.clamp(min=0)
```

```
    y_pred = h_relu.mm(w2)
```

```
    loss = (y_pred - y).pow(2).sum()
```

```
    grad_y_pred = 2.0 * (y_pred - y)
```

```
    grad_w2 = h_relu.t().mm(grad_y_pred)
```

```
    grad_h_relu = grad_y_pred.mm(w2.t())
```

```
    grad_h = grad_h_relu.clone()
```

```
    grad_h[h < 0] = 0
```

```
    grad_w1 = x.t().mm(grad_h)
```

```
    w1 -= learning_rate * grad_w1
```

```
    w2 -= learning_rate * grad_w2
```


PyTorch: Autograd

Creating Tensors with
requires_grad=True enables autograd

Operations on Tensors with
requires_grad=True cause PyTorch to
build a computational graph

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```


PyTorch: Autograd

We will not want gradients
(of loss) with respect to data

Do want gradients with
respect to weights

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd

Forward pass looks exactly the same as before, but we don't need to track intermediate values - PyTorch keeps track of them for us in the graph

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd

Computes gradients with respect to all inputs that have `requires_grad=True`!

```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```


PyTorch: Autograd



Every operation on a tensor with `requires_grad=True` will add to the computational graph, and the resulting tensors will also have `requires_grad=True`

```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd



Every operation on a tensor with `requires_grad=True` will add to the computational graph, and the resulting tensors will also have `requires_grad=True`

```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```


PyTorch: Autograd



```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd



```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd



```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```


PyTorch: Autograd



```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd *leaf nodes.*



```
import torch
```

```
N, D_in, H, D_out = 64, 1000, 100, 10
```

```
x = torch.randn(N, D_in)
```

```
y = torch.randn(N, D_out)
```

```
w1 = torch.randn(D_in, H, requires_grad=True)
```

```
w2 = torch.randn(H, D_out, requires_grad=True)
```

```
learning_rate = 1e-6
```

```
for t in range(500):
```

```
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
```

```
    loss = (y_pred - y).pow(2).sum()
```

```
    loss.backward()
```

```
    with torch.no_grad():
```

```
        w1 -= learning_rate * w1.grad
```

```
        w2 -= learning_rate * w2.grad
```

```
        w1.grad.zero_()
```

```
        w2.grad.zero_()
```


PyTorch: Autograd

x

w1

w2

y

After backward finishes, gradients are accumulated into w1.grad and w2.grad and the graph is destroyed

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

ReLU

PyTorch: Autograd

x

w1

w2

y

After backward finishes, gradients are **accumulated** into `w1.grad` and `w2.grad` and the graph is destroyed

Make gradient step on weights

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: Autograd

x

w1

w2

y

After backward finishes, gradients are **accumulated** into w1.grad and w2.grad and the graph is destroyed

Set gradients to zero – forgetting this is a common bug!

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```


PyTorch: Autograd


x

w1

w2

y

After backward finishes, gradients are **accumulated** into w1.grad and w2.grad and the graph is destroyed



Tell PyTorch not to build a graph for these operations

managers

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()

    with torch.no_grad():
        w1 -= learning_rate * w1.grad
        w2 -= learning_rate * w2.grad
        w1.grad.zero_()
        w2.grad.zero_()
```

PyTorch: New functions

Can define new operations
using Python functions


```
def sigmoid(x):  
    return 1.0 / (1.0 + (-x).exp())
```

```
import torch  
  
N, D_in, H, D_out = 64, 1000, 100, 10  
  
x = torch.randn(N, D_in)  
y = torch.randn(N, D_out)  
y = torch.randn(N, D_out)  
w1 = torch.randn(D_in, H, requires_grad=True)  
w2 = torch.randn(H, D_out, requires_grad=True)  
  
learning_rate = 1e-6  
for t in range(500):  
    y_pred = sigmoid(x.mm(w1)).mm(w2)  
    loss = (y_pred - y).pow(2).sum()  
  
    loss.backward()  
    if t % 50 == 0:  
        print(t, loss.item())  
  
    with torch.no_grad():  
        w1 -= learning_rate * w1.grad  
        w2 -= learning_rate * w2.grad  
        w1.grad.zero_()  
        w2.grad.zero_()
```


PyTorch: New functions

Can define new operations
using Python functions

```
def sigmoid(x):  
    return 1.0 / (1.0 + (-x).exp())
```



When our function runs,
it will add to the graph

Gradients computed
with autograd

*just add
more
nodes.*

```
import torch
```

```
N, D_in, H, D_out = 64, 1000, 100, 10
```

```
x = torch.randn(N, D_in)
```

```
y = torch.randn(N, D_out)
```

```
y = torch.randn(N, D_out)
```

```
w1 = torch.randn(D_in, H, requires_grad=True)
```

```
w2 = torch.randn(H, D_out, requires_grad=True)
```

```
learning_rate = 1e-6
```

```
for t in range(500):
```

```
    y_pred = sigmoid(x.mm(w1)).mm(w2)
```

```
    loss = (y_pred - y).pow(2).sum()
```

```
    loss.backward()
```

```
    if t % 50 == 0:
```

```
        print(t, loss.item())
```

```
with torch.no_grad():
```

```
    w1 -= learning_rate * w1.grad
```

```
    w2 -= learning_rate * w2.grad
```


```
    w1.grad.zero_()
```

```
    w2.grad.zero_()
```

PyTorch: New functions

Can define new operations
using Python functions

```
def sigmoid(x):  
    return 1.0 / (1.0 + (-x).exp())
```



When our function runs,
it will add to the graph

Gradients computed
with autograd

Define new autograd operators
by subclassing Function, define
forward and backward


```
class Sigmoid(torch.autograd.Function):  
    @staticmethod  
    def forward(ctx, x):  
        y = 1.0 / (1.0 + (-x).exp())  
        ctx.save_for_backward(y)  
        return y  
  
    @staticmethod  
    def backward(ctx, grad_y):  
        y, = ctx.saved_tensors  
        grad_x = grad_y * y * (1.0 - y)  
        return grad_x  
  
def sigmoid(x):  
    return Sigmoid.apply(x)
```

Recall:
$$\frac{\partial}{\partial x} [\sigma(x)] = (1 - \sigma(x))\sigma(x)$$

PyTorch: New functions

Can define new operations
using Python functions

```
def sigmoid(x):  
    return 1.0 / (1.0 + (-x).exp())
```




When our function runs,
it will add to the graph

Gradients computed
with autograd

Define new autograd operators
by subclassing Function, define
forward and backward

```
class Sigmoid(torch.autograd.Function):  
    @staticmethod  
    def forward(ctx, x):  
        y = 1.0 / (1.0 + (-x).exp())  
        ctx.save_for_backward(y)  
        return y  
  
    @staticmethod  
    def backward(ctx, grad_y):  
        y, = ctx.saved_tensors  
        grad_x = grad_y * y * (1.0 - y)  
        return grad_x  
  
def sigmoid(x):  
    return Sigmoid.apply(x)
```


Now when our function runs,
it adds one node to the graph!



PyTorch: New functions

Can define new operations
using Python functions

```
def sigmoid(x):  
    return 1.0 / (1.0 + (-x).exp())
```



When our function runs,
it will add to the graph

Gradients computed
with autograd

Define new autograd operators
by subclassing Function, define
forward and backward

```
class Sigmoid(torch.autograd.Function):  
    @staticmethod  
    def forward(ctx, x):  
        y = 1.0 / (1.0 + (-x).exp())  
        ctx.save_for_backward(y)  
        return y  
  
    @staticmethod  
    def backward(ctx, grad_y):  
        y, = ctx.saved_tensors  
        grad_x = grad_y * y * (1.0 - y)  
        return grad_x  
  
def sigmoid(x):  
    return Sigmoid.apply(x)
```

In practice this is pretty rare – in most
cases Python functions are good enough

PyTorch: nn

Higher-level wrapper for
working with neural nets

Use this! It will make your
life easier

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    with torch.no_grad():
        for param in model.parameters():
            param -= learning_rate * param.grad
    model.zero_grad()
```


PyTorch: nn

Object-oriented API: Define model object as sequence of layers objects, each of which holds weight tensors

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    with torch.no_grad():
        for param in model.parameters():
            param -= learning_rate * param.grad
    model.zero_grad()
```

PyTorch: nn

Forward pass: Feed data to model and compute loss

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    with torch.no_grad():
        for param in model.parameters():
            param -= learning_rate * param.grad
    model.zero_grad()
```

PyTorch: nn

Forward pass: Feed data to model and compute loss

torch.nn.functional has useful helpers like loss functions

Criterion

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)
    loss.backward()

    with torch.no_grad():
        for param in model.parameters():
            param -= learning_rate * param.grad
    model.zero_grad()
```

PyTorch: nn

Backward pass: compute gradient with respect to all model weights (they have `requires_grad=True`)

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)
    loss.backward()

    with torch.no_grad():
        for param in model.parameters():
            param -= learning_rate * param.grad
    model.zero_grad()
```


PyTorch: nn

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)


model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-2
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    with torch.no_grad():
        for param in model.parameters():
            param -= learning_rate * param.grad
        model.zero_grad()
```

Make gradient step on
each model parameter
(with gradients disabled)



PyTorch: optim

Use an **optimizer** for
different update rules

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-4
optimizer = torch.optim.Adam(model.parameters(),
                               lr=learning_rate)

for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: optim

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    torch.nn.Linear(D_in, H),
    torch.nn.ReLU(),
    torch.nn.Linear(H, D_out))

learning_rate = 1e-4
optimizer = torch.optim.Adam(model.parameters(),
                               lr=learning_rate)

for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()

    optimizer.step()
    optimizer.zero_grad()
```

After computing
gradients, use optimizer to
update and zero gradients



PyTorch: nn Defining Modules

A PyTorch **Module** is a neural net layer; it inputs and outputs Tensors

Modules can contain weights or other modules

Very common to define your own models or layers as custom Modules

```
import torch

class TwoLayerNet(torch.nn.Module):
    def __init__(self, D_in, H, D_out):
        super(TwoLayerNet, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, H)
        self.linear2 = torch.nn.Linear(H, D_out)

    def forward(self, x):
        h_relu = self.linear1(x).clamp(min=0)
        y_pred = self.linear2(h_relu)
        return y_pred

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```


PyTorch: nn Defining Modules

Define our whole model as
a single Module

```
import torch

class TwoLayerNet(torch.nn.Module):
    def __init__(self, D_in, H, D_out):
        super(TwoLayerNet, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, H)
        self.linear2 = torch.nn.Linear(H, D_out)

    def forward(self, x):
        h_relu = self.linear1(x).clamp(min=0)
        y_pred = self.linear2(h_relu)
        return y_pred

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: nn Defining Modules

Initializer sets up two
children (Modules can
contain modules)

```
import torch

class TwoLayerNet(torch.nn.Module):
    def __init__(self, D_in, H, D_out):
        super(TwoLayerNet, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, H)
        self.linear2 = torch.nn.Linear(H, D_out)

    def forward(self, x):
        h_relu = self.linear1(x).clamp(min=0)
        y_pred = self.linear2(h_relu)
        return y_pred

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: nn

Defining Modules

Define forward pass using child modules and tensor operations

No need to define backward - autograd will handle it

```
import torch

class TwoLayerNet(torch.nn.Module):
    def __init__(self, D_in, H, D_out):
        super(TwoLayerNet, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, H)
        self.linear2 = torch.nn.Linear(H, D_out)

    def forward(self, x):
        h_relu = self.linear1(x).clamp(min=0)
        y_pred = self.linear2(h_relu)
        return y_pred

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)

    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```


PyTorch: nn Defining Modules

Very common to mix and match
custom Module subclasses and
Sequential containers

*build
residual blocks.*

```
import torch

class ParallelBlock(torch.nn.Module):
    def __init__(self, D_in, D_out):
        super(ParallelBlock, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, D_out)
        self.linear2 = torch.nn.Linear(D_in, D_out)

    def forward(self, x):
        h1 = self.linear1(x)
        h2 = self.linear2(x)
        return (h1 * h2).clamp(min=0)



N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

model = torch.nn.Sequential(
    ParallelBlock(D_in, H),
    ParallelBlock(H, H),
    torch.nn.Linear(H, D_out))

optimizer = torch.optim.Adam(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)
    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```


PyTorch: nn Defining Modules

Define network component
as a Module subclass



```
import torch
```

```
class ParallelBlock(torch.nn.Module):  
    def __init__(self, D_in, D_out):  
        super(ParallelBlock, self).__init__()  
        self.linear1 = torch.nn.Linear(D_in, D_out)  
        self.linear2 = torch.nn.Linear(D_in, D_out)  
    def forward(self, x):  
        h1 = self.linear1(x)  
        h2 = self.linear2(x)  
        return (h1 * h2).clamp(min=0)
```


```
N, D_in, H, D_out = 64, 1000, 100, 10  
x = torch.randn(N, D_in)  
y = torch.randn(N, D_out)
```

```
model = torch.nn.Sequential(  
    ParallelBlock(D_in, H),  
    ParallelBlock(H, H),  
    torch.nn.Linear(H, D_out))
```

```
optimizer = torch.optim.Adam(model.parameters(), lr=1e-4)  
for t in range(500):  
    y_pred = model(x)  
    loss = torch.nn.functional.mse_loss(y_pred, y)  
    loss.backward()  
    optimizer.step()  
    optimizer.zero_grad()
```

PyTorch: nn Defining Modules

Stack multiple instances of the component in a sequential



Very easy to quickly
build complex network
architectures!

```
import torch

class ParallelBlock(torch.nn.Module):
    def __init__(self, D_in, D_out):
        super(ParallelBlock, self).__init__()
        self.linear1 = torch.nn.Linear(D_in, D_out)
        self.linear2 = torch.nn.Linear(D_in, D_out)

    def forward(self, x):
        h1 = self.linear1(x)
        h2 = self.linear2(x)
        return (h1 * h2).clamp(min=0)
```

```
N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
```

```
model = torch.nn.Sequential(
    ParallelBlock(D_in, H),
    ParallelBlock(H, H),
    torch.nn.Linear(H, D_out))
```

```
optimizer = torch.optim.Adam(model.parameters(), lr=1e-4)
for t in range(500):
    y_pred = model(x)
    loss = torch.nn.functional.mse_loss(y_pred, y)
    loss.backward()
    optimizer.step()
    optimizer.zero_grad()
```

PyTorch: DataLoaders

A **DataLoader** wraps a **Dataset** and provides minibatching, shuffling, multithreading, for you

When you need to load custom data, just write your own Dataset class

```
import torch
from torch.utils.data import TensorDataset, DataLoader

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

loader = DataLoader(TensorDataset(x, y), batch_size=8)
model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-2)
for epoch in range(20):
    for x_batch, y_batch in loader:
        y_pred = model(x_batch)
        loss = torch.nn.functional.mse_loss(y_pred, y_batch)

        loss.backward()
        optimizer.step()
        optimizer.zero_grad()
```


PyTorch: DataLoaders

Iterate over loader to
form minibatches



```
import torch
from torch.utils.data import TensorDataset, DataLoader

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

loader = DataLoader(TensorDataset(x, y), batch_size=8)
model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-2)
for epoch in range(20):
    for x_batch, y_batch in loader:
        y_pred = model(x_batch)
        loss = torch.nn.functional.mse_loss(y_pred, y_batch)

        loss.backward()
        optimizer.step()
        optimizer.zero_grad()
```


PyTorch: DataLoaders

Iterate over loader to
form minibatches



```
import torch
from torch.utils.data import TensorDataset, DataLoader

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)

loader = DataLoader(TensorDataset(x, y), batch_size=8)
model = TwoLayerNet(D_in, H, D_out)

optimizer = torch.optim.SGD(model.parameters(), lr=1e-2)
for epoch in range(20):
    for x_batch, y_batch in loader:
        y_pred = model(x_batch)
        loss = torch.nn.functional.mse_loss(y_pred, y_batch)

        loss.backward()
        optimizer.step()
        optimizer.zero_grad()
```

PyTorch: Pretrained Models

Super easy to use pretrained models with torchvision

<https://github.com/pytorch/vision>

```
import torch
import torchvision

alexnet = torchvision.models.alexnet(pretrained=True)
vgg16 = torchvision.models.vgg16(pretrained=True)
resnet101 = torchvision.models.resnet101(pretrained=True)
```

PyTorch: Dynamic Computation Graphs

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

PyTorch: Dynamic Computation Graphs

x

w1

w2

y

```
import torch
```


```
N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)
```

```
learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Create Tensor objects

PyTorch: Dynamic Computation Graphs



```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Build graph data structure
AND perform computation

PyTorch: Dynamic Computation Graphs




```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()
    loss.backward()
```

Build graph data structure
AND perform computation

PyTorch: Dynamic Computation Graphs



```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Perform backprop,
throw away graph

PyTorch: Dynamic Computation Graphs

x

w1

w2

y

```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Perform backprop,
throw away graph

PyTorch: Dynamic Computation Graphs



```
import torch


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Build graph data structure
AND perform computation

PyTorch: Dynamic Computation Graphs




```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()
    loss.backward()
```

Build graph data structure
AND perform computation

PyTorch: Dynamic Computation Graphs



```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2 = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
for t in range(500):
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
```

Perform backprop,
throw away graph

PyTorch: Dynamic Computation Graphs

Dynamic graphs let you use
regular Python control flow
during the forward pass!

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2a = torch.randn(H, D_out, requires_grad=True)
w2b = torch.randn(H, D_out, requires_grad=True)


learning_rate = 1e-6
prev_loss = 5.0
for t in range(500):
    w2 = w2a if prev_loss < 5.0 else w2b
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
    prev_loss = loss.item()
```


PyTorch: Dynamic Computation Graphs

Dynamic graphs let you use regular Python control flow during the forward pass!

Initialize two different weight matrices for second layer



```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2a = torch.randn(H, D_out, requires_grad=True)
w2b = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
prev_loss = 5.0
for t in range(500):
    w2 = w2a if prev_loss < 5.0 else w2b
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()

    loss.backward()
    prev_loss = loss.item()
```

PyTorch: Dynamic Computation Graphs

benefit

Dynamic graphs let you use regular Python control flow during the forward pass!

Decide which one to use at each layer based on loss at previous iteration

(this model doesn't make sense! Just a simple dynamic example)

```
import torch

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2a = torch.randn(H, D_out, requires_grad=True)
w2b = torch.randn(H, D_out, requires_grad=True)

learning_rate = 1e-6
prev_loss = 5.0
for t in range(500):
    w2 = w2a if prev_loss < 5.0 else w2b
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()


    loss.backward()
    prev_loss = loss.item()
```

Alternative: Static Computation Graphs

Alternative: **Static** graphs

Step 1: Build computational graph describing our computation (including finding paths for backprop)

Step 2: Reuse the same graph on every iteration



```
graph = build_graph()

for x_batch, y_batch in loader:
    run_graph(graph, x=x_batch, y=y_batch)
```

PyTorch: Static Graphs with JIT

Define model as a
Python function

```
import torch
```

```
def model(x, y, w1, w2a, w2b, prev_loss):  
    w2 = w2a if prev_loss < 5.0 else w2b  
    y_pred = x.mm(w1).clamp(min=0).mm(w2)  
    loss = (y_pred - y).pow(2).sum()  
    return loss
```

```
N, D_in, H, D_out = 64, 1000, 100, 10  
x = torch.randn(N, D_in)  
y = torch.randn(N, D_out)  
w1 = torch.randn(D_in, H, requires_grad=True)  
w2a = torch.randn(H, D_out, requires_grad=True)  
w2b = torch.randn(H, D_out, requires_grad=True)
```

```
graph = torch.jit.script(model)
```

```
prev_loss = 5.0  
learning_rate = 1e-6  
for t in range(500):  
    loss = graph(x, y, w1, w2a, w2b, prev_loss).  
  
    loss.backward()  
    prev_loss = loss.item()
```


PyTorch: Static Graphs with JIT

Just-In-Time compilation:
Introspect the source code
of the function, **compile** it
into a graph object.

Lots of magic here!

```
import torch

def model(x, y, w1, w2a, w2b, prev_loss):
    w2 = w2a if prev_loss < 5.0 else w2b
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()
    return loss


N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2a = torch.randn(H, D_out, requires_grad=True)
w2b = torch.randn(H, D_out, requires_grad=True)

graph = torch.jit.script(model)

prev_loss = 5.0
learning_rate = 1e-6
for t in range(500):
    loss = graph(x, y, w1, w2a, w2b, prev_loss)

    loss.backward()
    prev_loss = loss.item()
```

PyTorch: Static Graphs with JIT



```
import torch
```

```
def model(x, y, w1, w2a, w2b, prev_loss):  
    w2 = w2a if prev_loss < 5.0 else w2b  
    y_pred = x.mm(w1).clamp(min=0).mm(w2)  
    loss = (y_pred - y).pow(2).sum()  
    return loss
```

```
N, D_in, H, D_out = 64, 1000, 100, 10
```

```
x = torch.randn(N, D_in)
```

```
y = torch.randn(N, D_out)
```

```
w1 = torch.randn(D_in, H, requires_grad=True)
```

```
w2a = torch.randn(H, D_out, requires_grad=True)
```

```
w2b = torch.randn(H, D_out, requires_grad=True)
```

```
graph = torch.jit.script(model)
```

```
prev_loss = 5.0
```

```
learning_rate = 1e-6
```

```
for t in range(500):
```

```
    loss = graph(x, y, w1, w2a, w2b, prev_loss.)
```

```
    loss.backward()
```

```
    prev_loss = loss.item()
```

PyTorch: Static Graphs with JIT

Use our compiled graph object at each forward pass

```
import torch

def model(x, y, w1, w2a, w2b, prev_loss):
    w2 = w2a if prev_loss < 5.0 else w2b
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()
    return loss

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2a = torch.randn(H, D_out, requires_grad=True)
w2b = torch.randn(H, D_out, requires_grad=True)

graph = torch.jit.script(model)

prev_loss = 5.0
learning_rate = 1e-6
for t in range(500):
    loss = graph(x, y, w1, w2a, w2b, prev_loss).
    loss.backward()
    prev_loss = loss.item()
```

PyTorch: Static Graphs with JIT

Even easier: add **annotation** to function, Python function compiled to a graph when it is defined

Calling function uses graph

```
import torch

@torch.jit.script
def model(x, y, w1, w2a, w2b, prev_loss):
    w2 = w2a if prev_loss < 5.0 else w2b
    y_pred = x.mm(w1).clamp(min=0).mm(w2)
    loss = (y_pred - y).pow(2).sum()
    return loss

N, D_in, H, D_out = 64, 1000, 100, 10
x = torch.randn(N, D_in)
y = torch.randn(N, D_out)
w1 = torch.randn(D_in, H, requires_grad=True)
w2a = torch.randn(H, D_out, requires_grad=True)
w2b = torch.randn(H, D_out, requires_grad=True)


prev_loss = 5.0
learning_rate = 1e-6
for t in range(500):
    loss = model(x, y, w1, w2a, w2b, prev_loss)

    loss.backward()
    prev_loss = loss.item()
```


Static vs Dynamic Graphs: Optimization

With static graphs, framework can **optimize** the graph for you before it runs!

The graph you wrote



Equivalent graph with **fused operations**



Static vs Dynamic Graphs: Serialization

Static

Once graph is built, can **serialize** it and run it without the code that built the graph!

e.g. train model in Python, deploy in C++

↖ can run in C++ with python.

Dynamic

Graph building and execution are intertwined, so always need to keep code around

need python interpreter every time

Static vs Dynamic Graphs: Debugging

Static


Lots of indirection between the code you write and the code that runs – can be hard to debug, benchmark, etc

Dynamic

The code you write is the code that runs! Easy to reason about, debug, profile, etc

Dynamic Graph Applications


Model structure
depends on the input:
- Recurrent Networks



Dynamic Graph Applications

Model structure
depends on the input:

- Recurrent Networks
- Recursive Networks




Karpathy and Fei-Fei, "Deep Visual-Semantic Alignments for Generating Image Descriptions", CVPR 2015

Dynamic Graph Applications

Model structure depends on the input:

- Recurrent Networks
- Recursive Networks
- Modular Networks




Andreas et al, "Neural Module Networks", CVPR 2016

Andreas et al, "Learning to Compose Neural Networks for Question Answering", NAACL 2016

Johnson et al, "Inferring and Executing Programs for Visual Reasoning", ICCV 2017

Dynamic Graph Applications

- Model structure depends on the input:
- Recurrent Networks
 - Recursive Networks
 - Modular Networks
 - (Your idea here!)



Andreas et al, "Neural Module Networks", CVPR 2016

Andreas et al, "Learning to Compose Neural Networks for Question Answering", NAACL 2016

Johnson et al, "Inferring and Executing Programs for Visual Reasoning", ICCV 2017

TensorFlow

TensorFlow Versions

TensorFlow 1.0

- Final release: 1.15.0-rc2
 - Released yesterday!
- Default: **static graphs**
- Optional: dynamic graphs (eager mode)

TensorFlow 2.0

- Released Monday 9/30!
- Default: **dynamic graphs**
- Optional: static graphs

TensorFlow 1.0: Static Graphs

```
import numpy as np
import tensorflow as tf
```

(Assume imports at the
top of each snippet)

```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])

with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D),}
    out = sess.run([loss, grad_w1, grad_w2],
                    feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow 1.0: Static Graphs

First **define** computational
graph




```
N, D, H = 64, 1000, 100
x = tf.placeholder(tf.float32, shape=(N, D))
y = tf.placeholder(tf.float32, shape=(N, D))
w1 = tf.placeholder(tf.float32, shape=(D, H))
w2 = tf.placeholder(tf.float32, shape=(H, D))

h = tf.maximum(tf.matmul(x, w1), 0)
y_pred = tf.matmul(h, w2)
diff = y_pred - y
loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

grad_w1, grad_w2 = tf.gradients(loss, [w1, w2])
```

Then **run** the graph many
times



```
with tf.Session() as sess:
    values = {x: np.random.randn(N, D),
              w1: np.random.randn(D, H),
              w2: np.random.randn(H, D),
              y: np.random.randn(N, D),}
    out = sess.run([loss, grad_w1, grad_w2],
                    feed_dict=values)
    loss_val, grad_w1_val, grad_w2_val = out
```

TensorFlow 2.0: Dynamic Graphs

Create TensorFlow
Tensors for data and
weights

Weights need to be
wrapped in `tf.Variable`
so we can mutate them

```
import tensorflow as tf

N, Din, H, Dout = 16, 1000, 100, 10

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))
w1 = tf.Variable(tf.random.normal((Din, H)))
w2 = tf.Variable(tf.random.normal((H, Dout)))

learning_rate = 1e-6
for t in range(1000):
    with tf.GradientTape() as tape:
        h = tf.maximum(tf.matmul(x, w1), 0)
        y_pred = tf.matmul(h, w2)
        diff = y_pred - y
        loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

    grad_w1, grad_w2 = tape.gradient(loss, [w1, w2])

    w1.assign(w1 - learning_rate * grad_w1)
    w2.assign(w2 - learning_rate * grad_w2)
```


TensorFlow 2.0: Dynamic Graphs

Scope forward pass
under a GradientTape to
tell TensorFlow to start
building a graph

```
import tensorflow as tf

N, Din, H, Dout = 16, 1000, 100, 10

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))
w1 = tf.Variable(tf.random.normal((Din, H)))
w2 = tf.Variable(tf.random.normal((H, Dout)))

learning_rate = 1e-6
for t in range(1000):
    with tf.GradientTape() as tape:
        h = tf.maximum(tf.matmul(x, w1), 0)
        y_pred = tf.matmul(h, w2)
        diff = y_pred - y
        loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

    grad_w1, grad_w2 = tape.gradient(loss, [w1, w2])

    w1.assign(w1 - learning_rate * grad_w1)
    w2.assign(w2 - learning_rate * grad_w2)
```

TensorFlow 2.0: Dynamic Graphs

Ask the tape to
compute gradients



```
import tensorflow as tf

N, Din, H, Dout = 16, 1000, 100, 10

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))
w1 = tf.Variable(tf.random.normal((Din, H)))
w2 = tf.Variable(tf.random.normal((H, Dout)))

learning_rate = 1e-6
for t in range(1000):
    with tf.GradientTape() as tape:
        h = tf.maximum(tf.matmul(x, w1), 0)
        y_pred = tf.matmul(h, w2)
        diff = y_pred - y
        loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

    grad_w1, grad_w2 = tape.gradient(loss, [w1, w2])

    w1.assign(w1 - learning_rate * grad_w1)
    w2.assign(w2 - learning_rate * grad_w2)
```

TensorFlow 2.0: Dynamic Graphs

```
import tensorflow as tf

N, Din, H, Dout = 16, 1000, 100, 10

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))
w1 = tf.Variable(tf.random.normal((Din, H)))
w2 = tf.Variable(tf.random.normal((H, Dout)))

learning_rate = 1e-6
for t in range(1000):
    with tf.GradientTape() as tape:
        h = tf.maximum(tf.matmul(x, w1), 0)
        y_pred = tf.matmul(h, w2)
        diff = y_pred - y
        loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

    grad_w1, grad_w2 = tape.gradient(loss, [w1, w2])


    w1.assign(w1 - learning_rate * grad_w1)
    w2.assign(w2 - learning_rate * grad_w2)
```

Gradient descent
step, update weights



TensorFlow 2.0: Static Graphs

Define a function that
implements forward,
backward, and update



Annotating with
tf.function will compile
the function into a graph!
(similar to torch.jit.script)

```
@tf.function
def step(x, y, w1, w2):
    with tf.GradientTape() as tape:
        h = tf.maximum(tf.matmul(x, w1), 0)
        y_pred = tf.matmul(h, w2)
        diff = y_pred - y
        loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

    grad_w1, grad_w2 = tape.gradient(loss, [w1, w2])

    w1.assign(w1 - learning_rate * grad_w1)
    w2.assign(w2 - learning_rate * grad_w2)
    return loss
```

```
N, Din, H, Dout = 16, 1000, 100, 10

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))
w1 = tf.Variable(tf.random.normal((Din, H)))
w2 = tf.Variable(tf.random.normal((H, Dout)))

learning_rate = 1e-6
for t in range(1000):
    loss = step(x, y, w1, w2)
```


TensorFlow 2.0: Static Graphs

Define a function that
implements forward,
backward, and update

Annotating with
tf.function will compile
the function into a graph!
(similar to torch.jit.script)

(note TF graph can
include gradient
computation and update,
unlike PyTorch)

```
@tf.function
def step(x, y, w1, w2):
    with tf.GradientTape() as tape:
        h = tf.maximum(tf.matmul(x, w1), 0)
        y_pred = tf.matmul(h, w2)
        diff = y_pred - y
        loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

        grad_w1, grad_w2 = tape.gradient(loss, [w1, w2])

        w1.assign(w1 - learning_rate * grad_w1)
        w2.assign(w2 - learning_rate * grad_w2)
    return loss


N, Din, H, Dout = 16, 1000, 100, 10

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))
w1 = tf.Variable(tf.random.normal((Din, H)))
w2 = tf.Variable(tf.random.normal((H, Dout)))

learning_rate = 1e-6
for t in range(1000):
    loss = step(x, y, w1, w2)
```

TensorFlow 2.0: Static Graphs

Call the compiled step
function in the training
loop



```
@tf.function
def step(x, y, w1, w2):
    with tf.GradientTape() as tape:
        h = tf.maximum(tf.matmul(x, w1), 0)
        y_pred = tf.matmul(h, w2)
        diff = y_pred - y
        loss = tf.reduce_mean(tf.reduce_sum(diff ** 2, axis=1))

    grad_w1, grad_w2 = tape.gradient(loss, [w1, w2])

    w1.assign(w1 - learning_rate * grad_w1)
    w2.assign(w2 - learning_rate * grad_w2)
    return loss

N, Din, H, Dout = 16, 1000, 100, 10

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))
w1 = tf.Variable(tf.random.normal((Din, H)))
w2 = tf.Variable(tf.random.normal((H, Dout)))

learning_rate = 1e-6
for t in range(1000):
    loss = step(x, y, w1, w2)
```

Keras: High-level API

```
import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import InputLayer, Dense

N, Din, H, Dout = 16, 1000, 100, 10

model = Sequential()
model.add(InputLayer(input_shape=(Din,)))
model.add(Dense(units=H, activation='relu'))
model.add(Dense(units=Dout))
params = model.trainable_variables

loss_fn = tf.keras.losses.MeanSquaredError()
opt = tf.keras.optimizers.SGD(learning_rate=1e-6)

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))

for t in range(1000):
    with tf.GradientTape() as tape:
        y_pred = model(x)
        loss = loss_fn(y_pred, y)
        grads = tape.gradient(loss, params)
        opt.apply_gradients(zip(grads, params))
```

Keras: High-level API

Object-oriented API:
build the model as a
stack of layers

```
import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import InputLayer, Dense

N, Din, H, Dout = 16, 1000, 100, 10

model = Sequential()
model.add(InputLayer(input_shape=(Din,)))
model.add(Dense(units=H, activation='relu'))
model.add(Dense(units=Dout))
params = model.trainable_variables

loss_fn = tf.keras.losses.MeanSquaredError()
opt = tf.keras.optimizers.SGD(learning_rate=1e-6)

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))

for t in range(1000):
    with tf.GradientTape() as tape:
        y_pred = model(x)
        loss = loss_fn(y_pred, y)
        grads = tape.gradient(loss, params)
        opt.apply_gradients(zip(grads, params))
```


Keras: High-level API

Keras gives you
common loss
functions and
optimization
algorithms



```
import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import InputLayer, Dense

N, Din, H, Dout = 16, 1000, 100, 10

model = Sequential()
model.add(InputLayer(input_shape=(Din,)))
model.add(Dense(units=H, activation='relu'))
model.add(Dense(units=Dout))
params = model.trainable_variables

loss_fn = tf.keras.losses.MeanSquaredError()
opt = tf.keras.optimizers.SGD(learning_rate=1e-6)

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))

for t in range(1000):
    with tf.GradientTape() as tape:
        y_pred = model(x)
        loss = loss_fn(y_pred, y)
        grads = tape.gradient(loss, params)
        opt.apply_gradients(zip(grads, params))
```

Keras: High-level API

Forward pass:
Compute loss,
build graph

Backward pass:
compute gradients

```
import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import InputLayer, Dense


N, Din, H, Dout = 16, 1000, 100, 10

model = Sequential()
model.add(InputLayer(input_shape=(Din,)))
model.add(Dense(units=H, activation='relu'))
model.add(Dense(units=Dout))
params = model.trainable_variables

loss_fn = tf.keras.losses.MeanSquaredError()
opt = tf.keras.optimizers.SGD(learning_rate=1e-6)

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))

for t in range(1000):
    with tf.GradientTape() as tape:
        y_pred = model(x)
        loss = loss_fn(y_pred, y)
        grads = tape.gradient(loss, params)
        opt.apply_gradients(zip(grads, params))
```



Keras: High-level API

```
import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import InputLayer, Dense

N, Din, H, Dout = 16, 1000, 100, 10


model = Sequential()
model.add(InputLayer(input_shape=(Din,)))
model.add(Dense(units=H, activation='relu'))
model.add(Dense(units=Dout))
params = model.trainable_variables

loss_fn = tf.keras.losses.MeanSquaredError()
opt = tf.keras.optimizers.SGD(learning_rate=1e-6)

x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))

for t in range(1000):
    with tf.GradientTape() as tape:
        y_pred = model(x)
        loss = loss_fn(y_pred, y)
        grads = tape.gradient(loss, params)
        opt.apply_gradients(zip(grads, params))
```

Optimizer object
updates parameters



Keras: High-level API

Define a function
that returns the loss



```
import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import InputLayer, Dense

N, Din, H, Dout = 16, 1000, 100, 10

model = Sequential()
model.add(InputLayer(input_shape=(Din,)))
model.add(Dense(units=H, activation='relu'))
model.add(Dense(units=Dout))

params = model.trainable_variables

loss_fn = tf.keras.losses.MeanSquaredError()
opt = tf.keras.optimizers.SGD(learning_rate=1e-6)


x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))

def step():
    y_pred = model(x)
    loss = loss_fn(y_pred, y)
    return loss

for t in range(1000):
    opt.minimize(step, params)
```


Keras: High-level API

Optimizer computes
gradients and
updates parameters



```
import tensorflow as tf
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import InputLayer, Dense

N, Din, H, Dout = 16, 1000, 100, 10

model = Sequential()
model.add(InputLayer(input_shape=(Din,)))
model.add(Dense(units=H, activation='relu'))
model.add(Dense(units=Dout))

params = model.trainable_variables

loss_fn = tf.keras.losses.MeanSquaredError()
opt = tf.keras.optimizers.SGD(learning_rate=1e-6)



x = tf.random.normal((N, Din))
y = tf.random.normal((N, Dout))

def step():
    y_pred = model(x)
    loss = loss_fn(y_pred, y)
    return loss

for t in range(1000):
    opt.minimize(step, params)
```



TensorBoard

Add logging to code to record loss, stats, etc
Run server and get pretty graphs!



TensorBoard

Also works with PyTorch: [torch.utils.tensorboard](https://pytorch.org/docs/stable/torchutils.html#torch.utils.tensorboard)



PyTorch vs TensorFlow

PyTorch

- My personal favorite
- Clean, imperative API
- Easy dynamic graphs for debugging
- JIT allows static graphs for production
- Cannot use TPUs
- Not easy to deploy on mobile

TensorFlow 1.0

- Static graphs by default
- Can be confusing to debug
- API a bit messy

TensorFlow 2.0


- Dynamic by default
- Standardized on Keras API
- Just came out, no consensus yet

Summary: Hardware

CPU



GPU



TPU



Summary: Software

Static Graphs vs Dynamic Graphs

PyTorch vs TensorFlow

Next time:
Training Neural Networks