

Makkar (2020)

Minh Chau Do

09 10 2023

Daten von Makkar (2020)

```
#Datensortierung

# In Mortalität umrechnen
makkar2020_r$V2 <- 100 - makkar2020_r$V2

makkar2020_r <- makkar2020_r[complete.cases(makkar2020_r),]

makkar2020_r <- makkar2020_r[order(makkar2020_r$V2), ]

# Werte außerhalb des Bereichs [0, inf] raus
makkar2020_r <- makkar2020_r[makkar2020_r$V1 >= 0, ]
xr_makkar2020 <- sort(makkar2020_r$V1)
yr_makkar2020 <- makkar2020_r$V2

# In Mortalität umrechnen
makkar2020_b$V2 <- 100 - makkar2020_b$V2

makkar2020_b <- makkar2020_b[complete.cases(makkar2020_b),]

makkar2020_b <- makkar2020_b[order(makkar2020_b$V2), ]

# Werte außerhalb des Bereichs [0, inf] raus
makkar2020_b <- makkar2020_b[makkar2020_b$V1 >= 0, ]
xb_makkar2020 <- sort(makkar2020_b$V1)
yb_makkar2020 <- makkar2020_b$V2
```

Startfunktion

Um die bestmögliche Anpassung an den vorliegenden Datenpunkten darzustellen wurde mithilfe einer Funktion der beste Startparameter mit dem kleinsten Fehler ermittelt, da die Anpassung stark von den initialen Startwerten abhängig ist.

```
find_best_start_2parameter <- function(p, q, max_beta, max_eta, steps_beta,
                                       steps_eta, fitting_function) {

  best_errors <- numeric() # Vektor für Fehlerwerte
  best_starts <- matrix(nrow = 0, ncol = 2) # Matrix für Startparameter
```

```

for (beta in seq(0, max_beta, by = steps_beta)) {
  for (eta in seq(0, max_eta, by = steps_eta)) {
    start_params <- c(beta, eta)

    # Schätze die Parameter mit den aktuellen Startparametern
    if(identical(as.character(substitute(fitting_function)), "getstuexp2")){
      output <- capture.output({
        result <- getstuexp2(
          p = p, q = q, start = start_params,
          show.output = TRUE, plot = FALSE, wert1 = 2
        )
      })
    }
    else{
      output <- capture.output({
        result <- fitting_function(p = p, q = q, start = start_params,
          show.output = TRUE, plot = FALSE)
      })
    }

    # Berechne den Fehler (makkar2020_r_1$value) für die aktuellen Startparameter
    current_error <- as.numeric(gsub("\\[1\\]\\s+", "", output[5]))

    # Speichere Fehler und die Startparameter, wenn der Fehler nicht NA ist
    if (!is.na(current_error)) {
      best_errors <- c(best_errors, current_error)
      best_starts <- rbind(best_starts, start_params)
    }
  }
}

# Finde den Index des kleinsten Fehlers (ignoriere NA-Werte)
best_index <- which.min(best_errors)

# Wähle den besten Startparameter mit dem kleinsten Fehler aus
best_start <- best_starts[best_index, ]

# Gib den besten Startparameter und den entsprechenden Fehler aus
cat("Bester Startparameter:", best_start, "\n")
cat("Bester Fehler:", best_errors[best_index], "\n")

return(best_start)
}

find_best_start_3parameter <- function(p, q, max_shape1 = 10, max_shape2 = 10,
  max_scale = 10, steps_shape1, steps_shape2,
  steps_scale, fitting_function) {

  best_errors <- numeric() # Vektor für Fehlerwerte
  best_starts <- matrix(nrow = 0, ncol = 3) # Matrix für Startparameter

```

```

for (shape1 in seq(0, max_shape1, by = steps_shape1)) {
  for (shape2 in seq(0, max_shape2, by = steps_shape2)) {
    for (scale in seq(0, max_shape1, by = steps_scale)) {
      start_params <- c(shape1, shape2, scale)

      # Schätze die Parameter mit den aktuellen Startparametern
      if(identical(as.character(substitute(fitting_function)), "getstuexp3")){
        output <- capture.output({
          result <- getstuexp3(
            p = p, q = q, start = start_params,
            show.output = TRUE, plot = FALSE, wert1 = 2, wert2 = 6)
        })
      }

      else{
        output <- capture.output({
          result <- fitting_function(p = p, q = q, start = start_params,
            show.output = TRUE, plot = FALSE)
        })
      }

      # Berechne den Fehler (makkar2020_r_1$value) für die aktuellen Startparameter
      current_error <- as.numeric(gsub("\\[1\\]\\s+", "", output[5]))

      # Speichere Fehler und die Startparameter, wenn der Fehler nicht NA ist
      if (!is.na(current_error)) {
        best_errors <- c(best_errors, current_error)
        best_starts <- rbind(best_starts, start_params)
      }
    }
  }
}

# Finde den Index des kleinsten Fehlers (ignoriere NA-Werte)
best_index <- which.min(best_errors)

# Wähle den besten Startparameter mit dem kleinsten Fehler aus
best_start <- best_starts[best_index, ]

# Gib den besten Startparameter und den entsprechenden Fehler aus
cat("Bester Startparameter:", best_start, "\n")
cat("Bester Fehler:", best_errors[best_index], "\n")

return(best_start)
}

find_best_start_4parameter <- function(p, q, max_shape, max_scale, max_rate,
                                       max_mix, steps_shape, steps_scale,
                                       steps_rate, steps_mix, fitting_function) {

  best_errors <- numeric() # Vektor für Fehlerwerte

```

```

best_starts <- matrix(nrow = 0, ncol = 4) # Matrix für Startparameter

for (shape in seq(0, max_shape, by = steps_shape)) {
  for (scale in seq(0, max_scale, by = steps_scale)) {
    for (rate in seq(0, max_rate, by = steps_rate)) {
      for (mix in seq(0, max_mix, by = steps_mix)) {
        start_params <- c(shape, scale, rate, mix)

        # Schätze die Weibull-Parameter mit den aktuellen Startparametern
        output <- capture.output({
          result <- fitting_function(p = p, q = q, start = start_params,
                                     show.output = TRUE, plot = FALSE)
        })

        # Berechne den Fehler (makkar2020_r_1$value) für die aktuellen Startparameter
        current_error <- as.numeric(gsub("\\[1\\]\\s+", "", output[5]))

        # Speichere Fehler und die Startparameter, wenn der Fehler nicht NA ist
        if (!is.na(current_error)) {
          best_errors <- c(best_errors, current_error)
          best_starts <- rbind(best_starts, start_params)
        }
      }
    }
  }
}

# Finde den Index des kleinsten Fehlers (ignoriere NA-Werte)
best_index <- which.min(best_errors)

# Wähle den besten Startparameter mit dem kleinsten Fehler aus
best_start <- best_starts[best_index, ]

# Gib den besten Startparameter und den entsprechenden Fehler aus
cat("Bester Startparameter:", best_start, "\n")
cat("Bester Fehler:", best_errors[best_index], "\n")

return(best_start)
}

```

Datenanpassung an die Daten von Makkar (2020)

Weibullverteilung

```

# Weibullverteilung
source("C:/Users/nhonh/OneDrive/Dokumente/Unikrams/Masterarbeit/R Funktionen/getweibullpar.R")

best_makkar2020_r_1 <- find_best_start_2parameter(p = yr_makkar2020/100, q = xr_makkar2020,
                                                  max_beta = 10, max_eta = 10,
                                                  steps_beta = 1, steps_eta = 1,
                                                  fitting_function = getweibullpar)

```


```
## Bester Startparameter: 5 4
```

```
makkar2020_r_1 <- getweibullpar(
  p = yr_makkar2020/100,
  q = xr_makkar2020,
  start = best_makkar2020_r_1,
  show.output = TRUE,
  plot = TRUE
)
```

```
makkar2020_r_1
```

```
##      shape      scale  
## 0.6213152 184.1955121
```

```
plot(xr_makkar2020,  
     pweibull(xr_makkar2020,  
              scale = makkar2020_r_1["scale"],  
              shape = makkar2020_r_1["shape"]), type = "l")
```



```
best_makkar2020_b_1 <- find_best_start_2parameter(p = yb_makkar2020/100, q = xb_makkar2020,  
                                                  max_beta = 10, max_eta = 10,  
                                                  steps_beta = 1, steps_eta = 1,  
                                                  fitting_function = getweibullpar)
```


```
## Bester Startparameter: 2 3  
## Bester Fehler: 5.51537e-06
```

```
makkar2020_b_1 <- getweibullpar(  
  p = yb_makkar2020/100,  
  q = xb_makkar2020,  
  start = best_makkar2020_b_1,  
  show.output = TRUE,  
  plot = TRUE  
)
```


```
## $par  
## [1] 0.8953249 110.0154033
```

```
##  
## $value  
## [1] 5.51537e-06  
##  
## $counts  
## function gradient  
##      75      75  
##  
## $convergence  
## [1] 0  
##  
## $message  
## [1] "CONVERGENCE: REL_REDUCTION_OF_F <= FACTR*EPSMCH"
```

Weibull (shape = 0.895, scale = 110)

[illegible]

```
plot(xb_makkar2020,
     pweibull(xb_makkar2020,
              scale = makkar2020_b_1["scale"],
              shape = makkar2020_b_1["shape"]), type = "l")
```



Exponentiierte Weibullverteilung

```
# exponentiierte Weibullverteilung
source("C:/Users/nhonh/OneDrive/Dokumente/Unikrams/Masterarbeit/R Funktionen/getweibpar.R")

best_weibbull_xr_makkar2020 <- find_best_start_2parameter(p = yr_makkar2020/100,
                                                         q = xr_makkar2020,
                                                         max_beta = 10,
                                                         max_eta = 10,
                                                         steps_beta = 1,
                                                         steps_eta = 1,
                                                         fitting_function = getweibpar)

## Bester Startparameter: 6 0
## Bester Fehler: 6.825406e-06


weibbull_xr_makkar2020 <- getweibpar(
  p = yr_makkar2020/100,
  q = xr_makkar2020,
  start = best_weibbull_xr_makkar2020,
  show.output = TRUE,
  plot = TRUE
)

## $par
## [1] 0.1868055 7.7442109
```



```
##  
## $value  
## [1] 6.825406e-06  
##  
## $counts  
## function gradient  
##      37      37  
##  
## $convergence  
## [1] 0  
##  
## $message  
## [1] "CONVERGENCE: REL_REDUCTION_OF_F <= FACTR*EPSMCH"
```

exp. Weibull (alpha = 0.187, theta = 7.74)


[illegible]

weibbull_xr_makkar2020

```
##      alpha      theta
## 0.1868055 7.7442109
```

```
plot(xr_makkar2020,
     pexpo.weibull(xr_makkar2020,
                   alpha = weibbull_xr_makkar2020 ["alpha"],
                   theta = weibbull_xr_makkar2020 ["theta"]), type = "l")
```

2020, alpha = weibull_xr_makkar2020["alpha"], theta = weibull



```
best_weibull_xb_makkar2020 <- find_best_start_2parameter(p = yb_makkar2020/100,
                                                       q = xb_makkar2020,
                                                       max_beta = 10,
                                                       max_eta = 10,
                                                       steps_beta = 1,
                                                       steps_eta = 1,
                                                       fitting_function = getweibpar)
```


```
## Bester Startparameter: 1 7
## Bester Fehler: 8.451577e-06
```

```
weibull_xb_makkar2020 <- getweibpar(
  p = yb_makkar2020/100,
  q = xb_makkar2020,
  start = best_weibull_xb_makkar2020,
  show.output = TRUE,
  plot = TRUE
)
```

```
## $par
## [1] 0.2348442 11.2479479
##
## $value
## [1] 8.451577e-06
##
## $counts
## function gradient
```

```
##          27          27
##
## $convergence
## [1] 0
##
## $message
## [1] "CONVERGENCE: REL_REDUCTION_OF_F <= FACTR*EPSMCH"
```

exp. Weibull (alpha = 0.235, theta = 11.2)


[illegible]

weibbull_xb_makkar2020

```
##      alpha      theta
## 0.2348442 11.2479479
```

```
plot(xb_makkar2020,
     pexpo.weibull(xb_makkar2020,
                   alpha = weibbull_xb_makkar2020 ["alpha"],
                   theta = weibbull_xb_makkar2020 ["theta"]), type = "l")
```

020, alpha = weibull_xb_makkar2020["alpha"], theta = weibull_xb_makkar2020["theta"])



Mischung aus Weibull- und Exponentialverteilung

```
# Mischung aus Weibull- und Exponentialverteilung
source("C:/Users/nhonh/OneDrive/Dokumente/Unikrams/Masterarbeit/R Funktionen/getweibex.R")

best_weibex_xr_makkar2020 <- find_best_start_4parameter(p = yr_makkar2020/100,
                                                       q = xr_makkar2020,
                                                       max_shape = 1,
                                                       max_scale = 100,
                                                       max_rate = 0.7,
                                                       max_mix = 1,
                                                       steps_shape = 0.1,
                                                       steps_scale = 20,
                                                       steps_rate = 0.1,
                                                       steps_mix = 0.1,
                                                       fitting_function = getweibex)

## Bester Startparameter: 0.9 80 0.5 0.1
## Bester Fehler: 5.604454e-07


weibex_xr_makkar2020 <- getweibex(
  p = yr_makkar2020/100,
  q = xr_makkar2020,
  start = best_weibex_xr_makkar2020, # c(0.5, 60, 0.4, 0.1),
  show.output = TRUE,
  plot = TRUE)
```



```

        shape = weibex_xr_makkar2020["shape"],
        scale = weibex_xr_makkar2020["scale"]) +
(1 - exp(weibex_xr_makkar2020["mix"])) / (1 + exp(weibex_xr_makkar2020["mix"]))) *
stats::pexp(q = xr_makkar2020,
            rate = weibex_xr_makkar2020["rate"])),
type = "l")

```



```

best_weibex_xb_makkar2020 <- find_best_start_4parameter(p = yb_makkar2020/100,
q = xb_makkar2020,
max_shape = 1,
max_scale = 100,
max_rate = 0.7,
max_mix = 1,
steps_shape = 0.1,
steps_scale = 20,
steps_rate = 0.1,
steps_mix = 0.1,
fitting_function = getweibex)

```

```

## Bester Startparameter: 0.8 100 0.5 1
## Bester Fehler: 5.936047e-07

```

```

weibex_xb_makkar2020 <- getweibex(
p = yb_makkar2020/100,
q = xb_makkar2020,
start = best_weibex_xb_makkar2020, # c(0.5, 60, 0.7, 0.1),
show.output = TRUE,


```



```

        shape = weibex_xb_makkar2020["shape"],
        scale = weibex_xb_makkar2020["scale"]) +
(1 - exp(weibex_xb_makkar2020["mix"])) / (1 + exp(weibex_xb_makkar2020["mix"])) *
stats::pexp(q = xb_makkar2020,
            rate = weibex_xb_makkar2020["rate"])),
type = "l")

```



Mischung von exponentiierter Weibull- und Exponentialverteilung

```

# Mischung von exponentiierter Weibull- und Exponentialverteilung
source("C:/Users/nhonh/OneDrive/Dokumente/Unikrams/Masterarbeit/R Funktionen/get2weibex.R")

best_weibex2_xr_makkar2020 <- find_best_start_4parameter(p = yr_makkar2020/100,
               q = xr_makkar2020,
               max_shape = 1,
               max_scale = 100,
               max_rate = 0.7,
               max_mix = 1,
               steps_shape = 0.1,
               steps_scale = 20,
               steps_rate = 0.1,
               steps_mix = 0.1,
               fitting_function = get2weibex)


## Bester Startparameter: 0.4 20 0.7 0.8

```



```
weibex2_xr_makkar2020 <- get2weibex(  
  p = yr_makkar2020/100,  
  q = xr_makkar2020,  
  start = best_weibex2_xr_makkar2020,  
  show.output = TRUE,  
  plot = TRUE  
)
```


```
exp.Weibull&Exponetial(alpha= 0.288, theta= 28.6, rate= 0.988, mix= 0.8)
```



```
weibex2_xr_makkar2020
```

```
##      alpha      theta      rate      mix
## 0.2880812 28.5805265 0.9879211 1.7577107
```

```
plot(xr_makkar2020,
      (exp(weibex2_xr_makkar2020["mix"]) / (1 + exp(weibex2_xr_makkar2020["mix"]))) *
      reliaR::pexpo.weibull(q = xr_makkar2020,
                           alpha = weibex2_xr_makkar2020["alpha"],
                           theta = weibex2_xr_makkar2020["theta"]) +
      (1 - exp(weibex2_xr_makkar2020["mix"]) / (1 + exp(weibex2_xr_makkar2020["mix"]))) *
      stats::pexp(q = xr_makkar2020,
                  rate = weibex2_xr_makkar2020["rate"])),
      type = "l")
```




```
best_weibex2_xb_makkar2020 <- find_best_start_4parameter(p = yb_makkar2020/100,
                                                         q = xb_makkar2020,
                                                         max_shape = 1,
                                                         max_scale = 100,
                                                         max_rate = 0.7,
                                                         max_mix = 1,
                                                         steps_shape = 0.1,
                                                         steps_scale = 20,
                                                         steps_rate = 0.1,
                                                         steps_mix = 0.1,
                                                         fitting_function = get2weibex)
```

```
weibex2_xb_makkar2020 <- get2weibex(  
  p = yb_makkar2020/100,  
  q = xb_makkar2020,  
  start = best_weibex2_xb_makkar2020,  
  show.output = TRUE,  
  plot = TRUE  
)
```

```
## $par
## [1] 0.3460935 59.9916544 0.2206192 1.6395206
##
## $value
## [1] 7.795408e-07
##
## $counts
## function gradient
##      35      35
##
## $convergence
## [1] 0
##
## $message
## [1] "CONVERGENCE: REL_REDUCTION_OF_F <= FACTR*EPSMCH"
```


```
exp.Weibull&Exponential(alpha= 0.346, theta= 60, rate= 0.221, mix= 0.8
```

[illegible]

```
weibex2_xb_makkar2020
```

```
##      alpha      theta      rate      mix
## 0.3460935 59.9916544 0.2206192 1.6395206
```

```
plot(xb_makkar2020,
      (exp(weibex2_xb_makkar2020["mix"]) / (1 + exp(weibex2_xb_makkar2020["mix"]))) *
      reliaR::pexpo.weibull(q = xb_makkar2020,
                           alpha = weibex2_xb_makkar2020["alpha"],
                           theta = weibex2_xb_makkar2020["theta"]) +
      (1 - exp(weibex2_xb_makkar2020["mix"]) / (1 + exp(weibex2_xb_makkar2020["mix"]))) *
      stats::pexp(q = xb_makkar2020,
                  rate = weibex2_xb_makkar2020["rate"])),
      type = "l")
```



Exponentiierte Weibullverteilung ohne Lambda = 1

```
# exponentiierte Weibullverteilung ohne Lambda = 1
source("C:/Users/nhonh/OneDrive/Dokumente/Unikrams/Masterarbeit/R Funktionen/getexpweib.R")

best_expweib_xr_makkar2020 <- find_best_start_3parameter(p = yr_makkar2020/100,
                                                         q = xr_makkar2020,
                                                         max_shape1 = 10,
                                                         max_shape2 = 10,
                                                         max_scale = 10,
                                                         steps_shape1 = 1,
```


```
steps_shape2 = 1,  
steps_scale = 1,  
fitting_function = getexpweib)
```

```
## Bester Startparameter: 2 10 1  
## Bester Fehler: 4.060702e-06
```

```
expweib_xr_makkar2020 <- getexpweib(  
  p = yr_makkar2020/100,  
  q = xr_makkar2020,  
  start = best_expweib_xr_makkar2020,  
  show.output = TRUE,  
  plot = TRUE  
)
```

```
## $par  
## [1] 331.0622803 2.1568081 0.2494453  
##  
## $value  
## [1] 4.060702e-06  
##  
## $counts  
## function gradient  
## 101 101  
##  
## $convergence  
## [1] 0  
##  
## $message  
## [1] "CONVERGENCE: REL_REDUCTION_OF_F <= FACTR*EPSMCH"
```


exp. Weibull (scale = 331, 1.shape = 2.16, 2.shape = 0.249)

[illegible]

expweib_xr_makkar2020

```
##          scale      1.shape      2.shape
## 331.0622803    2.1568081    0.2494453
```

```
plot(xr_makkar2020,
      (1 - exp(-(xr_makkar2020 / expweib_xr_makkar2020["scale"])^
                  (expweib_xr_makkar2020["1.shape"])))) ^ (expweib_xr_makkar2020["2.shape"]),
      type = "l")
```



```
best_expweib_xb_makkar2020 <- find_best_start_3parameter(p = yb_makkar2020/100,
  q = xb_makkar2020,
  max_shape1 = 10,
  max_shape2 = 10,
  max_scale = 10,
  steps_shape1 = 1,
  steps_shape2 = 1,
  steps_scale = 1,
  fitting_function = getexpweib)
```


```
## Bester Startparameter: 2 10 3
## Bester Fehler: 4.117816e-06
```

```
expweib_xb_makkar2020 <- getexpweib(
  p = yb_makkar2020/100,
  q = xb_makkar2020,
  start = best_expweib_xb_makkar2020,
  show.output = TRUE,
  plot = TRUE
)
```

```
## $par
## [1] 168.2794985 3.8990343 0.1974689
##
## $value
## [1] 4.117816e-06
##
```

```
## $counts
## function gradient
##      90      90
##
## $convergence
## [1] 0
##
## $message
## [1] "CONVERGENCE: REL_REDUCTION_OF_F <= FACTR*EPSMCH"
```


exp. Weibull (scale = 168, 1.shape = 3.9, 2.shape = 0.197)

[illegible]

expweib_xb_makkar2020

```
##          scale      1.shape      2.shape
## 168.2794985  3.8990343  0.1974689
```

```
plot(xb_makkar2020,
      (1 - exp(-(xb_makkar2020 / expweib_xb_makkar2020["scale"])-(expweib_xb_makkar2020["1.shape"])))^(expweib_xb_makkar2020["1.shape"])))^2,
      type = "l")
```

3-Stufige Exponentialverteilung


```
# 3-Stufige Exponentialverteilung
source("C:/Users/nhonh/OneDrive/Dokumente/Unikrams/Masterarbeit/R Funktionen/getstuexp3.R")
```

```
best_stuexp3_xr_makkar2020 <- find_best_start_3parameter(p = yr_makkar2020/100,
                                                         q = xr_makkar2020,
                                                         max_shape1 = 0.1,
                                                         max_shape2 = 0.1,
                                                         max_scale = 0.1,
                                                         steps_shape1 = 0.01,
                                                         steps_shape2 = 0.01,
                                                         steps_scale = 0.01,
                                                         fitting_function = getstuexp3)
```

```
## Bester Startparameter: 0.07 0.03 0.04
## Bester Fehler: 1.611591e-06
```

```
stuexp3_xr_makkar2020 <- getstuexp3(
  p = yr_makkar2020/100,
  q = xr_makkar2020,
  start = best_stuexp3_xr_makkar2020,
  show.output = TRUE,
  plot = TRUE,
  wert1 = 2,
  wert2 = 6)
```

3 stueckw. Exponential (1.para = 0.0488, 2.para = 0.00498, 3.para = 0.

[illegible]

stuexp3_xr_makkar2020


```
##      1.para      2.para      3.para
## 0.048832318 0.004982594 0.001000000
```

```
plot(xr_makkar2020,
      ((xr_makkar2020 > 0 & xr_makkar2020 <= 2) * (1 - exp(-stuexp3_xr_makkar2020[1] * xr_makkar2020)) +
       (xr_makkar2020 > 2 & xr_makkar2020 <= 6) *
       (1 - exp(-stuexp3_xr_makkar2020[1] * 2)) +
```

```

      (exp(-2 * stuexp3_xr_makkar2020[2]) -
        exp(-stuexp3_xr_makkar2020[2] * xr_makkar2020)) +
      (xr_makkar2020 > 6 & xr_makkar2020 <= 65 ) *
      (1 - exp(-stuexp3_xr_makkar2020[1] * 2)) +
      (exp(-2 * stuexp3_xr_makkar2020[2]) - exp(-6 * stuexp3_xr_makkar2020
      (exp(-6 * stuexp3_xr_makkar2020[3]) -
        exp(-stuexp3_xr_makkar2020[3] * xr_makkar2020))),
      type = "l")

```



```

best_stuexp3_xb_makkar2020 <- find_best_start_3parameter(p = yb_makkar2020/100,
  q = xb_makkar2020,
  max_shape1 = 0.1,
  max_shape2 = 0.1,
  max_scale = 0.1,
  steps_shape1 = 0.01,
  steps_shape2 = 0.01,
  steps_scale = 0.01,
  fitting_function = getstuexp3)

```

```

## Bester Startparameter: 0.05 0.04 0.02
## Bester Fehler: 2.634432e-06

```

```


stuexp3_xb_makkar2020 <- getstuexp3(
  p = yb_makkar2020/100,
  q = xb_makkar2020,
  start = best_stuexp3_xb_makkar2020,
  show.output = TRUE,

```

```
## $par
## [1] 0.028383143 0.005137945 0.002417541
##
## $value
## [1] 2.634432e-06
##
## $counts
## function gradient
##      46      46
##
## $convergence
## [1] 0
##
## $message
## [1] "CONVERGENCE: REL_REDUCTION_OF_F <= FACTR*EPSMCH"
```

```
##      1.para      2.para      3.para
## 0.028383143 0.005137945 0.002417541
```

```
plot(xb_makkar2020,
     ((xb_makkar2020 > 0 & xb_makkar2020 <= 2) * (1 - exp(-stuexp3_xb_makkar2020[1] * xb_makkar2020)) +
      (xb_makkar2020 > 2 & xb_makkar2020 <= 6) *
      (1 - exp(-stuexp3_xb_makkar2020[1] * 2)) +
      (exp(-2 * stuexp3_xb_makkar2020[2]) - exp(-stuexp3_xb_makkar2020[2] *
      xb_makkar2020)) +
      (xb_makkar2020 > 6 & xb_makkar2020 <= 65) *
      (1 - exp(-stuexp3_xb_makkar2020[1] * 2)) +
      (exp(-2 * stuexp3_xb_makkar2020[2]) - exp(-6 * stuexp3_xb_makkar2020
      (exp(-6 * stuexp3_xb_makkar2020[3]) -
      exp(-stuexp3_xb_makkar2020[3] * xb_makkar2020))),
     type = "l")
```



2-Stufige Exponentialverteilung


```
# 2-Stufige Exponentialverteilung
source("C:/Users/nhonh/OneDrive/Dokumente/Unikrams/Masterarbeit/R Funktionen/getstuexp2.R")

best_stuexp2_xr_makkar2020 <- find_best_start_2parameter(p = yr_makkar2020/100,
                                                         q = xr_makkar2020,
                                                         max_beta = 1,
                                                         max_eta = 0.5,
                                                         steps_beta = 0.1,
                                                         steps_eta = 0.01,
                                                         fitting_function = getstuexp2)
```

```
stuexp2_xr_makkar2020 <- getstuexp2(
  p = yr_makkar2020/100,
  q = xr_makkar2020,
  start = best_stuexp2_xr_makkar2020,
  show.output = TRUE,
  plot = TRUE,
  wert1 = 2
)
```

```
## $par
## [1] 0.057289445 0.006243732
##
## $value
## [1] 2.401904e-06
##
## $counts
## function gradient
##      18      18
##
## $convergence
## [1] 0
##
## $message
## [1] "CONVERGENCE: REL_REDUCTION_OF_F <= FACTR*EPSMCH"
```


2 stueckw. Exponential (1.para = 0.0573, 2.para = 0.00624)

[illegible]

```
stuexp2_xr_makkar2020
```

```
##      1.para      2.para  
## 0.057289445 0.006243732
```

```
plot(xr_makkar2020,  
      ((xr_makkar2020 > 0 & xr_makkar2020 <= 2) * (1 - exp(-stuexp2_xr_makkar2020[1] * xr_makkar2020)) +  
        (xr_makkar2020 > 2) * (1 - exp(-stuexp2_xr_makkar2020[1] * 2)) +  
        (exp(-2 * stuexp2_xr_makkar2020[2]) -  
         exp(-stuexp2_xr_makkar2020[2] * xr_makkar2020))),  
      type = "l")
```



```
best_stuexp2_xb_makkar2020 <- find_best_start_2parameter(p = yb_makkar2020/100,  
                                                         q = xb_makkar2020,  
                                                         max_beta = 1,  
                                                         max_eta = 0.5,  
                                                         steps_beta = 0.1,  
                                                         steps_eta = 0.01,  
                                                         fitting_function = getstuexp2)
```


```
## Bester Startparameter: 0.4 0.09  
## Bester Fehler: 3.927055e-06
```

```
stuexp2_xb_makkar2020 <- getstuexp2(  
  p = yb_makkar2020/100,  
  q = xb_makkar2020,  
  start = best_stuexp2_xb_makkar2020,
```

```
## $par
## [1] 0.03200031 0.00835331
##
## $value
## [1] 3.927055e-06
##
## $counts
## function gradient
##      14      14
##
## $convergence
## [1] 0
##
## $message
## [1] "CONVERGENCE: REL_REDUCTION_OF_F <= FACTR*EPSMCH"
```



```
plot(xb_makkar2020,
      ((xb_makkar2020 > 0 & xb_makkar2020 <= 2) * (1 - exp(-stuexp2_xb_makkar2020[1] * xb_makkar2020)) +
        (xb_makkar2020 > 2) * (1 - exp(-stuexp2_xb_makkar2020[1] * 2)) +
        (exp(-2 * stuexp2_xb_makkar2020[2]) -
         exp(-stuexp2_xb_makkar2020[2] * xb_makkar2020))),
      type = "l")
```



Mischung aus 2 Exponentialverteilungen

```
# Mischung aus 2 Exponentialverteilungen
source("C:/Users/nhonh/OneDrive/Dokumente/Unikrams/Masterarbeit/R Funktionen/getexex.R")


best_exex_xr_makkar2020 <- find_best_start_3parameter(p = yr_makkar2020/100,
  q = xr_makkar2020,
  max_shape1 = 0.7,
  max_shape2 = 0.7,
  max_scale = 1,
  steps_shape1 = 0.1,
  steps_shape2 = 0.1,
  steps_scale = 0.1,
  fitting_function = getexex)

## Bester Startparameter: 0.4 0.6 0.4
## Bester Fehler: 1.275518e-06
```

```
## $par
## [1] 0.007291547 10.228316755 2.348045152
##
## $value
## [1] 1.275518e-06
##
## $counts
## function gradient
##      37      37
##
## $convergence
## [1] 0
##
## $message
## [1] "CONVERGENCE: REL_REDUCTION_OF_F <= FACTR*EPSMCH"
```

```
## 0.007291547 10.228316755 2.348045152
```

```
plot(xr_makkar2020,
      (exp(exex_xr_makkar2020["mix"]) / (1 + exp(exex_xr_makkar2020["mix"]))) * stats::pexp(q = xr_makkar2020["rate"],
                                                    rate = exex_xr_makkar2020["rate2"])),
      (1 - exp(exex_xr_makkar2020["mix"]) / (1 + exp(exex_xr_makkar2020["mix"]))) *
      stats::pexp(q = xr_makkar2020,
                  rate = exex_xr_makkar2020["rate2"])),
      type = "l")
```



```
best_exex_xb_makkar2020 <- find_best_start_3parameter(p = yb_makkar2020/100,
                                                    q = xb_makkar2020,
                                                    max_shape1 = 0.7,
                                                    max_shape2 = 0.7,
                                                    max_scale = 1,
                                                    steps_shape1 = 0.1,
                                                    steps_shape2 = 0.1,
                                                    steps_scale = 0.1,
                                                    fitting_function = getexex)
```

```
## Bester Startparameter: 0 0.6 0.1
```

```
## Bester Fehler: 3.197647e-06
```

```
exex_xb_makkar2020 <- getexex(
  p = yb_makkar2020/100,
  q = xb_makkar2020,
  start = best_exex_xb_makkar2020,
  show.output = TRUE,
```


```

    plot = TRUE
  )

## $par
## [1] 0.008962805 15.352217077 3.135107171
##
## $value
## [1] 3.197647e-06
##
## $counts
## function gradient
##      59      59
##
## $convergence
## [1] 0
##
## $message
## [1] "CONVERGENCE: REL_REDUCTION_OF_F <= FACTR*EPSMCH"

```

Exponential & Exponential (rate1 = 0.00896, rate1 = 15.4, mix = 0.95)

[illegible]


```
##          rate1          rate2          mix
## 0.008962805 15.352217077 3.135107171
```

```
plot(xb_makkar2020,
      (exp(exex_xb_makkar2020["mix"]) / (1 + exp(exex_xb_makkar2020["mix"]))) * stats::pexp
      rate = exex_xb
```

```

      (1 - exp(exex_xb_makkar2020["mix"])) / ( 1 + exp(exex_xb_makkar2020["mix"]))) *
stats::pexp(q = xb_makkar2020,
            rate = exex_xb_makkar2020["rate2"])),
type = "l")

```



Ergebnnis

```

getvalue <- function(p, q, best_start, fitting_function){
  if(identical(as.character(substitute(fitting_function)), "getstuexp2")){
    output <- capture.output({
      result <- getstuexp2(p = p, q = q, start = best_start, show.output = TRUE,
                           plot = FALSE, wert1 = 2)
    })
  }
  else if(identical(as.character(substitute(fitting_function)), "getstuexp3")){
    output <- capture.output({
      result <- getstuexp3(
        p = p, q = q, start = best_start,
        show.output = TRUE, plot = FALSE, wert1 = 2, wert2 = 6)
    })
  }
  else{
    output <- capture.output({
      result <- fitting_function(p = p, q = q, start = best_start,

```

```

        show.output = TRUE, plot = FALSE)
    })
}

# Berechne den Fehler (makkar2020_r_1$value) für die aktuellen Startparameter
error <- as.numeric(gsub("\\[1\\]\\s+", "", output[5]))

return(error)
}

best_test <- function(p, q, weibull, weib, weibex, weibex2, expweib, stuexp3, stuexp2,
                      exex, start_weibull, start_weib, start_weibex, start_weibex2,
                      start_expweib, start_stuexp3, start_stuexp2, start_exex,
                      group){
  weibull_val <- getvalue(p, q, start_weibull, getweibullpar)
  weib_val <- getvalue(p, q, start_weib, getweibpar)
  weibex_val <- getvalue(p, q, start_weibex, getweibex)
  weibex2_val <- getvalue(p, q, start_weibex2, get2weibex)
  expweib_val <- getvalue(p, q, start_expweib, getexpweib)
  stuexp3_val <- getvalue(p, q, start_stuexp3, getstuexp3)
  stuexp2_val <- getvalue(p, q, start_stuexp2, getstuexp2)
  exex_val <- getvalue(p, q, start_exex, getexex)

  error_distribution_pairs <- list(
    list(weibull_val, "W"),
    list(weib_val, "e.W."),
    list(weibex_val, "M. W&E"),
    list(weibex2_val, "M. e.W&E"),
    list(expweib_val, "e.W o. lambda = 1"),
    list(stuexp3_val, "3 s.E."),
    list(stuexp2_val, "2 s.E."),
    list(exex_val, "M. E&E")
  )

  # Suchen Verteilung mit dem kleinsten Fehler
  best_pair <- error_distribution_pairs[[which.min(sapply(
    error_distribution_pairs, function(pair) pair[[1]]))]]

  # Drucken Sie die Ergebnisse
  cat("Beste Verteilung:", best_pair[[2]], "\n")
  cat("Bester Fehler:", best_pair[[1]], "\n")
  cat("Gruppe: ", group)

  return(c(group, best_pair[[2]], best_pair[[1]]))
}

best_tavr <- best_test(yb_makkar2020/100, xb_makkar2020, makkar2020_b_1, weibull_xb_makkar2020,
                      weibex_xb_makkar2020, weibex2_xb_makkar2020, expweib_xb_makkar2020,
                      stuexp3_xb_makkar2020, stuexp2_xb_makkar2020, exex_xb_makkar2020,
                      best_makkar2020_b_1, best_weibull_xb_makkar2020,
                      best_weibex_xb_makkar2020, best_weibex2_xb_makkar2020,
                      best_expweib_xb_makkar2020, best_stuexp3_xb_makkar2020,
                      best_stuexp2_xb_makkar2020, best_exex_xb_makkar2020, "TAVR")

```

```

## Beste Verteilung: M. W&E
## Bester Fehler: 5.936047e-07
## Gruppe: TAVR

best_savr <- best_test(yr_makkar2020/100, xr_makkar2020, makkar2020_r_1, weibull_xr_makkar2020,
  weibex_xr_makkar2020, weibex2_xr_makkar2020, expweib_xr_makkar2020,
  stuexp3_xr_makkar2020, stuexp2_xr_makkar2020, exex_xr_makkar2020,
  best_makkar2020_r_1, best_weibull_xr_makkar2020,
  best_weibex_xr_makkar2020, best_weibex2_xr_makkar2020,
  best_expweib_xr_makkar2020, best_stuexp3_xr_makkar2020,
  best_stuexp2_xr_makkar2020, best_exex_xr_makkar2020, "SAVR")

## Beste Verteilung: M. W&E
## Bester Fehler: 5.604454e-07
## Gruppe: SAVR

tab <- matrix(c("PARTNER2", "MiRi", "TSmF", best_tavr[1], best_tavr[2],
  best_tavr[3], NA, NA, weibex_xb_makkar2020[1:2], NA,
  weibex_xb_makkar2020[3:4],
  "PARTNER2", "MiRi", "TSmF", best_savr[1], best_savr[2],
  best_savr[3], NA, NA, weibex_xr_makkar2020[1:2], NA,
  weibex_xr_makkar2020[3:4]),
  ncol=13, byrow=TRUE)

rownames(tab) <- NULL
colnames(tab) <- c('Studie', 'PG', 'EP', 'GR', 'Verteilung', 'SSE', '$\\alpha$',
  '$\\theta$', '$\\lambda_1$', '$\\lambda_2$', '$\\lambda_3$',
  '$\\vartheta$', '$\\psi$')

results <- as.data.frame(tab)

# Speichern
write.table(results, "results_makkar2020.txt", sep = "\t", row.names = FALSE)

# Funktion zur Überprüfung von NA-Werten für Zeichenketten und numerische Werte
is_non_empty <- function(x) {
  return(!is.na(x) & x != "")
}

# Spalten mit mindestens einem nicht-NA-Wert ermitteln
nicht_leere_spalten <- colSums(sapply(results, is_non_empty)) > 0

# Konvertieren Sie die Tabelle in eine Markdown-Tabelle
print(results[, nicht_leere_spalten])

##      Studie  PG  EP  GR Verteilung      SSE      $\\lambda_1$
## 1 PARTNER2 MiRi TSmF TAVR      M. W&E 5.936047e-07 1.76189589462931
## 2 PARTNER2 MiRi TSmF SAVR      M. W&E 5.604454e-07 1.45698058615981
##      $\\lambda_2$      $\\vartheta$      $\\psi$
## 1 86.1203614139029 0.590063215231932 2.02940410918326
## 2 108.520412893644 1.74392668424074 1.89903088078703

```