




Collaborative Filtering

LinUCB for MovieLens dataset



Bandit problem introduction



Goal: minimize the expected total regret

$$R(T) = \mathbb{E}_{I_t} \left[\sum_{t=1}^T r_{i^*,t} \right] - \mathbb{E}_{I_t} \left[\sum_{t=1}^T r_{i,t} \right]$$



Implemented UCB vs e-greedy vs random



LinUCB Disjoint

$$E[r_{t,a}|x_{t,a}] = x_{t,a}^T \theta_a^*$$

LinUCB Hybrid

$$E[r_{t,a}|x_{t,a}] = z_{t,a}^T \beta^* + x_{t,a}^T \theta_a^*$$

Movielens dataset & Data processing

Dataset: Movielens 1M

1 million votes of 6000 users on 4000 films


Pre-processing:

- Resized ratings between 0 and 1
- Selected the movies watched by more than 1000 users
- Selected users who watched more than 150 movies
- Selected 30 most important features


Matrix factorization (SVD): $M = \phi_u^T W \phi_a$

=> Feature user matrix and film (item) matrix

<i>users/items</i>	<i>i</i> ₁	<i>i</i> ₂	<i>i</i> _{<i>m</i>}
<i>u</i> ₁	<i>r</i> _{1,1}	...	<i>r</i> _{1,<i>j</i>}	...	<i>r</i> _{1,<i>k</i>}	...	<i>r</i> _{1,<i>m</i>}
<i>u</i> ₂	<i>r</i> _{2,1}	...	<i>r</i> _{2,<i>j</i>}	...	<i>r</i> _{2,<i>k</i>}	...	<i>r</i> _{2,<i>m</i>}
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
<i>u</i> _{<i>i</i>}	<i>r</i> _{<i>i</i>,1}	...	<i>r</i> _{<i>i</i>,<i>j</i>}	...	<i>r</i> _{<i>i</i>,<i>k</i>}	...	<i>r</i> _{<i>i</i>,<i>m</i>}
⋮	⋮	⋮	⋮	⋮	⋮	⋮	⋮
<i>u</i> _{<i>n</i>}	<i>r</i> _{<i>n</i>,1}	...	<i>r</i> _{<i>n</i>,<i>j</i>}	...	<i>r</i> _{<i>n</i>,<i>k</i>}	...	<i>r</i> _{<i>n</i>,<i>m</i>}




Most frequently recommended films




Rating percentages


LinUCB Disjoint



Accumulated regret for one user





Average movies rating in iterations






Estimated movies rating


LinUCB Disjoint - Parameters



LinUCB Hybrid - Parameters



Method comparison and conclusions



- LinUCB is much better, especially LinUCB hybrid
- Choice of parameters for the model is important, as we noted that they can drastically impact the results
- Expanding the context with other information would be worthwhile