

# FChat接口文档

Version	Update Time	Status	Author	Description
0.0.1-dev		创建状态	mini2436	面试项目API接口文档

## 测试API

### Redis测试接口

**URL:** <https://fchat-api-dev.mini2436.xyz/test/>

**Type:** GET

**Author:** mini2436

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** Redis测试接口

**Request-headers:**

Header	Type	Description	Required	Since
fchat-token	string	该值在登陆接口中返回,后续接口调用必传	true	-

**Request-example:**

```
curl -X GET -k -H 'fchat-token' -i https://fchat-api-dev.mini2436.xyz/test/
```

**Response-fields:**

Field	Type	Description	Since
code	int32	返回状态自定义code	-
msg	string	返回消息定义	-
data	object	返回请求体定义	-
└any object	object	any object.	-

## Response-example:

```
{
  "code": 580,
  "msg": "syrka7",
  "data": {
    "mapKey": {
      "waring": "You may use java.util.Object for Map value; smart-doc can't be handle."
    }
  }
}
```

## Mysql异步测试接口

**URL:** <https://fchat-api-dev.mini2436.xyz/test/>

**Type:** POST

**Author:** mini2436

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** Mysql异步测试接口

### Request-headers:

Header	Type	Description	Required	Since
fchat-token	string	该值在登陆接口中返回,后续接口调用必传	true	-

### Request-example:

```
curl -X POST -k -H 'fchat-token' -i https://fchat-api-dev.mini2436.xyz/test/
```

### Response-fields:

Field	Type	Description	Since
code	int32	返回状态自定义code	-
msg	string	返回消息定义	-
data	object	返回请求体定义	-

### Response-example:

```
{
  "code": 368,
  "msg": "hfqsyn",
  "data": true
}
```

## 根据id查询数据库中的测试数据

**URL:** <https://fchat-api-dev.mini2436.xyz/test/{id}>

**Type:** GET

**Author:** mini2436

**Content-Type:** application/x-www-form-urlencoded;charset=utf-8

**Description:** 根据id查询数据库中的测试数据

### Request-headers:

Header	Type	Description	Required	Since
fchat-token	string	该值在登陆接口中返回,后续接口调用必传	true	-

### Path-parameters:

Parameter	Type	Description	Required	Since
id	int32	查询的用户主键	true	-

### Request-example:

```
curl -X GET -k -H 'fchat-token' -i https://fchat-api-dev.mini2436.xyz/test/990
```

### Response-fields:

Field	Type	Description	Since
code	int32	返回状态自定义code	-
msg	string	返回消息定义	-
data	object	返回请求体定义	-
└─id	int32	主键	-
└─name	string	名称	-

Field	Type	Description	Since
↳phone	string	手机号	-
↳age	int32	年龄	-

### Response-example:

```
{
  "code": 114,
  "msg": "phdru1",
  "data": {
    "id": 95,
    "name": "笑愚.曾",
    "phone": "15239181587",
    "age": 38
  }
}
```