


Opamp Inverting Amplifier

PART NUMBER	04A-005
GROUP NAME	Opamp Amplifiers (04A)
CIRCUIT NAME	Inverting Amplifier
VARIANT DESCRIPTION	Single supply, DC Bias Trimmer
BOARD DESIGN	PCB50-A-05
PRODUCT DESCRIPTION	Panel of #04A-005 miniPCBs, v-scored (1 Panel = 4 Pieces)


Theory of Operation

This circuit amplifies a small voltage signal.

Panel Board




TOP VIEW




BOTTOM VIEW

Single Board




TOP VIEW




BOTTOM VIEW

Part Locations




TOP VIEW



BOTTOM VIEW


Schematic




Gerber Files

This section contains images of the layers included in each Gerber file.


TOP COPPER (GLTX)




TOP CREAM (GCTX)

	THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.	FILE DESCRIPTION TOP CREAM	
		DWG NO X04A-005-BXB	FILE EXT GCTX


BOTTOM CREAM (GCBX)

	THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.	FILE DESCRIPTION BOTTOM CREAM	
		DWG NO X04A-005-BXB	FILE EXT GCBX



BOTTOM COPPER (GLBX)




TOP SILKSCREEN (GOTX)




BOTTOM SILKSCREEN (GOBX)

		<p>FILE DESCRIPTION</p> <p>BOTTOM SILKSCREEN</p>	
		<p>DWG NO</p> <p>X04A-005-BXB</p>	<p>FILE EXT</p> <p>GOBX</p>
	<p>THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.</p>		


TOP SOLDERMASK (GSTX)




BOTTOM SOLDER MASK (GSBX)





EDGE (GM1)




	THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.	FILE DESCRIPTION	
		EDGE	
		DWG NO	FILE EXT
		X04A-005-BXB	GM1

VSCORE (GM2)

		FILE DESCRIPTION	
		V-SCORE	
	THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.	DWG NO	FILE EXT
		X04A-005-BXB	GM2

MILLING (GM3)

		<p>THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.</p>		FILE DESCRIPTION	
				MILLING	
		DWG NO		FILE EXT	
		X04A-005-BXB		GM3	

Design Inputs

Design Requirements Form

POWER REQUIREMENTS

PARAMETER NAME	SYMBOL	UNITS	LOWER LIMIT	TARGET VALUE	UPPER LIMIT
Postive DC Supply	+V	V			
Negative DC Supply	-V	V			

STIMULI REQUIREMENTS

PARAMETER NAME	SYMBOL	UNITS	LOWER LIMIT	TARGET VALUE	UPPER LIMIT
Signal Voltage, Peak to Peak	V_s	V			
Signal Frequency	f_s	Hz			
Common Mode	V_{cm}	V			
Source Impedance	R_s	Ω			

PERFORMANCE CHARACTERISTICS

PARAMETER NAME	SYMBOL	UNITS	LOWER LIMIT	TARGET VALUE	UPPER LIMIT
Quiescent Current	I_q	A			
Voltage Gain	A_v	V/V			
Current Gain	A_i	A/A			
Power Gain	A_p	P/P			
Input Impedance	R_i	Ω			
Output Impedance	R_o	Ω			

Design Outputs

Parts List Form

REF DES	PART TYPE	MFG PART NUMBER	PART DESCRIPTION	FIND
				1
				2
				3
				4
				5
				6
				7
				8
				9
				10
				11

Testing Plans

Developmental Testing

1. Plan each calibration and service test.
2. Predict expected values for each test measurement.
3. Determine if expected values satisfy design requirements.
4. Assemble a prototype that is representative of what might be the final design.
5. Perform the calibration and service testing plans.
6. Determine if the design outputs satisfy design requirements.

Calibration and Service Testing

1. With power off, measure resistances between each pin.
2. If measured resistances are not as expected, end testing fail, components need to be replaced.
3. With power on, measure voltages at each pin.
4. If measured voltages are not as expected, end testing fail, components need to be replaced.
5. With power on, adjust potentiometer PX such that the voltage at test point TPX is ##.
6. If measured voltages cannot be adjusted to an expected value, end testing fail, components need to be replaced.
7. With power on, apply stimuli and measure outputs.
8. If measured output signals are not as expected, end testing fail, components need to be replaced.
9. If measured output signals are as expected, end testing pass.-

Design Example

Design Inputs

POWER REQUIREMENTS

PARAMETER NAME	SYMBOL	UNITS	LOWER LIMIT	TARGET VALUE	UPPER LIMIT
Postive DC Supply	+V	V	4.9	5	5.1
Negative DC Supply	-V	V			

STIMULI REQUIREMENTS

PARAMETER NAME	SYMBOL	UNITS	LOWER LIMIT	TARGET VALUE	UPPER LIMIT
Signal Voltage, Peak to Peak	V_s	V	0.015	0.02	0.025
Signal Frequency	f_s	Hz			
Common Mode	V_{cm}	V			
Source Impedance	R_s	Ω			

PERFORMANCE CHARACTERISTICS

PARAMETER NAME	SYMBOL	UNITS	LOWER LIMIT	TARGET VALUE	UPPER LIMIT
Quiescent Current	I_q	A			
Voltage Gain	A_v	V/V			
Current Gain	A_i	A/A			
Power Gain	A_p	P/P			
Input Impedance	R_i	Ω			
Output Impedance	R_i	Ω			

Design Outputs

PARTS LIST

QTY REQ	REFERENCE DESIGNATORS	MFG PART NUMBER	PART DESCRIPTION	FIND
3	R1, R2, R5		RESISTOR, 1.5K, 1/4W, 1%	1
2	R3, R4		100	2
1	Q1		2N2222	3
1	C1		10u	4
1	C2		1u	5
1	C3		0.1u	6

Developmental Tests per Example

Test Report per Example

Change and Liability Notice

This document is subject to change without notice. While effort has been made to ensure the accuracy of the material contained within this document, Nolan Manteufel shall under no circumstances be liable for incidental or consequential damages or related expenses resulting from the use of this document.

Trademark Notice

miniPCB is a trademark of Nolan Manteufel.

This datasheet does not constitute permission to use the miniPCB trademark.

WORDMARK	FIGUREMARK	FIGUREMARK
miniPCB™		

Revision History

REV	DESCRIPTION	ECO	DATE
A	Initial Release		