

# Opamp Inverting Amplifier

<b>PART NUMBER</b>	04A-005
<b>GROUP NAME</b>	Opamp Amplifiers (04A)
<b>CIRCUIT NAME</b>	Inverting Amplifier
<b>VARIANT DESCRIPTION</b>	Single supply, DC Bias Trimmer
<b>BOARD DESIGN</b>	PCB50
<b>PRODUCT DESCRIPTION</b>	Panel of 04A-005 miniPCBs, v-scored (1 Panel = 4 Pieces)

## Basic Circuit Diagram






Figure 1 – Source: [https://www.electronics-tutorials.ws/opamp/opamp\\_2.html](https://www.electronics-tutorials.ws/opamp/opamp_2.html)

## Theory of Operation


This circuit amplifies a voltage signal. Since there is no DC blocking capacitor on the signal input pin P1-4, the DC voltage difference between pin P1-4 and the reference voltage set by the trimmer potentiometer R2 will be amplified.




The feedback capacitor C6 allows larger feedback resistor values to be used without decreasing the amplifier's gain bandwidth.



A low-pass Butterworth filter is formed by resistor R6 and capacitor C3 to minimize noise on the non-inverting opamp input.




The input impedance is largely determined by resistor R4. The output impedance is largely determined by opamp U1.




The minimum and maximum supply voltage is largely determined by opamp U1. Only the V+ power source is needed to operate this circuit.


Capacitors C2 and C5 filter the V+ power rail. Using capacitors with different values, generally between 10X and 1000X different, will provide better performance than two capacitors with similar values. Using low noise dielectric capacitors are recommended.



## Panel Board




TOP VIEW




BOTTOM VIEW


## Single Board




TOP VIEW




BOTTOM VIEW



TOP VIEW



BOTTOM VIEW



## Design Example

## Parts List

QTY REQ	PART	REF DES	MFG	MFG PN	VALUE	FIND
1	PCB	-	miniPCB	04A-005	N/A	1
1	CAPACITOR	C1	NICHICON	UFW2A470MPD	47 uF	2
1	CAPACITOR	C2	TDK	FA28X7S2A473KRU06	47 nF	3
1	CAPACITOR	C3	TDK	FA28X7S2A473KRU06	47 nF	4
1	CAPACITOR	C4	TDK	FA28X7S2A473KRU06	47 nF	5
1	CAPACITOR	C5	NICHICON	UFW2A470MPD	47 uF	6
1	CAPACITOR	C6	TDK	FA24NP02W102JNU06	1000pF	7
1	PINS, 2mm	P1	MOLEX	87754-0552	N/A	8
1	RESISTOR	R1	VISHAY	RL07S101GRE6	100 $\Omega$	9
1	TRIMMER	R2	VISHAY	T93YA104KT20	100 K $\Omega$	10
1	RESISTOR	R3	VISHAY	RL07S101GRE6	100 $\Omega$	11
1	RESISTOR	R4	VISHAY	PTF6550R000BYEK	50 $\Omega$	12
1	RESISTOR	R5	VISHAY	PTF56500R00BYEB	500 $\Omega$	13
1	RESISTOR	R6	VISHAY	RL07S101GRE6	100 $\Omega$	14
1	OPAMP, DUAL	U1	NISSHINBO	NJM2904D	N/A	15
			NISSHINBO	NJM14558D		
			TAIWAN SEMICONDUCTOR	TS358		
			MICROCHIP	MCP6002-I/P		
			ANALOG DEVICES	AD827JNZ		
			TEXAS INSTRUMENTS	LF412CP		
10	TEST POINT	TP*	KEYSTONE ELECTRONICS	5000	N/A	16

## Assembly

I want this section to include step by step pictures of the assembly process.

Capture the imaginations of the readers.

Make it look like I'm having fun.

## Testing

## Test List

TEST #	TEST NAME	TEST DESCRIPTION
1	+V Bus Short-Circuit	Measure resistance between TP9 and TP10.
2	U1 Pin 2 Short-Circuit	Measure resistance between TP1 and TP10.
3	U1 Pin 1 Short-Circuit	Measure resistance between TP8 and TP10.
4	Resistance Value, R1	Measure resistance between TP9 and TP2.
5	Resistance Value, R2	Measure resistance between TP2 and TP3.
6	Resistance Value, R3	Measure resistance between TP3 and TP10.
7	Resistance Value, R4	Measure resistance between TP1 and TP4.
8	Resistance Value, R5	Measure resistance between TP4 and TP8.
9	Resistance Value, R6	Measure resistance between TP5 and TP7.
10	Capacitance Value, C3	Measure capacitance between TP5 and TP10.
11	Capacitance Value, C4	Measure capacitance between TP6 and TP10.
12	Capacitance Value, C5	Measure capacitance between TP9 and TP10.
13	Capacitance Value, C6	Measure capacitance between TP4 and TP8.
14	Safe Turn-On	Apply power while monitoring current draw.
15	Voltage Adjustment, TP5	Set voltage between TP5 and TP10 to 2.50 V.
16	Standby Power Consumption	Measure power consumption during standby operation.
17	Common-Mode Offset	TBD (Waveforms)
18	Output Voltage Swing	TBD (Waveforms)
19	Output Impedance	TBD (Waveforms)
20	Impulse Response	TBD (Waveforms)
21	Step Response	TBD (Waveforms)
22	BODE Plot	TBD (Waveforms)

## Test Results

Test Conclusions



## Performance

## POWER REQUIREMENTS

PARAMETER NAME	SYMBOL	UNITS	LOWER LIMIT	TARGET VALUE	UPPER LIMIT
Postive DC Supply	+V	V	3.1	3.3	3.5
Negative DC Supply	-V	V	N/A	N/A	N/A

## STIMULI REQUIREMENTS

PARAMETER NAME	SYMBOL	UNITS	LOWER LIMIT	TARGET VALUE	UPPER LIMIT
Maximum Voltage Gain	$A_v$	$\frac{V}{V}$	9.9	10.0	10.1
Bandwidth	$f_{-3dB}$	Hz		5 MHz	
Common-Mode Offset	$V_{cm}$	$\frac{V}{V}$			
Common-Mode Gain	$A_{cm}$	$\frac{V}{V}$			
Maximum Input Bias Current	$I_{bias}$	A			
Maximum Phase Shift	$\phi_{max}$	°			
Source Impedance	$R_s$	$\Omega$			

## PERFORMANCE CHARACTERISTICS

PARAMETER NAME	SYMBOL	UNITS	LOWER LIMIT	TARGET VALUE	UPPER LIMIT
Quiescent Current	$I_q$	A	0.01	0.02	0.03
Voltage Gain	$A_v$	$\frac{V}{V}$		10	
Input Impedance	$R_i$	$\Omega$		50	
Output Impedance	$R_o$	$\Omega$		0.001	

## Engineering Forms


## Parts List (FORM)


QTY REQ	PART	REF DES	MFG	MFG PN	VALUE	FIND
1	PCB	-	miniPCB	04A-005	N/A	1
1	CAPACITOR	C1				2
1	CAPACITOR	C2				3
1	CAPACITOR	C3				4
1	CAPACITOR	C4				5
1	CAPACITOR	C5				6
1	CAPACITOR	C6				7
1	PINS, 2mm	P1			N/A	8
1	RESISTOR	R1				9
1	TRIMMER	R2				10
1	RESISTOR	R3				11
1	RESISTOR	R4				12
1	RESISTOR	R5				13
1	RESISTOR	R6				14
1	OPAMP, DUAL	U1			N/A	15
10	TEST POINT	TP*	KEYSTONE ELECTRONICS	5000	N/A	16

Gerber Files


This section contains images of the layers included in each Gerber file.

TOP COPPER (GLTX)





	THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.	FILE DESCRIPTION TOP COPPER	
		DWG NO X04A-005-B- <del>GLTX</del>	FILE EXT GLTX


TOP CREAM (GCTX)

	THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.	FILE DESCRIPTION TOP CREAM	
		DWG NO X04A-005-B-XBTX	FILE EXT GCTX

## BOTTOM CREAM (GCBX)

			
	THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.	FILE DESCRIPTION BOTTOM CREAM	
		DWG NO X04A-005-B-	FILE EXT XBBX

BOTTOM COPPER (GLBX)




THIS DRAWING AND  
THE INFORMATION IT CONTAINS  
IS PROVIDED  
FOR EDUCATIONAL USE ONLY.

FILE DESCRIPTION  
BOTTOM COPPER

DWG NO  
X04A-005-B-~~GB~~X

FILE EXT  
~~GB~~X

TOP SILKSCREEN (GOTX)



THIS DRAWING AND  
THE INFORMATION IT CONTAINS  
IS PROVIDED  
FOR EDUCATIONAL USE ONLY.

FILE DESCRIPTION  
TOP SILKSCREEN



DWG NO

X04A-005-B-

FILE EXT


XBTX

## BOTTOM SILKSCREEN (GOBX)


		
	THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.	FILE DESCRIPTION BOTTOM SILKSCREEN
		DWG NO X04A-005-B-XB
		FILE EXT GBX



TOP SOLDERMASK (GSTX)



## BOTTOM SOLDER MASK (GSBX)



THIS DRAWING AND  
THE INFORMATION IT CONTAINS  
IS PROVIDED  
FOR EDUCATIONAL USE ONLY.

FILE DESCRIPTION

**BOTTOM SOLDERMASK**


DWG NO


**X04A-005-B-**

FILE EXT


**GSBX**

EDGE (GM1)




	THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.	FILE DESCRIPTION	
		EDGE	
		DWG NO	FILE EXT
		X04A-005-B-	GM1

VSCORE (GM2)

	THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.	FILE DESCRIPTION V-SCORE	
		DWG NO X04A-005-B- <del>XB</del> 2	FILE EXT GM2

MILLING (GM3)

	THIS DRAWING AND THE INFORMATION IT CONTAINS IS PROVIDED FOR EDUCATIONAL USE ONLY.	FILE DESCRIPTION MILLING	
		DWG NO X04A-005-B-GM3	FILE EXT X04A-005-B-GM3

## Change and Liability Notice

This document is subject to change without notice. While effort has been made to ensure the accuracy of the material contained within this document, Nolan Manteufel shall under no circumstances be liable for incidental or consequential damages or related expenses resulting from the use of this document.

## Trademark Notice

miniPCB is a trademark of Nolan Manteufel.

This datasheet does not constitute permission to use the miniPCB trademark.

WORDMARK	FIGUREMARK	FIGUREMARK
miniPCB™		

## Revision History

REV	DESCRIPTION	ECO	DATE
A	Initial Release	1002	

## Related Content

#	TYPE	DESCRIPTION	LOCATION
1	Sale Posting	eBay	
2	Sale Posting	Mouser	
3	Repository	Engineering Files	<a href="https://github.com/miniPCB/EAGLE/tree/main/miniPCB/04/A/04A-005">https://github.com/miniPCB/EAGLE/tree/main/miniPCB/04/A/04A-005</a>
4	Repository	Datasheet	
5	Video	Development	
6	Video	Development	
7	Video	Testing	
8	Video	Engineering Release	