

1.数据库出现死锁，收到报警邮件

```
16:50:09.292 [http-nio-8080-exec-23] ERROR c.m.s.c.o.PopCallbackController - popWaybillTrack Exception: {}
org.springframework.dao.DeadlockLoserDataAccessException:
### Error updating database. Cause: com.mysql.jdbc.exceptions.jdbc4.MySQLTransactionRollbackException: Deadlock found
when trying to get lock; try restarting transaction
### The error may involve com.mryx.skylark.dao.tms.OrderDao.updateOrderInfoByBean-Inline
### The error occurred while setting parameters
### SQL: update `order` SET updated_at = now() where tid = ?
### Cause: com.mysql.jdbc.exceptions.jdbc4.MySQLTransactionRollbackException: Deadlock found when trying to get lock; try
restarting transaction
; SQL []; Deadlock found when trying to get lock; try restarting transaction; nested exception is
com.mysql.jdbc.exceptions.jdbc4.MySQLTransactionRollbackException: Deadlock found when trying to get lock; try restarting
transaction
at
org.springframework.jdbc.support.SQLExceptionTranslator.doTranslate(SQLExceptionTranslator.java:263)
at
org.springframework.jdbc.support.AbstractFallbackSQLExceptionTranslator.translate(AbstractFallbackSQLExceptionTranslator.java:73)
at org.mybatis.spring.MyBatisExceptionTranslator.translateExceptionIfPossible(MyBatisExceptionTranslator.java:73)
at org.mybatis.spring.SqlSessionInterceptor.invoke(SqlSessionInterceptor.java:446)
at com.sun.proxy.$Proxy124.update(Unknown Source)
at org.mybatis.spring.SqlSessionTemplate.update(SqlSessionTemplate.java:294)
at org.apache.ibatis.binding.MapperMethod.execute(MapperMethod.java:62)
at org.apache.ibatis.binding.MapperProxy.invoke(MapperProxy.java:59)
--
at org.apache.tomcat.util.net.SocketProcessorBase.run(SocketProcessorBase.java:49)
at java.util.concurrent.ThreadPoolExecutor.runWorker(ThreadPoolExecutor.java:1142)
at java.util.concurrent.ThreadPoolExecutor$Worker.run(ThreadPoolExecutor.java:617)
at org.apache.tomcat.util.threads.TaskThread$WrappingRunnable.run(TaskThread.java:61)
at java.lang.Thread.run(Thread.java:748)
Caused by: com.mysql.jdbc.exceptions.jdbc4.MySQLTransactionRollbackException: Deadlock found when trying to get lock; try
restarting transaction
at sun.reflect.NativeConstructorAccessorImpl.newInstance0(Native Method)
at sun.reflect.NativeConstructorAccessorImpl.newInstance(NativeConstructorAccessorImpl.java:62)
at sun.reflect.DelegatingConstructorAccessorImpl.newInstance(DelegatingConstructorAccessorImpl.java:45)
at java.lang.reflect.Constructor.newInstance(Constructor.java:423)
```

2.查找到相关代码，发现分析不出来问题

```
waybillBean.setLastStatus(waybill.getDbStatus());
waybillBean.setLcStatus(waybill.getLcStatus());
waybillBean.setStatus(waybill.getStatus());
waybillBean.setDmOperator(waybill.getDmOperator());
waybillBean.setDmMobile(waybill.getDmMobile());
logger.info("OrderServiceImpl updateWaybillInfo waybillBean {}", waybillBean);
waybillDao.updateWaybillInfoByBean(waybillBean);

//更新订单状态
OrderBean orderBean = new OrderBean();
orderBean.setTid(waybill.getOrderId());
orderBean.setStatus(waybill.getOrderStatus());
orderBean.setUpdatedAt(waybill.getTime());
logger.info("OrderServiceImpl updateWaybillInfo orderBean {}", orderBean);
orderDao.updateOrderInfoByBean(orderBean);

//插入流转信息
```

3.学习查找关于数据库死锁的资料如下：

<http://hedengcheng.com/>

<https://www.cnblogs.com/LBSer/p/5183300.htm>

<https://www.cnblogs.com/huanongying/p/7021555.html>

4.通过数据库命令查看数据库，获取相关数据库死锁的相关的事务和sql语句，通过查看日志发现，事物1需要获取waybill表中的锁，事物2持有waybill表中的锁，

```
show engine innodb status;
```

5.通过分析上面数据库引擎日志，找到两个事务对应的代码

```
TransactionStatus status = dataSourceTransactionManager.getTransaction(def);
try {
    if (!orderBean.getStatus().equals(orderStatus)) {
        orderDao.updateOrderInfo(orderParams);
    }
    if (!waybillBean.getStatus().equals(waybillStatus)) {
        waybillDao.updateWaybillInfo(waybillParams);
    }
    if (insertTrace) {
        waybillTraceBean.setCreatedAt(new Date());
        waybillTraceBean.setUpdatedAt(new Date());
    }
}
```

事务2对应的代码:

```

waybillBean.setLastStatus(waybill.getDbStatus());
waybillBean.setLcStatus(waybill.getLcStatus());
waybillBean.setStatus(waybill.getStatus());
waybillBean.setDmOperator(waybill.getDmOperator());
waybillBean.setDmMobile(waybill.getDmMobile());
logger.info("OrderServiceImpl updateWaybillInfo waybillBean {}", waybillBean);
waybillDao.updateWaybillInfoByBean(waybillBean);

```

//更新订单状态

```

OrderBean orderBean = new OrderBean();
orderBean.setTid(waybill.getOrderid());
orderBean.setStatus(waybill.getOrderStatus());
orderBean.setUpdatedAt(waybill.getTime());
logger.info("OrderServiceImpl updateWaybillInfo orderBean {}", orderBean);
orderDao.updateOrderInfoByBean(orderBean);

```

//插入流转信息

这时，一下子恍然大悟，两个事物更新SQL语句的顺序刚好相反，并且持有对方需要的X锁，刚好满足死锁的条件。

6.继续查看服务器日志，看看什么场景，满足上面的场景。

场景1：三方物流公司回调取消订单

```

16:50:09.185 [http-nio-8080-exec-23] INFO c.m.s.service.impl.OrderServiceImpl - OrderServiceImpl updateWaybillInfo waybillBean WaybillBean{id=null, createdAt=null, u
pdatedAt=null, waybillNo='301668003014', orderId='null', dmMobile='13717706173', dmOperator='梁永勤', status='CANCELED', company='null', lastStatus='ACCEPT', remark=
'null', waybillType='null', lastExcept=null, lcStatus='CANCEL', outerNo='null'}
16:50:09.186 [http-nio-8080-exec-23] INFO c.m.s.service.impl.OrderServiceImpl - OrderServiceImpl updateWaybillInfo orderBean OrderBean{id=null, createdAt=null, updat
edAt=Thu Jun 28 16:50:09 CST 2018, tid='19230743518945846', originId='null', erpName='null', internalId='null', receiverName='null', receiverMobile='null', receiver
State='null', receiverCity='null', receiverDistrict='null', receiverAddress='null', receiverLat='null', receiverLng='null', buyerIdentity='null', buyerNick='null', pa
yment='null', totalFee='null', postFee='null', payType='null', shippingDate='null', deliveryTimeLeft='null', deliveryTimeRight='null', createdAt='null', stationName='null', statu
s='null', lastStatus='null', companyStationId='null', stationCompanyCode='null', stationId='null', exceptStatus='null', saving1='null', saving2='null', saving3='null', sa
ving4='null', saving5='null', payTime='null', stationArea='null', deliveryType='null', buyerMessage='null', sellerMessage='null', exceptMessage='null', exceptInfo='null'}
16:50:09.228 [http-nio-8080-exec-23] INFO o.s.b.f.xml.XmlBeanDefinitionReader - Loading XML bean definitions from class path resource [org/springframework/jdbc/suppo
rt/sql-error-codes.xml]
16:50:09.278 [http-nio-8080-exec-23] INFO o.s.j.support.SQLExceptionCodesFactory - SQLExceptionCodes loaded: [DB2, Derby, H2, HSQL, Informix, MS-SQL, MySQL, Oracle, PostgreS
QL, Sybase, Hana]
16:50:09.292 [http-nio-8080-exec-23] ERROR c.m.s.c.o.PopCallbackController - popWaybillTrack Exception: {}
org.springframework.dao.DeadlockLoserDataAccessException:
### Error updating database. Cause: com.mysql.jdbc.exceptions.jdbc4.MySQLTransactionRollbackException: Deadlock found when trying to get lock; try restarting transac
tion
### The error may involve com.mryx.skyark.dao.tms.OrderDao.updateOrderInfoByBean-Inline
### The error occurred while setting parameters
### SQL: update `order` SET updated_at = now() where tid = ?
### Cause: com.mysql.jdbc.exceptions.jdbc4.MySQLTransactionRollbackException: Deadlock found when trying to get lock; try restarting transaction
--
at com.sun.proxy.$Proxy202.update(Unknown Source)
at org.apache.ibatis.session.defaults.DefaultSqlSession.update(DefaultSqlSession.java:198)
at sun.reflect.GeneratedMethodAccessor372.invoke(Unknown Source)
at sun.reflect.DelegatingMethodAccessorImpl.invoke(DelegatingMethodAccessorImpl.java:43)
at java.lang.reflect.Method.invoke(Method.java:498)
at org.mybatis.spring.SqlSessionTemplate$SqlSessionInterceptor.invoke(SqlSessionTemplate.java:433)
... 85 common frames omitted

```

场景2：每日优鲜站长通过云雀系统手动取消订单

```

[jww@idc01-tms-api-06 skyark]$ cat skyark.log |grep "19230743518945846"
16:50:08.915 [http-nio-8080-exec-26] INFO c.m.s.c.openapi.OrderInfoController - order_operation params:{optType=2, lcStatus=REJECTED, reason_type=REJECTED_PRODUCT, d
mMobile=15226598163, remark=, lc_status=REJECTED, reasonType=REJECTED_PRODUCT, dm_name=张海超, dmName=%E5%B0%A0%E6%B5%B7%E8%B6%85, tid=19230743518945846, dm_mobile=15
226598163}
16:50:08.915 [http-nio-8080-exec-26] INFO c.m.s.s.impl.OrderStatusServiceImpl - OrderStatusServiceImpl changeOrderStatus params:{optType=2, lcStatus=REJECTED, reason
_type=REJECTED_PRODUCT, dmMobile=15226598163, remark=, lc_status=REJECTED, reasonType=REJECTED_PRODUCT, dm_name=张海超, dmName=%E5%B0%A0%E6%B5%B7%E8%B6%85, tid=192307
43518945846, dm_mobile=15226598163}
16:50:08.918 [http-nio-8080-exec-26] INFO c.m.s.s.impl.AmsRequestServiceImpl - AmsRequestServiceImpl sendRejected url:http://ams.missfresh.cn/ams/orderreject/synReje
ct.json, params:{'reason':'REJECTED_PRODUCT','orderNo':'19230743518945846','createTime':'2018-06-28 16:50:08','remark':'','createUser':'张海超'}

```

上面两个场景都需要各自在一个事务中修改订单和运单表，并且更新的订单和运单相同且更新顺序相反，在相同时间点刚好满足死锁条件，好在数据库在死锁的情况下，回超时回滚事务，其中一个事务会主动释放锁。