Chapter 84 — Distributed Tracing & Correlation IDs

> **Part X — Performance, Observability & Quality** · Complexity: **Standard** (≥25 interview questions)
>
> **Prerequisites:** Ch 1 (networking/OkHttp), Ch 82 (analytics pipeline), Ch 83 (crash reporting), Ch 81 (feedback/correlation), Ch 2 (retries), Ch 28 (privacy). Pairs with Ch 85 (perf monitoring), Ch 87 (error telemetry).
>
> **Reference surface in StreamCart:** the thread that ties a user action on the device to the backend work it triggers — a **trace/correlation id** propagated from the app through every request so a slow checkout, a failed order, or a crash can be followed end-to-end across client and server logs, traces, analytics (Ch 82), and crash reports (Ch 83).

84.1 Problem Definition and Real-World Context

When something goes wrong — a checkout fails, a screen is slow, an order never arrives — engineers need to **follow one user's one action across many systems**: the client code, the network request, the backend services it fans out to, the database, and back. Without a shared **identifier** threaded through all of it, client logs and server logs are disconnected islands; you can't tell **which** backend trace corresponds to **this** user's failed tap. **Distributed tracing** (trace + span ids propagated across service boundaries) and **correlation ids** (a stable id linking a client session/action to its backend work and to analytics/crash data) solve this — they make the whole system **observable end-to-end**.

Concretely, teams hit:

- **Disconnected client/server logs.** A user reports a failed order; support has a client log and the backend has thousands of traces — with **no way to link them**. A **correlation id** sent on the request and logged on both sides joins them.
- **No trace propagation.** The backend uses distributed tracing (OpenTelemetry/Jaeger), but the **client doesn't start or propagate** a trace, so backend traces don't include the **client-originated** context (which screen/action started this). The client should **inject trace context** (W3C `traceparent`) into outgoing requests.
- **Can't correlate across observability pillars.** Analytics events (Ch 82), crash reports (Ch 83), feedback (Ch 81), and backend traces are separate — a **shared correlation id** (per session/action) lets you jump between them.
- **Per-request vs per-session ids.** You need both: a **per-request id** (trace a single call) and a **session/correlation id** (tie all of a session's activity together) — consistently generated and propagated.
- **Retries and id reuse.** A retried request (Ch 2) should keep its trace semantics correct (new span, same trace); an idempotency key (Ch 15) is distinct from a trace id.
- **Privacy.** Trace/correlation ids must be **opaque** (not PII, Ch 28) — they identify a flow, not a person.

- **Sampling & overhead.** Tracing everything is costly; **sample** traces while keeping correlation ids cheap and always-on.

The architecture: generate a **correlation/session id** (opaque) on the client and a **per-request trace context** (W3C Trace Context `traceparent`), **propagate** them on every outgoing request via an **OkHttp interceptor** (Ch 1); **log** the correlation id on the client (analytics Ch 82, crash Ch 83, feedback Ch 81) and have the **server log/trace** it too, so one id joins client logs, backend traces, analytics, and crashes; manage **per-request vs per-session** ids and **retry** semantics (Ch 2); keep ids **opaque/ non-PII** (Ch 28); and **sample** traces. This chapter is about **threading one id through everything so the system is traceable end-to-end**.

Three practical use cases

1. **Debug a failed checkout (StreamCart).** The checkout flow carries a correlation id; the failed `placeOrder` (Ch 75) request's `traceparent` links to the backend trace showing which service failed — joined to the client's analytics/crash via the correlation id.
2. **Trace a slow screen.** A screen's load fans out to several API calls, all sharing the session correlation id and each with its own trace; the end-to-end latency breakdown is visible across client and server.
3. **Support ties a report to a session.** A user's feedback (Ch 81) carries the correlation id; support finds the exact backend traces, client logs, and crashes for that session.

Why this is architectural

Distributed tracing/correlation is the **connective tissue of observability**, tying networking (Ch 1), analytics (Ch 82), crash reporting (Ch 83), feedback (Ch 81), and backend tracing into one followable thread. The decisions — correlation + trace ids, W3C propagation via an interceptor, cross-pillar logging, opaque/non-PII, sampling — determine whether you can actually debug production end-to-end.

84.2 Requirements Engineering

Functional requirements

ID	Requirement
F1	Generate an opaque correlation/session id and per-request trace context (W3C `traceparent`).
F2	Propagate them on every outgoing request via an OkHttp interceptor (Ch 1).
F3	Log the correlation id on the client across analytics, crash, and feedback (Ch 82/83/81).
F4	Enable the server to log/trace the same id, joining client and backend.
F5	Handle per-request vs per-session ids and retry semantics (new span, same trace) (Ch 2).
F6	Keep ids opaque/non-PII; sample traces for cost (Ch 28).

Non-functional requirements

Attribute	Policy
Traceability	One id joins client logs/analytics/crashes + backend traces.
Standards	W3C Trace Context propagation; OpenTelemetry-compatible.
Privacy	Opaque ids, not PII (Ch 28).
Overhead	Correlation always-on + cheap; traces sampled.
Consistency	Ids generated/propagated uniformly (interceptor).

Scope

- **In scope:** correlation/session id + per-request trace context (W3C `traceparent`), propagation via OkHttp interceptor (Ch 1), cross-pillar correlation (analytics Ch 82, crash Ch 83, feedback Ch 81), per-request vs per-session ids, retry/span semantics (Ch 2), opaque/non-PII ids (Ch 28), sampling, OpenTelemetry-on-mobile overview.
- **Out of scope:** analytics pipeline (Ch 82), crash reporting (Ch 83), feedback (Ch 81), networking internals (Ch 1), backend tracing infra, perf monitoring (Ch 85).

Assumptions & constraints

- OkHttp (Ch 1) for propagation; the backend uses **distributed tracing** (OpenTelemetry/ W3C Trace Context) and logs correlation ids; analytics/crash/feedback pipelines accept a correlation id (Ch 82/83/81). `minSdk 24`. Ids are **opaque** (non-PII, Ch 28); traces are **sampled**.

84.3 System Design Fundamentals

- **Two kinds of id: trace context (per request) + correlation/session id (per session/ flow).**
  - **Trace context (W3C Trace Context):** a `traceparent` header carrying a **trace id** (the whole distributed operation) and a **span id** (this hop), plus flags (sampled). The client **starts or continues** a trace and injects `traceparent` into each outgoing request; the **backend continues** the same trace across its services — producing one end-to-end **distributed trace**. This is the **standard** (W3C Trace Context, OpenTelemetry).
  - **Correlation/session id:** a **stable, opaque id** for a **session** (or a logical user action/flow) that ties together **all** of a session's client activity — analytics events (Ch 82), crash reports (Ch 83), feedback (Ch 81) — **and** is sent to the backend so server logs carry it. Where a trace follows **one request**, the correlation id joins **everything in a session/flow**. Both are needed: the trace gives you the **per-request latency/error breakdown across services**; the correlation id gives you the **"all activity for this session" join across observability pillars**.
- **Propagate via one interceptor (Ch 1).** An **OkHttp interceptor** injects the `traceparent` (and a correlation-id header, e.g., `X-Correlation-Id`) into **every** outgoing request — uniformly, in one place (like auth, Ch 19). This guarantees consistency and means feature code doesn't manage headers. The interceptor also creates the per-request **span**.
- **Log the correlation id across all client pillars (Ch 82/83/81).** Set the correlation id as a:

    - **Analytics** super-property (Ch 82) so every event carries it,
    - **Crash reporter** custom key (Ch 83) so crashes carry it,
    - **Feedback** attachment (Ch 81) so reports carry it,
    - **Client log** field. Then **one id** lets you jump from a crash → the session's analytics → the backend traces → the feedback. This cross-pillar join is the whole point.
- **Server logs/traces the same id.** The backend, on receiving `traceparent` + `X-Correlation-Id`, **continues the trace** and **logs the correlation id** on every log line/span for that request — so client-sent ids appear in **server** logs and traces, completing the join. (This is a backend requirement the client enables by sending the ids.)
- **Per-request vs per-session + retries (Ch 2).** Each **request** gets a **new span** (and usually a new `traceparent` span id) under the **trace**; a **retry** (Ch 2) is a **new span** (it's a new attempt) but can share the **trace/correlation** context so the retry is visible in the same trace. The **correlation/session id** persists across requests within a session. (Note: a **trace id** is **not** an **idempotency key**, Ch 15 — different purpose: tracing vs dedup.)
- **Opaque, non-PII ids (Ch 28).** Trace/correlation ids are **random opaque identifiers** (UUID/128-bit) — they identify a **flow/session**, **not a person**. **Never** embed PII (email, user id in the clear) in them. This keeps tracing **privacy-safe** (Ch 28/82/83).
- **Sampling (cost).** Full distributed tracing is **expensive** (storage/overhead), so traces are **sampled** (a fraction, with the sampled flag in `traceparent` so the backend agrees) — while the **correlation id is always-on and cheap** (just a header + a logged field). Sample traces; always correlate.
- **OpenTelemetry on mobile.** OpenTelemetry (OTel) provides SDKs and the W3C Trace Context standard; on mobile it's emerging — you can use OTel or a lighter custom correlation layer, but **standard propagation (W3C `traceparent`)** is what makes client traces continue into the backend's tracing system.

Core insight: **thread two opaque, non-PII identifiers through the system — a W3C Trace Context (`traceparent`: trace id + per-hop span id) that the client starts and injects into every request so the backend continues one end-to-end distributed trace, and a stable correlation/session id that joins all of a session's client activity (analytics Ch 82, crash Ch 83, feedback Ch 81) and is sent so server logs carry it — propagated uniformly by a single OkHttp interceptor (Ch 1), logged across every client observability pillar and the server, with new spans per request/retry (Ch 2) under a persistent session correlation, opaque/non-PII ids (Ch 28), and sampled traces (correlation always-on) — so one user's one action can be followed end-to-end across client and server.**

84.4 High-Level Architecture


84.4 High-Level Architecture

Components & ownership

- **Correlation/session id + trace** started per action; set across **analytics/crash/ feedback** (Ch 82/83/81).
- **OkHttp interceptor** injects `traceparent` + correlation id on **every** request and creates the per-request span (Ch 1).
- **Backend** continues the trace and logs the correlation id → **one id joins** all pillars.
- **Sampling** for traces; **opaque/non-PII** ids (Ch 28).

Direction: action → correlation id + trace → set across pillars → interceptor injects on requests → backend continues trace + logs id → end-to-end join.

84.5 Detailed Component Design




Component	Responsibility
`TraceContext`	W3C trace id + span id + sampled flag (`traceparent`)
`CorrelationManager`	opaque session/action correlation id
`TracingInterceptor`	inject `traceparent` + correlation id + new span per request (Ch 1)
`ObservabilityBinder`	set correlation id on analytics/crash/feedback (Ch 82/83/81)

84.6 End-to-End Data Flow

One action, end-to-end



Retry keeps trace, new span



84.7 Complete Kotlin Implementation

Package: `com.streamcart.tracing`.

84.7.1 Correlation id + trace context (opaque, non-PII, Ch 28)

```
@Singleton
class CorrelationManager @Inject constructor() {
    val sessionId: String = UUID.randomUUID().toString()   // opaque, per session; NOT PII (Ch 28)
    private var currentAction: String? = null
    fun startAction(): String { currentAction = UUID.randomUUID().toString(); return currentAction!! }
    fun currentCorrelationId(): String = currentAction ?: sessionId   // action id if in a flow, else session
}

data class TraceContext(val traceId: String, val spanId: String, val sampled: Boolean) {
    // W3C traceparent: version-traceId-spanId-flags
    fun toTraceparent() = "00-$traceId-$spanId-%02x".format(if (sampled) 1 else 0)
    companion object {
        fun start(sampledRate: Double): TraceContext = TraceContext(
            traceId = randomHex(32), spanId = randomHex(16), sampled = Random.nextDouble() < sampledRate)  // sample (cost)
        fun childSpan(parent: TraceContext) = parent.copy(spanId = randomHex(16))   // new span, same trace (retry/next request)
    }
}
```

84.7.2 OkHttp interceptor: inject traceparent + correlation id (Ch 1)

```
class TracingInterceptor @Inject constructor(private val correlation: CorrelationManager) : Interceptor {
    override fun intercept(chain: Interceptor.Chain): Response {
        val trace = TraceContext.start(sampledRate = 0.1)              // per-request trace/span (sampled)
        val request = chain.request().newBuilder()
            .header("traceparent", trace.toTraceparent())              // W3C Trace Context -> backend continues trace
            .header("X-Correlation-Id", correlation.currentCorrelationId())  // joins client+server (always-on)
            .build()
        // (A full OTel SDK would create a real span with timing here.)
        return chain.proceed(request)   // retry (Ch 2) -> a new interceptor pass -> new span, same correlation
    }
}
// Added to the OkHttp stack alongside auth/logging interceptors (Ch 1/19).
```

84.7.3 Bind correlation id across observability pillars (Ch 82/83/81)

```
@Singleton
class ObservabilityBinder @Inject constructor(
    private val analytics: Analytics,        // Ch 82
    private val crash: CrashReporter,         // Ch 83
    private val correlation: CorrelationManager,
) {
    /** One correlation id on EVERY pillar -> jump between crash <-> analytics <-> backend
traces <-> feedback. */
    fun bind() {
        val id = correlation.currentCorrelationId()
        analytics.setSuperProperty("correlation_id", id)   // every event carries it (Ch 82)
        crash.setCustomKey("correlation_id", id)           // every crash carries it (Ch 83)
        // feedback attaches it too (Ch 81); client logs include it.
    }
}
```

84.7.4 Start a traced action (e.g., checkout, Ch 75)

```
fun startTracedCheckout(correlation: CorrelationManager, binder: ObservabilityBinder) {
    correlation.startAction()   // new correlation id for this flow (ties its requests + events
+ any crash)
    binder.bind()               // propagate to analytics/crash/feedback
    // subsequent requests carry traceparent + X-Correlation-Id via the interceptor -> backend
joins them.
}
```

84.7.5 Server-side expectation (what the client enables)

```
// The BACKEND must: read `traceparent` -> continue the W3C trace (OpenTelemetry);
// read `X-Correlation-Id` -> log it on every log line/span for the request.
// Then a single id joins client observability (Ch 82/83/81) and backend traces/logs.
// (Client enables this by sending the headers; backend owns continuation + logging.)
```

84.7.6 Module structure

```
:core:tracing  CorrelationManager, TraceContext (W3C), TracingInterceptor (Ch 1),
ObservabilityBinder
# Analytics -> Ch 82; crash -> Ch 83; feedback -> Ch 81. OpenTelemetry SDK optional. Backend
continues trace + logs id.
```

84.8 Concurrency and Race Conditions

Scenario	Risk	Handling
Id not propagated on some requests	broken trace/join	inject in one interceptor (all requests, Ch 1)
Retry reuses span id	wrong trace graph	new span per attempt, same trace/correlation (Ch 2)
Correlation id missing on crash	can't join	set as crash custom key on bind (Ch 83)
PII in id	privacy leak	opaque random ids only (Ch 28)
Trace not sampled but logged	inconsistent	sampled flag in traceparent; backend honors it
Concurrent actions share id	ambiguous	per-action correlation id for distinct flows
Backend ignores headers	no join	backend must continue trace + log id (requirement)

- **One interceptor guarantees propagation:** injecting `traceparent` + correlation id in a single OkHttp interceptor (Ch 1) means **every** request carries them — scattered manual headers inevitably miss some, breaking the trace/join.
- **New span per request/retry, persistent correlation:** each attempt is a **new span** under the **same trace** (Ch 2), and the **correlation/session id persists** across the flow — so retries and fan-out appear correctly in one trace and one session join.
- **Opaque ids keep it private:** random 128-bit ids identify a flow, not a person (Ch 28) — never encode PII.

84.9 Failure Scenarios and Recovery

Failure	Detection	Response	Outcome
Client/server logs disconnected	support can't trace	correlation id sent + server-logged	joined
Backend trace lacks client context	incomplete trace	client injects `traceparent` (continue trace)	end-to-end
Can't jump crash → backend	debugging gap	correlation id on crash (Ch 83) + server	linked
PII in ids	privacy audit	opaque ids (Ch 28)	safe
Tracing too costly	cost	sample traces (correlation always-on)	affordable
Missing on some requests	gaps	single interceptor (Ch 1)	consistent
Retry confuses trace	wrong graph	new span, same trace (Ch 2)	correct



> **One opaque id, propagated by one interceptor and logged on every pillar and the server, makes the whole system followable.** The W3C `traceparent` continues the backend's distributed trace with client context; the correlation id joins the client's analytics, crashes, and feedback to those traces. Sample the expensive traces; keep the cheap correlation always-on.

84.10 Scaling the Implementation

- **Level 1.** Correlation/session id + `X-Correlation-Id` header via an OkHttp interceptor (Ch 1); log it on the client.
- **Level 2.** W3C `traceparent` propagation (continue backend trace); set correlation id on analytics/crash/feedback (Ch 82/83/81).
- **Level 3 — production.** Per-request spans + retry semantics (Ch 2); sampling; opaque non-PII ids (Ch 28); server-side continuation + logging.
- **Level 4 — large.** OpenTelemetry SDK with real client spans (screen load, request timing); trace-based perf (Ch 85); cross-service dashboards; adaptive sampling.
- **Level 5 — enterprise.** Full client-to-backend distributed tracing, SLO/trace-based alerting, trace governance, PII/consent review, multi-platform correlation parity.

Avoid overengineering: a correlation id + W3C `traceparent` via one interceptor + binding to the pillars covers most debugging needs. Don't hand-roll a tracing system; use W3C/OTel standards. Don't trace everything — sample.

84.11 Alternative Approaches and Trade-offs

Dimension	Option A	Option B	When
Standard	W3C Trace Context / OpenTelemetry	custom headers	W3C/OTel (backend continuation, interop)
Ids	Trace (per request) + correlation (per session)	one id	Both (per-request latency + session join)
Propagation	One interceptor (Ch 1)	per-call headers	Interceptor (consistency)
Cross-pillar	Correlation id on analytics/crash/feedback	separate	Correlation id (join, Ch 82/83/81)
Ids	Opaque, non-PII (Ch 28)	embed user id	Opaque (privacy)
Cost	Sample traces, correlation always-on	trace everything	Sample (cost)
Trace id vs idempotency	Distinct (Ch 15)	reuse	Distinct (tracing ≠ dedup)

W3C/OpenTelemetry vs custom tracing: a custom header scheme can carry an id, but it **won't continue the backend's distributed trace** unless it follows the **W3C Trace Context** standard the backend tracing system (OTel/Jaeger/Zipkin) understands. Using **W3C** `traceparent` means client-originated context **flows into the backend trace** and tools interoperate. Use the standard; don't invent a propagation format.

Trace + correlation vs a single id: a **trace id** follows **one request** across services (latency/error breakdown); a **correlation/session id** joins **all** of a session's client activity (analytics, crashes, feedback) and server logs. They answer different questions — "what did this request do across services?" vs "show me everything for this session." Use **both**.

One interceptor vs per-call propagation: adding trace headers per call site inevitably **misses requests** (breaking traces/joins) and duplicates logic. A **single OkHttp interceptor** (Ch 1) injects them on **every** request uniformly — like auth (Ch 19). Centralize propagation.

84.12 Security & Privacy Considerations

- **Opaque, non-PII ids (Ch 28):** trace and correlation ids are **random identifiers** of a flow/session, **never** PII — don't embed email/clear user id. This keeps tracing privacy-safe across analytics/crash/feedback (Ch 82/83/81).
- **Consent (Ch 28/82):** correlation/tracing follows the same **consent** regime as analytics — if the user opted out, don't collect/correlate beyond what's essential.
- **Don't leak sensitive data in traces:** spans/logs tied to the trace must **not** carry request bodies with PII/secrets, tokens, or card data (Ch 28) — redact as everywhere.
- **Server-side access control:** traces/logs with correlation ids are **internal** observability data — access-controlled (support/engineering), retention-limited (Ch 28).
- **Id spoofing:** a client-sent `traceparent`/correlation id is **not** a security credential — the backend uses it for **correlation only**, never authorization (auth is Ch 19); treat incoming ids as untrusted labels.
- **Per-account (Ch 42):** reset correlation/session on logout so a session's trace isn't attributed across users (and ids stay opaque).
- Client vs backend: the **client** generates opaque ids, propagates via the interceptor, and binds to pillars; the **backend** continues traces, logs ids, and access-controls/retains the observability data — neither stores PII in ids.

84.13 Performance and Resource Optimization

- **Correlation id is cheap** (a header + a logged field) — **always-on**; negligible overhead.
- **Sample traces** — full span timing/export is costly; sample a fraction (sampled flag in `traceparent`), keep correlation always-on.
- **One interceptor** — minimal per-request cost (header injection); no per-call-site logic.
- **Lazy span creation** — only create detailed spans for sampled traces.
- **Bounded trace export** — batch/async export (don't block requests) if using an OTel SDK.
- **Profiling:** propagation overhead (µs), trace sampling rate, correlation-join success (can we link a report to a trace?), export cost.

84.14 Testing Strategy

Propagation, correlation binding, and retry/span semantics are testable with a fake chain.

```
class TracingInterceptorTest {
    @Test fun `injects traceparent and correlation id on every request`() {
        val req = runInterceptor(TracingInterceptor(FakeCorrelation("corr-1")))
        assertTrue(req.header("traceparent")!!.matches(Regex("00-[0-9a-f]{32}-[0-9a-f]{16}-[0-
9a-f]{2}")))  // W3C
        assertEquals("corr-1", req.header("X-Correlation-Id"))
    }
    @Test fun `correlation id is opaque, not PII`() {
assertFalse(CorrelationManager().sessionId.contains("@")) }  // Ch 28
}

class CorrelationBindTest {
    @Test fun `binds correlation id to analytics and crash`() {
        binder.bind()
        assertEquals("corr-1", fakeAnalytics.superProps["correlation_id"])   // Ch 82
        assertEquals("corr-1", fakeCrash.customKeys["correlation_id"])       // Ch 83
    }
}

class SpanSemanticsTest {
    @Test fun `retry creates a new span under the same trace`() {
        val t = TraceContext.start(1.0); val child = TraceContext.childSpan(t)
        assertEquals(t.traceId, child.traceId); assertNotEquals(t.spanId, child.spanId)  // same
trace, new span (Ch 2)
    }
}
```

What to test: interceptor injects valid W3C `traceparent` + correlation id on every request; ids opaque/non-PII (Ch 28); correlation id bound to analytics/crash/feedback (Ch 82/83/81); retry → new span, same trace (Ch 2); sampling flag set; per-action correlation for distinct flows. Fake OkHttp chain + observability pillars; (integration) verify server logs the id.

84.15 Production Observability

- **Metrics:** correlation-join success (can a report/crash be linked to a backend trace?); trace sampling rate; propagation coverage (% requests with `traceparent`/correlation id → should be ~100%); end-to-end trace latency breakdown (client vs server); orphaned client/server logs (→ 0).
- **Logs:** every client log/analytics/crash carries `correlation_id`; requests carry `traceparent` — **no PII in ids** (Ch 28).
- **Debugging:** disconnected logs → id not sent/server not logging it; incomplete backend trace → `traceparent` not injected/continued; can't join crash↔trace → correlation id not on crash (Ch 83); PII in id → not opaque; tracing cost → increase sampling.
- **Alerting:** propagation-coverage drop (interceptor regression); correlation-join failure spike.
- **Dashboards:** end-to-end traces (client→backend) with latency breakdown; correlation-join rate; sampling.

84.16 System Design Interview Preparation

> ≥25 questions.

Fundamentals

1. *Distributed tracing?* Trace + span ids propagated across service boundaries → one end-to-end trace.
2. *Correlation id?* Stable opaque id joining a session's client activity + server logs.
3. *Both needed?* Trace = per-request cross-service; correlation = per-session cross-pillar join.
4. *Standard?* W3C Trace Context (`traceparent`) / OpenTelemetry.
5. `traceparent` *?* trace id + span id + sampled flag.

Propagation 6. *How propagate?* One OkHttp interceptor injects headers on every request (Ch 1). 7. *Why interceptor?* Consistency — never miss a request. 8. *Backend role?* Continue the trace + log the correlation id.

Cross-pillar 9. *Join crash ↔ analytics ↔ trace?* Correlation id on all pillars (Ch 82/83/81). 10. *Analytics?* Super-property; **crash?** custom key; **feedback?** attachment. 11. *Why one id?* Jump between observability pillars.

Semantics 12. *Per-request vs per-session?* New span per request; correlation persists per session. 13. *Retry?* New span, same trace/correlation (Ch 2). 14. *Trace id vs idempotency key?* Distinct (tracing ≠ dedup, Ch 15).

Privacy 15. *Ids and PII?* Opaque, non-PII (Ch 28) — identify a flow, not a person. 16. *Consent?* Same regime as analytics (Ch 28/82). 17. *Sensitive data in traces?* Redact; no PII/secrets in spans/logs.

Cost 18. *Tracing cost?* Sample traces. 19. *Correlation cost?* Cheap — always-on. 20. *Sampled flag?* In `traceparent` ; backend agrees.

Mobile/standards 21. *OpenTelemetry on mobile?* Emerging; use W3C propagation for backend continuation. 22. *Custom vs standard?* Standard (interop + continuation).

Testing/Production 23. *Test propagation?* Interceptor injects valid headers on every request. 24. *Test join?* Correlation id on all pillars. 25. *Disconnected logs in prod?* Id not sent / server not logging. 26. *Key metric?* Propagation coverage + correlation-join success.

Design-change challenges

1. **Follow a failed checkout across client and backend.** Correlation id + `traceparent` propagated; server logs/continues (Ch 75).
2. **Jump from a crash to the backend trace.** Correlation id on the crash report (Ch 83) + server logs.
3. **Backend traces lack client context.** Inject W3C `traceparent` to continue the trace.
4. **Tracing is too expensive.** Sample traces; keep correlation always-on.
5. **Ids might leak PII.** Opaque random ids only (Ch 28).

Mock walkthrough (abridged)

Clarify (what to trace, backend tracing stack, privacy?) → two ids: W3C `traceparent` (per request) + correlation/session id (per session) → one OkHttp interceptor injects on every request (Ch 1) → bind correlation id to analytics/crash/feedback (Ch 82/83/81) → backend continues trace + logs id → per-request spans + retry semantics (Ch 2) → opaque/ non-PII + consent (Ch 28) → sample traces → observability (propagation coverage, join success).

84.17 Practical Exercises

1. **Beginner.** Add an OkHttp interceptor that injects an `X-Correlation-Id` (opaque) on every request and log it on the client (Ch 1/28). *Eval:* every request carries it; non-PII.
2. **Intermediate.** Add W3C `traceparent` propagation (trace id + span id + sampled) so the backend can continue the trace. *Eval:* valid `traceparent`; sampled flag.
3. **Advanced.** Bind the correlation id to analytics (super-property), crash (custom key), and feedback (Ch 82/83/81) so one id joins all pillars. *Eval:* crash and analytics carry the same id.
4. **Production debugging.** Fix disconnected client/server logs (send + server-log the id) and an incomplete backend trace (inject `traceparent`). *Eval:* end-to-end joined.
5. **System design challenge.** Add per-request spans with retry semantics (new span, same trace) and trace sampling; measure propagation coverage. *Eval:* correct trace graph; sampled; ~100% coverage.

(Solutions withheld unless requested.)

84.18 Chapter Summary & Reference Sheet

Key decisions: thread **two opaque, non-PII identifiers** through the system — a **W3C Trace Context** (`traceparent`: a **trace id** for the whole operation + a **per-hop span id** + a sampled flag) that the client **starts and injects into every outgoing request** so the **backend continues one end-to-end distributed trace** (OpenTelemetry-compatible), and a **stable correlation/session id** that **joins all of a session's client activity** — analytics (Ch 82), crash reports (Ch 83), feedback (Ch 81) — **and is sent so server logs carry it**; **propagate both uniformly via a single OkHttp interceptor** (Ch 1) that also creates the **per-request span** (a **retry** is a **new span under the same trace**, Ch 2; a trace id is **not** an idempotency key, Ch 15); **bind the correlation id across every client pillar** (analytics super-property, crash custom key, feedback attachment, log field) so **one id lets you jump between crash ↔ analytics ↔ backend traces ↔ feedback**; keep ids **opaque/non-PII** under the same **consent** regime as analytics (Ch 28/82); and **sample the expensive traces while keeping the cheap correlation always-on** — so **one user's one action is followable end-to-end across client and server**.

Concepts: W3C Trace Context (`traceparent`), distributed tracing (trace/span), correlation/session id, single-interceptor propagation (Ch 1), cross-pillar binding (analytics/crash/feedback, Ch 82/83/81), per-request vs per-session + retry span semantics (Ch 2), opaque/non-PII ids (Ch 28), sampling, OpenTelemetry on mobile.

Common mistakes: disconnected client/server logs (no shared id); not injecting `traceparent` (backend trace lacks client context); per-call-site headers (missed requests); not binding the correlation id to crash/analytics (can't join

pillars); PII in ids; tracing everything (cost — sample); reusing span ids across retries (wrong trace graph); custom non-standard propagation (backend can't continue).

Checklist: ☐ opaque correlation/session id + W3C `traceparent` (non-PII, Ch 28) ☐ single OkHttp interceptor injects both on every request (Ch 1) ☐ backend continues trace + logs correlation id ☐ bind correlation id to analytics/crash/feedback (Ch 82/83/81) ☐ new span per request/retry, same trace (Ch 2) ☐ sample traces, correlation always-on ☐ consent regime (Ch 28) ☐ no PII/secrets in spans/logs ☐ reset on logout (Ch 42) ☐ propagation-coverage + correlation-join telemetry.

Key APIs: W3C Trace Context `traceparent` header, OkHttp `Interceptor` (Ch 1), `UUID`/128-bit random ids (opaque), analytics super-property (Ch 82), crash `setCustomKey` (Ch 83), feedback correlation (Ch 81), OpenTelemetry SDK (optional), sampling.

References:

- W3C Trace Context: https://www.w3.org/TR/trace-context/
- OpenTelemetry (Android/mobile): https://opentelemetry.io/docs/instrumentation/android/
- (composes) Ch 1 Networking, Ch 82 Analytics, Ch 83 Crash Reporting, Ch 81 Feedback, Ch 2 Retries, Ch 28 Privacy, Ch 85 Perf Monitoring

Chapter review (Phase 4)

- **Completeness:** all 18 sections; architecture/class/sequence/retry/failure diagrams; correlation manager + W3C trace context + interceptor + observability binder + traced-action code; concurrency (one-interceptor propagation, span-per-retry, opaque ids); failure (one-id
    - propagate + bind + sample principle); 5 levels; W3C-vs-custom, trace+correlation, single- interceptor trade-offs; security (opaque/non-PII, consent, not-a-credential, access control); perf (always-on correlation, sampled traces); interceptor + bind + span tests; observability (propagation coverage, join success); 26 Q&A + 5 challenges. ✅
- **Expand later:** perf monitoring (Ch 85), error telemetry (Ch 87), analytics (Ch 82), crash (Ch 83).
- **Interview coverage:** exceeds ≥25 bar.