Chapter 68 — Network State Monitoring (Wi-Fi / Cellular / Metered)

> **Part VIII — Real-Time & Connectivity** · Complexity: **Standard** (≥25 interview questions)
>
> **Prerequisites:** Ch 1 (networking), Ch 2 (retries), Ch 29 (offline-first), Ch 30 (WorkManager), Ch 63 (WebSocket), Ch 44 (lifecycle), Ch 6 (UI state). Pairs with Ch 17/18 (uploads/downloads), Ch 32 (sync), Ch 56 (images).
>
> **Reference surface in StreamCart:** knowing the network's real state — connected or not, Wi-Fi vs cellular, **metered** or unmetered, **validated** (actually has internet) — so the app reconnects promptly, defers heavy transfers to Wi-Fi, shows an offline banner, and reacts to Wi-Fi ↔ cellular switches, via one `ConnectivityManager` abstraction.

68.1 Problem Definition and Real-World Context

Apps constantly need to know the **network state** and **react** to changes: reconnect a WebSocket when connectivity returns (Ch 63), defer a large download to Wi-Fi (Ch 18), avoid auto-playing video on **metered** cellular (Ch 58), show an offline banner, retry a failed request when the network recovers (Ch 2). But network state on Android is subtle: "connected" doesn't mean "has internet" (captive portals), the network **transport** (Wi-Fi/ cellular/ethernet) and **capabilities** (**metered**, **validated**, bandwidth) matter, and networks **switch** constantly (Wi-Fi ↔ cellular hand-off). Getting this wrong means stale offline banners, data-plan burn, failed-but-not-retried requests, or dead real-time connections.

Concretely, teams hit:

- **"Connected" ≠ "has internet".** A device on Wi-Fi behind a **captive portal** or a dead router is "connected" but has no real internet. You must check `NET_CAPABILITY_ VALIDATED`, not just connectivity.
- **Deprecated/polling APIs.** Old `ConnectivityManager.activeNetworkInfo` and broadcast `CONNECTIVITY_ACTION` are deprecated/unreliable; the modern approach is a `NetworkCallback` observing the active network's **capabilities** as a `Flow`.
- **Ignoring metered.** Streaming video, large downloads (Ch 18), prefetch (Ch 56), and sync (Ch 32) on a **metered** cellular connection burn the user's data plan — respect `NET_CAPABILITY_NOT_METERED` and let WorkManager constrain to unmetered (Ch 30/47).
- **Not reacting to changes.** On Wi-Fi ↔ cellular switch or recovery, a WebSocket (Ch 63) dies and a failed request (Ch 2) should retry — the app must **observe** transitions and react, not assume a static network.
- **Per-screen ad-hoc checks.** Scattered connectivity checks drift and misbehave; one **observable abstraction** feeding UI state (Ch 6) and background decisions is needed.
- **Don't gate on connectivity for correctness.** Offline-first (Ch 29) means the app **works offline** from the SSOT (Ch 3); network state informs **UX and scheduling**, not whether a feature functions.

The architecture: expose network state as a `Flow` via a single `ConnectivityManager.NetworkCallback` abstraction reporting **connected + transport (Wi-Fi/cellular) + metered + validated**; **react** to changes — reconnect real-time (Ch 63), retry failed requests (Ch 2), **defer heavy transfers to unmetered** (WorkManager constraints, Ch 30/47), adjust quality (Ch 58/56), show an offline banner (Ch 6); treat the state as **advisory for UX/scheduling**, not a correctness gate (offline-first, Ch 29); and feed it to the UI and background layers from **one source**. This chapter is about **a correct, reactive, single-source network-state abstraction**.

Three practical use cases

1. **Offline banner + auto-reconnect (StreamCart).** An observable network state drives an offline banner (Ch 6) and triggers WebSocket reconnect (Ch 63) + failed-request retry (Ch 2) on recovery.
2. **Defer heavy transfer to Wi-Fi.** Large downloads (Ch 18/59) and backups wait for **unmetered** via WorkManager constraints (Ch 30/47); the UI explains "will download on Wi-Fi".
3. **Metered-aware quality.** On metered cellular, lower video bitrate (Ch 58), skip image prefetch (Ch 56), and pause non-essential sync (Ch 32).

Why this is architectural

Network state is a **cross-cutting signal** every connectivity feature consumes — real-time (Ch 63), transfers (Ch 17/18), sync (Ch 32), media (Ch 58/56), UI (Ch 6), background scheduling (Ch 30/47). The decisions — modern `NetworkCallback` Flow, validated/ metered/transport awareness, react-to-changes, advisory-not-gating, single source — determine data-plan respect, reconnection correctness, and UX accuracy.

68.2 Requirements Engineering

Functional requirements

ID	Requirement
F1	Expose network state (connected, transport, metered, validated) as an observable Flow.
F2	React to changes: reconnect real-time (Ch 63), retry failed requests (Ch 2).
F3	Defer heavy transfers to unmetered (WorkManager constraints) (Ch 30/47).
F4	Adjust behavior by metered/transport (quality, prefetch, sync) (Ch 58/56/32).
F5	Drive UI (offline banner) from one source (Ch 6).
F6	Treat state as advisory for UX/scheduling, not a correctness gate (offline-first, Ch 29).

Non-functional requirements

Attribute	Policy
Correctness	Validated (real internet), not just connected; metered respected.
Reactivity	Observe changes (callback), not poll; react promptly.
Data respect	Defer heavy work on metered; user data plan honored.
Consistency	Single source feeding UI + background.
Resilience	Offline-first; network state never blocks core features (Ch 29).

Scope

- **In scope:** `ConnectivityManager.NetworkCallback` as a Flow, capabilities (transport Wi-Fi/cellular/ethernet, `NOT_METERED`, `VALIDATED`, bandwidth), reacting (reconnect, retry, defer, quality), WorkManager network constraints (Ch 30/47), offline banner (Ch 6), advisory-not-gating (Ch 29), captive-portal/validated handling, single abstraction.
- **Out of scope:** networking stack (Ch 1), retry/backoff (Ch 2), offline-first (Ch 29), WorkManager internals (Ch 30), WebSocket (Ch 63), media quality (Ch 58/56), sync (Ch 32).

Assumptions & constraints

- `ConnectivityManager` + `NetworkCallback` (`registerDefaultNetworkCallback`), Kotlin Flow (`callbackFlow`), WorkManager (Ch 30). `minSdk 24`. Deprecated `activeNetworkInfo` / `CONNECTIVITY_ACTION` avoided. "Connected" ≠ validated; networks switch; metered matters.

68.3 System Design Fundamentals

- **Observe, don't poll — `NetworkCallback` as a Flow.** The modern API is **`ConnectivityManager.registerDefaultNetworkCallback`** (or `registerNetworkCallback` with a `NetworkRequest`), which **pushes** `onAvailable` / `onLost` / `onCapabilitiesChanged` callbacks. Wrap it in a **`callbackFlow`** to expose a **`Flow<NetworkState>`** the whole app observes (Ch 6). The deprecated `activeNetworkInfo` polling and `CONNECTIVITY_ACTION` broadcast are unreliable — don't use them.
- **"Connected" ≠ "has internet" — check `VALIDATED`.** `onAvailable` means a network exists, **not** that it reaches the internet (captive portals, dead routers). Check **`NetworkCapabilities.NET_CAPABILITY_VALIDATED`** (the OS verified real connectivity). Treat "connected but not validated" as effectively offline for UX, and let the OS's captive-portal flow handle sign-in. This is the most-missed subtlety.
- **Capabilities that matter:**
  - **Transport:** `TRANSPORT_WIFI`, `TRANSPORT_CELLULAR`, `TRANSPORT_ETHERNET` — what kind of network.
  - **Metered:** **`NET_CAPABILITY_NOT_METERED`** — whether the user **pays per byte** (cellular usually metered; some Wi-Fi is metered too — use the capability, not "is Wi-Fi"). The key signal for deferring heavy transfers.
  - **Validated:** real internet (above).

    - **Bandwidth:** `linkDownstreamBandwidthKbps` (rough) for adaptive decisions. Derive a clean `NetworkState` (`Offline` / `Online(transport, metered, validated, bandwidth)`) from these.
- **React to changes (the point):**
    - **Reconnect real-time** (Ch 63): on recovery, reconnect the WebSocket/SSE promptly (don't thrash while offline).
    - **Retry failed requests** (Ch 2): a request that failed for connectivity should retry on recovery (WorkManager/backoff).
    - **Defer heavy transfers to unmetered** (Ch 30/47): large downloads (Ch 18/59), backups, prefetch wait for `NOT_METERED` — ideally via **WorkManager network constraints** (`NetworkType.UNMETERED`), which the OS enforces, rather than manual checks.
    - **Adjust quality** (Ch 58/56): lower bitrate / skip prefetch on metered; full quality on unmetered.
    - **UI** (Ch 6): offline banner / "will sync on Wi-Fi" messaging.
- **Advisory, not a correctness gate (offline-first, Ch 29).** Network state informs **UX and scheduling**, it does **not** decide whether a feature **works** — the app functions offline from the **SSOT** (Ch 3/29), queues mutations in the outbox (Ch 31), and syncs when online (Ch 32). Don't block reads/composing on connectivity; don't show a blocking "no internet" wall for features that work offline. (Many apps over-gate on connectivity — avoid it.)
- **Prefer WorkManager constraints over manual checks for background work (Ch 30/47).** For deferrable transfers, **declare** a `NetworkType.UNMETERED` / `CONNECTED` constraint and let WorkManager schedule it — it handles connectivity waiting, Doze, and retries (Ch 47). Use the live `Flow` for **foreground UX** (banner, reconnect, quality) and **immediate** decisions.
- **Single source of truth for network state.** One `ConnectivityObserver` emitting the `Flow` — injected everywhere (UI, real-time, transfers). Scattered per-screen connectivity checks drift and misbehave; centralize.
- **Lifecycle (Ch 44).** Observe the callback app-wide (it's cheap and app-global); the UI collects the `Flow` lifecycle-aware (Ch 6); unregister the callback when truly done (usually app-scoped for the lifetime).

Core insight: **expose network state as a single observable `Flow` built on `ConnectivityManager.NetworkCallback` (not deprecated polling), reporting connected + transport + metered + validated — and critically check `VALIDATED` because "connected" ≠ "has internet"; react to changes by reconnecting real-time (Ch 63), retrying failed requests (Ch 2), deferring heavy transfers to unmetered (preferably via WorkManager constraints, Ch 30/47), and adjusting quality/UI; and treat network state as advisory for UX and scheduling, never as a correctness gate — the app works offline from the SSOT (Ch 29) and syncs when connectivity (validated, suitable) returns.**

68.4 High-Level Architecture



Components & ownership

- **`ConnectivityObserver`** wraps `NetworkCallback` into one `Flow<NetworkState>` (single source).
- **`NetworkState`** carries connected + transport + metered + validated + bandwidth.
- **Consumers react:** real-time reconnect (Ch 63), retry (Ch 2), quality (Ch 58/56), UI (Ch 6); **heavy transfers** use WorkManager constraints (Ch 30/47).

- **Advisory, not gating** — offline-first (Ch 29) underlies it.

Direction: `NetworkCallback` → one `Flow` → validated/metered-aware state → consumers react (reconnect/retry/quality/UI); heavy work via WorkManager constraints; advisory only.

68.5 Detailed Component Design



Component	Responsibility
`ConnectivityObserver`	single `Flow<NetworkState>` from `NetworkCallback`
`NetworkState`	connected + transport + metered + validated + bandwidth
`NetworkReactor`	react: reconnect (Ch 63), retry (Ch 2), quality (Ch 58/56)
WorkManager constraints	defer heavy transfers to unmetered (Ch 30/47)

68.6 End-to-End Data Flow

Observe + react to recovery



Metered-aware decision



68.7 Complete Kotlin Implementation

Package: `com.streamcart.connectivity`.

68.7.1 ConnectivityObserver: NetworkCallback → Flow (validated + metered +

transport)

```
sealed interface NetworkState {
    data object Offline : NetworkState
    data class Online(val transport: Transport, val metered: Boolean, val validated: Boolean,
val bandwidthKbps: Int) : NetworkState
    enum class Transport { WIFI, CELLULAR, ETHERNET, OTHER }
}

@Singleton
class ConnectivityObserver @Inject constructor(@ApplicationContext private val ctx: Context) {
    private val cm = ctx.getSystemService(ConnectivityManager::class.java)

    fun observe(): Flow<NetworkState> = callbackFlow {
        fun emitState() {
            val caps = cm.activeNetwork?.let { cm.getNetworkCapabilities(it) }
            trySend(caps?.toState() ?: NetworkState.Offline)
        }
        val callback = object : ConnectivityManager.NetworkCallback() {
            override fun onAvailable(network: Network) = emitState()
            override fun onLost(network: Network) = emitState()
            override fun onCapabilitiesChanged(n: Network, c: NetworkCapabilities) =
trySend(c.toState()).let {}
            override fun onUnavailable() { trySend(NetworkState.Offline) }
        }
        cm.registerDefaultNetworkCallback(callback)   // modern API (not deprecated
polling/broadcast)
        emitState()                                    // initial
        awaitClose { cm.unregisterNetworkCallback(callback) }
    }.distinctUntilChanged().conflate()               // de-dup transitions

    private fun NetworkCapabilities.toState(): NetworkState {
        val hasInternet = hasCapability(NetworkCapabilities.NET_CAPABILITY_INTERNET)
        if (!hasInternet) return NetworkState.Offline
        return NetworkState.Online(
            transport = when {
                hasTransport(NetworkCapabilities.TRANSPORT_WIFI) -> NetworkState.Transport.WIFI
                hasTransport(NetworkCapabilities.TRANSPORT_CELLULAR) ->
NetworkState.Transport.CELLULAR
                hasTransport(NetworkCapabilities.TRANSPORT_ETHERNET) ->
NetworkState.Transport.ETHERNET
                else -> NetworkState.Transport.OTHER
            },
            metered = !hasCapability(NetworkCapabilities.NET_CAPABILITY_NOT_METERED),   // KEY
signal
```

```
            validated = hasCapability(NetworkCapabilities.NET_CAPABILITY_VALIDATED),    // real
internet, not captive
            bandwidthKbps = linkDownstreamBandwidthKbps,
        )
    }
}
```

68.7.2 React: reconnect + retry + offline banner (Ch 63/2/6)

```
@Singleton
class NetworkReactor @Inject constructor(
    private val observer: ConnectivityObserver, private val realtime: RealtimeConnection,  // Ch
63
    private val retryScheduler: RetryScheduler, private val scope: CoroutineScope,          //
Ch 2
) {
    fun start() = scope.launch {
        observer.observe().collect { state ->
            when (state) {
                is NetworkState.Online -> if (state.validated) {    // "connected" is not enough
                    realtime.reconnect()                            // reconnect WebSocket (Ch
63)
                    retryScheduler.retryPending()                   // retry failed requests (Ch
2)
                } // not validated -> treat as offline for UX (captive portal)
                NetworkState.Offline -> realtime.pause()            // don't thrash reconnect
while offline
            }
        }
    }
}

// UI (Ch 6): val net by observer.observe().collectAsStateWithLifecycle(NetworkState.Offline)
//            if (net !is Online || !net.validated) OfflineBanner()
```

68.7.3 Metered-aware behavior (quality/prefetch, Ch 58/56)

```
fun videoBitrateCap(state: NetworkState): Int = when {
    state is NetworkState.Online && !state.metered -> Int.MAX_VALUE       // unmetered -> full
(Ch 58)
    state is NetworkState.Online && state.metered -> 720                  // metered -> cap
(data respect)
    else -> 0                                                             // offline ->
downloaded only (Ch 59)
}
fun shouldPrefetchImages(state: NetworkState): Boolean =
    state is NetworkState.Online && !state.metered                        // skip prefetch on
metered (Ch 56)
```

68.7.4 Defer heavy transfers to unmetered — WorkManager constraints (Ch 30/47)

```
// PREFER OS-enforced constraints over manual checks for deferrable background transfers.
fun scheduleBackup(workManager: WorkManager) = workManager.enqueue(
    OneTimeWorkRequestBuilder<BackupWorker>()
        .setConstraints(Constraints.Builder()
            .setRequiredNetworkType(NetworkType.UNMETERED)       // waits for Wi-Fi (Ch 30/47)
            .setRequiresBatteryNotLow(true).build())
        .build())
// Live Flow is for FOREGROUND/immediate decisions (banner, reconnect, quality);
// WorkManager constraints are for deferrable background work.
```

68.7.5 Advisory, not a gate (offline-first, Ch 29)

```
// WRONG: if (!online) { showNoInternetWall(); return }   // over-gating
// RIGHT: feature works offline from SSOT (Ch 3/29); network state only informs UX/scheduling.
@Composable
fun FeedScreen(vm: FeedViewModel = hiltViewModel()) {
    val feed by vm.feed.collectAsStateWithLifecycle()        // from SSOT (Ch 3) - works offline
    val net by vm.network.collectAsStateWithLifecycle(NetworkState.Offline)
    Column {
        if (net is NetworkState.Offline) OfflineBanner()     // advisory only
        FeedList(feed)                                       // renders regardless of
connectivity
    }
}
```

68.7.6 Module structure

```
:core:connectivity  ConnectivityObserver (Flow), NetworkState, NetworkReactor
# Consumers: real-time (Ch 63), retry (Ch 2), media quality (Ch 58/56), UI (Ch 6),
# WorkManager constraints (Ch 30/47). Offline-first underlies it (Ch 29).
```

68.8 Concurrency and Race Conditions

Scenario	Risk	Handling
Rapid Wi-Fi ↔ cellular flaps	thrash (reconnect storms)	`distinctUntilChanged` + debounce; jittered reconnect (Ch 2/63)
"Connected" but captive portal	fake online	check `VALIDATED`; treat non-validated as offline
Poll-based stale state	wrong decisions	callback-driven Flow (not polling)
Multiple observers register	leak/duplicate callbacks	single shared `Flow` (`shareIn`)
Reconnect while offline	wasted attempts	pause reconnect on Offline; resume on validated Online
Metered mis-detected as Wi-Fi	data burn	use `NOT_METERED` capability, not "is Wi-Fi"
Callback not unregistered	leak	`awaitClose` unregister; app-scoped

- **`VALIDATED` prevents the captive-portal false-online:** acting on `onAvailable` alone reconnects/retries against a network with no real internet; gating reactions on **`NET_CAPABILITY_VALIDATED`** avoids wasted attempts and wrong "online" UI.
- **Debounce flaps + jittered reconnect:** Wi-Fi ↔ cellular hand-offs flap quickly; `distinctUntilChanged`/conflate the state and use jittered reconnect (Ch 2/63) so you don't thrash connections.
- **One shared Flow:** multiple independent callback registrations leak and duplicate; share a single `Flow` (`shareIn`/singleton) across all consumers.

68.9 Failure Scenarios and Recovery

Failure	Detection	Response	Outcome
Fake "online" (captive portal)	validated=false	treat as offline for UX	correct
Stale offline banner	polling/no callback	callback-driven Flow	accurate
Data-plan burn	metered ignored	respect `NOT_METERED`; defer/lower (Ch 30/58)	data saved
WebSocket stays dead after recovery	no reaction	reconnect on validated Online (Ch 63)	reconnects
Failed request never retried	no reaction	retry on recovery (Ch 2)	completes
Reconnect storm on flaps	thrash	debounce + jittered reconnect	stable
Feature blocked offline	over-gating	advisory-only; offline-first SSOT (Ch 29)	works
Callback leak	memory	unregister in `awaitClose`	no leak


68.9 Failure Scenarios and Recovery

> **Two rules fix most network-state bugs: check `VALIDATED` (connected ≠ internet) and treat state as advisory, not a gate (offline-first, Ch 29).** Build one callback-driven `Flow`, react to validated transitions (reconnect/retry/quality), respect `metered` (prefer WorkManager constraints for deferrable work), and never block an offline-capable feature on connectivity.

68.10 Scaling the Implementation

- **Level 1.** `ConnectivityObserver` Flow (connected/offline); offline banner (Ch 6).
- **Level 2.** Validated + metered + transport awareness; react (reconnect Ch 63, retry Ch 2); metered-aware quality (Ch 58/56).
- **Level 3 — production.** WorkManager constraints for deferrable transfers (Ch 30/47); debounced flaps + jittered reconnect; single shared Flow; advisory-not-gating (Ch 29).
- **Level 4 — large.** Bandwidth-adaptive behavior; per-feature network policies; captive- portal handling; data-saver mode respect.
- **Level 5 — enterprise.** Connectivity analytics (transport mix, validated rate, metered usage), network-policy governance, adaptive sync/transfer strategies, cross-platform parity.

Avoid overengineering: one observable `NetworkState` + validated/metered checks + WorkManager constraints covers most needs. Don't poll, don't gate offline-capable features, don't scatter checks.

68.11 Alternative Approaches and Trade-offs

Dimension	Option A	Option B	When
Observe	`NetworkCallback` Flow	`activeNetworkInfo` polling / broadcast	Callback (modern, reactive); polling deprecated/stale
Online check	`VALIDATED` capability	connected only	Validated (connected ≠ internet)
Metered	`NOT_METERED` capability	"is Wi-Fi?"	Capability (some Wi-Fi metered, some cellular not)
Deferrable transfers	WorkManager constraints (Ch 30)	manual Flow checks	WorkManager (OS-enforced, Doze-aware, Ch 47)
Immediate decisions	Live Flow (reconnect/quality/UI)	WorkManager	Flow for foreground/immediate
Role	Advisory (UX/scheduling)	correctness gate	Advisory (offline-first, Ch 29)
Source	Single shared observer	per-screen checks	Single (consistency)

Callback Flow vs polling/broadcast: the deprecated `activeNetworkInfo` polling and `CONNECTIVITY_ACTION` broadcast are unreliable and stale — they miss transitions and capability details. A **`NetworkCallback`** wrapped in a `callbackFlow` **pushes** accurate, capability-rich state (transport/metered/validated) reactively. Always use the callback Flow.

Validated/metered capabilities vs naive checks: checking "connected" misses captive portals (fake online); checking "is Wi-Fi?" misses **metered Wi-Fi** and **unmetered cellular**. The OS **capabilities** (`VALIDATED` , `NOT_METERED`) are the correct signals — use them, not transport-type heuristics.

WorkManager constraints vs manual Flow checks for background transfers: for a deferrable transfer, **declaring** a `NetworkType.UNMETERED` constraint lets the **OS** wait for Wi-Fi, handle Doze, and retry (Ch 30/47) — far more robust than manually observing the Flow and launching work. Use WorkManager constraints for **deferrable background** work; reserve the live Flow for **immediate foreground** decisions (banner, reconnect, quality).

68.12 Security Considerations

- **Don't trust the network type for security:** being on "Wi-Fi" or "a trusted network" is **not** a security boundary — always use **TLS + certificate pinning** (Ch 23) regardless of transport; a hostile Wi-Fi is a MITM risk.
- **Captive portals (`VALIDATED`):** a captive portal can intercept traffic; treat non-validated networks as untrusted/offline and rely on the OS captive-portal flow — don't send sensitive requests assuming a clean path.
- **Metered awareness is a user-cost concern, not security**, but respect it (data plans).
- **No sensitive data in connectivity logs** (Ch 28); network state itself (transport/ metered) is low-sensitivity but don't log identifiers.
- **Data-saver mode:** respect the user's Data Saver setting (`ConnectivityManager.getRestrictBackgroundStatus`) — don't do background data when the user

restricted it.
- Client vs backend: network state is a client concern for UX/scheduling; the backend enforces auth/TLS regardless of the client's transport (Ch 19/23) — never assume a "trusted network".

68.13 Performance and Resource Optimization

- **Callback over polling** — no wasted periodic checks; react only on change.
- **Single shared Flow** (`shareIn`) — one callback for the whole app, not many.
- **Debounce flaps** (`distinctUntilChanged` /conflate) — avoid reconnect storms on hand-off (Ch 63).
- **WorkManager constraints** — OS schedules transfers in good conditions (unmetered/ charging, Ch 30/47) instead of the app spinning.
- **Metered-aware** — defer/lower on metered saves the user's data and battery (radio).
- **Bandwidth-adaptive** — scale quality/prefetch to `bandwidthKbps` where useful.
- **Profiling:** reconnect frequency, metered-vs-unmetered data usage, validated rate, callback overhead (negligible), transfer deferral effectiveness.

68.14 Testing Strategy

`ConnectivityObserver` tests with a fake `ConnectivityManager` /shadow; reactions in isolation.

```
class ConnectivityObserverTest {
    @Test fun `emits offline when no internet capability`() = runTest {
        shadowCm.setNoNetwork()
        assertEquals(NetworkState.Offline, observer.observe().first())
    }
    @Test fun `online but not validated is treated as offline for UX`() = runTest {
        shadowCm.setCapabilities(internet = true, validated = false)
        val s = observer.observe().first()
        assertTrue(s is NetworkState.Online && !(s).validated)   // consumer treats as offline
    }
    @Test fun `detects metered cellular`() = runTest {
        shadowCm.setCapabilities(internet = true, validated = true, transport = CELLULAR,
notMetered = false)
        assertTrue((observer.observe().first() as NetworkState.Online).metered)
    }
}

class NetworkReactorTest {
    @Test fun `reconnects and retries on validated recovery`() = runTest {
        emit(NetworkState.Offline); emit(online(validated = true))
        assertTrue(realtime.reconnected && retry.retried)
    }
    @Test fun `does not reconnect when not validated`() = runTest { /* captive portal -> no
reconnect */ }
}

class MeteredPolicyTest { @Test fun `skips prefetch and caps bitrate on metered`() { /* ... */ }
}
```

What to test: observer maps capabilities → state (offline/validated/metered/transport); reactor reconnects+retries only on **validated** recovery (not captive portal); metered- aware quality/prefetch; WorkManager UNMETERED constraint on deferrable work; advisory-not- gating (feature renders offline); flap debounce. Use Robolectric shadow `ConnectivityManager`; instrumentation for real transitions.

68.15 Production Observability

- **Metrics:** validated rate (captive-portal frequency); **metered vs unmetered data usage**; reconnect frequency (flaps); transport mix (Wi-Fi/cellular); failed-request retry-on-recovery success; transfer-deferral effectiveness (how much heavy work ran on Wi-Fi); offline-banner accuracy.
- **Logs:** `net{transport, metered, validated, event}` — no identifiers/PII (Ch 28).
- **Debugging:** fake online → not checking `VALIDATED`; stale banner → polling / not callback-driven; data burn → metered ignored / not using WorkManager constraints; dead reconnect → not reacting to recovery (Ch 63); over-gating → blocking offline-capable features (Ch 29); reconnect storm → no flap debounce.

- **Alerting:** reconnect-storm spike; metered-data-usage spike (deferral regression); low validated rate (connectivity issues).
- **Dashboards:** transport mix + validated rate; metered data usage; reconnect frequency.

68.16 System Design Interview Preparation

> ≥25 questions.

Fundamentals

1. *Modern API?* `ConnectivityManager.NetworkCallback` (wrap in a Flow); not deprecated polling/broadcast.
2. *Why not polling?* Stale, misses transitions/capabilities.
3. *"Connected" vs "has internet"?* Check `NET_CAPABILITY_VALIDATED` (captive portals).
4. *Capabilities that matter?* Transport, `NOT_METERED`, `VALIDATED`, bandwidth.
5. *Derive what?* A clean `NetworkState` (Offline / Online(transport, metered, validated, bandwidth)).

Metered/transport 6. *Metered signal?* `NET_CAPABILITY_NOT_METERED` — not "is Wi-Fi". 7. *Why not "is Wi-Fi"?* Some Wi-Fi is metered; some cellular isn't. 8. *On metered?* Defer heavy transfers; lower quality; skip prefetch (Ch 30/58/56).

Reacting 9. *On recovery?* Reconnect real-time (Ch 63) + retry failed requests (Ch 2) — if validated. 10. *While offline?* Pause reconnect (don't thrash); show banner. 11. *Deferrable transfers?* WorkManager `NetworkType.UNMETERED` constraint (Ch 30/47). 12. *Flow vs WorkManager?* Flow for immediate/foreground; constraints for deferrable background.

Advisory 13. *Is network state a correctness gate?* No — advisory for UX/scheduling (offline-first, Ch 29). 14. *Over-gating?* Blocking offline-capable features on connectivity — avoid. 15. *Offline features work how?* From the SSOT (Ch 3); sync when online (Ch 32).

Correctness 16. *Captive portal?* Non-validated → treat as offline for UX. 17. *Flaps?* Debounce (`distinctUntilChanged`) + jittered reconnect. 18. *Single source?* One shared observer Flow.

Security 19. *Trust the network type?* No — TLS + pinning regardless (Ch 23). 20. *Data Saver?* Respect `getRestrictBackgroundStatus`.

Testing/Production 21. *Test observer?* Shadow `ConnectivityManager` → capabilities → state. 22. *Test reactor?* Reconnect/retry only on validated. 23. *Fake online in prod?* Not checking validated. 24. *Data burn?* Metered ignored / no WorkManager constraint. 25. *Stale banner?* Polling not callback. 26. *Key metrics?* Validated rate, metered data usage, reconnect frequency.

Design-change challenges

1. **Offline banner + auto-reconnect.** Observer Flow → banner (Ch 6) + reconnect on validated recovery (Ch 63).
2. **Don't burn data on cellular.** Respect `NOT_METERED`; defer downloads (WorkManager UNMETERED), cap bitrate (Ch 30/58).

3. **App shows "online" on a captive-portal Wi-Fi.** Check `VALIDATED`.
4. **Failed requests don't retry when Wi-Fi returns.** React to recovery → retry (Ch 2).
5. **Feature blocked with a "no internet" wall though it works offline.** Make state advisory; offline-first SSOT (Ch 29).

Mock walkthrough (abridged)

Clarify (what reacts to network, metered-sensitive, offline-capable?) → one `ConnectivityObserver` Flow from `NetworkCallback` → `NetworkState` (transport/metered/ **validated**) → react (reconnect Ch 63, retry Ch 2, quality Ch 58/56, banner Ch 6) → defer heavy work via WorkManager constraints (Ch 30/47) → advisory-not-gating (offline-first, Ch 29) → security (TLS regardless, Data Saver) → observability (validated rate, metered usage).

68.17 Practical Exercises

1. **Beginner.** Build a `ConnectivityObserver` Flow from `registerDefaultNetworkCallback` emitting Offline/Online, and drive an offline banner (Ch 6). *Eval:* reactive; accurate.
2. **Intermediate.** Extend `NetworkState` with transport + metered + **validated**; treat non-validated (captive portal) as offline for UX. *Eval:* correct online detection.
3. **Advanced.** React to validated recovery by reconnecting the WebSocket (Ch 63) and retrying failed requests (Ch 2); debounce flaps. *Eval:* reconnects; no storm.
4. **Production debugging.** Fix data-plan burn (metered ignored → add WorkManager UNMETERED
    - bitrate cap) and a "no internet" wall on an offline-capable feature. *Eval:* data saved; feature works offline.
5. **System design challenge.** Make one shared observer feed UI + real-time + transfers, add bandwidth-adaptive quality, and a validated-rate/metered-usage dashboard. *Eval:* single source; adaptive; observable.

(Solutions withheld unless requested.)

68.18 Chapter Summary & Reference Sheet

Key decisions: expose network state as a **single observable** `Flow` built on `ConnectivityManager.NetworkCallback` (`registerDefaultNetworkCallback`, wrapped in a `callbackFlow` and shared) — **never** the deprecated `activeNetworkInfo` polling or `CONNECTIVITY_ACTION` broadcast — reporting **connected + transport (Wi-Fi/cellular) + metered + validated + bandwidth**, and **critically check** `NET_CAPABILITY_VALIDATED` because "connected" ≠ "has internet" (captive portals) and use `NET_CAPABILITY_NOT_METERED` (not "is Wi-Fi") for the metered signal; **react** to **validated** transitions — reconnect real-time (Ch 63), retry failed requests (Ch 2), adjust quality/prefetch on metered (Ch 58/56), show an offline banner (Ch 6) — while **deferring heavy background transfers to unmetered via WorkManager constraints** (`NetworkType.UNMETERED`, OS-enforced, Ch 30/47) rather than manual checks; **debounce flaps** and use jittered reconnect to avoid storms (Ch 2/63); and treat network state as **advisory for UX and scheduling, never a correctness gate** — the app **works offline from the SSOT** (Ch 29) and syncs when suitable connectivity returns. Never trust the network type as a security boundary — **TLS + pinning regardless** (Ch 23) — and respect **Data Saver**.

Concepts: `NetworkCallback` Flow, capabilities (transport/ `NOT_METERED` / `VALIDATED` / bandwidth), validated (connected ≠ internet), metered-aware behavior, react (reconnect/ retry/quality/UI), WorkManager constraints for deferrable work, advisory-not-gating (offline-first), single source, flap debounce.

Common mistakes: polling/deprecated APIs (stale); treating "connected" as online (captive portal — missing `VALIDATED`); using "is Wi-Fi" for metered (missing `NOT_METERED`); not reacting to recovery (dead reconnect/no retry); manual checks instead of WorkManager constraints for background transfers; gating offline-capable features on connectivity (over-gating); scattered per-screen checks; no flap debounce (reconnect storms); trusting the network type for security.

Checklist: ☐ `NetworkCallback` Flow (single shared source), not polling ☐ check `VALIDATED` (connected ≠ internet) ☐ use `NOT_METERED` capability (not "is Wi-Fi") ☐ react to validated recovery: reconnect (Ch 63) + retry (Ch 2) ☐ metered-aware quality/prefetch (Ch 58/56) ☐ defer heavy transfers via WorkManager UNMETERED (Ch 30/47) ☐ debounce flaps + jittered reconnect ☐ advisory, not a gate — offline-first SSOT (Ch 29) ☐ TLS+pinning regardless of transport (Ch 23) ☐ respect Data Saver ☐ validated-rate + metered-usage telemetry.

Key APIs: `ConnectivityManager.registerDefaultNetworkCallback` / `registerNetworkCallback` / `unregisterNetworkCallback`, `NetworkCallback` (`onAvailable` / `onLost` / `onCapabilitiesChanged` / `onUnavailable`), `NetworkCapabilities` (`NET_CAPABILITY_VALIDATED` / `NET_CAPABILITY_NOT_METERED` / `NET_CAPABILITY_INTERNET` / `TRANSPORT_*` / `linkDownstreamBandwidthKbps`), `callbackFlow` / `distinctUntilChanged` / `shareIn`, WorkManager `Constraints` / `NetworkType.UNMETERED` (Ch 30), `getRestrictBackgroundStatus` (Data Saver).

References:

- Monitor connectivity: https://developer.android.com/training/monitoring-device-state/connectivity-status-type
- NetworkCapabilities: https://developer.android.com/reference/android/net/NetworkCapabilities
- WorkManager constraints: https://developer.android.com/develop/background-work/background-tasks/persistent/getting-started/define-work#work-constraints
- (composes) Ch 1 Networking, Ch 2 Retries, Ch 29 Offline-First, Ch 30 WorkManager, Ch 63 WebSocket, Ch 58/56 Media, Ch 23 Security

Chapter review (Phase 4)

- **Completeness:** all 18 sections; architecture/class/sequence/flow/failure diagrams; ConnectivityObserver (callback→Flow, validated/metered) + reactor + metered policy + WorkManager constraints + advisory-not-gating code; concurrency (validated, flap debounce, single Flow); failure (check-validated + advisory principles); 5 levels; callback-vs- polling, capabilities-vs-heuristics, WorkManager-vs-manual trade-offs; security (no network trust, Data Saver); perf (callback/shared/debounce/constraints); shadow tests; observability (validated/metered/reconnect); 26 Q&A + 5 challenges. ✅
- **Expand later:** networking (Ch 1), retries (Ch 2), offline-first (Ch 29), WorkManager (Ch 30), WebSocket (Ch 63).
- **Interview coverage:** exceeds ≥25 bar.