Chapter 45 — App Startup Optimization

> **Part VI — Lifecycle, Background & Platform** · Complexity: **Standard** (≥25 interview questions)
>
> **Prerequisites:** Ch 44 (lifecycle, `Application.onCreate`), Ch 5 (Hilt/init), Ch 6 (UI state), Ch 12/13 (cache/paging for first screen). Pairs with Ch 46/47 (background), Ch 86/89 (perf/profiling).
>
> **Reference surface in StreamCart:** getting from tap to usable content fast — cold-start time, time-to-first-frame, and time-to-first-meaningful-content on the home feed.

45.1 Problem Definition and Real-World Context

Startup is the user's **first impression on every launch** and a ranked Play Store / Android vitals metric. A slow cold start (blank screen, spinner, jank) causes drop-off, bad reviews, and (past Google's thresholds) reduced store visibility. The problem is that everything competes to run at startup — DI graph creation, library initialization, first network calls, database opens, first-screen layout — and if that work lands on the **critical path to first frame**, the app feels slow.

Concretely, teams hit:

- **Heavy `Application.onCreate`.** Every SDK (analytics, crash, ads, image loader, feature flags) wants to initialize there; serialized on the main thread, this delays the first frame directly (Ch 44).
- **Three start types, one experience. Cold** (new process), **warm** (process alive, Activity recreated), and **hot** (Activity in memory) start cost very differently; optimizing only cold, or measuring the wrong one, misleads.
- **Blocking the first frame on data.** Waiting for a network call before showing anything → long blank screen. Should show cached/skeleton first (Ch 12/34).
- **Uncoordinated initialization.** Each library registers its own `ContentProvider` to auto-init (each one costs main-thread time); order and laziness are unmanaged.
- **No measurement.** Without startup traces / Android vitals, teams can't tell cold from warm, or find the slow initializer.

The architecture: understand the **three start types** and the **phases** (process fork → `Application` → first Activity → first frame → first meaningful content); **move work off the critical path** (lazy init, background init, defer non-essential SDKs); **coordinate initialization** with **Jetpack App Startup** instead of per-library `ContentProvider`s; **show content fast** (cached data + skeletons, not a blank wait on the network); and **measure** with startup traces, `reportFullyDrawn()`, Macrobenchmark, and Android vitals. This chapter is about **minimizing time-to-usable** and keeping it from regressing.

Three practical use cases

1. **StreamCart cold start.** Trim `Application.onCreate`, defer non-essential SDKs, show a cached/skeleton home feed immediately, and stream fresh data (Ch 29/34).

2. **Baseline Profiles.** Ship a Baseline Profile so hot code paths are AOT-compiled on first run → faster startup and smoother first scroll.
3. **Regression gate.** Macrobenchmark cold-start test in CI to catch startup regressions before release.

Why this is architectural

Startup optimization is about **what runs on the critical path** and **what the user sees first** — cross-cutting decisions touching DI, every SDK, the first screen's data strategy, and the build (Baseline Profiles, R8). It's measured, gated, and defended over time, not a one-off tweak.

45.2 Requirements Engineering

Functional requirements

ID	Requirement
F1	Show a first frame quickly (fast time-to-initial-display).
F2	Show meaningful content quickly (cached/skeleton, not a blank network wait).
F3	Keep `Application.onCreate` minimal; defer non-essential init.
F4	Coordinate initialization (App Startup) with correct ordering/laziness.
F5	Measure cold/warm/hot startup; report fully-drawn.
F6	Gate regressions (Macrobenchmark in CI; Android vitals).

Non-functional requirements

Attribute	Target/Policy
Cold start (TTID)	Fast (target e.g. <1s initial display on mid device; team-specific).
TTFMC	Meaningful content quickly (cached first).
Regression	CI gate on cold-start benchmark.
Correctness	Deferred init must not break first-use (lazy, not broken).
Battery	Don't do unnecessary eager work at startup.

Scope

- **In scope:** start types (cold/warm/hot), startup phases, `Application.onCreate` trimming, lazy/background init, Jetpack App Startup, first-screen data strategy (cache + skeleton), Baseline Profiles/R8 relation, measurement (traces, `reportFullyDrawn`, Macrobenchmark, vitals), regression gating.
- **Out of scope:** general lifecycle (Ch 44), background work (Ch 46/47), deep perf profiling methodology (Ch 86), Compose perf (Ch 60).

Assumptions & constraints

- Hilt, Compose, Jetpack App Startup, Macrobenchmark, R8/Baseline Profiles. `minSdk 24`. Cold start is unavoidable (process was killed, Ch 8); optimize its cost, not its existence.

45.3 System Design Fundamentals

- **Three start types (measure the right one):**
  - **Cold start:** no process exists. OS forks the process, creates `Application`, then the first Activity, then the first frame. The expensive case; `Application. onCreate` is on its critical path.
  - **Warm start:** process alive but the Activity was destroyed (e.g., returned after the OS reclaimed the Activity). Skips `Application` creation; recreates the Activity.
  - **Hot start:** Activity still in memory; cheapest (just bring to foreground).
- **Startup phases and the "critical path":** fork → `Application.onCreate` → first Activity `onCreate`/layout → **first frame drawn (TTID, time to initial display) → first meaningful content (TTFMC, `reportFullyDrawn`)**. Any main-thread work in these phases pushes the first frame later. The goal is to **shrink the critical path**: do only what's needed for the first frame now; defer the rest.
- **Move work off the critical path (the main lever):**
  - **Lazy init:** create expensive singletons when first used, not at startup (DI makes this natural, Ch 5).
  - **Background init:** initialize things that aren't needed for the first frame on a background dispatcher.
  - **Defer non-essential SDKs:** analytics/ads/feature-flags that aren't needed to render → init after first frame (e.g., post-`reportFullyDrawn`, or App Startup dependency ordering).
- **Jetpack App Startup (coordinated init):** replaces each library's own auto-initializing `ContentProvider` (each a main-thread cost) with a **single** `InitializationProvider` and `Initializer<T>` components with declared dependencies — so init order is explicit and you can make initializers lazy. Fewer providers, ordered init.
- **Show content fast, not a blank network wait:** render **cached data** (Ch 12/34) or a **skeleton** (Ch 6) on the first frame; fetch fresh in the background and update (offline-first, Ch 29). Blocking the first frame on a network call is the classic "slow launch" that's really a data-strategy problem.
- **Build-time help:**
  - **Baseline Profiles:** ship a profile of hot startup/first-scroll code so ART AOT-compiles it on install → faster startup and smoother first frames (big, nearly free win).
  - **R8** (Ch 27): smaller/faster code; startup-aware optimizations.
  - **Startup theme/splash:** a proper `SplashScreen` (windowBackground) avoids a blank white/black flash and gives perceived speed.
- **Measurement: startup traces** (Perfetto/System Trace), **`reportFullyDrawn()`** (marks TTFMC), **Macrobenchmark** (`StartupTimingMetric`, cold/warm/hot, in CI), and **Android vitals** (field cold-start distribution). Optimize what you measure.

Core insight: **cold start is the expensive case; shrink its critical path by doing only first-frame-essential work on the main thread (lazy/background/deferred init, coordinated via App Startup), show cached/skeleton content immediately instead of blocking on the network, lean on Baseline Profiles, and measure/gate with traces, `reportFullyDrawn`, Macrobenchmark and Android vitals** so startup is fast and stays fast.

45.4 High-Level Architecture



Components & ownership

- `Application` does only essential init; non-essential SDKs deferred.
- **Jetpack App Startup** coordinates/ordered initializers (one provider).
- **First Activity** renders cached/skeleton immediately; fetches fresh in background; calls `reportFullyDrawn()`.
- **Baseline Profile / R8** speed the code at build/install time.
- **Macrobenchmark / vitals** measure and gate.

Direction: minimal critical path → fast first frame → cached content now, fresh later → measured and gated.

45.5 Detailed Component Design



Technique	What it does	Cost of ignoring
Minimal `onCreate`	less main-thread work	slow every cold start
Lazy/background init	off critical path	slow first frame
App Startup	ordered, single provider	many providers, unordered
Cache + skeleton	content now	blank network wait
Baseline Profile	AOT hot paths	slower startup/jank
`reportFullyDrawn` + Macrobenchmark	measure/gate	silent regressions

45.6 End-to-End Data Flow

Cold start (optimized)



Init placement decision



45.7 Complete Kotlin Implementation

Package: `com.streamcart.startup`.

45.7.1 Minimal Application, deferred non-essential init

```
@HiltAndroidApp
class StreamCartApp : Application() {
    @Inject lateinit var appScope: CoroutineScope          // @ApplicationScope (Ch 5)
    @Inject lateinit var analytics: Lazy<AnalyticsSdk>     // Lazy -> not created at startup

    override fun onCreate() {
        super.onCreate()
        // ESSENTIAL, cheap, main-thread only:
        Timber.plant(/* redacting tree */)                 // crash/log context (Ch 28)
        // NON-ESSENTIAL -> background, off critical path:
        appScope.launch(Dispatchers.Default) {
            analytics.get().initialize()                    // deferred, not needed for first
frame
        }
    }
}
```

45.7.2 Jetpack App Startup: ordered, lazy initializers

```
// Essential, must run before first frame -> App Startup with explicit order.
class CrashReportingInitializer : Initializer<CrashReporter> {
    override fun create(context: Context): CrashReporter =
        CrashReporter.init(context)                         // cheap, essential
    override fun dependencies(): List<Class<out Initializer<*>>> = emptyList()
}

// Non-essential -> remove its auto-init (manifest) and init lazily/deferred instead.
// <provider android:name="androidx.startup.InitializationProvider" ...>
//   <meta-data android:name="...AnalyticsInitializer" tools:node="remove" />
// </provider>
```

45.7.3 First screen: cached/skeleton now, fresh later + reportFullyDrawn

```
class FirstScreenViewModel @Inject constructor(
    private val repo: FeedRepository,                       // offline-first (Ch 29)
) : ViewModel() {
    val uiState: StateFlow<FeedUiState> = repo.observeFeed() // emits cached immediately (Ch 3)
        .map { FeedUiState.Content(it) }
        .stateIn(viewModelScope, SharingStarted.Eagerly, FeedUiState.Skeleton)  // skeleton
first
    init { viewModelScope.launch { repo.refresh() } }       // fresh in background
}

@Composable
fun FirstScreen(vm: FirstScreenViewModel = hiltViewModel()) {
    val state by vm.uiState.collectAsStateWithLifecycle()
    val activity = LocalContext.current as? ComponentActivity
    when (state) {
        is FeedUiState.Skeleton -> SkeletonFeed()           // first frame content (perceived
speed)
        is FeedUiState.Content  -> {
            FeedList((state as FeedUiState.Content).items)
            LaunchedEffect(Unit) { activity?.reportFullyDrawn() }  // mark TTFMC
        }
    }
}
```

45.7.4 Macrobenchmark cold-start gate (CI)

```
@RunWith(AndroidJUnit4::class)
class StartupBenchmark {
    @get:Rule val rule = MacrobenchmarkRule()
    @Test fun coldStartup() = rule.measureRepeated(
        packageName = "com.streamcart",
        metrics = listOf(StartupTimingMetric()),            // timeToInitialDisplay +
fullDisplay
        iterations = 10,
        startupMode = StartupMode.COLD,
    ) {
        pressHome(); startActivityAndWait()                 // measures cold start to
reportFullyDrawn
    }
    // CI asserts the median stays under the budget -> regression gate.
}
```

45.7.5 Module structure

```
:app        minimal Application, App Startup initializers, SplashScreen
:feature:*  first-screen VM (cache-first + reportFullyDrawn)
:benchmark  Macrobenchmark (StartupTimingMetric) + Baseline Profile generation
# Baseline Profile shipped in :app; R8 full mode (Ch 27).
```

45.8 Concurrency and Race Conditions

Scenario	Risk	Handling
Background init not ready on first use	NPE/crash	`Lazy` / `await`; init essential synchronously
Deferred SDK used before init	missing event	essential path synchronous; others lazy-safe
First frame blocked on IO	slow TTID	load cache off main thread; skeleton first
App Startup dependency cycle	crash	acyclic `dependencies()`
`reportFullyDrawn` called repeatedly	wrong metric	once, when content first shown
Parallel init races	corrupted singletons	each init idempotent / `@Singleton` (Ch 5)

- **Essential vs deferred must be correct:** anything the first frame truly needs must be ready synchronously (cheaply) or awaited; only genuinely-not-needed work is deferred/background. Deferring something the first screen uses causes a crash or missing data — the subtle bug of aggressive startup trimming.
- **First-frame work must be off the main thread for IO:** loading cache should be on a background dispatcher (Room suspending, Ch 3); the main thread draws the skeleton immediately.

45.9 Failure Scenarios and Recovery

Failure	Detection	Response	Outcome
Slow cold start	vitals / Macrobenchmark	trim onCreate; defer SDKs; Baseline Profile	fast
Blank screen on launch	user report / trace	skeleton + cache first	content now
Deferred init crash on use	crash	make essential-for-first-use synchronous	no crash
Regression shipped	vitals spike	CI Macrobenchmark gate	caught pre-release
White flash before UI	visual	SplashScreen (windowBackground)	smooth
Jank on first scroll	frame metrics	Baseline Profile	smooth
Measuring wrong start type	misleading data	distinguish cold/warm/hot	correct focus


45.9 Failure Scenarios and Recovery

> **"Slow launch" is almost always one of four things:** heavy `Application.onCreate`, a first frame blocked on the network, un-AOT'd hot code, or measuring the wrong start type. A startup trace tells you which — don't optimize blind.

45.10 Scaling the Implementation

- **Level 1.** Minimal `Application.onCreate`; skeleton + cached first screen.
- **Level 2.** Jetpack App Startup for ordered init; defer non-essential SDKs; ship a Baseline Profile.
- **Level 3 — production.** `reportFullyDrawn`; Macrobenchmark cold-start in CI; Android vitals monitoring; SplashScreen API.
- **Level 4 — large.** Per-module init budgets; lazy feature initialization (Ch 5/96); R8 full mode; profile-guided optimization; startup-cost reviews per SDK added.
- **Level 5 — enterprise.** Startup SLOs with vitals alerting; automated regression gates per PR; per-device-class budgets (low-end vs flagship); dashboards of TTID/ TTFMC distributions.

Avoid overengineering: for most apps, a minimal `onCreate` + cache-first first screen + Baseline Profile + one Macrobenchmark gets 90% of the win. Don't micro-defer cheap init or build elaborate startup frameworks prematurely.

45.11 Alternative Approaches and Trade-offs

Dimension	Option A	Option B	When
Init coordination	Jetpack App Startup	per-library `ContentProvider`	App Startup (one provider, ordered); auto-providers cost main-thread time
Non-essential SDK	Defer/lazy	eager in onCreate	Defer unless needed for first frame
First screen	Cache + skeleton	block on network	Cache-first always (offline-first, Ch 29)
Compile	Baseline Profile + R8	none	Always ship a Baseline Profile
Measurement	Macrobenchmark + vitals	manual timing	Macrobenchmark (reproducible, CI) + vitals (field)
Splash	SplashScreen API	custom splash Activity	SplashScreen API (no extra Activity/latency)

App Startup vs per-library auto-init: many libraries auto-initialize via their own `ContentProvider`, each adding fixed main-thread cost at process start and giving you no control over order or laziness. Jetpack App Startup consolidates these into one `InitializationProvider` with explicit `Initializer` dependencies, so you pay for one provider, control ordering, and can defer/remove initializers. Prefer it; remove auto-init providers you don't need.

Cache-first vs network-blocking first screen: blocking the first frame on a network response produces a long blank/spinner launch that users perceive as "slow app," even when `onCreate` is fast. Rendering cached data (or a

skeleton) immediately and streaming fresh data in makes launch feel instant and is the offline-first default (Ch 29). The only cost is briefly showing slightly-stale data, which is almost always the right trade.

45.12 Security Considerations

- **Don't do security-sensitive heavy work on the hot startup path** in a way that leaks timing, but **do** gate sensitive screens (re-auth, Ch 21) before showing content — perceived speed must not bypass auth.
- **SplashScreen must not show protected content**; keep it a brand/skeleton.
- **Deferred analytics/attribution SDKs** still must honor consent (Ch 28/87) — defer *initialization timing*, not *consent*.
- **Baseline Profiles / R8** don't weaken security; R8 also obfuscates (Ch 27).
- Client vs backend: startup is a client-perceived-performance concern; backend is unaffected except that cache-first reduces cold-start request spikes.

45.13 Performance and Resource Optimization

This chapter *is* a performance chapter; key levers recap:

- **Trim the critical path:** minimal `onCreate`; defer/background non-essential init.
- **Baseline Profiles:** AOT hot startup + first-scroll paths (largest low-effort win).
- **Cache-first first screen:** content now, not a network wait.
- **R8 full mode** (Ch 27): smaller, faster code.
- **Avoid main-thread IO** at startup (cache load off-main; lazy DB open).
- **SplashScreen API** for perceived speed without an extra Activity.
- **Measure:** startup traces (find the slow initializer), Macrobenchmark (`StartupTimingMetric` cold/warm/hot), `reportFullyDrawn` (TTFMC), Android vitals (field distribution), per-device-class budgets.

45.14 Testing Strategy

Startup is validated by **Macrobenchmark** (timing) and field **vitals**; correctness of deferred init by unit/integration tests.

```
// Macrobenchmark: cold/warm/hot timing (see 45.7.4). Assert medians under budget in CI.

// Baseline Profile generation (run on CI/device):
@Test fun generateBaselineProfile() = baselineProfileRule.collect(packageName =
"com.streamcart") {
    pressHome(); startActivityAndWait()
    // scroll the first screen so the profile captures first-scroll hot paths
}

// Correctness: deferred SDK is initialized before first use path; essential init is
synchronous.
class StartupInitTest {
    @Test fun `essential init completes before first screen uses it`() { /* ... */ }
    @Test fun `deferred analytics initializes off critical path`() { /* ... */ }
}
```

What to test: cold/warm/hot timing (Macrobenchmark, CI-gated), Baseline Profile generation + presence, first screen renders skeleton then cached content, deferred init doesn't break first-use, `reportFullyDrawn` called exactly once.

45.15 Production Observability

- **Metrics:** Android vitals cold-start distribution (p50/p90/p95), TTID/TTFMC, excessive-startup rate, per-device-class startup, Baseline Profile coverage, first- frame jank.
- **Logs/traces:** startup Perfetto traces (per-phase), `reportFullyDrawn` timing, per-initializer timing (App Startup).
- **Debugging:** regression → Macrobenchmark + trace to find the new slow init; field- only slowness → low-end device class; blank launch → first-frame data blocking; jank → missing/stale Baseline Profile.
- **Alerting:** vitals cold-start p90 over budget → alert; CI benchmark regression → block merge.
- **Dashboards:** startup time by device class and app version over releases.

45.16 System Design Interview Preparation

> ≥25 questions.

Fundamentals

1. *Cold vs warm vs hot?* New process / process-alive-Activity-recreated / Activity-in- memory — decreasing cost.
2. *Startup phases?* fork → Application → first Activity → first frame (TTID) → first meaningful content (TTFMC).
3. *What's the critical path?* Main-thread work before the first frame.

4. *Biggest `onCreate` risk?* Heavy serialized SDK init.
5. *TTID vs TTFMC?* First frame drawn vs content actually meaningful (`reportFullyDrawn`).

Optimizing

6. *Main lever?* Move non-essential work off the critical path (lazy/background/defer).
7. *What to defer?* SDKs not needed for the first frame (analytics, ads).
8. *Jetpack App Startup?* One `InitializationProvider` + ordered `Initializer`s vs per-library providers.
9. *Why remove auto-init providers?* Each costs main-thread time at process start.
10. *First screen strategy?* Cached/skeleton now, fresh in background.
11. *Baseline Profiles?* AOT-compile hot startup/scroll paths → faster + smoother.
12. *R8's role?* Smaller/faster code (Ch 27).
13. *SplashScreen API?* Perceived speed, no extra Activity.

Measurement

14. *How measure startup?* Startup traces, Macrobenchmark `StartupTimingMetric`, `reportFullyDrawn`, Android vitals.
15. *Macrobenchmark vs manual?* Reproducible, CI-gateable, cold/warm/hot modes.
16. *Field vs lab?* Vitals (field distribution) vs Macrobenchmark (lab).
17. *Mark TTFMC?* `reportFullyDrawn()` when content is shown.

Pitfalls

18. *Deferring too much?* Deferred-but-needed init crashes first use.
19. *Measuring wrong type?* Confusing warm/hot with cold misleads.
20. *Blank launch cause?* First frame blocked on network.
21. *Jank on first scroll?* Missing Baseline Profile.

Security

22. *Speed vs auth?* Still gate sensitive screens (re-auth); splash shows no protected content.
23. *Deferred analytics + consent?* Defer timing, not consent.

Production

24. *Regression gate?* CI Macrobenchmark budget + vitals alert.
25. *Field-only slowness?* Low-end device class — set per-class budgets.
26. *Find the slow initializer?* Startup Perfetto trace.

Design-change challenges

1. **Cold start is 3s.** Trace → trim `onCreate`/defer SDKs, cache-first screen, Baseline Profile.
2. **Launch shows a blank screen for 2s.** Skeleton + cached content first; fetch in background.
3. **An SDK must init but not block startup.** Background/deferred init; essential path synchronous.
4. **Startup regressed after a release.** CI Macrobenchmark gate; trace the new init.
5. **First scroll janks.** Ship/refresh Baseline Profile; R8 full mode.

Mock walkthrough (abridged)

Clarify (which start type, target, device classes?) → phases & critical path → trim `onCreate`/App Startup/defer SDKs → cache-first first screen + `reportFullyDrawn` → Baseline Profile + R8 → measure (Macrobenchmark + vitals) → regression gate → security (auth still enforced).

45.17 Practical Exercises

1. **Beginner.** Move a non-essential SDK init out of `Application.onCreate` to a deferred/background init. *Eval:* first frame unaffected; SDK still works.
2. **Intermediate.** Make the first screen render a skeleton, then cached data, then fresh; call `reportFullyDrawn`. *Eval:* no blank wait; TTFMC marked.
3. **Advanced.** Add a Macrobenchmark cold-start test and a Baseline Profile; gate in CI. *Eval:* benchmark runs; profile ships; CI fails on regression.
4. **Production debugging.** A trace shows `onCreate` dominated by one initializer — convert it to App Startup lazy/background. *Eval:* critical path shortened.
5. **System design challenge.** Define per-device-class startup budgets and vitals alerting; investigate a field-only regression. *Eval:* budgets + alert; low-end diagnosed.

(Solutions withheld unless requested.)

45.18 Chapter Summary & Reference Sheet

Key decisions: treat **cold start** as the expensive case and **shrink its critical path** — keep `Application.onCreate` minimal, make init **lazy/background/deferred** unless it's needed for the first frame, and coordinate it with **Jetpack App Startup** (one provider, ordered initializers) instead of per-library auto-init providers; **show content immediately** (skeleton + cached data, fresh in the background — offline-first, Ch 29) rather than blocking the first frame on the network; ship a **Baseline Profile** (+ R8) so hot paths are AOT-compiled; use the **SplashScreen API** for perceived speed; and **measure and gate** with startup traces, `reportFullyDrawn()`, **Macrobenchmark** (cold/warm/hot in CI) and **Android vitals** (field) so startup is fast and stays fast.

Concepts: start types (cold/warm/hot), startup phases, critical path, TTID/TTFMC, lazy/background/deferred init, App Startup, cache-first first screen, Baseline Profiles, R8, SplashScreen API, Macrobenchmark, Android vitals, regression gating.

Common mistakes: heavy `Application.onCreate`; eager non-essential SDK init; blocking the first frame on the network; per-library auto-init providers; no Baseline Profile (jank); deferring something the first screen needs (crash); measuring the wrong start type; no CI regression gate.

Checklist:

- [ ] minimal `onCreate`
- [ ] defer/background non-essential init
- [ ] App Startup for ordering
- [ ] skeleton + cached first screen

- [ ] `reportFullyDrawn()`
- [ ] Baseline Profile + R8
- [ ] SplashScreen API
- [ ] Macrobenchmark cold-start in CI
- [ ] Android vitals monitoring
- [ ] per-device-class budgets.

Key APIs: `Application` / `@HiltAndroidApp`, `androidx.startup.Initializer` / `InitializationProvider`, `Lazy<T>` (Hilt), `ComponentActivity.reportFullyDrawn()`, `core-splashscreen` `SplashScreen`, Macrobenchmark `StartupTimingMetric` / `StartupMode`, Baseline Profile (`baselineProfileRule`), R8/ `proguard-rules`.

References:

- App startup time: https://developer.android.com/topic/performance/vitals/launch-time
- Jetpack App Startup: https://developer.android.com/topic/libraries/app-startup
- Baseline Profiles: https://developer.android.com/topic/performance/baselineprofiles/overview
- Macrobenchmark: https://developer.android.com/topic/performance/benchmarking/macrobenchmark-overview
- SplashScreen: https://developer.android.com/develop/ui/views/launch/splash-screen
- (composes) Ch 5 DI/lazy, Ch 29 Offline-First, Ch 27 R8, Ch 86 Profiling

Chapter review (Phase 4)

- **Completeness:** all 18 sections; architecture/class/sequence/decision/failure diagrams; minimal Application + App Startup + cache-first screen + reportFullyDrawn + Macrobenchmark code; concurrency (essential-vs-deferred, off-main IO); failure (slow/ blank/regression triage); 5 levels; App-Startup-vs-auto-init and cache-vs-network trade-offs; security (auth not bypassed); perf (Baseline Profiles etc.); Macrobenchmark
    - Baseline Profile tests; vitals observability; 26 Q&A + 5 challenges. ✅
- **Expand later:** profiling methodology (Ch 86), Compose perf (Ch 60), R8 (Ch 27).
- **Interview coverage:** exceeds ≥25 bar.