Chapter 58 — Media Playback State (Media3/ExoPlayer)

> **Part VII — Media & Files** · Complexity: **Complex** (≥40 interview questions)
>
> **Prerequisites:** Ch 46 (foreground services/MediaSessionService), Ch 44 (lifecycle), Ch 6 (UI state), Ch 3 (SSOT), Ch 8 (process death), Ch 32 (sync). Pairs with Ch 59 (offline downloads), Ch 57 (thumbnails), Ch 67 (background).
>
> **Reference surface in StreamCart:** the streaming half of the super-app — playing audio/video (adaptive HLS/DASH), keeping **playback state** consistent across the UI, notification, background, lock screen, Bluetooth/Auto, and process death, and resuming where the user left off.

58.1 Problem Definition and Real-World Context

Media playback is one of the hardest state-management problems on Android because **playback state lives in many places at once** and must stay consistent: the player engine, the on-screen UI, the media notification (Ch 46/50), the lock screen, Bluetooth headsets / Android Auto / Wear, and across **background** and **process death**. A naive implementation (an `ExoPlayer` created in a Fragment) breaks the moment the user backgrounds the app, rotates the screen, plugs in headphones, or the OS kills the process mid-stream.

Concretely, teams hit:

- **Player tied to the UI lifecycle.** An `ExoPlayer` owned by an Activity/Composable is destroyed on config change (Ch 44) and can't play in the background — playback should outlive the UI, in a `MediaSessionService` (Ch 46).
- **State scattered and inconsistent.** The notification shows "playing" while the UI shows "paused"; the lock-screen controls do nothing; Bluetooth next/previous is ignored. There must be **one source of truth for playback state** (the `MediaSession` / `Player`) that every surface observes and controls.
- **No system integration.** Audio focus (another app starts playing → you must duck/ pause), becoming-noisy (headphones unplugged → pause), media buttons, Android Auto/ Wear/Assistant — all require a `MediaSession`; hand-rolling misses them.
- **Adaptive streaming complexity.** HLS/DASH with multiple bitrates, ABR (adaptive bitrate), buffering, seeking, track selection (audio/subtitle), and DRM (Ch 59) — this is what ExoPlayer/Media3 handles; reinventing it is futile.
- **Resume & progress.** Saving and restoring **playback position** across process death (Ch 8) and app restarts, and syncing "continue watching" position across devices (Ch 32).
- **Lifecycle correctness.** Pause/resume on app background (Ch 44/67), release the player when truly done (resources/battery), handle interruptions (calls, other media).

The architecture: use **Media3** (the modern ExoPlayer) as the player engine inside a `MediaSessionService` (Ch 46) so playback **outlives the UI and runs in the background** with a system-managed media notification; expose a

`MediaSession` as the **single source of playback state** that the UI connects to via a `MediaController` (observe state, send commands) and that the system (notification, lock screen, Bluetooth, Auto, Assistant) controls uniformly; handle **audio focus**, **becoming-noisy**, and **interruptions**; support **adaptive streaming** (HLS/DASH, ABR, track selection) and hooks for **DRM/offline** (Ch 59); **persist and restore playback position** (SSOT + process death, Ch 3/8) and **sync** continue-watching (Ch 32); and manage **lifecycle** (background pause/continue per content type, release when done). This chapter is about **consistent, system-integrated, resilient media playback state**.

Three practical use cases

1. **Video playback (StreamCart).** An HLS stream plays in a Media3 player inside a `MediaSessionService`; the UI is a thin `MediaController` view; backgrounding keeps audio playing with a notification; rotation doesn't interrupt; position persists.
2. **Audio/podcast with background + controls.** Plays in the background with notification/lock-screen/Bluetooth controls; pauses on headphone unplug and on a phone call (audio focus); resumes after.
3. **Continue watching across devices.** Playback position is saved to the SSOT and synced (Ch 32); the user resumes on another device where they left off.

Why this is architectural

Playback state is a **multi-surface consistency problem** (UI, notification, lock screen, Bluetooth, Auto) layered on **background execution** (Ch 46/67), **lifecycle** (Ch 44), **process death** (Ch 8), **sync** (Ch 32), and **adaptive streaming/DRM** (Ch 59). The decisions — service-hosted player, `MediaSession` as the single source of truth, controller-based UI, audio-focus/interruption handling, position persistence/sync — determine whether playback is consistent, controllable everywhere, and resilient.

58.2 Requirements Engineering

Functional requirements

ID	Requirement
F1	Play audio/video (adaptive HLS/DASH), including in the background.
F2	Single source of playback state controllable from UI, notification, lock screen, Bluetooth/Auto.
F3	Handle audio focus, becoming-noisy, and interruptions (calls/other media).
F4	Persist/restore playback position across process death; sync continue-watching (Ch 8/32).
F5	Support track selection (audio/subtitle), seeking, playlist/queue.
F6	Manage lifecycle (background pause/continue by content, release when done).

Non-functional requirements

Attribute	Policy
Consistency	All surfaces reflect/control one state (no drift).
Resilience	Survives config change, background, process death.
Battery/Resources	Release player when done; background only when intended (Ch 46).
Quality	Smooth ABR, fast start, correct seeking/buffering.
Integration	Works with notification, lock screen, Bluetooth, Auto, Assistant.

Scope

- **In scope:** Media3/ExoPlayer, `MediaSessionService` (Ch 46), `MediaSession` as single source of truth, `MediaController` UI, audio focus / becoming-noisy / interruptions, adaptive streaming (HLS/DASH/ABR) + track selection, playlists/queue, position persist/ restore (Ch 8) + continue-watching sync (Ch 32), lifecycle (background/release), notification integration (Ch 46/50), DRM/offline hooks (Ch 59).
- **Out of scope:** offline downloads/DRM detail (Ch 59), foreground-service mechanics (Ch 46), notifications UI (Ch 50), thumbnails/posters (Ch 57), sync algorithm (Ch 32), background limits detail (Ch 67/47).

Assumptions & constraints

- **Media3** (`androidx.media3` , the current ExoPlayer), `MediaSessionService` / `MediaSession` / `MediaController` , Hilt, Room/DataStore (Ch 3/4), WorkManager (Ch 30). `minSdk 24` . Playback must run in the background (FGS, Ch 46) and survive process death (Ch 8); the system expects a `MediaSession` for integration.

58.3 System Design Fundamentals

- **Media3 is the engine; don't reinvent it.** Media3 (the evolution of ExoPlayer) handles **adaptive streaming** (HLS/DASH/SmoothStreaming), **ABR** (adaptive bitrate), buffering, seeking, **track selection** (audio/video/subtitle), **DRM** (Widevine, Ch 59), caching, and extensible `MediaSource` / `DataSource` pipelines. You configure and observe it — you don't build a player.
- **The player must outlive the UI → `MediaSessionService` (Ch 46).** Create the `ExoPlayer` / `MediaSession` inside a `MediaSessionService` (a foreground service, Ch 46, type `mediaPlayback`) so playback **continues in the background**, survives **config changes**, and is **owned** independently of any Activity. The UI is a **client**, not the owner.
- **`MediaSession` = the single source of playback state (the crux).** The `MediaSession` (wrapping the `Player`) exposes the **authoritative** playback state (playing/paused, position, duration, queue, metadata) and accepts **commands** (play/pause/seek/skip). Every surface — your UI, the system **media notification** (Ch 46/50), the **lock screen**, **Bluetooth** headsets, **Android Auto**, **Wear**, **Assistant** — observes and controls the *same* session. This is why there's no drift: there's one state, many controllers.
- **UI connects via `MediaController` .** The UI (Compose/Views) creates a `MediaController` that connects to the `MediaSession` (even across process), observes state (`Player.Listener`), and sends commands. The UI

holds **no** player state of its own — it renders the session's state (UDF, Ch 6). On config change the UI is recreated and re-attaches to the still-running session (no interruption).

- **System integration via the session:**
  - **Audio focus:** request focus; when another app takes it, **pause or duck** (Media3's `AudioAttributes` + `setHandleAudioBecomingNoisy` + focus handling do much automatically). On regaining focus, resume if appropriate.
  - **Becoming noisy:** headphones unplugged → **pause** (expected UX; `setHandleAudioBecomingNoisy(true)`).
  - **Media buttons / Bluetooth / Auto / Assistant:** routed to the session's command handlers automatically.
- **Adaptive streaming & track selection.** Provide an HLS/DASH `MediaItem`; Media3's `DefaultTrackSelector` + ABR pick bitrate by bandwidth; expose **track selection** (quality, audio language, subtitles) through the selector. Buffering/seeking are handled; you surface state (buffering spinner) from the player's state.
- **Playlists / queue.** Media3 supports a **playlist** (`setMediaItems`, queue navigation `seekToNext/Previous`); the session exposes queue metadata to all surfaces.
- **Position persistence & resume (Ch 8/3/32):**
  - **Process death:** save the current `mediaId + position` periodically and on pause/stop to the **SSOT** (Ch 3) / `SavedState` so you can **restore** on relaunch (Media3 also supports state restoration).
  - **Continue watching:** persist position to the SSOT and **sync** it (Ch 32) so other devices resume where the user left off (position is synced state).
- **Lifecycle (Ch 44/67).** For **audio** (podcast/music), **continue in background** (FGS, Ch 46). For **video**, you may **pause on background** (unless PiP/audio-only) to save resources/battery, per content type. **Release** the player/session when playback is truly done (`onDestroy` of the service / no controllers + stopped) to free codecs/ battery. Handle **interruptions** (incoming call → pause via focus; resume after).
- **DRM / offline hooks (Ch 59).** Protected content uses a DRM session (Widevine); offline playback uses downloaded media + offline license (Ch 59) — Media3 integrates both through its `MediaSource` / `DrmSessionManager` /download modules.

Core insight: **host the Media3 player in a `MediaSessionService` (Ch 46) so playback outlives the UI and runs in the background, and make the `MediaSession` the single source of playback state that the UI (via a `MediaController`, UDF, Ch 6) and the whole system (notification, lock screen, Bluetooth, Auto, Assistant) observe and control — eliminating state drift; let Media3 handle adaptive streaming/ABR/track-selection/DRM; handle audio focus, becoming-noisy, and interruptions; persist and restore playback position across process death (Ch 8) and sync continue-watching across devices (Ch 32); and manage lifecycle per content type (background-continue audio, pause video; release when done).**

58.4 High-Level Architecture


58.4 High-Level Architecture

Components & ownership

- `MediaSessionService` owns the **Media3 player** and the `MediaSession` — playback runs here, background-capable (Ch 46).

- `MediaSession` is the **single source of playback state**; all surfaces (notification, lock screen, Bluetooth, Auto) and the UI (`MediaController`) observe/ control it.
- **Persistence/sync** saves position to the SSOT and syncs continue-watching (Ch 3/32).

Direction: service-hosted player → session (single truth) → all surfaces + UI controller; position persisted/synced; lifecycle managed.

58.5 Detailed Component Design

 58.5 Detailed Component Design

Component	Responsibility
`PlaybackService`	own Media3 player + `MediaSession` ; background; release
`MediaSession`	single source of playback state + command target
`MediaController` (in UI/VM)	observe state + send commands (UDF, Ch 6)
`PositionTracker`	persist position (SSOT, Ch 3/8) + sync continue-watching (Ch 32)

58.6 End-to-End Data Flow

UI, notification, and Bluetooth all control one session

 UI, notification, and Bluetooth all control one session

Resume across process death + continue-watching sync

 Resume across process death + continue-watching sync

---

58.7 Complete Kotlin Implementation

Package: `com.streamcart.playback` .

58.7.1 MediaSessionService hosting the Media3 player (Ch 46)

```
@AndroidEntryPoint
class PlaybackService : MediaSessionService() {       // FGS type mediaPlayback (Ch 46)
    @Inject lateinit var positionTracker: PositionTracker
    private lateinit var player: ExoPlayer
    private lateinit var session: MediaSession

    override fun onCreate() {
        super.onCreate()
        player = ExoPlayer.Builder(this)
            .setAudioAttributes(AudioAttributes.DEFAULT, /* handleAudioFocus = */ true)   //
audio focus
            .setHandleAudioBecomingNoisy(true)                                            //
pause on unplug
            .build()
            .also { it.addListener(positionListener()) }
        session = MediaSession.Builder(this, player).build()   // the SINGLE source of playback
state
    }
    override fun onGetSession(controllerInfo: MediaSession.ControllerInfo) = session

    private fun positionListener() = object : Player.Listener {
        override fun onIsPlayingChanged(isPlaying: Boolean) {
            if (!isPlaying) positionTracker.save(player.currentMediaItem?.mediaId,
player.currentPosition)  // Ch 3
        }
        override fun onMediaItemTransition(item: MediaItem?, reason: Int) { /* save on track
change */ }
    }

    override fun onDestroy() {                          // release when done (resources/battery)
        positionTracker.save(player.currentMediaItem?.mediaId, player.currentPosition)
        session.release(); player.release(); super.onDestroy()
    }
}
```

58.7.2 UI connects via MediaController (observes the single state, UDF Ch 6)

```
@HiltViewModel
class PlaybackViewModel @Inject constructor(
    @ApplicationContext private val ctx: Context,
) : ViewModel() {
    private var controller: MediaController? = null
    private val _state = MutableStateFlow(PlaybackUiState())
    val state: StateFlow<PlaybackUiState> = _state.asStateFlow()

    fun connect() {
        val token = SessionToken(ctx, ComponentName(ctx, PlaybackService::class.java))
        val future = MediaController.Builder(ctx, token).buildAsync()
        future.addListener({
            controller = future.get().also { c ->
                c.addListener(object : Player.Listener {           // render the SESSION's state
(no local truth)
                    override fun onEvents(player: Player, events: Player.Events) {
                        _state.value = PlaybackUiState(
                            isPlaying = player.isPlaying, position = player.currentPosition,
                            duration = player.duration, buffering = player.playbackState ==
Player.STATE_BUFFERING)
                    }
                })
            }
        }, MoreExecutors.directExecutor())
    }
    fun playPause() { controller?.let { if (it.isPlaying) it.pause() else it.play() } }  //
commands -> session
    fun seekTo(ms: Long) { controller?.seekTo(ms) }
    override fun onCleared() { controller?.release() }   // release controller, NOT the
session/player
}
```

58.7.3 Playing adaptive content + resume to saved position

```
fun PlaybackViewModel.play(mediaId: String, hlsUrl: String) {
    val resumeAt = positionTracker.restore(mediaId)        // continue-watching (Ch 3/32)
    val item = MediaItem.Builder().setMediaId(mediaId).setUri(hlsUrl)
        .setMimeType(MimeTypes.APPLICATION_M3U8)           // HLS; Media3 handles ABR
        .build()
    controller?.apply { setMediaItem(item, resumeAt); prepare(); play() }   // seek to saved
position
}
```

58.7.4 Position persistence + continue-watching sync (Ch 3/32)

```
@Singleton
class PositionTracker @Inject constructor(
    private val dao: PlaybackPositionDao,       // Room SSOT (Ch 3)
    private val syncRepo: SyncRepository,       // Ch 32
    private val scope: CoroutineScope,          // app scope (Ch 5)
) {
    fun save(mediaId: String?, positionMs: Long) {
        mediaId ?: return
        scope.launch {
            dao.upsert(PlaybackPosition(mediaId, positionMs, System.currentTimeMillis()))  // survive process death (Ch 8)
            syncRepo.pushContinueWatching(mediaId, positionMs)   // sync across devices (Ch 32, debounced/outbox Ch 31)
        }
    }
    suspend fun restore(mediaId: String): Long = dao.get(mediaId)?.positionMs ?: 0L
}
```

58.7.5 Track selection (quality / subtitles)

```
// Expose Media3 track selection to the UI (quality, audio language, subtitles).
fun PlaybackViewModel.selectSubtitle(languageTag: String) {
    controller?.trackSelectionParameters = controller!!.trackSelectionParameters.buildUpon()
        .setPreferredTextLanguage(languageTag).build()
}
fun PlaybackViewModel.capQuality(maxHeight: Int) {
    controller?.trackSelectionParameters = controller!!.trackSelectionParameters.buildUpon()
        .setMaxVideoSize(Int.MAX_VALUE, maxHeight).build()   // ABR within cap
}
```

58.7.6 Module structure

```
:feature:player   PlaybackService (MediaSessionService), PlaybackViewModel (MediaController), player UI
:core:playback    PositionTracker, PlaybackPositionDao (Room SSOT, Ch 3), continue-watching sync (Ch 32)
# FGS/notification -> Ch 46/50; offline/DRM -> Ch 59; background limits -> Ch 67.
```

58.8 Concurrency and Race Conditions

Scenario	Risk	Handling
UI owns player state	drift with notification/BT	session is single truth; UI observes via controller
Config change recreates UI	playback interrupted	player in service; UI re-attaches controller
Multiple controllers (UI + Auto)	conflicting commands	session serializes commands; single player
Position save races with transition	wrong position saved	save on pause/stop/transition from player state
Audio focus loss during command	double pause/resume	let Media3 handle focus; idempotent commands
Process death mid-playback	lost position	periodic + on-pause save to SSOT (Ch 8); restore on relaunch
Controller released but service running	leaks/wrong lifetime	release controller in UI `onCleared`, not the session

- **The `MediaSession` serializes state and commands**, so multiple controllers (your UI, Android Auto, a Bluetooth remote) can't drive conflicting states — there's one player, one state, commands applied in order. This is the whole reason drift disappears.
- **Separate the controller's lifecycle from the session's:** the UI `MediaController` is released on UI teardown, but the **session/player live in the service** and keep playing — never release the player when the UI goes away (only when playback is truly done).
- **Persist position from the player's authoritative state** (on pause/stop/transition + periodically) so saves reflect true position, surviving process death (Ch 8).

58.9 Failure Scenarios and Recovery

Failure	Detection	Response	Outcome
Notification/UI/BT state drift	user report	single session as truth; all observe it	consistent
Playback stops on background	user report	`MediaSessionService` FGS (Ch 46)	continues (audio)
Playback lost on rotation	user report	player in service; UI re-attaches	uninterrupted
Position lost on process death	user report	periodic + on-pause SSOT save; restore (Ch 8)	resumes
Doesn't pause on headphone unplug	user report	`setHandleAudioBecomingNoisy(true)`	pauses
Keeps playing over a phone call	user report	audio focus handling	pauses/ducks
Player never released	battery/resources	release in service `onDestroy`/when done	freed
Continue-watching not synced	user report	persist + sync position (Ch 32)	cross-device


58.9 Failure Scenarios and Recovery

> **One principle resolves most playback bugs: the `MediaSession` (in a service) is the single source of playback state.** Drift (UI vs notification vs Bluetooth), background survival, and config-change resilience all

> follow from putting the player in a `MediaSessionService` and having every surface — including your UI — observe and control that one session rather than holding its own state.

58.10 Scaling the Implementation

- **Level 1.** Media3 player in a `MediaSessionService`; UI via `MediaController`; HLS/DASH playback.
- **Level 2.** Audio focus / becoming-noisy / interruptions; media notification + lock screen + Bluetooth (free via session); position persist + resume (Ch 8).
- **Level 3 — production.** Continue-watching sync (Ch 32); track selection (quality/ subtitles); playlist/queue; lifecycle (bg-audio/pause-video, release when done).
- **Level 4 — large.** Android Auto/Wear/Assistant integration; ABR tuning; DRM + offline (Ch 59); PiP for video; casting (Cast); analytics (QoE: start time, rebuffering).
- **Level 5 — enterprise.** Playback QoE SLOs (startup latency, rebuffer ratio), adaptive- bitrate policy, multi-DRM, cross-device resume governance, A/B of player behavior.

Avoid overengineering: use Media3 + `MediaSessionService` + `MediaController`; the session gives you notification/lock-screen/Bluetooth/Auto nearly for free. Don't hand-roll the player, the notification, or a second state store.

58.11 Alternative Approaches and Trade-offs

Dimension	Option A	Option B	When
Player engine	Media3/ExoPlayer	`MediaPlayer` / custom	Media3 (ABR/HLS/DASH/DRM); `MediaPlayer` only for trivial cases
Player host	`MediaSessionService` (FGS)	in Activity/Fragment	Service (background, outlives UI); in-UI breaks on bg/rotation
State source	`MediaSession` (single truth)	UI-held state	Session (no drift, system integration)
UI link	`MediaController`	direct player reference	Controller (cross-process, lifecycle-safe)
Background video	Pause (unless PiP/audio)	keep rendering	Pause (battery) unless PiP/audio-only
Position	SSOT persist + sync (Ch 3/32)	in-memory only	Persist+sync (process death + cross-device)
Audio focus	Media3-managed	manual	Media3-managed (handles duck/pause/resume)

Media3/ExoPlayer vs `MediaPlayer`: `MediaPlayer` is a thin wrapper suitable only for trivial single-file playback — it lacks robust adaptive streaming (HLS/DASH), ABR, track selection, DRM, and a modern state model. **Media3/ExoPlayer** is the production standard: adaptive streaming, extensible pipelines, DRM, offline (Ch 59), and `MediaSession` integration. Use Media3 for any real media app.

`MediaSession` as single truth vs UI-held state: holding playback state in the UI guarantees drift — the notification, lock screen, and Bluetooth can't see or control it, and config changes/background break it. Making the

`MediaSession` the single authoritative state (in a service) means every surface, including your UI via a `MediaController`, observes and controls the *same* state — the system handles notification/ lock-screen/Bluetooth/Auto automatically. This is the central design decision.

Service-hosted vs UI-hosted player: an `ExoPlayer` created in an Activity/Composable is destroyed on config change and can't play in the background. Hosting it in a `MediaSessionService` (Ch 46) lets playback **outlive the UI**, run in the **background**, and survive rotation — the UI becomes a reconnectable client. Always host the player in a service for real playback.

58.12 Security & DRM Considerations

- **DRM for protected content (Ch 59):** premium video uses **Widevine** via Media3's `DrmSessionManager`; keys are handled by the platform DRM stack, never exposed to app code; offline playback uses offline licenses (Ch 59). Don't attempt to decrypt in app code.
- **Secure output / screen capture:** DRM content may require `FLAG_SECURE` and secure surfaces to block screenshots/recording of protected video (Ch 44).
- **Authenticated manifests/segments:** HLS/DASH URLs and license requests go over the **authenticated, pinned** network stack (Ch 19/23); use signed/expiring URLs for content; don't leak content URLs.
- **Don't log media URLs/keys/PII** (Ch 28); playback analytics use content ids, not signed URLs.
- **Per-account entitlements (Ch 42):** verify the user is entitled to the content server-side (Ch 23); the client player trusts the server's authorization.
- Client vs backend: the backend issues **entitlements, signed URLs, and DRM licenses**; the client plays within those and uses secure surfaces — it never holds decryption keys or bypasses entitlement.

58.13 Performance and Resource Optimization

- **Release the player when done** (no controllers + stopped / service destroyed) — the top battery/memory lever (codecs/buffers are heavy).
- **Pause video on background** (unless PiP/audio-only) to stop decoding/rendering.
- **ABR tuning:** let Media3 adapt bitrate to bandwidth; cap quality on cellular/low battery (track selection) to save data.
- **Buffering policy:** tune load control (buffer sizes) for fast start vs memory; prefetch next item modestly.
- **Reuse one player/session** (don't create per screen); the service owns it.
- **Efficient position saves:** debounce/periodic + on-pause, not every frame (Ch 31/32).
- **Profiling:** QoE — startup latency (time to first frame), **rebuffer ratio**, bitrate distribution, dropped frames, battery during playback, player create/release counts.

58.14 Testing Strategy

Media3 provides test utilities (`TestExoPlayerBuilder`, `FakeMediaSource`, `RobolectricUtil`); state/persistence test in isolation.

```
@RunWith(AndroidJUnit4::class)
class PlaybackStateTest {
    @Test fun `controller reflects session state - no local truth`() {
        val player = TestExoPlayerBuilder(context).build()
        // attach a controller; assert UI state mirrors player.isPlaying/position
    }
    @Test fun `pause saves position to SSOT`() = runTest {
        val tracker = PositionTracker(fakeDao, fakeSync, testScope)
        tracker.save("m1", 12_340); assertEquals(12_340, fakeDao.get("m1")?.positionMs)
    }
    @Test fun `restore seeks to saved position`() = runTest { /* restore -> setMediaItem(item,
pos) */ }
}

class PositionSyncTest {
    @Test fun `continue-watching position synced`() = runTest { /* assert
syncRepo.pushContinueWatching */ }
}
// Audio focus / becoming-noisy / background: instrumentation on device (unplug, call,
background).
```

What to test: UI state mirrors the session (no local truth); position persist on pause/ transition + restore (Ch 8); continue-watching sync (Ch 32); command routing (play/pause/ seek) via controller; track selection; lifecycle (player survives config change, released when done). Instrumentation for audio focus, becoming-noisy, background continuation, notification/Bluetooth control.

58.15 Production Observability

- **Metrics (QoE): startup latency** (play → first frame), **rebuffer ratio/ frequency**, bitrate distribution, dropped frames, playback-error rate, continue- watching resume success, cross-device resume accuracy; state-drift incidents (0); player create/release balance; background-playback battery.
- **Logs:** `playback{mediaId, state, position, bitrate, event}` — no signed URLs/keys/PII (Ch 28).
- **Debugging:** drift → UI holding state (not observing session); stops in background → not in a service (Ch 46); position lost → not persisted (Ch 8); rebuffering → ABR/buffer policy/network; no Bluetooth control → session misconfigured; battery → player not released.
- **Alerting:** rebuffer-ratio or startup-latency regression; playback-error spike (CDN/ DRM); state-drift reports.
- **Dashboards:** QoE (startup latency, rebuffer ratio) by network/device; resume success.

58.16 System Design Interview Preparation

> ≥40 questions.

Fundamentals

1. *Why is playback state hard?* It lives across UI, notification, lock screen, Bluetooth, Auto, background, process death.
2. *Engine?* Media3/ExoPlayer (ABR, HLS/DASH, DRM, track selection).
3. *Why not* `MediaPlayer`*?* No robust adaptive streaming/DRM/state model.
4. *Where does the player live?* In a `MediaSessionService` (Ch 46) — outlives UI, background.
5. *Single source of playback state?* The `MediaSession`.

Session/controller

6. *What does* `MediaSession` *expose?* Authoritative state + command target.
7. *Who controls it?* UI (`MediaController`), notification, lock screen, Bluetooth, Auto, Assistant.
8. *How does the UI connect?* `MediaController` (cross-process), observes + commands.
9. *UI-held state?* No — render the session's state (UDF, Ch 6).
10. *Config change?* UI recreated, re-attaches to the running session.
11. *Multiple controllers conflict?* Session serializes; one player.

System integration

12. *Audio focus?* Request; pause/duck on loss; resume on regain (Media3-managed).
13. *Becoming noisy?* Pause on headphone unplug (`setHandleAudioBecomingNoisy`).
14. *Media buttons/Bluetooth/Auto?* Routed to the session automatically.
15. *Notification?* System media notification via the service (Ch 46/50).

Streaming

16. *Adaptive streaming?* HLS/DASH + ABR (Media3).
17. *Track selection?* Quality/audio/subtitle via `TrackSelectionParameters`.
18. *Buffering/seeking?* Handled; surface state from the player.
19. *Playlist/queue?* `setMediaItems`, seekToNext/Previous.

Persistence/resume

20. *Process death?* Save mediaId+position to SSOT; restore on relaunch (Ch 8).
21. *When to save?* Periodically + on pause/stop/transition.
22. *Continue watching cross-device?* Persist + sync position (Ch 32).

Lifecycle

23. *Background audio?* Continue (FGS, Ch 46).
24. *Background video?* Pause (unless PiP/audio-only) for battery.
25. *When to release?* When done (no controllers + stopped / service destroyed).
26. *Interruptions (call)?* Pause via audio focus; resume after.

DRM/security

27. *Protected content?* Widevine via `DrmSessionManager` (Ch 59); platform-held keys.
28. *Block screen capture?* `FLAG_SECURE`/secure surface.
29. *URLs/manifests?* Authed, pinned, signed/expiring (Ch 19/23).

30. *Entitlement?* Server-side per account (Ch 42/23).
31. *Logging?* No URLs/keys/PII (Ch 28).

Perf/QoE

32. *Top battery lever?* Release the player when done.
33. *ABR on cellular?* Cap quality (track selection).
34. *QoE metrics?* Startup latency, rebuffer ratio, bitrate, dropped frames.
35. *Buffer policy?* Tune load control (start vs memory).

Testing/Production

36. *Test playback?* `TestExoPlayerBuilder` / `FakeMediaSource`; state in isolation.
37. *Test persistence?* Save/restore position.
38. *Drift in prod?* UI holding state, not observing session.
39. *Stops in background?* Not in a service.
40. *Rebuffering?* ABR/buffer/network.
41. *Key reliability signal?* QoE (startup latency + rebuffer ratio) + zero drift.

Design-change challenges

1. **Audio must keep playing in the background with controls.** `MediaSessionService` + session-driven notification/lock-screen/Bluetooth (Ch 46).
2. **Notification and UI show different play/pause states.** Single `MediaSession` as truth; UI observes it.
3. **Resume where the user left off, across devices.** Persist position to SSOT + sync (Ch 3/32).
4. **Playback dies on rotation.** Host the player in the service; UI re-attaches.
5. **Protected 4K must block screenshots.** DRM (Widevine) + `FLAG_SECURE` (Ch 59).

Mock walkthrough (abridged)

Clarify (audio/video, background, DRM, continue-watching, Auto?) → Media3 in a `MediaSessionService` (Ch 46) → `MediaSession` as single truth → UI via `MediaController` (UDF, Ch 6) → audio focus/becoming-noisy/interruptions → adaptive streaming + track selection → position persist (Ch 8) + continue-watching sync (Ch 32) → lifecycle (bg-audio/pause-video, release) → DRM/security (Ch 59/23) → QoE observability.

58.17 Practical Exercises

1. **Beginner.** Play an HLS stream with Media3 inside a `MediaSessionService`; drive it from a Compose UI via a `MediaController`. *Eval:* plays; UI reflects session; survives rotation.
2. **Intermediate.** Add background audio with notification/lock-screen/Bluetooth controls, audio focus, and becoming-noisy pause. *Eval:* consistent across surfaces; pauses on unplug/call.
3. **Advanced.** Persist playback position across process death and sync continue-watching across devices. *Eval:* resumes after kill; resumes on another device.
4. **Production debugging.** Fix notification/UI state drift (UI held its own state) and playback dying on background (player in the Activity). *Eval:* single session truth; survives background.

5. **System design challenge.** Add track selection (quality/subtitles), cap bitrate on cellular, and a QoE dashboard (startup latency, rebuffer ratio). *Eval:* selectable; capped; measurable.

(Solutions withheld unless requested.)

58.18 Chapter Summary & Reference Sheet

Key decisions: host the **Media3/ExoPlayer** engine in a `MediaSessionService` (Ch 46) so playback **outlives the UI and runs in the background**, and make the `MediaSession` **the single source of playback state** that your UI (via a `MediaController`, UDF, Ch 6) and the **entire system** (media notification, lock screen, Bluetooth, Android Auto, Wear, Assistant) observe and control — which eliminates state drift and gives system integration nearly for free; let **Media3 handle adaptive streaming (HLS/DASH), ABR, track selection, and DRM** (Ch 59); handle **audio focus**, **becoming-noisy** (pause on unplug), and **interruptions** (calls); **persist playback position to the SSOT** and **restore across process death** (Ch 3/8), and **sync continue-watching across devices** (Ch 32); manage **lifecycle per content type** (continue audio in the background, pause video for battery, **release the player when done**); and secure protected content with **Widevine + `FLAG_SECURE` + authed/signed URLs + server-side entitlement** (Ch 59/23/42).

Concepts: Media3/ExoPlayer, `MediaSessionService` (Ch 46), `MediaSession` as single truth, `MediaController` UI (UDF), audio focus/becoming-noisy/interruptions, adaptive streaming/ABR/track selection, position persist (Ch 8) + continue-watching sync (Ch 32), lifecycle/release, DRM/secure output.

Common mistakes: player in the Activity/Composable (dies on bg/rotation); UI-held playback state (drift with notification/Bluetooth); hand-rolling the player/ `MediaPlayer` (no ABR/DRM); no audio focus/becoming-noisy handling; position not persisted (lost on death) or not synced (no cross-device resume); never releasing the player (battery); leaving video rendering in the background; no DRM/secure output for protected content.

Checklist:

- [ ] Media3 player in `MediaSessionService` (Ch 46)
- [ ] `MediaSession` = single truth
- [ ] UI via `MediaController` (no local state, UDF)
- [ ] audio focus + becoming-noisy + interruptions
- [ ] adaptive streaming + track selection
- [ ] persist position (SSOT/process death, Ch 3/8)
- [ ] continue-watching sync (Ch 32)
- [ ] bg-continue audio / pause video / release when done
- [ ] DRM + `FLAG_SECURE` + authed/signed URLs + entitlement (Ch 59/23/42)
- [ ] QoE telemetry (startup latency, rebuffer ratio).

Key APIs: `ExoPlayer.Builder` (`setAudioAttributes(handleAudioFocus)` / `setHandleAudioBecomingNoisy`), `MediaSessionService` / `MediaSession.Builder` / `onGetSession`, `MediaController.Builder` / `SessionToken`, `Player.Listener` / `onEvents`, `MediaItem` (HLS/DASH mime), `TrackSelectionParameters` (quality/subtitle), `DefaultTrackSelector`, `DrmSessionManager` (Ch 59), `FLAG_SECURE`, `TestExoPlayerBuilder` (test), Room SSOT (Ch 3), sync (Ch 32).

References:

- Media3 / ExoPlayer: https://developer.android.com/media/media3/exoplayer
- MediaSession: https://developer.android.com/media/media3/session/control-playback
- Background playback (MediaSessionService): https://developer.android.com/media/media3/session/background-playback
- Audio focus: https://developer.android.com/media/optimize/audio-focus
- Track selection: https://developer.android.com/media/media3/exoplayer/track-selection
- (composes) Ch 46 Foreground Services, Ch 59 Offline/DRM, Ch 44 Lifecycle, Ch 8 Process Death, Ch 32 Sync, Ch 6 UI State

Chapter review (Phase 4)

- **Completeness:** all 18 sections; architecture/class/2 sequence+flow/failure diagrams; MediaSessionService + MediaController VM + position tracker + track selection code; concurrency (session serialization, controller-vs-session lifecycle, position races); failure (single-session principle); 5 levels; Media3-vs-MediaPlayer, session-as-truth, service-hosting trade-offs; security/DRM (Widevine, FLAG_SECURE, signed URLs, entitlement); perf/QoE (release, ABR, rebuffer); Media3 test utils; observability (QoE); 41 Q&A + 5 challenges. ✅
- **Expand later:** offline/DRM (Ch 59), foreground services (Ch 46), process death (Ch 8), sync (Ch 32).
- **Interview coverage:** exceeds ≥40 Complex bar.