Chapter 72 — Optimistic Updates (Likes / Comments)

> **Part IX — Feature Architectures** · Complexity: **Complex** (≥40 interview questions)
>
> **Prerequisites:** Ch 3 (SSOT/Room), Ch 31 (outbox), Ch 15 (idempotency), Ch 2 (retries), Ch 6 (UI state/UDF), Ch 32 (sync), Ch 29 (offline-first). Pairs with Ch 71 (feed), Ch 64 (chat), Ch 33 (conflict resolution).
>
> **Reference surface in StreamCart:** instant-feeling interactions — like/unlike, favorite, follow, add-to-cart, post a comment, rate — that update the UI immediately, persist and retry reliably, reconcile with the server, and roll back cleanly on failure, all while staying consistent across every screen the item appears on.

72.1 Problem Definition and Real-World Context

An **optimistic update** applies a user action to the UI **immediately**, assuming it will succeed, then confirms (or rolls back) once the server responds. It's what makes likes, follows, and comments feel **instant** instead of showing a spinner on every tap. But doing it correctly is deceptively hard: the update must **persist** (survive process death and work offline), **retry** reliably, be **idempotent** (double-taps, retries), **reconcile** with the server's authoritative value, **roll back** cleanly on genuine failure, stay **consistent** across every screen the item appears on, and handle **concurrent** actions (rapid like/unlike) and **conflicts** (server state diverged). Naive optimistic UI ("flip a boolean in memory, fire a POST") loses updates on death, double-counts on double-tap, shows the wrong state after failure, and diverges across screens.

Concretely, teams hit:

- **In-memory only → lost on death/offline.** Flipping a UI flag without persisting means a like is lost on process death or if offline. The optimistic change must go into the **SSOT** (Room, Ch 3) and an **outbox** (Ch 31), not just memory.
- **Double-count / non-idempotent.** Rapid double-taps or retries fire multiple requests; without **idempotency** (Ch 15) the like counts twice or the comment posts twice.
- **No reconciliation.** The optimistic value is a **guess**; the server's response is **authoritative** (the real like count may differ due to others' actions). You must **reconcile** to the server value, not keep the guess.
- **Bad rollback.** On genuine failure, the UI must revert to the **pre-action** state (and ideally tell the user) — but only for real failures, not transient retries.
- **Inconsistency across screens.** The same item appears in the feed (Ch 71), detail, profile; an optimistic like must update **all** of them — only possible if it's one **SSOT row** (Ch 3), not per-screen state.
- **Concurrency / conflicts.** Rapid like→unlike→like, or the server state changing underneath, needs ordering, idempotency (Ch 15), and conflict handling (Ch 33).
- **Which actions to optimize.** Likes/follows (cheap, reversible) are great candidates; **payments/irreversible** actions should **not** be optimistic (show real state).

The architecture: apply the action **optimistically to the SSOT** (Room, Ch 3) so the UI updates instantly **everywhere the item appears** (UDF, Ch 6); record the intent in an **outbox** (Ch 31) with an **idempotency key** (Ch 15) so it **persists, retries, and dedups**; **reconcile** with the server's authoritative response (don't keep the guess); **roll back** the SSOT to the pre-action value on genuine failure (with user feedback); handle **concurrency** (rapid toggles) and **conflicts** (Ch 33); and **don't** apply optimism to **irreversible/high-stakes** actions. This chapter is the **end-to-end pattern for reliable, consistent, reversible optimistic interactions**.

Three practical use cases

1. **Like/unlike (StreamCart feed, Ch 71).** Tap like → SSOT updates instantly (count+1, likedByMe=true) across feed/detail; outbox syncs with idempotency; reconcile to server count; roll back on failure.
2. **Post a comment.** Comment appears immediately (status "sending") in the SSOT; outbox posts it idempotently; on success it's confirmed (server id/timestamp), on failure marked "failed" with retry.
3. **Follow / add-to-cart.** Instant toggle; offline-capable; reconciled; rolled back if the server rejects (e.g., blocked, out of stock).

Why this is architectural

Optimistic updates **compose** SSOT (Ch 3), outbox (Ch 31), idempotency (Ch 15), retries (Ch 2), sync/reconciliation (Ch 32), conflict resolution (Ch 33), and UDF (Ch 6) into a reusable interaction pattern used across the whole app (feed Ch 71, chat Ch 64, cart Ch 38). The decisions — SSOT-not-memory, outbox+idempotency, reconcile-don't-keep-guess, clean rollback, consistency-via-one-row, don't-optimize-irreversible — determine whether interactions feel instant *and* stay correct.

72.2 Requirements Engineering

Functional requirements

ID	Requirement
F1	Apply the action to the UI instantly (optimistic), via the SSOT (Ch 3/6).
F2	Persist the intent (outbox) so it survives process death and works offline (Ch 31/29).
F3	Send idempotently with retry; dedup double-taps/retries (Ch 15/2).
F4	Reconcile with the server's authoritative value (don't keep the guess).
F5	Roll back to pre-action state on genuine failure, with user feedback.
F6	Stay consistent across all screens (one SSOT row); handle concurrency/conflicts (Ch 3/33).

Non-functional requirements

Attribute	Policy
Instant UX	UI updates immediately; no spinner for reversible actions.
Reliability	Persists (death/offline); retries; never lost (Ch 31/29).
Correctness	Idempotent; reconciled to server truth; clean rollback (Ch 15).
Consistency	One SSOT row → all screens consistent (Ch 3).
Safety	Not applied to irreversible/high-stakes actions.

Scope

- **In scope:** the optimistic pattern (SSOT apply → outbox → idempotent send → reconcile / rollback), consistency via one SSOT row (Ch 3/6), outbox + idempotency + retry (Ch 31/15/ 2), reconciliation to server truth, rollback UX, concurrency (rapid toggles), conflicts (Ch 33), offline (Ch 29), when-not-to-optimize (irreversible), count vs boolean vs create (like/comment) shapes.
- **Out of scope:** SSOT internals (Ch 3), outbox/sync/idempotency mechanics (Ch 31/32/15), conflict resolution depth (Ch 33), feed (Ch 71), chat send (Ch 64), UDF (Ch 6).

Assumptions & constraints

- Room SSOT (Ch 3), outbox (Ch 31), WorkManager (Ch 30), UDF/StateFlow (Ch 6). `minSdk 24`. The **server is authoritative** for the real value (like counts, comment ids); actions have **idempotency keys**; optimistic UI is for **reversible** actions.

72.3 System Design Fundamentals

- **Optimistic = apply now, confirm/revert later.** On the user action, **immediately** apply the expected result to local state, show it, and send the request in the background; when the server responds, **confirm** (replace the guess with the real value) or **roll back** (revert) on failure. This removes the per-tap spinner and makes the app feel instant.
- **Apply to the SSOT, not memory (the consistency key, Ch 3/6).** The optimistic change must mutate the **SSOT (Room row)** — not a screen-local variable. Because the item is **one row** rendered by every screen (feed Ch 71, detail, profile) via UDF (Ch 6), a single SSOT mutation makes the like appear **everywhere at once** and stay consistent. In-memory optimism diverges across screens and is lost on death.
- **Persist the intent in an outbox (Ch 31).** Record the action (like X, comment Y) in an **outbox** so it **survives process death and offline** and is **retried** reliably (Ch 2). The outbox op carries an **idempotency key** (Ch 15). (Same reliable-send pattern as chat, Ch 64, and cart mutations, Ch 38.)
- **Idempotency (Ch 15) — mandatory.** Rapid double-taps, retries, and the outbox re-sending must **not** double-apply. Use an **idempotency key** (per action) so the server dedups: a like is "set liked=true" (idempotent) not "increment" (not idempotent); a comment carries a client-generated id so a retry doesn't post twice (Ch 15/64). Model actions idempotently.
- **Reconcile with the server's authoritative value (don't keep the guess).** The optimistic value is an **estimate** — the real like count depends on **everyone's** actions, so the server's response is **truth**. On confirmation,

replace the local guess with the server value (e.g., the real count), not just "mark confirmed." This corrects drift (your +1 guess vs the actual count). Background sync (Ch 32) also reconciles.

- **Rollback on genuine failure (not transient).** Distinguish:
  - **Transient failure** (network, 5xx): **keep** the optimistic state and **retry** (outbox/backoff, Ch 2/31) — don't roll back on a blip.
  - **Genuine failure** (4xx: forbidden, blocked, out-of-stock, validation): **roll back** the SSOT to the **pre-action** value and **tell the user** (toast/snackbar). Store the pre-action value so rollback is exact. Rolling back on every transient error causes flicker; never rolling back leaves wrong state — distinguish by response.
- **Consistency across screens = one SSOT row (Ch 3).** Don't special-case the feed's like vs the detail's like — they read the **same row**. Optimistic mutation + reconciliation happen on that row; every observer updates. This is why SSOT-backing (not per-screen state) is non-negotiable.
- **Concurrency & conflicts (Ch 33).** Rapid **like→unlike→like** must end in the correct final state: model as **idempotent set-state** (last intent wins) with the outbox coalescing/ordering (Ch 31), not racing increments. Server-state **conflicts** (someone else changed it; your offline action conflicts) reconcile via the server value / conflict policy (Ch 33) — typically the **server's count** wins for counts, **last-writer** for booleans, with the user's own action honored.
- **Action shapes:**
  - **Boolean toggle** (like/follow/favorite): optimistic `liked=true/false`; reconcile the **count** to server; idempotent set-state.
  - **Create** (comment/review): optimistic insert with status **Sending → Sent/Failed** and a client id (Ch 64); reconcile to the server-assigned id/timestamp.
  - **Counter**: never optimistic-increment blindly; set-state + reconcile to server count.
- **When NOT to be optimistic (safety). Irreversible or high-stakes** actions — **payments, placing an order, deleting data, money transfer** — should **not** be optimistic; show the **real** state (confirmed by the server) because a rollback after the user believed it succeeded is unacceptable. Optimism is for **cheap, reversible** actions (likes, follows, comments, cart toggles).

Core insight: **apply the user's reversible action optimistically to the SSOT (one Room row, Ch 3) so the UI updates instantly and consistently across every screen (UDF, Ch 6); persist the intent in an outbox with an idempotency key (Ch 31/15) so it survives process death and offline, retries reliably, and dedups double-taps/retries; reconcile with the server's authoritative value (replace the guess — the real count depends on everyone, Ch 32); distinguish transient failures (keep + retry) from genuine ones (roll back to the stored pre-action value + tell the user); model actions as idempotent set-state and resolve concurrency/conflicts via the server value (Ch 33); and never apply optimism to irreversible or high-stakes actions (payments/orders/deletes) — show real state there.**

72.4 High-Level Architecture


72.4 High-Level Architecture

Components & ownership

- **Optimistic apply** mutates the **SSOT row** (storing the pre-action value) → UI instant
  - consistent.

- **Outbox + idempotency** persist/retry/dedup the intent (Ch 31/15).
- **Reconcile** replaces the guess with server truth; **rollback** reverts on genuine failure; **conflict policy** (Ch 33) resolves divergence.
- **Irreversible actions bypass** optimism.

Direction: tap → optimistic SSOT apply (+pre-value) → instant UI + outbox(idempotent) → server → reconcile / keep-retry / rollback → SSOT truth; conflicts via policy; irreversible excluded.


72.5 Detailed Component Design

 72.5 Detailed Component Design

Component	Responsibility
`InteractionRepository`	optimistic apply → outbox → reconcile/rollback over SSOT
`ItemRow`	SSOT row with current + **pre-action** values (rollback)
`OptimisticAction`	typed actions (toggle / create)
`OutboxOp`	persisted intent + idempotency key (Ch 31/15)

72.6 End-to-End Data Flow

Like: optimistic → reconcile / rollback

 Like: optimistic → reconcile / rollback

Rapid toggle (idempotent set-state)

 Rapid toggle (idempotent set-state)

72.7 Complete Kotlin Implementation

Package: `com.streamcart.interactions`.

72.7.1 SSOT row with pre-action values (for rollback)

```
@Entity(tableName = "posts")
data class PostRow(
    @PrimaryKey val id: String, val likeCount: Int, val likedByMe: Boolean,
    // pre-action snapshot for exact rollback (or store in the outbox op):
    val pendingLike: Boolean = false,
)
```

72.7.2 Optimistic like: apply to SSOT → outbox (idempotent)

```
@Singleton
class InteractionRepository @Inject constructor(
    private val dao: PostDao, private val outbox: Outbox, private val api: InteractionApi,  // Ch 31
) {
    suspend fun like(postId: String, like: Boolean) {
        val current = dao.byId(postId) ?: return
        val preLiked = current.likedByMe; val preCount = current.likeCount
        // 1) Optimistic SSOT mutation -> UI instant EVERYWHERE (Ch 3/6). Idempotent SET-STATE (not increment).
        dao.setLike(postId, liked = like, count = preCount + if (like && !preLiked) 1 else if (!like && preLiked) -1 else 0)
        // 2) Persist intent with idempotency key; survives death/offline; retried (Ch 31/15/2).
        outbox.enqueue(OutboxOp.SetLike(postId, like, idempotencyKey = "$postId:like:$like", preLiked, preCount))
    }

    // OutboxProcessor calls this.
    suspend fun syncSetLike(op: OutboxOp.SetLike): OutboxResult = runCatching {
        val serverCount = api.setLike(op.postId, op.like, op.idempotencyKey)   // idempotent set-state (Ch 15)
        dao.reconcileCount(op.postId, serverCount)                              // 3) RECONCILE to server truth (Ch 32)
        OutboxResult.Done
    }.getOrElse { e ->
        when {
            e.isTransient() -> OutboxResult.Retry                               // 5xx/network: keep + retry (Ch 2)
            else -> { dao.setLike(op.postId, op.preLiked, op.preCount); OutboxResult.Failed(e) }  // 4) ROLLBACK (4xx) + user feedback
        }
    }
}
```

72.7.3 Optimistic create (comment): Sending → Sent/Failed (Ch 64 pattern)

```
suspend fun InteractionRepository.comment(postId: String, text: String) {
    val clientId = UUID.randomUUID().toString()                    // idempotency + optimistic
match (Ch 15/64)
    dao.insertComment(Comment(clientId, postId, text, status = Status.Sending, serverId = null))
// optimistic insert
    outbox.enqueue(OutboxOp.PostComment(clientId, postId, text))
}
suspend fun InteractionRepository.syncComment(op: OutboxOp.PostComment): OutboxResult =
runCatching {
    val posted = api.postComment(op.postId, op.text, idempotencyKey = op.clientId)   //
idempotent (Ch 15)
    dao.confirmComment(op.clientId, serverId = posted.id, status = Status.Sent)       //
reconcile to server id
    OutboxResult.Done
}.getOrElse { e ->
    if (e.isTransient()) OutboxResult.Retry
    else { dao.markComment(op.clientId, Status.Failed); OutboxResult.Failed(e) }      // show
"failed" + manual retry
}
```

72.7.4 UI: render SSOT (instant + consistent), failure feedback (Ch 6)

```
@Composable
fun LikeButton(post: PostRow, vm: PostViewModel = hiltViewModel()) {
    // Reads the SSOT row -> same state in feed/detail/profile (Ch 3). Tap updates instantly.
    IconToggleButton(checked = post.likedByMe, onCheckedChange = { vm.like(post.id, it) }) {
        Icon(if (post.likedByMe) Icons.Filled.Favorite else Icons.Outlined.FavoriteBorder, null)
    }
    Text("${post.likeCount}")   // reconciled to server truth after sync (Ch 32)
    // Genuine-failure rollback surfaces a snackbar ("Couldn't like — try again") via a one-time
event (Ch 7).
}
```

72.7.5 When NOT to be optimistic (irreversible)

```
// Payments/orders/deletes: show REAL state (server-confirmed), not optimistic.
suspend fun placeOrder(cart: Cart): Outcome<Order> {
    // NO optimistic "order placed". Show "Placing…" -> await server -> show confirmed/failed.
    return api.placeOrder(cart)   // real state only; a rollback after "order placed" is
unacceptable
}
```

72.7.6 Module structure

```
:core:interactions  InteractionRepository, OptimisticAction, OutboxOp (idempotency),
reconcile/rollback
:core:data          SSOT rows (Ch 3); :core:outbox Outbox + processor (Ch 31)
# Idempotency -> Ch 15; retries -> Ch 2; reconcile/sync -> Ch 32; conflicts -> Ch 33. Used by
feed (Ch 71), chat (Ch 64), cart (Ch 38).
```

72.8 Concurrency and Race Conditions

Scenario	Risk	Handling
Double-tap / retry	double-count/post	idempotency key + set-state (not increment) (Ch 15)
Rapid like→unlike→like	wrong final state	idempotent set-state (latest intent); outbox coalesces (Ch 31)
Server count diverges	stale guess	reconcile to server value (Ch 32)
Process death mid-action	lost action	outbox persisted (Ch 31)
Transient failure	false rollback/flicker	keep + retry; roll back only on genuine 4xx (Ch 2)
Same item on many screens	divergent state	one SSOT row (Ch 3)
Offline action then conflict	divergence	queue; reconcile/conflict policy on sync (Ch 29/33)

- **Idempotent set-state beats increments:** modeling a like as "set liked=true" (not "increment count") makes double-taps, retries, and re-sends **idempotent** (Ch 15); the **count** is then reconciled to the **server's** authoritative value (which reflects everyone). Increment-based optimism double-counts and can't reconcile cleanly.
- **Latest-intent wins for rapid toggles:** like→unlike→like should send the **final** set-state; the outbox **coalesces** rapid toggles to the latest (Ch 31) rather than racing N requests, and idempotency makes any that do go out safe.
- **One SSOT row = inherent cross-screen consistency:** because feed/detail/profile read the same row (Ch 3), there's no multi-screen sync problem — the optimistic mutation and reconciliation happen once.

72.9 Failure Scenarios and Recovery

Failure	Detection	Response	Outcome
Lost on process death	action gone	outbox persisted (Ch 31)	survives
Double-count on double-tap	wrong count	idempotent set-state (Ch 15)	single
Stale count vs server	drift	reconcile to server value (Ch 32)	correct
Genuine failure (blocked/4xx)	response	roll back to pre-action + tell user	reverted
Transient failure	5xx/network	keep optimistic + retry (Ch 2/31)	eventually sent
Divergent across screens	inconsistency	one SSOT row (Ch 3)	consistent
Offline conflict	server diverged	conflict policy / server value (Ch 33)	resolved
Optimistic on a payment	wrong "success"	don't optimize irreversible; show real state	safe


72.9 Failure Scenarios and Recovery

> **Optimistic updates are "guess, persist, reconcile, revert" — not "flip a boolean."** Apply to the SSOT (one row → consistent + death-safe), persist in an outbox with an idempotency key (reliable + dedup), reconcile to the server's authoritative value (not your guess), and roll back only on genuine failure. Model actions as idempotent set-state, and never optimize irreversible actions.

72.10 Scaling the Implementation

- **Level 1.** Optimistic SSOT mutation + instant UI (one row); basic send.
- **Level 2.** Outbox + idempotency key + retry (Ch 31/15/2); reconcile to server value; rollback on genuine failure.
- **Level 3 — production.** Transient-vs-genuine failure distinction + user feedback; comment create (Sending/Sent/Failed); rapid-toggle coalescing; offline (Ch 29).
- **Level 4 — large.** Conflict resolution (Ch 33); cross-device consistency (Ch 32); per-action-type policies; analytics (optimistic success/rollback rate); reusable optimistic framework across features (feed Ch 71, chat Ch 64, cart Ch 38).
- **Level 5 — enterprise.** Interaction QoE SLOs, A/B of optimistic behavior, abuse/rate- limit handling, consistency guarantees, irreversible-action governance.

Avoid overengineering: SSOT apply + outbox + idempotency + reconcile + rollback is the reusable core. Don't build optimism for irreversible actions; don't hand-roll per-feature — reuse one pattern.

72.11 Alternative Approaches and Trade-offs

Dimension	Option A	Option B	When
State location	SSOT row (Ch 3)	screen-local memory	SSOT (consistent, death-safe); memory diverges/loses
Persistence	Outbox (Ch 31)	fire-and-forget POST	Outbox (survives death/offline, retries)
Action model	Idempotent set-state (Ch 15)	increment / non-idempotent	Set-state (double-tap/retry safe)
Server value	Reconcile (replace guess)	keep optimistic value	Reconcile (count reflects everyone, Ch 32)
Failure	Roll back on genuine, keep on transient	roll back on any error	Distinguish (avoid flicker vs wrong state)
Candidates	Reversible (like/follow/comment)	everything incl. payments	Reversible only; never irreversible
Create	Status Sending/Sent/Failed + client id (Ch 64)	optimistic with no status	Status + client id (reconcile, retry)

SSOT vs in-memory optimistic state: flipping a screen-local boolean is the common naive approach — it diverges across screens (feed vs detail show different like states), is lost on process death, and can't reconcile. Applying to the **SSOT row** (Ch 3) makes the change **consistent everywhere** (one row, UDF Ch 6), **death-safe**, and reconcilable. Always optimize the SSOT, never memory.

Reconcile vs keep-the-guess: the optimistic "+1" is a **guess** — the real like count changes as **others** act, so keeping your guess drifts from reality. **Reconciling** to the server's authoritative value on confirmation (and via background sync, Ch 32) keeps counts correct. Model booleans as your-own-state (honored) but counts as **server truth**.

Idempotent set-state vs increment: "increment the like count" is **not idempotent** — double-taps and retries double-count. "**Set** liked=true/false" is **idempotent** (Ch 15): applying it twice is the same as once, and the server dedups via the idempotency key. Model toggles as set-state and reconcile the derived count.

Optimistic vs real-state for irreversible actions: optimism is great for **cheap, reversible** actions, but for **payments, orders, deletes, transfers** a rollback after the user believed it succeeded is **unacceptable** (they think they paid/ordered). Show the **real, server-confirmed** state for irreversible/high-stakes actions; reserve optimism for likes/follows/comments/cart-toggles.

72.12 Security Considerations

- **Server authorizes the action (Ch 23/19):** optimistic UI is **client convenience**; the **server** validates and authorizes (can this user like/comment/follow? blocked? rate- limited?). A genuine 4xx (forbidden) triggers rollback — never treat the optimistic state as authorization.
- **Idempotency key integrity (Ch 15):** the key dedups retries; the server enforces idempotency so a replayed request can't double-apply (also prevents some abuse).
- **Untrusted content (Ch 52):** optimistically-inserted comments are user content — sanitize on render; the server validates/moderates (don't trust client text).

- **Rate limiting / abuse:** rapid toggles and spam are **server-rate-limited**; the client's optimism must handle server rejections (rollback) gracefully — don't let optimism mask abuse controls.
- **Per-account isolation (Ch 42):** interaction state (likedByMe) is per-account; clear/ scope on logout.
- **Don't optimize security-relevant or irreversible actions:** permission changes, payments, deletes show real state (above).
- Client vs backend: the **server** is authoritative (validates, authorizes, dedups, ranks counts), the **client** applies optimistically and reconciles/rolls back to the server's verdict — optimism never overrides server authority.

72.13 Performance and Resource Optimization

- **Instant UI** is the whole point — no network round-trip blocking the tap (SSOT mutation is local/fast).
- **Coalesce rapid toggles** (Ch 31) — send the final set-state, not N requests (battery/ server load).
- **Batch reconciliations** where possible (e.g., sync counts for visible items, Ch 32).
- **Idempotent set-state** avoids wasted re-work from retries/duplicates.
- **Outbox efficiency** — debounce/dedupe ops (Ch 31); don't spam.
- **Reconcile visible items** (don't fetch counts for off-screen).
- **Profiling:** optimistic→confirmed latency, rollback rate, double-send rate (→ 0), outbox depth, reconcile frequency.

72.14 Testing Strategy

Highly unit-testable (SSOT apply, idempotency, reconcile, rollback) with fakes.

```
class OptimisticLikeTest {
    @Test fun `applies optimistically and enqueues idempotent outbox op`() = runTest {
        repo.like("p1", true)
        assertTrue(dao.byId("p1").likedByMe)                        // instant (Ch 3)
        assertEquals("p1:like:true", outbox.last().idempotencyKey)   // idempotent (Ch 15)
    }
    @Test fun `reconciles count to server value`() = runTest {
        api.nextCount = 57; repo.syncSetLike(opLike("p1"))
        assertEquals(57, dao.byId("p1").likeCount)                   // replace guess (Ch 32)
    }
    @Test fun `rolls back on genuine 4xx, keeps on transient`() = runTest {
        api.failWith(403); repo.syncSetLike(opLike("p1", preCount = 41))
        assertEquals(41, dao.byId("p1").likeCount)                   // rolled back
        api.failWith(503); val r = repo.syncSetLike(opLike("p2"))
        assertTrue(r is OutboxResult.Retry)                          // kept + retry (Ch 2)
    }
    @Test fun `double-tap does not double-count`() = runTest {
        repo.like("p1", true); repo.like("p1", true)                 // idempotent set-state
        assertEquals(1, dao.byId("p1").likeCount - baseCount)
    }
}

class OptimisticCommentTest {
    @Test fun `comment shows Sending then Sent with server id`() = runTest { /* reconcile to
server id (Ch 64) */ }
    @Test fun `comment marks Failed on genuine error`() = runTest { /* ... */ }
}
```

What to test: optimistic SSOT apply (instant) + idempotent outbox op; reconcile to server value; rollback on genuine 4xx vs keep+retry on transient; double-tap/rapid-toggle idempotency; comment Sending→Sent/Failed; cross-screen consistency (same row); process-death resume (outbox). Fake API/outbox; Room in-memory.

72.15 Production Observability

- **Metrics:** optimistic→confirmed **latency**; **rollback rate** (by reason: 4xx/validation); double-send/double-count rate (→ 0); reconcile corrections (guess vs server delta); outbox depth + retry rate; offline-queued actions; per-action-type success.
- **Logs:** `interaction{type, action, result(confirmed/rolledback/retry)}` — no content/PII (Ch 28).
- **Debugging:** lost actions → not using outbox (Ch 31); double-count → non-idempotent (increment vs set-state, Ch 15); wrong count → not reconciling (Ch 32); flicker → rolling back on transient; inconsistent screens → not SSOT-backed (Ch 3); "success" then gone → optimistic on an irreversible action.
- **Alerting:** rollback-rate spike (server rejecting — bug/abuse); double-count detection; reconcile-correction spike (guess drift).
- **Dashboards:** rollback rate by reason; optimistic latency; outbox depth.

72.16 System Design Interview Preparation

> ≥40 questions.

Fundamentals

1. *Optimistic update?* Apply the action to the UI immediately, confirm/revert on server response.
2. *Why?* Instant feel; no per-tap spinner.
3. *Apply where?* The SSOT row (Ch 3), not memory.
4. *Why SSOT not memory?* Consistent across screens + death-safe + reconcilable.
5. *Persist how?* Outbox (Ch 31) with an idempotency key (Ch 15).

Idempotency/model

6. *Why idempotency?* Double-tap/retry must not double-apply (Ch 15).
7. *Set-state vs increment?* Set-state is idempotent; increment double-counts.
8. *Comment idempotency?* Client-generated id (Ch 64).
9. *Rapid like→unlike→like?* Latest set-state wins; outbox coalesces (Ch 31).

Reconciliation

10. *Is the optimistic value truth?* No — a guess; server is authoritative.
11. *Reconcile?* Replace guess with server value (real count, Ch 32).
12. *Why counts differ?* Others act too; server reflects everyone.
13. *Boolean vs count?* Your boolean honored; count reconciled to server.

Rollback

14. *When roll back?* Genuine failure (4xx: forbidden/blocked/validation).
15. *When keep?* Transient (5xx/network) → retry (Ch 2).
16. *Why distinguish?* Rolling back on transient causes flicker; never rolling back leaves wrong state.
17. *Rollback to what?* The stored pre-action value.
18. *User feedback?* Snackbar/toast on rollback.

Consistency/concurrency

19. *Same item many screens?* One SSOT row → all consistent (Ch 3).
20. *Process death?* Outbox persisted (Ch 31).
21. *Offline?* Queue; reconcile/conflict on sync (Ch 29/33).
22. *Conflicts?* Server value / conflict policy (Ch 33).

Create (comment)

23. *Comment states?* Sending → Sent/Failed; client id; reconcile to server id.
24. *Failed comment?* Mark failed + manual retry.

Safety

25. *Don't optimize what?* Irreversible/high-stakes (payments/orders/deletes).
26. *Why?* Rollback after perceived success is unacceptable.
27. *Server role?* Authorize/validate/dedup (Ch 23); optimism is client convenience.

Testing/Production

28. *Test optimistic?* Instant SSOT apply + idempotent op.
29. *Test reconcile?* Count → server value.
30. *Test rollback?* Genuine 4xx reverts; transient retries.
31. *Test double-tap?* No double-count.
32. *Lost in prod?* Not using outbox.
33. *Double-count?* Non-idempotent.
34. *Wrong count?* Not reconciling.
35. *Flicker?* Rollback on transient.
36. *Inconsistent screens?* Not SSOT-backed.
37. *Key metrics?* Rollback rate, optimistic latency, double-count.

Composition

38. *Used by?* Feed (Ch 71), chat send (Ch 64), cart (Ch 38).
39. *Reuse?* One pattern (SSOT+outbox+idempotency+reconcile+rollback).
40. *Cross-device?* Reconcile via sync (Ch 32).
41. *Abuse?* Server rate-limits; client handles rejection (rollback).

Design-change challenges

1. **Make likes feel instant but correct.** Optimistic SSOT set-state + outbox idempotency + reconcile count + rollback (Ch 3/31/15/32).
2. **Double-tap double-counts.** Idempotent set-state + idempotency key (Ch 15).
3. **Like count wrong vs server.** Reconcile to server value (Ch 32).
4. **UI flickers on flaky network.** Keep on transient, roll back only on genuine 4xx (Ch 2).
5. **Optimistic "order placed" then it failed.** Don't optimize irreversible; show real state.

Mock walkthrough (abridged)

Clarify (which actions, reversible?, offline?, multi-screen?) → optimistic SSOT apply (one row, store pre-value, Ch 3) → outbox + idempotency key (persist/retry/dedup, Ch 31/15) → idempotent set-state model → reconcile to server value (Ch 32) → rollback on genuine 4xx vs keep+retry on transient (Ch 2) → consistency via one row + conflicts (Ch 3/33) → exclude irreversible actions → security (server authorizes) → observability (rollback rate).

72.17 Practical Exercises

1. **Beginner.** Make like/unlike optimistic via an SSOT set-state mutation so it updates instantly in both the feed and detail (one row). *Eval:* instant; consistent.
2. **Intermediate.** Add an outbox op with an idempotency key, retry, and reconcile the count to the server value. *Eval:* survives death/offline; count correct; double-tap safe.

3. **Advanced.** Implement rollback on genuine 4xx (revert to pre-action + snackbar) vs keep+retry on transient; handle rapid like→unlike→like via coalescing. *Eval:* no flicker; correct final state.
4. **Production debugging.** Fix double-counting (increment → idempotent set-state) and a count that drifts from the server (add reconciliation). *Eval:* single count; reconciled.
5. **System design challenge.** Add optimistic comment create (Sending/Sent/Failed + client id) and ensure a payment is **not** optimistic (real state). *Eval:* comments reconcile; payment shows confirmed-only.

(Solutions withheld unless requested.)

72.18 Chapter Summary & Reference Sheet

Key decisions: apply the user's **reversible** action **optimistically to the SSOT** (one Room row, Ch 3) so the UI updates **instantly and consistently across every screen** (UDF, Ch 6) and survives process death; **persist the intent in an outbox with an idempotency key** (Ch 31/15) so it works **offline**, **retries** reliably (Ch 2), and **dedups** double-taps/retries — modeling actions as **idempotent set-state** (not increments); **reconcile with the server's authoritative value** (replace the guess — the real count reflects everyone, Ch 32); **distinguish transient failures** (keep the optimistic state + retry) from **genuine failures** (4xx → **roll back to the stored pre-action value** + tell the user), avoiding both flicker and wrong state; resolve **concurrency** (rapid toggles → latest set-state, coalesced) and **conflicts** via the server value / policy (Ch 33); and **never apply optimism to irreversible or high-stakes actions** (payments, orders, deletes) — show **real, server-confirmed** state there. The **server is authoritative** (validates/authorizes/dedups, Ch 23); optimism is client convenience.

Concepts: optimistic apply to SSOT (one row), outbox + idempotency (persist/retry/ dedup), idempotent set-state, reconcile-to-server-truth, transient-vs-genuine rollback, cross-screen consistency, concurrency/conflict (Ch 33), create (Sending/Sent/Failed), irreversible-exclusion.

Common mistakes: in-memory optimism (diverges across screens, lost on death); fire-and- forget (lost offline/on death); increment instead of set-state (double-count); keeping the guess (count drifts); rolling back on transient errors (flicker); never rolling back (wrong state); not reconciling; optimizing irreversible actions (unacceptable rollback); per-screen state instead of SSOT; ignoring server authorization.

Checklist:

- [ ] optimistic apply to the SSOT row (store pre-action value, Ch 3)
- [ ] instant + consistent across screens (one row, UDF Ch 6)
- [ ] outbox + idempotency key (Ch 31/15)
- [ ] idempotent set-state (not increment)
- [ ] reconcile count/id to server value (Ch 32)
- [ ] roll back on genuine 4xx (+ user feedback); keep+retry on transient (Ch 2)
- [ ] rapid-toggle coalescing (Ch 31)
- [ ] conflicts via server/policy (Ch 33)
- [ ] offline-capable (Ch 29)
- [ ] NOT optimistic for irreversible/high-stakes actions
- [ ] server authorizes (Ch 23)
- [ ] rollback-rate + double-count telemetry.

Key APIs: Room `@Dao` set-state mutation + reconcile (Ch 3), Outbox + `OutboxOp` + idempotency key (Ch 31/15), WorkManager retry (Ch 30/2), `UUID.randomUUID` (comment client id, Ch 64), UDF `StateFlow` (Ch 6), one-time events for failure feedback (Ch 7), sync reconcile (Ch 32), conflict policy (Ch 33).

References:

- Offline-first mutations: https://developer.android.com/topic/architecture/data-layer/offline-first#create-update-delete
- (composes) Ch 3 SSOT, Ch 31 Outbox, Ch 15 Idempotency, Ch 2 Retries, Ch 32 Delta Sync, Ch 33 Conflict Resolution, Ch 6 UI State, Ch 71 Feed, Ch 64 Chat, Ch 38 Cart

Chapter review (Phase 4)

- **Completeness:** all 18 sections; architecture/class/sequence/flow/failure diagrams; SSOT row (pre-action) + optimistic like + comment create + reconcile/rollback + irreversible exclusion code; concurrency (idempotent set-state, coalesce, one-row consistency); failure (guess-persist-reconcile-revert principle); 5 levels; SSOT-vs-memory, reconcile-vs-guess, set-state-vs-increment, optimistic-vs-real trade-offs; security (server authority, idempotency, untrusted content, irreversible exclusion); perf (instant/coalesce/batch); idempotency+reconcile+rollback tests; observability (rollback rate); 41 Q&A + 5 challenges. ✅
- **Expand later:** feed (Ch 71), chat (Ch 64), conflict resolution (Ch 33), outbox (Ch 31), sync (Ch 32).
- **Interview coverage:** exceeds ≥40 Complex bar.