Chapter 82 — Centralized Logging & Analytics

> **Part X — Performance, Observability & Quality** · Complexity: **Complex** (≥40 interview questions)
>
> **Prerequisites:** Ch 14 (batching/queueing), Ch 28 (PII redaction), Ch 31 (outbox), Ch 3 (SSOT/Room), Ch 47 (background limits), Ch 44 (lifecycle), Ch 87 (A/B). Pairs with Ch 83 (crash/ANR), Ch 89 (logging), Ch 73 (rec signals).
>
> **Reference surface in StreamCart:** one pipeline for **analytics events** (screen views, taps, purchases, rec signals Ch 73) and **operational logs/telemetry** — a single, reliable, offline-buffered, batched, consented, PII-safe client SDK feeding the backend, decoupled from any vendor.
>
> **Note:** this chapter opens **Part X — Performance, Observability & Quality (Ch 82–93)**.

82.1 Problem Definition and Real-World Context

Every product decision, ranking model (Ch 73), funnel (Ch 80), and operational dashboard depends on **analytics events and telemetry** flowing reliably from the app. But a naive analytics integration (call the vendor SDK directly everywhere, fire events synchronously, send PII, lose events offline) is a mess: it couples the whole codebase to a vendor, drops events, drains battery/data, and leaks personal data. A **centralized logging & analytics pipeline** is the client-side system that **captures events through one internal API**, **buffers them durably** (offline-safe), **batches** uploads efficiently (Ch 14/47), **redacts PII and enforces consent** (Ch 28), and is **decoupled from the vendor** behind an abstraction — so events are reliable, cheap, private, and portable.

Concretely, teams hit:

- **Vendor lock-in / scattered calls.** Calling `FirebaseAnalytics` / `Mixpanel` /… directly across the codebase couples everything to one vendor and makes schema/consent/redaction impossible to enforce centrally. Need **one internal analytics API** behind an **abstraction**.
- **Lost events (offline/death).** Firing events over the network synchronously loses them offline or on process death. Events must be **durably buffered** (a persistent queue/ outbox, Ch 31/3) and sent later.
- **Battery/data from chatty sends.** Sending each event immediately drains the radio (Ch 47). Events must be **batched** and flushed on **sensible triggers** (size/time/ background/network, Ch 14/47).
- **PII + consent violations (Ch 28).** Events can carry **PII** (emails, names, content) and must respect **consent** (GDPR/CCPA opt-out, regional). The pipeline must **redact PII** and **gate on consent** centrally (Ch 28) — not per call site.
- **No schema / bad data.** Free-form event names/params produce unusable data. A **typed event schema** (names, params, versioning) keeps analytics meaningful.
- **Ordering/dedup/identity.** Events need stable ordering, **dedup** (retries), and a consistent **user/session/device identity** (reset on logout, Ch 42) — without over- identifying (privacy).
- **Operational logs vs analytics.** The same pipeline (or a sibling) carries **operational telemetry** (performance, errors, breadcrumbs Ch 89) distinct from **product analytics**, both PII-safe.

The architecture: a **single internal analytics/telemetry API** (`track(event)`) behind a **vendor-agnostic abstraction**; a **typed event schema**; **durable buffering** (persistent queue, Ch 31/3) so events survive offline/death; **batched, trigger-based upload** respecting background limits (Ch 14/47); **central consent gating + PII redaction** (Ch 28); consistent **identity/session** management (reset on logout, Ch 42); **dedup/ordering**; and clean separation of **product analytics vs operational telemetry** (with crash Ch 83 and logging Ch 89 as siblings). This chapter is the **reliable, private, vendor-decoupled observability pipeline**.

Three practical use cases

1. **Product analytics (StreamCart).** Screen views, taps, add-to-cart, purchase, rec signals (Ch 73) captured via `track(...)`, buffered, batched, consented, PII-redacted, uploaded — feeding funnels (Ch 80) and models (Ch 73).
2. **Operational telemetry.** Performance timings, non-fatal errors, network metrics, and breadcrumbs (Ch 89) through the same reliable pipeline, PII-safe, for dashboards/alerting.
3. **Vendor swap / multi-sink.** Change analytics vendor (or fan out to several sinks) without touching call sites — the abstraction isolates the vendor.

Why this is architectural

Centralized analytics is a **cross-cutting pipeline** every feature feeds and that underpins product decisions, ranking (Ch 73), funnels (Ch 80), and ops — composing batching (Ch 14), durable buffering (Ch 31/3), PII redaction + consent (Ch 28), background limits (Ch 47), identity (Ch 42), and vendor abstraction. The decisions — one API, typed schema, durable + batched + consented + redacted + vendor-agnostic — determine data quality, reliability, privacy, cost, and portability.

82.2 Requirements Engineering

Functional requirements

ID	Requirement
F1	Capture analytics/telemetry via one internal, vendor-agnostic API with a typed schema.
F2	Durably buffer events (survive offline/process death); don't lose events (Ch 31/3).
F3	Batch uploads on sensible triggers (size/time/background/network), respecting limits (Ch 14/47).
F4	Centrally gate on consent and redact PII (GDPR/CCPA) (Ch 28).
F5	Manage identity/session consistently; reset on logout; dedup/order events (Ch 42/15).
F6	Separate product analytics from operational telemetry; decouple from vendor (swap/fan-out).

Non-functional requirements

Attribute	Policy
Reliability	No lost events (durable buffer + retry); at-least-once + dedup.
Battery/data	Batched, trigger-based, background-friendly (Ch 14/47).
Privacy	Central consent + PII redaction; regional compliance (Ch 28).
Data quality	Typed schema; versioned; consistent identity.
Portability	Vendor-agnostic abstraction; multi-sink.

Scope

- **In scope:** single internal `track` API + vendor abstraction, typed event schema + versioning, durable buffering (persistent queue/outbox, Ch 31/3), batching + flush triggers (Ch 14/47), central consent gating + PII redaction (Ch 28), identity/session (reset on logout, Ch 42), dedup/ordering (Ch 15), product-vs-operational separation, offline/death survival, sampling.
- **Out of scope:** batching mechanics (Ch 14), redaction framework (Ch 28), outbox (Ch 31), crash/ANR (Ch 83), logging/breadcrumbs (Ch 89), A/B platform (Ch 87), backend analytics stack.

Assumptions & constraints

- A vendor SDK (Firebase/Amplitude/self-hosted) sits **behind an abstraction**; durable buffering via Room/outbox (Ch 31/3); batching + background flush via WorkManager (Ch 14/ 30/47); central consent + PII redaction (Ch 28). `minSdk 24`. Delivery is **at-least-once** (dedup server-side); events are **PII-safe** and **consented**.

82.3 System Design Fundamentals

- **One internal API behind a vendor-agnostic abstraction (the decoupling core).** All event capture goes through a **single internal interface** — `analytics.track(event)` — **not** direct vendor SDK calls scattered across the app. Behind it, an **`AnalyticsSink`** abstraction wraps the vendor(s). This lets you **enforce schema, consent, and redaction centrally**, **swap vendors** or **fan out to multiple sinks** without touching call sites, and **test** the pipeline. Scattered vendor calls are the anti-pattern.
- **Typed event schema (data quality).** Events are **typed** (sealed hierarchy or a schema) with **defined names and params**, not free-form strings — so data is consistent, queryable, and refactor-safe. **Version** the schema (events evolve, Ch 16-style). A typed schema prevents the "1000 inconsistent event names" problem.
- **Durable buffering — don't lose events (Ch 31/3).** Events are **written to a persistent queue** (Room/outbox, Ch 31/3) **immediately** (fast, local), **not** sent synchronously. This makes capture **non-blocking**, **offline-safe**, and **process-death-safe** — events wait in the durable buffer and upload later. Losing events because they were fired over the network inline is the classic reliability bug.
- **Batched, trigger-based upload (Ch 14/47).** The buffer is **flushed in batches** on **sensible triggers**: **size** (N events), **time** (every few minutes), **app background** (flush on `ON_STOP`, Ch 44), and **network** (prefer unmetered/WorkManager, Ch 47). This respects **battery/data** (Ch 14) and **Doze/background limits** (Ch 47) — never a request per event. WorkManager (Ch 30) handles reliable background flush.

- **Central consent + PII redaction (Ch 28) — the privacy core.** Before any event leaves the device:
  - **Consent gating:** if the user hasn't consented (or opted out — GDPR/CCPA, regional), **don't collect/send** analytics (or collect only essential/anonymized per policy). The pipeline checks consent **centrally**.
  - **PII redaction:** events are **redacted** (Ch 28) — no raw emails/names/content/tokens; param allowlists; hashed/anonymized ids where needed. Enforced **in the pipeline**, not per call site (so no event can accidentally carry PII). This central enforcement is **only possible** because of the single API/abstraction.
- **Identity, session, dedup, ordering (Ch 42/15).** Events carry a **user id** (consented/ anonymized), a **session id**, a **device id**, and a **sequence/timestamp**. On **logout/ account switch** (Ch 42), **reset identity** (new anonymous id; don't leak across users). Delivery is **at-least-once**, so events have a **stable event id** for **server-side dedup** (Ch 15), and ordering uses sequence/timestamp. Avoid **over-identifying** (privacy).
- **Sampling (cost/volume).** High-volume events (e.g., scroll, impressions Ch 73) may be **sampled** (send a fraction) to control cost/volume while preserving statistical validity; critical events (purchase) are **never** sampled. Sampling is a pipeline policy.
- **Product analytics vs operational telemetry.** Keep **product analytics** (user behavior: funnels, ranking signals) and **operational telemetry** (performance, non-fatal errors, breadcrumbs Ch 89) conceptually separate (different schemas/sinks/retention), though they can share the pipeline. **Crash/ANR** (Ch 83) and **logging** (Ch 89) are siblings feeding observability. Both must be **PII-safe**.

Core insight: **route all analytics and telemetry through one internal, vendor-agnostic `track` API with a typed, versioned schema, so you can enforce schema, consent, and PII redaction centrally and swap or fan out vendors without touching call sites; capture events by writing them to a durable persistent buffer immediately (non-blocking, offline- and death-safe, Ch 31/3) rather than sending synchronously, then upload in batches on sensible triggers (size/time/background/network) that respect battery and background limits (Ch 14/ 47); gate on consent and redact PII in the pipeline (GDPR/CCPA, Ch 28) before anything leaves the device; manage consistent identity/session with logout reset (Ch 42) and at-least-once delivery with stable event ids for server-side dedup (Ch 15); sample high-volume events; and keep product analytics distinct from operational telemetry (with crash Ch 83 and logging Ch 89 as siblings) — all PII-safe.**

82.4 High-Level Architecture


82.4 High-Level Architecture

Components & ownership

- **One internal `track` API** (typed schema) → **central consent gate + PII redaction** (Ch 28) → **durable buffer** (Ch 31/3) → **batched trigger-based upload** (Ch 14/30/47) → **vendor-agnostic sink(s)**.
- **Identity/session** (reset on logout, dedup ids) and **sampling** are pipeline policies.
- **Product analytics + operational telemetry** both flow through it, PII-safe.

Direction: `track` → consent → redact → durable buffer → batched upload → vendor sink; identity/sampling/dedup as policies; vendor-decoupled.

82.5 Detailed Component Design



Component	Responsibility
`Analytics`	the one internal API: track, consent, identity reset
`AnalyticsEvent`	typed, versioned event + stable event id (dedup, Ch 15)
`EventPipeline`	consent + redact (Ch 28) → durable buffer (Ch 31/3) → batched flush (Ch 14/47)
`AnalyticsSink`	vendor-agnostic sink abstraction (swap/fan-out)

82.6 End-to-End Data Flow

Capture → buffer → batched upload (consented, redacted)



Consent + logout reset



82.7 Complete Kotlin Implementation

Package: `com.streamcart.analytics`.

82.7.1 One internal API + typed event schema

```
sealed interface AnalyticsEvent {               // TYPED, versioned schema - not free-form
strings
    val name: String; val params: Map<String, Any?>
    data class ScreenView(val screen: String) : AnalyticsEvent {
        override val name = "screen_view"; override val params = mapOf("screen" to screen)
    }
    data class AddToCart(val productId: String, val price: Long) : AnalyticsEvent {
        override val name = "add_to_cart"; override val params = mapOf("product_id" to
productId, "price" to price)
    }
    data class Purchase(val orderId: String, val total: Long) : AnalyticsEvent { /* never
sampled */ ... }
    // Operational: data class PerfTiming(...), data class NonFatal(...) (Ch 89)
}

interface Analytics {                           // THE ONE API - all call sites use this (no
vendor SDK directly)
    fun track(event: AnalyticsEvent)
    fun setConsent(granted: Boolean)
    fun resetIdentity()                         // logout (Ch 42)
}
```

82.7.2 Pipeline: consent + redact → durable buffer (Ch 28/31/3)

```
@Singleton
class EventPipeline @Inject constructor(
    private val consent: ConsentManager,         // Ch 28
    private val redactor: PiiRedactor,           // Ch 28
    private val dao: EventDao,                    // durable buffer (Room, Ch 3/31)
    private val identity: IdentityProvider,      // user/session/device (Ch 42)
    private val sampler: Sampler,
    private val scope: CoroutineScope,
) : Analytics {
    override fun track(event: AnalyticsEvent) {
        if (!consent.analyticsGranted()) return                      // CENTRAL consent gate
(Ch 28)
        if (!sampler.keep(event)) return                             // sample high-volume
(never critical)
        val redacted = redactor.redactParams(event.params)           // CENTRAL PII redaction
(Ch 28) - allowlist
        val record = EventRecord(
            eventId = UUID.randomUUID().toString(),                  // stable id -> server
dedup (Ch 15)
            name = event.name, params = redacted,
            userId = identity.userId, sessionId = identity.sessionId, deviceId =
identity.deviceId,
            timestamp = System.currentTimeMillis(), schemaVersion = SCHEMA_VERSION,
        )
        scope.launch { dao.insert(record) }                          // DURABLE buffer,
immediate, non-blocking (Ch 31/3)
    }
    override fun setConsent(granted: Boolean) = consent.set(granted)  // if revoked -> stop +
optionally purge buffer
    override fun resetIdentity() { identity.reset(); /* flush then clear user scope on logout
(Ch 42) */ }
}
```

82.7.3 Batched, trigger-based upload (Ch 14/30/47)

```
@Singleton
class EventUploader @Inject constructor(private val dao: EventDao, private val sink:
AnalyticsSink, private val wm: WorkManager) {
    /** Flush on triggers: size, time, app background (Ch 44), network. WorkManager for reliable
background (Ch 30/47). */
    fun scheduleBatchFlush() = wm.enqueueUniquePeriodicWork("analytics-flush", KEEP,
        PeriodicWorkRequestBuilder<FlushWorker>(15, TimeUnit.MINUTES)

.setConstraints(Constraints.Builder().setRequiredNetworkType(NetworkType.CONNECTED).build()).bui
ld())  // Ch 47

    suspend fun flush(): Result {
        val batch = dao.nextBatch(limit = 200)                        // batch (Ch 14)
        if (batch.isEmpty()) return Result.success()
        return runCatching { sink.send(batch) }                       // vendor-agnostic sink
            .fold({ dao.deleteAll(batch.map { it.eventId }); Result.success() },  // remove on
ack
                  { Result.retry() })                                 // keep + retry (at-least-
once, Ch 2/31)
    }
    // Flush on ON_STOP (background) too: appScope flush (Ch 44) so events aren't stranded.
}
```

82.7.4 Vendor-agnostic sink (swap / fan-out)

```
interface AnalyticsSink { suspend fun send(batch: List<EventRecord>) }   // the abstraction

class FirebaseSink @Inject constructor(...) : AnalyticsSink { override suspend fun send(batch:
List<EventRecord>) { /* vendor */ } }
class SelfHostedSink @Inject constructor(private val api: TelemetryApi) : AnalyticsSink {
override suspend fun send(batch) = api.ingest(batch) }
class FanOutSink(private val sinks: List<AnalyticsSink>) : AnalyticsSink {   // send to several
(multi-sink)
    override suspend fun send(batch: List<EventRecord>) = sinks.forEach { it.send(batch) }
}
// Swapping the vendor = swapping the bound AnalyticsSink in DI (Ch 5). Call sites never change.
```

82.7.5 Identity + logout reset (Ch 42) + consent revoke

```
@Singleton
class IdentityProvider @Inject constructor(private val prefs: DataStore<Preferences>) {
    var userId: String? = null; var deviceId: String = deviceId(); var sessionId: String =
newSession()
    fun reset() {                                  // logout/account switch (Ch 42)
        userId = null; sessionId = newSession()   // new anonymous session; don't leak across
users
    }
}
// Consent revoke: pipeline stops collecting; optionally PURGE the durable buffer (Ch 28) per
policy.
```

82.7.6 Module structure

```
:core:analytics  Analytics (API), AnalyticsEvent (typed schema), EventPipeline
(consent+redact+buffer),
                 EventUploader (batch+WorkManager), AnalyticsSink (+ vendor/self-hosted/fan-
out), IdentityProvider, Sampler
:core:privacy  ConsentManager + PiiRedactor (Ch 28); :core:data EventDao (durable buffer, Ch
3/31)
# Crash/ANR -> Ch 83; logging/breadcrumbs -> Ch 89 (siblings). Batching -> Ch 14; background ->
Ch 30/47.
```

82.8 Concurrency and Race Conditions

Scenario	Risk	Handling
Event fired over network inline	lost offline/on death; jank	enqueue to durable buffer immediately (Ch 31/3)
Flush retried after partial send	duplicate events	at-least-once + stable event id → server dedup (Ch 15)
Consent revoked mid-session	collecting without consent	central consent gate; stop + optional purge (Ch 28)
Logout leaks events across users	wrong attribution/privacy	reset identity (new anon id) on logout (Ch 42)
High-volume floods buffer	storage/cost	sample high-volume (never critical); bounded buffer
Chatty uploads	battery/data	batch + trigger-based + unmetered (Ch 14/47)
Vendor change	code churn	vendor-agnostic sink abstraction (swap/fan-out)

- **Durable buffer + at-least-once + dedup** is the reliability model: capture **writes to a persistent queue immediately** (non-blocking, offline/death-safe, Ch 31/3); upload is **at-least-once** (retry on failure) so a partial send may **duplicate**, resolved by a **stable event id** the server **dedups** (Ch 15). Never send inline.

- **Central consent + redaction** (Ch 28) are enforced **in the pipeline** (possible only because of the single API) — no call site can bypass them; consent revoke stops collection (and may purge the buffer).
- **Logout identity reset** (Ch 42) prevents events being attributed across users (privacy + correctness).

82.9 Failure Scenarios and Recovery

Failure	Detection	Response	Outcome
Lost events (offline/death)	gaps	durable buffer + retry (Ch 31/3)	retained
Duplicate events	inflated metrics	stable event id + server dedup (Ch 15)	correct
PII in events	privacy audit	central redaction (Ch 28)	safe
Collecting without consent	legal	central consent gate (Ch 28)	compliant
Battery/data complaints	vitals	batch + trigger-based + unmetered (Ch 14/47)	efficient
Vendor lock-in	migration pain	vendor-agnostic sink (swap/fan-out)	portable
Inconsistent event data	unusable	typed, versioned schema	queryable
Cross-user attribution	privacy/accuracy	identity reset on logout (Ch 42)	isolated


82.9 Failure Scenarios and Recovery

> **A good analytics pipeline is one API, durably buffered, batched, consented, redacted, and vendor-decoupled.** The single `track` API makes central consent + PII redaction + schema enforceable; the durable buffer + at-least-once + dedup make it reliable; batching + triggers make it cheap; and the sink abstraction makes it portable. Direct scattered vendor calls fail all of these at once.

82.10 Scaling the Implementation

- **Level 1.** One `track` API + typed schema + vendor sink; events sent via the vendor SDK.
- **Level 2.** Durable buffer (Ch 31/3) + batched trigger-based upload (Ch 14/47) — offline/ death-safe, efficient.
- **Level 3 — production.** Central consent gate + PII redaction (Ch 28); identity/session + logout reset (Ch 42); stable event id + server dedup (Ch 15); vendor-agnostic sink.
- **Level 4 — large.** Sampling policies; multi-sink/fan-out; schema versioning + validation; operational telemetry sink (perf/errors, Ch 89); regional consent/compliance; A/B exposure logging (Ch 87).
- **Level 5 — enterprise.** Self-hosted analytics, data governance (retention/PII policies), real-time streaming, data-quality monitoring, consent management platform, cross-platform schema parity.

Avoid overengineering: one API + durable buffer + batched upload + consent/redaction + sink abstraction is the core. Don't call vendor SDKs directly; don't send inline; don't skip consent/redaction.

82.11 Alternative Approaches and Trade-offs

Dimension	Option A	Option B	When
Capture API	One internal API + abstraction	direct vendor SDK calls	One API (central consent/redaction/schema/swap)
Send	Durable buffer + batched (Ch 31/14)	inline/synchronous	Buffer+batch (reliable, efficient)
Schema	Typed + versioned	free-form strings	Typed (data quality)
Privacy	Central consent + redaction (Ch 28)	per-call-site	Central (no bypass)
Delivery	At-least-once + dedup (Ch 15)	fire-and-forget / exactly-once	At-least-once + dedup (practical)
Vendor	Agnostic sink (swap/fan-out)	coupled	Agnostic (portability)
Volume	Sample high-volume	send everything	Sample (cost) — never critical events

One API + abstraction vs direct vendor calls: calling the vendor SDK directly across the codebase makes **consent, redaction, and schema impossible to enforce centrally**, couples everything to one vendor, and can't be tested. A **single internal `track` API** behind a **sink abstraction** lets you enforce privacy/schema in one place, **swap or fan out vendors** without touching call sites, and test the pipeline. This single decision enables everything else.

Durable buffer + batched vs inline send: sending each event synchronously over the network **loses events offline/on death**, **janks** the UI, and **drains battery/data**. Writing events to a **durable buffer immediately** (non-blocking) and **uploading in batches** on triggers (Ch 14/47) makes capture reliable, offline/death-safe, and efficient. Never send inline.

Central consent + redaction vs per-call-site: enforcing privacy at each call site is error-prone — one forgotten redaction leaks PII, one missed consent check violates law. The **pipeline** enforces **consent gating and PII redaction centrally** (Ch 28), so **no event can bypass** them. This is only possible with the single API/abstraction.

82.12 Security & Privacy Considerations

- **Consent gating (Ch 28):** collect/send analytics **only with consent** (GDPR/CCPA, regional opt-out); on revoke, **stop** and optionally **purge** the buffer. Essential/ anonymized-only modes per policy. Enforced **centrally**.
- **PII redaction (Ch 28): no raw PII** in events — param **allowlists**, redact/hash emails/names/content/ids, **never tokens/secrets**. Enforced in the pipeline so no event carries PII. Operational telemetry (Ch 89) is PII-safe too.
- **Identity minimization (Ch 28/42):** use anonymized/consented ids; **don't over-identify**; **reset identity on logout** so events aren't linked across users.
- **Secure, authed upload (Ch 19/23):** events upload over **TLS-pinned, authed** channels; access-controlled server-side.

- **Data governance:** retention limits, deletion on request (right to erasure), regional data residency — pipeline + backend policies (Ch 28).
- **No sensitive events:** don't log security-sensitive actions in a way that leaks (e.g., full card data, auth tokens) — ever.
- Client vs backend: the **client** enforces consent + redaction + identity + reliable batched upload; the **backend** dedups, applies retention/governance, and controls access — neither stores raw PII in analytics.

82.13 Performance and Resource Optimization

- **Non-blocking capture** — `track` writes to the buffer async; never blocks the caller/UI.
- **Batching + triggers** (Ch 14/47) — the main battery/data lever; flush on size/time/ background/unmetered, not per event.
- **Sampling** high-volume events (scroll/impressions, Ch 73) — control volume/cost; never sample critical (purchase).
- **Bounded durable buffer** — cap size; drop lowest-priority on overflow (never critical).
- **Efficient redaction** (Ch 28) — allowlist params (cheap) rather than scanning free-form.
- **WorkManager background flush** (Ch 30/47) — reliable, Doze-aware, unmetered.
- **Profiling:** event capture overhead (µs), buffer size, upload batch size/frequency/ success, battery/data from analytics, event delivery rate, dedup rate.

82.14 Testing Strategy

The pipeline (consent, redaction, buffering, batching, dedup, vendor abstraction) is highly unit-testable with a fake sink.

```
class EventPipelineTest {
    @Test fun `drops events without consent`() = runTest {
        consent.granted = false; pipeline.track(ScreenView("home"))
        assertEquals(0, dao.count())                                  // central consent gate
(Ch 28)
    }
    @Test fun `redacts PII from params`() = runTest {
        pipeline.track(event(params = mapOf("email" to "a@b.com")))
        assertFalse(dao.last().params.toString().contains("a@b.com")) // central redaction (Ch
28)
    }
    @Test fun `buffers immediately - does not send inline`() = runTest {
        pipeline.track(ScreenView("home")); assertEquals(1, dao.count());
assertTrue(sink.sent.isEmpty())  // durable (Ch 31)
    }
    @Test fun `resets identity on logout`() = runTest { val s = identity.sessionId;
identity.reset(); assertNotEquals(s, identity.sessionId) }  // Ch 42
}

class EventUploaderTest {
    @Test fun `uploads in batches and removes on ack`() = runTest { /* nextBatch -> send ->
delete (Ch 14) */ }
    @Test fun `keeps events on failure for retry`() = runTest { sink.fail = true;
uploader.flush(); assertTrue(dao.count() > 0) }  // at-least-once (Ch 2/31)
}

class VendorSwapTest { @Test fun `swapping sink does not change call sites`() { /* bind
SelfHostedSink; track still works */ } }
```

What to test: consent gate (no consent → no collect); central PII redaction; **buffer-not- inline** capture; batched upload + remove-on-ack + keep-on-failure (at-least-once, Ch 14/31); stable event id (dedup, Ch 15); identity reset on logout (Ch 42); sampling; **vendor swap** via the sink. Fake sink/consent/redactor; Room in-memory.

82.15 Production Observability

- **Metrics:** event **delivery rate** (captured vs uploaded); buffer size/overflow; upload batch size/frequency/success; **dedup rate** (server); consent-gated drop rate; PII-leak incidents (→ 0, audited); battery/data from analytics; capture overhead; sampling rates.
- **Logs:** pipeline health only — **never event content/PII** (Ch 28).
- **Debugging:** lost events → not buffered/not flushing (Ch 31/14); duplicates → no event-id dedup (Ch 15); PII leak → redaction gap (Ch 28); collecting without consent → gate bypass; battery → inline/too-frequent sends; vendor migration pain → not using the sink abstraction; bad data → free-form schema.
- **Alerting: any PII in uploaded events** (privacy incident); delivery-rate drop (events lost); buffer overflow; consent-compliance regression.

- **Dashboards:** event delivery/dedup rates; buffer health; consent/redaction coverage; analytics battery/data cost.

82.16 System Design Interview Preparation

> ≥40 questions.

Fundamentals

1. *Why centralize?* Enforce schema/consent/redaction centrally; decouple vendor; reliable pipeline.
2. *One API?* `analytics.track(event)` behind a vendor-agnostic sink — no direct vendor calls.
3. *Typed schema?* Defined names/params, versioned — data quality.
4. *Capture model?* Write to a durable buffer immediately (non-blocking), not inline.
5. *Why not send inline?* Lost offline/on death; jank; battery.

Reliability

6. *Durable buffer?* Persistent queue (Room/outbox, Ch 31/3) — offline/death-safe.
7. *Upload?* Batched on triggers (size/time/background/network, Ch 14/47).
8. *Delivery semantics?* At-least-once + stable event id → server dedup (Ch 15).
9. *Partial send?* Keep + retry; dedup handles duplicates.
10. *Background flush?* WorkManager (Ch 30), unmetered pref (Ch 47); flush on ON_STOP.

Privacy

11. *Consent?* Central gate; collect only with consent (GDPR/CCPA, Ch 28); revoke stops + optional purge.
12. *PII?* Central redaction (allowlist params; no raw email/content/token, Ch 28).
13. *Why central?* No call site can bypass; only possible with one API.
14. *Identity?* Consented/anonymized; reset on logout (Ch 42); don't over-identify.

Schema/identity

15. *Event id?* Stable → dedup (Ch 15).
16. *Session/user/device?* Carried on events; reset identity on logout.
17. *Schema versioning?* Events evolve; version them.

Efficiency

18. *Batching?* The battery/data lever (Ch 14).
19. *Flush triggers?* Size/time/background/network.
20. *Sampling?* High-volume events; never critical.
21. *Bounded buffer?* Cap; drop lowest-priority on overflow.

Vendor

22. *Vendor abstraction?* `AnalyticsSink` — swap/fan-out without touching call sites.
23. *Multi-sink?* Fan-out sink.

24. *Self-hosted?* Just another sink.

Product vs ops

25. *Separation?* Product analytics (behavior) vs operational telemetry (perf/errors, Ch 89).
26. *Crash/ANR + logging?* Siblings (Ch 83/89); PII-safe.
27. *Rec signals (Ch 73)?* Product analytics through the same pipeline.

Security

28. *Upload channel?* Authed + TLS-pinned (Ch 19/23).
29. *Governance?* Retention/deletion/residency (Ch 28).
30. *Sensitive events?* Never leak card/tokens.

Testing/Production

31. *Test consent?* No consent → no collect.
32. *Test redaction?* PII removed.
33. *Test buffer?* Not inline; batched; remove-on-ack; keep-on-failure.
34. *Test vendor swap?* Rebind sink; call sites unchanged.
35. *Lost events in prod?* Not buffered/flushing.
36. *Duplicates?* No event-id dedup.
37. *PII leak?* Redaction gap (alert).
38. *Battery?* Inline/too-frequent.
39. *Bad data?* Free-form schema.
40. *Key metrics?* Delivery rate, dedup rate, PII incidents, battery cost.
41. *Vendor migration?* Sink abstraction.

Design-change challenges

1. **Decouple from the analytics vendor.** One `track` API + `AnalyticsSink` abstraction.
2. **Events lost offline.** Durable buffer + batched upload (Ch 31/14).
3. **PII in analytics / GDPR.** Central consent gate + PII redaction (Ch 28).
4. **Analytics drains battery.** Batch + trigger-based + unmetered (Ch 14/47).
5. **Inconsistent event data.** Typed, versioned schema.

Mock walkthrough (abridged)

Clarify (product + ops, vendor, consent/regions, volume?) → one internal `track` API + typed schema behind a vendor-agnostic sink → central consent gate + PII redaction (Ch 28) → durable buffer (Ch 31/3, non-blocking) → batched trigger-based upload (Ch 14/47 via WorkManager) → identity/session + logout reset (Ch 42) + at-least-once + event-id dedup (Ch 15) → sampling → product vs operational separation (crash Ch 83, logging Ch 89 siblings) → security (authed upload, governance) → observability (delivery/dedup, PII incidents).

82.17 Practical Exercises

1. **Beginner.** Build one `track(event)` API with a typed event schema behind an `AnalyticsSink` abstraction (no direct vendor calls). *Eval:* central API; vendor-agnostic.
2. **Intermediate.** Add a durable buffer (Room/outbox) and batched, trigger-based upload (size/time/background) via WorkManager (Ch 31/14/47). *Eval:* offline/death-safe; batched.
3. **Advanced.** Add central consent gating + PII redaction (Ch 28), identity with logout reset (Ch 42), and stable event ids for dedup (Ch 15). *Eval:* no PII/unconsented; reset on logout; dedupable.
4. **Production debugging.** Fix lost events (inline send → buffer) and PII in events (redaction gap). *Eval:* retained; redacted.
5. **System design challenge.** Add sampling, a fan-out sink (two vendors), and swap the vendor without touching call sites; add a delivery-rate dashboard. *Eval:* sampled; multi-sink; swappable; measured.

(Solutions withheld unless requested.)

82.18 Chapter Summary & Reference Sheet

Key decisions: route **all** analytics and operational telemetry through **one internal, vendor-agnostic `track` API** with a **typed, versioned event schema** — never direct vendor SDK calls — so that **consent gating, PII redaction, and schema** are enforced **centrally** and the **vendor can be swapped or fanned out** (via an `AnalyticsSink` abstraction) without touching call sites; **capture events by writing them to a durable persistent buffer immediately** (non-blocking, **offline- and process-death-safe**, Ch 31/3) rather than sending synchronously, then **upload in batches on sensible triggers** (size/time/background/network) that respect **battery and background limits** (Ch 14/47, via WorkManager); **gate on consent and redact PII in the pipeline** (GDPR/CCPA, allowlisted params, no raw emails/content/tokens, Ch 28) before anything leaves the device; manage **consistent identity/session** with **logout reset** (Ch 42) and **at-least-once delivery with stable event ids for server-side dedup** (Ch 15); **sample** high-volume events (never critical ones); and keep **product analytics distinct from operational telemetry** (with **crash/ANR** Ch 83 and **logging/ breadcrumbs** Ch 89 as PII-safe siblings). Upload over **authed, TLS-pinned** channels with **retention/deletion governance** (Ch 19/23/28).

Concepts: one `track` API + vendor-agnostic sink (swap/fan-out), typed versioned schema, durable buffering (persistent queue), batched trigger-based upload (Ch 14/47), central consent

- PII redaction (Ch 28), identity/session + logout reset (Ch 42), at-least-once + event-id dedup (Ch 15), sampling, product-vs-operational separation.

Common mistakes: direct scattered vendor calls (can't enforce consent/redaction/schema, lock-in); inline/synchronous send (lost offline/on death, jank, battery); no durable buffer; no batching (battery/data); PII in events / no consent gate (legal); free-form schema (bad data); no event-id dedup (inflated metrics); not resetting identity on logout (cross-user attribution); vendor-coupled (no portability).

Checklist:

- ☐ one `track` API + typed versioned schema behind `AnalyticsSink` (no direct vendor calls)
- ☐ durable persistent buffer, immediate non-blocking capture (Ch 31/3)
- ☐ batched, trigger-based upload (size/time/background/unmetered, Ch 14/47 via WorkManager)

- [ ] central consent gate + PII redaction (Ch 28)
- [ ] identity/session + reset on logout (Ch 42)
- [ ] at-least-once + stable event id → server dedup (Ch 15)
- [ ] sampling (never critical)
- [ ] product vs operational separation (crash Ch 83, logging Ch 89)
- [ ] authed + TLS-pinned upload + governance (Ch 19/23/28)
- [ ] delivery-rate + PII-incident telemetry.

Key APIs: `Analytics.track` / `setConsent` / `resetIdentity` (one API), sealed `AnalyticsEvent` (typed schema), `EventPipeline` (consent+redact+buffer), Room `EventDao` (durable buffer, Ch 3/31), `EventUploader` + WorkManager (batched flush, Ch 14/30/47), `AnalyticsSink` (vendor/self-hosted/fan-out), `ConsentManager` / `PiiRedactor` (Ch 28), `IdentityProvider` (Ch 42), `Sampler`, stable event id (Ch 15).

References:

- Analytics best practices (events/params): https://developer.android.com/topic/architecture (data layer) + vendor docs
- Data safety / consent: https://developer.android.com/privacy-and-security
- WorkManager (background flush): https://developer.android.com/develop/background-work/background-tasks/persistent
- (composes) Ch 14 Batching/Queueing, Ch 28 PII Redaction/Consent, Ch 31 Outbox, Ch 3 SSOT, Ch 47 Background Limits, Ch 42 Multi-Account, Ch 15 Idempotency/Dedup, Ch 83 Crash/ANR, Ch 89 Logging, Ch 73 Rec Signals, Ch 87 A/B

Chapter review (Phase 4)

- **Completeness:** all 18 sections; architecture/class/sequence/flow/failure diagrams; one-API + typed schema + pipeline (consent+redact+buffer) + batched uploader + vendor-sink abstraction + identity-reset code; concurrency (durable buffer+at-least-once+dedup, central consent/redaction, logout reset); failure (one-API+buffered+batched+consented+decoupled principle); 5 levels; one-API-vs-direct, buffer-vs-inline, central-privacy trade-offs; security/privacy (consent, redaction, identity minimization, governance); perf (non-blocking, batch, sample); pipeline + vendor-swap tests; observability (delivery/dedup, PII incidents); 41 Q&A + 5 challenges. ✅ Opens Part X.
- **Expand later:** batching (Ch 14), privacy (Ch 28), crash/ANR (Ch 83), logging (Ch 89), A/B (Ch 87).
- **Interview coverage:** exceeds ≥40 Complex bar.