Chapter 26 — App Integrity, Root & Tamper Detection

> **Part III — Authentication & Security** · Complexity: **Standard** (≥25 interview questions)
>
> **Prerequisites:** Ch 19 (tokens — what we protect), Ch 20 (Keystore/attestation), Ch 23 (pinning — the network side). Complements Ch 27 (obfuscation) and Ch 24 (at-rest). Establishes the *device/app trust* layer.
>
> **Reference surface in StreamCart:** deciding whether to trust that the StreamCart app running on a device is genuine, unmodified, and on a non-compromised Android before allowing a payment or serving premium content.

26.1 Problem Definition and Real-World Context

The client runs on hardware the attacker controls. For high-value features (payments, DRM content, anti-fraud, anti-cheat), the backend wants assurance that the request comes from a **genuine, unmodified app** on a **non-compromised device** — not a rooted phone, an emulator, a repackaged/instrumented APK, or a bot. Naive approaches fail or create false confidence:

- **Client-side-only detection is defeatable.** A root/tamper check that runs in the app and returns a boolean can be hooked (Frida), patched out, or spoofed on a rooted device. **Any purely local verdict can be bypassed** — relying on it for a security decision is a trap.
- **No server verification.** If the client just tells the backend "I'm not rooted," a modified client lies. Integrity signals are worthless unless **verified server-side** against a cryptographically-signed verdict.
- **Over-blocking.** Aggressive root/emulator blocking locks out legitimate power-users, test devices, and some OEMs — hurting real users while determined attackers adapt.
- **Treating integrity as authentication.** Integrity answers "is this a genuine app/device?", not "who is this user?" (Ch 19) — conflating them is a design error.

The architecture: use the **Play Integrity API** (Google's attestation) to get a **server-verifiable, signed verdict** about app/device integrity, **verify it on the backend** (with a nonce to prevent replay), combine with **defense-in-depth** (Keystore key attestation Ch 20, pinning Ch 23, obfuscation Ch 27), and apply **risk-based** responses rather than blunt blocking — all while knowing the honest **limits** of client integrity.

Three practical use cases

1. **Fintech (StreamCart Wallet).** Before a high-value payment, the backend requires a valid Play Integrity verdict; a failing verdict triggers step-up (Ch 21) or blocks the transaction.
2. **OTT (Watch).** Premium/DRM content is gated on integrity to deter content piracy via modified clients/emulators.
3. **Anti-fraud/abuse (all).** Account creation, promo redemption, and review-posting are rate-limited/blocked when the integrity verdict indicates a bot farm/emulator.

Why this is architectural

App integrity defines the **device/app trust layer**: what assurance the backend has about the client, how that assurance is **obtained (attestation) and verified (server-side)**, how it composes with auth/pinning/obfuscation, and the **honest boundary** of what client-side can prove — properties that determine whether high-value features can trust the client at all.

26.2 Requirements Engineering

Functional requirements

ID	Requirement
F1	Obtain a cryptographically-signed integrity verdict (Play Integrity API).
F2	Bind the verdict to the request (nonce) to prevent replay.
F3	Verify the verdict **server-side** (never trust a client boolean).
F4	Classify the verdict (genuine app, licensed, device integrity) and respond by risk.
F5	Apply defense-in-depth (attestation Ch 20, pinning Ch 23, obfuscation Ch 27).
F6	Gracefully handle integrity-unavailable (no Play Services, offline).

Non-functional requirements

Attribute	Policy
Security	Server-verified attestation; replay-resistant; not bypassable by client patching.
Reliability	Degrade gracefully where integrity can't be obtained.
UX	Risk-based (step-up/limit) over blunt blocking; avoid locking out legit users.
Performance	Integrity checks are cheap and infrequent (gate sensitive actions, not every call).
Privacy	No invasive device fingerprinting beyond the attestation.

Scope

- **In scope:** Play Integrity API (request + server verification + nonce), verdict classification, risk-based response, defense-in-depth composition, limits of client-side detection, graceful fallback.
- **Out of scope:** Keystore key attestation internals (Ch 20), pinning (Ch 23), obfuscation/R8 (Ch 27), auth (Ch 19), the backend verification service internals.

Assumptions & constraints

- Play Integrity API (`com.google.android.play:integrity`); a backend that verifies verdicts. Google Play distribution (Play Integrity needs Play Services). `minSdk 24` . **Client-side-only detection is a signal, not a guarantee.**

26.3 System Design Fundamentals

- **Attestation vs local detection.** *Local detection* (checking for `su`, Magisk, test-keys, emulator props) runs in the app and is **inherently bypassable** on a compromised device — useful only as weak, additional signal. *Attestation* (Play Integrity) produces a verdict **signed by Google**, generated outside the app's control, that the **backend verifies** — this is the real assurance.
- **Play Integrity verdicts.** The API returns labels such as: **app recognition** (the app is the genuine, Play-signed binary vs modified/unrecognized), **device integrity** (`MEETS_DEVICE_INTEGRITY` / `MEETS_BASIC_INTEGRITY` / `MEETS_STRONG_ INTEGRITY` — the device passes integrity checks vs rooted/emulator/compromised), and **account/licensing** (the user obtained the app from Play). These come in a signed token.
- **Nonce binding (anti-replay).** The client requests a verdict for a **server- issued nonce** (or a hash of the request); the backend checks the nonce matches, preventing a captured valid verdict from being replayed by an attacker.
- **Server-side verification is mandatory.** The signed integrity token must be decrypted/verified on the **backend** (or via Google's servers), never trusted as a client-reported boolean. **This is the whole point** — a modified client can fake a boolean but cannot forge Google's signature.
- **Risk-based response.** Rather than hard-blocking any non-perfect verdict (locking out legit users on some devices), apply graduated responses: allow, **step-up** (Ch 21), **limit** (lower transaction caps / rate limits), or **block** only the riskiest actions.
- **Defense-in-depth.** Integrity is one layer: combine with **Keystore key attestation** (Ch 20, hardware-backed key proof), **certificate pinning** (Ch 23), **obfuscation/R8** (Ch 27, raise the cost of tampering), and **server-side anomaly detection**. No single layer is sufficient.
- **Honest limits.** Even attestation isn't absolute (there are bypasses, and it depends on Play Services); it **raises the cost** of attacks and gives the backend a signal — it doesn't make the client trusted.

Core insight: **obtain a Google-signed integrity verdict bound to a nonce, verify it server-side, and respond by risk — treating client integrity as a cost-raising signal in a defense-in-depth stack, never as a client-trusted boolean.**

26.4 High-Level Architecture


26.4 High-Level Architecture

Components & ownership

- **Backend** issues the **nonce**, **verifies** the signed verdict, and decides the **risk-based response** — it is the trust authority.
- **Client** requests the verdict and forwards the token; it makes **no** trust decision itself.
- **Play Integrity (Google)** produces the signed verdict outside the app's control.
- **Defense-in-depth layers** (Ch 20/23/27) raise attacker cost.

Direction: action → backend nonce → client attests → backend verifies → risk response.

26.5 Detailed Component Design



Component	Responsibility	Trust
`IntegrityGate` (client)	request a verdict for a nonce	untrusted courier
Play Integrity (Google)	produce signed verdict	trusted producer
`BackendVerifier` (server)	verify signature + nonce + classify	trust authority
risk policy (server)	allow/step-up/limit/block	decision maker
defense-in-depth	attestation/pinning/obfuscation	cost raisers

> The client is a **courier**, not a decider. Every integrity decision happens on the backend after verifying Google's signature.

26.6 End-to-End Data Flow

Integrity-gated payment



Integrity unavailable (no Play Services)



26.7 Complete Kotlin Implementation

Package: `com.streamcart.core.integrity`.

26.7.1 Request an integrity verdict (client = courier)

```
class IntegrityGate @Inject constructor(@ApplicationContext private val context: Context) {

    // nonce comes from the BACKEND (anti-replay); the client never generates the trust
decision.
    suspend fun requestToken(nonce: String): Result<String> = runCatching {
        val manager = IntegrityManagerFactory.create(context)
        val response = manager.requestIntegrityToken(
            IntegrityTokenRequest.builder()
                .setNonce(nonce)                       // bind to the server-issued nonce
                .setCloudProjectNumber(CLOUD_PROJECT)  // your Google Cloud project
                .build()
        ).await()                                      // Play Services task -> coroutine
        response.token()                               // opaque, Google-signed; verified
server-side
    }
    private companion object { const val CLOUD_PROJECT = 1234567890L }
}
```

26.7.2 Sensitive-action flow (backend decides)

```
class PaymentFlow @Inject constructor(
    private val api: PaymentApi,
    private val integrity: IntegrityGate,
) {
    suspend fun pay(amount: Money): Outcome<Receipt> {
        val begin = api.beginPayment(amount)                  // backend returns a nonce
        val token = integrity.requestToken(begin.nonce).getOrNull()   // may be null (no Play
Services)
        // Forward the token; the BACKEND verifies it and enforces the risk policy.
        return safeApiCall(dispatchers.io) { api.confirmPayment(begin.id, integrityToken =
token) }
        // If token == null or verdict is weak, the backend responds with step-up/limit/deny.
    }
}
```

26.7.3 Backend verification (pseudocode — the real trust boundary)

```
// SERVER-SIDE (shown for completeness; not Android code).
fun verify(token: String, expectedNonce: String): Verdict {
    val payload = googlePlayIntegrity.decodeAndVerify(token)   // verify Google's signature
    require(payload.requestDetails.nonce == expectedNonce)     // anti-replay
    require(payload.appIntegrity.appRecognitionVerdict == "PLAY_RECOGNIZED")   // genuine app
    val device = payload.deviceIntegrity.deviceRecognitionVerdict   // MEETS_DEVICE_INTEGRITY,
...
    return classify(device)                                    // -> allow / step-up / limit /
block
}
```

26.7.4 Weak local signals (defense-in-depth only — never decisive)

```
// Additional, EASILY-BYPASSED signals. Use only to raise cost / feed server risk scoring.
// NEVER make a security decision on these alone.
fun weakLocalSignals(): Map<String, Boolean> = mapOf(
    "emulator_hint" to (Build.FINGERPRINT.contains("generic") || Build.MODEL.contains("sdk")),
    "test_keys" to Build.TAGS.orEmpty().contains("test-keys"),
    "debuggable" to (context.applicationInfo.flags and ApplicationInfo.FLAG_DEBUGGABLE != 0),
    // su-binary / Magisk checks omitted: trivially defeated on a rooted device.
)
```

26.7.5 Module structure

```
:core:integrity   IntegrityGate, weak local signals (optional), IntegrityToken
:feature:wallet   PaymentFlow (gates on backend-verified verdict)
# Backend owns: nonce issuance, token verification, risk policy.
```

26.8 Concurrency and Race Conditions

Scenario	Risk	Handling
Concurrent integrity requests	redundant tokens	request per sensitive action; cache a recent token only if the nonce matches
Nonce reuse	replay	one nonce per request (server); verify match
Token fetched, action delayed	stale token	short validity; re-request if the nonce/request changed
Play Services slow	blocks UI	request on IO; show progress; time out gracefully
Verdict verification race (server)	TOCTOU	bind verdict to the specific request via nonce; verify atomically with the action

- **The nonce binds the verdict to one request**, eliminating replay/stale-token races — the verdict is only valid for that exact server-issued challenge.

26.9 Failure Scenarios and Recovery

Failure	Detection	Response	Outcome
Device rooted / failed integrity	verdict fails (server)	step-up/limit/block high-value action	protected; legit basic use may continue
Repackaged/modified app	app-recognition fails	block; alert; force official install	tamper blocked
Emulator / bot	device integrity weak	rate-limit/block abuse-prone actions	fraud reduced
No Play Services (non-GMS device)	request fails	fallback policy (limit / alternate checks / allow low-value)	app still usable for most
Offline	can't fetch verdict	defer verdict for online-only sensitive actions	graceful
Play Integrity rate limits/quota	API error	cache recent valid verdict (nonce-bound); backoff	resilient
Over-blocking legit users	support tickets	risk-based, not blunt; allow-list test devices	fewer false positives
Client claims "not rooted" (spoof)	server ignores client booleans	only trust the signed verdict	not bypassable



> **Never hard-fail the whole app on integrity** — non-GMS devices, some OEMs, and power-users will hit it. Gate only **sensitive actions**, respond by **risk**, and keep basic functionality working.

26.10 Scaling the Implementation

- **Level 1.** Request a Play Integrity verdict before the single most sensitive action (payment); verify server-side.
- **Level 2.** Nonce binding; risk-based responses (step-up/limit/block); fallback for no-Play-Services.
- **Level 3 — production.** Defense-in-depth: Keystore attestation (Ch 20), pinning (Ch 23), obfuscation/R8 (Ch 27); server risk scoring combining signals; allow-list test devices.
- **Level 4 — large.** Integrity feeding a broader fraud/risk engine; per-action policies from remote config (Ch 41); analytics on verdict distribution.
- **Level 5 — enterprise.** Adaptive/risk-based auth, device reputation, anti-cheat/ anti-abuse platforms, coordinated client+server hardening, SafetyNet → Play Integrity migration governance.

Avoid overengineering: most apps don't need integrity attestation at all. Add it for genuine high-value/anti-fraud/DRM needs — and **never** add brittle local root-detection that annoys users without server verification.

26.11 Alternative Approaches and Trade-offs

Dimension	Option A	Option B	When
Assurance	Play Integrity (server-verified attestation)	local root/emulator checks	Attestation for real assurance; local checks only as weak extra signal
Decision	Server-side (signed verdict)	client-side boolean	**Always** server-side; client booleans are forgeable
Response	Risk-based (step-up/limit/block)	hard block	Risk-based to avoid false positives; hard block only for the riskiest
Key proof	Keystore key attestation (Ch 20)	none	Attestation for hardware-backed key proof (high assurance)
Scope	Gate sensitive actions	gate every request	Gate sensitive only (cost/UX); not every call
Distribution	Play Integrity (needs GMS)	alternative attestation	Play Integrity on Play; alternatives for non-GMS markets

Attestation vs local detection (the key point): local root/tamper detection runs *inside* the attacker-controlled app and can always be hooked/patched — it's a cost-raiser, not a guarantee, and over-reliance creates false confidence and false positives. Play Integrity produces a **Google-signed verdict** the **backend** verifies, which a modified client cannot forge. Use attestation for decisions; use local checks only to feed server-side risk scoring.

Risk-based vs hard block: blocking any imperfect verdict maximizes security but locks out legitimate users (custom ROMs, non-GMS, test devices) and still doesn't stop determined attackers. Graduated responses (step-up, lower limits) preserve UX for the many while constraining the risky few — usually the better product/security balance.

26.12 Security Considerations

- **Verify server-side, always.** The signed integrity token is only meaningful when the **backend** verifies Google's signature and the nonce. A client boolean is worthless.
- **Bind to a nonce** to prevent replay of a captured valid verdict.
- **Integrity ≠ authentication.** It proves "genuine app/device," not "who the user is" (Ch 19); compose them, don't conflate.
- **Defense-in-depth:** pair with Keystore attestation (Ch 20), pinning (Ch 23), obfuscation/R8 (Ch 27), and server anomaly detection — no single layer suffices.
- **Honest limits:** attestation raises cost but isn't unbeatable and depends on Play Services; don't assume a passing verdict means the client is fully trusted.
- **Avoid over-blocking / invasive fingerprinting:** respect privacy; risk-based responses; allow-list legitimate test/dev devices.
- **Protect the verdict path:** request over a pinned channel (Ch 23); don't let a MITM swap verdicts.
- Client vs backend: the client is an untrusted courier; the **backend is the sole trust authority** for integrity decisions.

26.13 Performance and Resource Optimization

- **Integrity checks are infrequent** — gate sensitive actions, not every request; the token fetch is a one-off per action.
- **Standard vs classic requests:** Play Integrity's standard request supports warming/caching for lower latency on frequent checks; use it where you need repeated verdicts.
- **Don't block the UI:** fetch on IO with a timeout; show progress for the gated action.
- **Cache a recent nonce-bound verdict** within its validity to avoid redundant calls (only if the nonce/request is the same).
- **Profiling:** verdict-fetch latency, failure/quota rate, verdict distribution, false-positive (legit-user-blocked) rate.

26.14 Testing Strategy

The verdict is produced by Google and verified server-side, so client tests focus on the courier flow + fallback; integration/manual tests cover real verdicts.

```
class IntegrityGateTest {
    @Test fun `forwards server nonce in the request`() = runTest {
        val gate = IntegrityGate(ctxWithFakeIntegrity(recorder))
        gate.requestToken("nonce-123")
        assertEquals("nonce-123", recorder.lastNonce)
    }
    @Test fun `returns failure gracefully when Play Services unavailable`() = runTest {
        val gate = IntegrityGate(ctxWithNoPlayServices())
        assertTrue(gate.requestToken("n").isFailure)      // -> fallback policy
    }
}

class PaymentFlowTest {
    @Test fun `payment proceeds with null token when integrity unavailable (backend decides)`()
= runTest {
        val api = RecordingPaymentApi()
        PaymentFlow(api, FailingIntegrityGate).pay(Money(100))
        assertNull(api.lastIntegrityToken)                // backend applies fallback/limit
    }
    @Test fun `token is attached when available`() = runTest {
        val api = RecordingPaymentApi()
        PaymentFlow(api, FakeIntegrityGate(token = "T")).pay(Money(100))
        assertEquals("T", api.lastIntegrityToken)
    }
}
```

What to test: nonce forwarding, graceful no-Play-Services fallback, token attachment, and (server-side/integration) verdict verification + risk policy + nonce anti-replay. Verify **no security decision** is made purely client-side.

26.15 Production Observability

- **Metrics (mostly backend):** verdict distribution (genuine/degraded/failed), integrity-gated action block/step-up/allow rates, verdict-fetch latency/failure, no-Play-Services rate, false-positive (legit-blocked) rate, fraud-prevented estimate.
- **Logs:** `integrity{action, verdict_class, response}` (server; no device fingerprints beyond policy); client: `integrity_fetch{result}` (no verdict content client-side).
- **Debugging:** legit users blocked → over-strict policy / non-GMS handling; fraud slipping through → relying on client booleans / no server verification; verdict-fetch failures spike → Play Services/quota issue.
- **Alerting:** surge in failed/tampered verdicts → possible attack campaign or a bad app release (correlate with release).
- **Privacy:** minimize device data; the verdict is the signal — avoid extra fingerprinting.

26.16 System Design Interview Preparation

> ≥25 questions.

Fundamentals

1. *Why can't the client prove it's untampered by itself?* Any local check runs in the attacker-controlled app and is bypassable (hook/patch).
2. *Attestation vs local detection?* Attestation = Google-signed, server-verified verdict; local detection = weak, bypassable signal.
3. *What is Play Integrity?* Google's API returning a signed verdict about app/ device integrity.
4. *What verdicts does it give?* App recognition (genuine/modified), device integrity (basic/device/strong), account/licensing.
5. *Why a nonce?* Anti-replay — bind the verdict to a specific server-issued challenge.

Architecture

6. *Where is the trust decision made?* The backend — it verifies the signature + nonce + verdict.
7. *Role of the client?* An untrusted courier that fetches and forwards the token.
8. *Why not trust a client boolean?* A modified client lies; only Google's signature is unforgeable.
9. *Integrity vs authentication?* "Genuine app/device" vs "who the user is" (Ch 19) — compose, don't conflate.

Response policy

10. *Risk-based vs hard block?* Graduated (step-up/limit/block) avoids false positives; hard block only for the riskiest.
11. *Handle no Play Services?* Fallback policy (limit/alternate/allow low-value); don't brick the app.
12. *Over-blocking risk?* Locks out custom ROMs/non-GMS/test devices; allow-list + risk-based.

Defense-in-depth

13. *What else to combine?* Keystore key attestation (Ch 20), pinning (Ch 23), obfuscation/R8 (Ch 27), server anomaly detection.
14. *Keystore attestation vs Play Integrity?* Hardware key-backing proof vs app/ device integrity — complementary.
15. *Why defense-in-depth?* No single layer is sufficient; each raises cost.

Limits

16. *Is attestation unbeatable?* No — raises cost, depends on Play Services; a passing verdict ≠ fully trusted client.
17. *Should every request be gated?* No — sensitive actions only (cost/UX).

Operational

18. *Replay of a valid verdict?* Prevented by nonce binding + server check.
19. *MITM swapping verdicts?* Pinned channel (Ch 23); server verifies signature.
20. *Migration from SafetyNet?* SafetyNet Attestation is deprecated → Play Integrity.

Testing

21. *What can client tests cover?* Nonce forwarding, fallback, token attachment — not the verdict itself.
22. *Where is the real test?* Server-side verification + risk policy + anti-replay.
23. *Key property to assert?* No client-side-only security decision.

Production debugging

24. *Legit users blocked?* Over-strict/no non-GMS handling.
25. *Fraud slipping through?* Trusting client booleans / no server verification.
26. *Verdict failures spike?* Play Services/quota, or an attack/bad release.

Design-change challenges

1. **Gate high-value payments on integrity.** Nonce + Play Integrity + server verify
    - step-up on degraded (Ch 21).
2. **Deter piracy of premium content.** Integrity + DRM + pinning; risk-based.
3. **Support non-GMS devices.** Fallback policy; alternative attestation; limit sensitive actions.
4. **Attacker repackages the app.** App-recognition verdict blocks; force official install.
5. **Reduce false positives.** Risk-based responses + allow-list + server risk scoring.

Mock walkthrough (abridged)

Clarify (what to protect, threat, GMS?) → attestation (Play Integrity) not local checks → nonce + server verification (trust authority) → risk-based response → defense-in-depth (Ch 20/23/27) → fallback for no-GMS → state honest limits → gate sensitive actions only → testing.

26.17 Practical Exercises

1. **Beginner.** Request a Play Integrity token for a server-issued nonce and attach it to a sensitive request. *Eval:* nonce forwarded; token attached.
2. **Intermediate.** Handle no-Play-Services/offline gracefully with a fallback policy; never block basic use. *Eval:* app usable; sensitive action limited.
3. **Advanced.** Design the server verification (signature + nonce + verdict) and a risk-based response (allow/step-up/limit/block). *Eval:* no client-side decision; anti-replay.
4. **Production debugging.** Fix an app that makes a security decision on a local root-check boolean (bypassable) and hard-blocks all rooted devices. *Eval:* server-verified verdict; risk-based.
5. **System design challenge.** Compose integrity with Keystore attestation (Ch 20), pinning (Ch 23), and server risk scoring for a payment flow. *Eval:* layered; degrades gracefully; low false positives.

(Solutions withheld unless requested.)

26.18 Chapter Summary & Reference Sheet

Key decisions: obtain a **Google-signed integrity verdict (Play Integrity)** bound to a **server-issued nonce**; **verify it server-side** (the client is an untrusted courier — never trust a client boolean); respond **by risk** (allow/ step-up/limit/block) rather than blunt blocking; treat integrity as **one layer** in defense-in-depth with **Keystore attestation (Ch 20), pinning (Ch 23), obfuscation/R8 (Ch 27)**; gate **sensitive actions only**; handle **no-Play-Services/ offline** gracefully; keep the **honest limits** in mind (attestation raises cost, isn't absolute, isn't authentication).

Concepts: attestation vs local detection, Play Integrity verdicts (app/device/ account), nonce anti-replay, server-side verification, risk-based response, defense-in-depth, integrity ≠ auth.

Common mistakes: client-side-only root/tamper booleans (bypassable); no server verification; no nonce (replay); hard-blocking all imperfect verdicts (false positives / non-GMS lockout); conflating integrity with authentication; relying on a single layer; invasive fingerprinting.

Checklist:

- [ ] Play Integrity verdict
- [ ] server-issued nonce (anti-replay)
- [ ] server-side verification
- [ ] risk-based response (not hard block)
- [ ] gate sensitive actions only
- [ ] defense-in-depth (Ch 20/23/27)
- [ ] no-GMS/offline fallback
- [ ] no client-side security decision
- [ ] allow-list test devices
- [ ] monitor verdict distribution/false positives.

Key APIs: `IntegrityManagerFactory` / `IntegrityManager`, `IntegrityTokenRequest` / `StandardIntegrityManager`, `setNonce`, `requestIntegrityToken`, Keystore key

attestation (Ch 20), `CertificatePinner` (Ch 23). Verdict verification is **server-side** (Google Play Integrity API / Google's servers).

References:

- Play Integrity API: https://developer.android.com/google/play/integrity
- Verdicts & server verification: https://developer.android.com/google/play/integrity/verdicts
- SafetyNet → Play Integrity migration: https://developer.android.com/google/play/integrity/migrate
- Key attestation (Ch 20): https://developer.android.com/privacy-and-security/security-key-attestation
- (composes with) Ch 20 Keystore, Ch 23 Pinning, Ch 27 Obfuscation

Chapter review (Phase 4)

- **Completeness:** all 18 sections; architecture/class/sequence/failure diagrams; IntegrityGate (courier) + nonce + server-verify pseudocode + weak-signals caveat; concurrency (nonce binding); failure (no-GMS, over-block); 5 levels; attestation- vs-local and risk-vs-block trade-offs; honest-limits threat model; perf (gate sensitive only); courier + fallback tests; observability (verdict distribution); 26 Q&A + 5 challenges. ✅
- **Expand later:** Keystore attestation (Ch 20), pinning (Ch 23), obfuscation (Ch 27), fraud/risk engines.
- **Interview coverage:** exceeds ≥25 bar.