Chapter 54 — App Update & Forced-Upgrade Flow

> **Part VI — Lifecycle, Background & Platform** · Complexity: **Standard** (≥25 interview questions)
>
> **Prerequisites:** Ch 16 (API schema evolution), Ch 41 (remote config/feature flags), Ch 19 (auth), Ch 44/45 (lifecycle/startup), Ch 52 (deep links). Pairs with Ch 26 (integrity), Ch 28 (privacy).
>
> **Reference surface in StreamCart:** keeping users on a supported app version — nudging optional updates in-app, forcing an upgrade when an old client is incompatible or insecure, and doing it without locking users out or breaking the store-review contract.

54.1 Problem Definition and Real-World Context

Users don't update apps promptly. Weeks after you ship a release, a long tail of users run old versions — and some of those versions are **incompatible** (a breaking API change, Ch 16), **insecure** (a patched vulnerability, Ch 23), or **broken** (a server-side change the old client can't handle). You need a way to **encourage** updates (soft nudge) and, when necessary, **require** them (hard gate) — while respecting Play policy and never stranding a user with a dead app they can't fix.

Concretely, teams hit:

- **No update strategy.** The app silently breaks for old-version users after a backend change (Ch 16) with no way to tell them to update — support floods, churn.
- **Forced upgrade done wrong.** A hard gate with no store link, or one that triggers for too many versions, or one driven by a hardcoded client constant (can't change without *another* release) — the thing you can't fix is a forced-upgrade bug itself.
- **In-App Updates misunderstood.** Google's **In-App Updates API** offers **flexible** (background download, user keeps using the app) and **immediate** (full-screen blocking update) flows — but these only work for apps installed from **Play**, require handling the update lifecycle, and are not a substitute for a **server-driven** minimum-version policy.
- **Version policy on the client vs server.** The decision "is this version still allowed?" must be **server-driven** (remote config / an endpoint, Ch 41) so you can change the floor without shipping a new build — a hardcoded min-version is useless for the very users who won't update.
- **Graceful degradation & escape hatches.** A forced upgrade must always give a working path (open Play), handle "update not available yet" (staged rollout), the no-network case, and never trap the user in a loop.

The architecture: define a **server-driven version policy** (minimum supported + "nudge above" thresholds, delivered via remote config / an endpoint, Ch 41) checked at startup/resume and on key API calls (a `426 Upgrade Required`-style signal, Ch 16); map it to **three states** — up-to-date, **soft update** (dismissible nudge), **forced upgrade** (blocking gate); drive updates with the **Play In-App Updates API** (flexible for soft, immediate for forced) with a **fallback to opening the store listing**; handle the **lifecycle** (download/resume/failure, staged rollout, not-from-Play installs); and **degrade gracefully** (always an escape to Play, offline tolerance, no loops). This chapter is about **steering users onto supported versions, forcibly when needed, without breaking them**.

Three practical use cases

1. **Soft nudge (StreamCart).** A new version is available with nice-to-have features → a dismissible in-app banner + Play flexible update (download in background, install when ready). The user can defer.
2. **Forced upgrade.** The server raises the minimum supported version (a breaking API change or security fix, Ch 16/23) → old clients get a **blocking** screen with an **Update** button (Play immediate update / store link) and cannot proceed until updated.
3. **Server signals incompatibility mid-session.** An API returns `426 Upgrade Required` → the client surfaces the forced-upgrade gate even without a fresh config fetch.

Why this is architectural

Update policy is a **server-driven control plane** touching API compatibility (Ch 16), remote config (Ch 41), security (Ch 23/26), startup/lifecycle (Ch 44/45), and store policy. The decisions — where the version floor lives (server), soft vs forced, how updates are delivered (In-App Updates vs store link), and how to never trap a user — determine whether you can safely evolve the backend and retire old clients.

54.2 Requirements Engineering

Functional requirements

ID	Requirement
F1	Determine update state (up-to-date / soft / forced) from a server-driven policy.
F2	Nudge soft updates (dismissible); block on forced upgrade.
F3	Drive the update (Play In-App Updates: flexible/immediate) with a store-link fallback.
F4	Handle a mid-session incompatibility signal (e.g., `426` , Ch 16).
F5	Degrade gracefully (offline, staged rollout, not-from-Play) — never trap the user.
F6	Change the version floor without shipping a new build (remote, Ch 41).

Non-functional requirements

Attribute	Policy
Controllability	Version floor is server-driven; changeable instantly (Ch 41).
Resilience	Always an escape to Play; offline tolerant; no loops.
Compliance	Play policy for forced updates / In-App Updates.
Security	Forced upgrade can be used for security fixes (Ch 23).
UX	Soft nudges are respectful (dismiss/snooze); forced is clear + actionable.

Scope

- **In scope:** server-driven version policy (min supported + nudge thresholds via remote config/endpoint, Ch 41), the 3 update states, soft vs forced gating, Play In-App Updates (flexible/immediate) lifecycle, store-link fallback, mid-session `426` handling (Ch 16), staged-rollout/not-from-Play/offline handling, no-loop/escape-hatch design, startup/resume checks.
- **Out of scope:** API compatibility detail (Ch 16), remote config internals (Ch 41), integrity/anti-tamper (Ch 26), security vuln handling (Ch 23), startup optimization (Ch 45).

Assumptions & constraints

- Play-distributed app (In-App Updates requires Play); remote config/endpoint available (Ch 41); `versionCode` monotonic; backend can emit `426`/compat signals (Ch 16). `minSdk 24`. Some installs aren't from Play (sideload/other stores) → store-link fallback needed.

54.3 System Design Fundamentals

- **The version floor must be server-driven (the core principle).** The decision "is version X still supported?" lives on the **server** (remote config, Ch 41, or a `/version-policy` endpoint), **not** a client constant. Why: the users you most need to force off an old version are exactly the ones who won't take a new build — a hardcoded min-version can't reach them. A server-driven floor lets you raise the minimum **instantly**, for a security fix or breaking change, without a release.
- **Three update states:**
  - **Up-to-date:** `installedVersion >= nudgeFloor` → nothing.
  - **Soft update (optional):** `recommendedFloor <= installed < latest` → a **dismissible** nudge (banner/dialog) + flexible update; user may defer/snooze.
  - **Forced upgrade (required):** `installed < minSupported` → a **blocking** screen; the app is unusable until updated (used for incompatibility/security). Thresholds (`minSupported`, `recommendedFloor`, `latest`) all come from the server-driven policy.
- **Two trigger paths:**
  - **Proactive check** at startup/resume (Ch 44/45): fetch policy (cached, Ch 41), compare to `versionCode`, set state.
  - **Reactive signal** mid-session: an API returns **`426 Upgrade Required`** (or a compat error, Ch 16) → immediately enter forced state even if the cached policy was stale. This catches users whose session predates a floor change.
- **Play In-App Updates API (the delivery mechanism):**
  - **Flexible flow:** downloads the update in the **background** while the user keeps using the app; you then prompt to **install** (a restart). Use for **soft** updates.
  - **Immediate flow:** a **full-screen, blocking** Google-provided UI that updates before the user can continue. Use for **forced** upgrades.
  - Requires the app to be installed from **Play**; you check availability (`AppUpdateManager.appUpdateInfo`), confirm the flow is allowed, start it, and handle the result/lifecycle (download progress, failure, user cancel).
- **Store-link fallback.** When In-App Updates isn't available (not from Play, staged rollout hasn't reached the device, API error), fall back to **opening the Play Store listing** (`market://details?id=...` →

`https://play.google.com/...`). The forced gate must **always** offer a working action.

- **Staged rollout reality.** A new version may not be downloadable yet for a given device (staged rollout / regional). A forced gate must handle "update not available right now" gracefully — show the store link, allow retry, and don't claim an update exists that the device can't get.
- **Never trap the user.** The forced screen must: always have an **Update** action; not loop (don't re-gate immediately after a successful update because of a stale cached policy — re-read `versionCode`); tolerate **offline** (explain, allow retry, don't crash); and ideally allow limited read-only/offline use if the incompatibility is partial (design choice).
- **Security use (Ch 23/26).** A forced upgrade is a **security control**: when a vulnerability is patched, raise the floor to retire exploitable clients. (It is not itself anti-tamper — a modified client can ignore the gate, so the **server must also reject** unsupported versions, Ch 16/23 — the client gate is UX, the server check is enforcement.)

Core insight: **keep the version floor on the server (remote config/endpoint, Ch 41) so you can retire old clients instantly; derive three states (up-to-date / soft dismissible nudge / forced blocking gate) from it, checked proactively at startup/resume and reactively on a `426`/compat signal (Ch 16); deliver updates via Play In-App Updates (flexible for soft, immediate for forced) with an always-available store-link fallback; handle staged rollout, offline, and not-from-Play so the user is never trapped in a loop; and enforce the floor on the server too, since the client gate is UX, not security.**

54.4 High-Level Architecture



Components & ownership

- **Server policy** (remote config/endpoint, Ch 41) owns the floor; **server** also enforces it (`426`).
- `UpdateManager` fetches policy, computes state, and drives the Play flow / store-link fallback.
- **Gate UI** renders soft nudge or forced screen.
- **No-loop/escape** logic ensures the user always has a working path.

Direction: server policy + `426` → state → soft/forced → Play update or store link → updated (re-checked, no loop).

54.5 Detailed Component Design



Component	Responsibility
`VersionPolicy`	server-driven thresholds + message (Ch 41)
`UpdateManager`	evaluate state; start Play flow; store-link fallback; no-loop
`UpdateState`	up-to-date / soft / forced
Gate UI	dismissible nudge vs blocking screen

54.6 End-to-End Data Flow

Startup check → forced upgrade


Startup check → forced upgrade

Reactive 426 mid-session


Reactive 426 mid-session

54.7 Complete Kotlin Implementation

Package: `com.streamcart.appupdate`.

54.7.1 Version policy + state evaluation (server-driven)

```
data class VersionPolicy(                    // from remote config / endpoint (Ch 41)
    val minSupported: Int, val recommendedFloor: Int, val latest: Int, val message: String,
)

sealed interface UpdateState {
    data object UpToDate : UpdateState
    data class SoftUpdate(val policy: VersionPolicy) : UpdateState
    data class ForcedUpgrade(val policy: VersionPolicy) : UpdateState
}

@Singleton
class UpdatePolicyEvaluator @Inject constructor(private val buildInfo: BuildInfo) {
    fun evaluate(policy: VersionPolicy): UpdateState = when {
        buildInfo.versionCode < policy.minSupported -> UpdateState.ForcedUpgrade(policy)   //
blocking
        buildInfo.versionCode < policy.recommendedFloor -> UpdateState.SoftUpdate(policy)  //
dismissible
        else -> UpdateState.UpToDate
    }
}
```

54.7.2 UpdateManager: Play In-App Updates + store fallback

```
@Singleton
class UpdateManager @Inject constructor(
    @ApplicationContext private val ctx: Context,
    private val appUpdateManager: AppUpdateManager,      // Play core
    private val evaluator: UpdatePolicyEvaluator,
    private val configRepo: RemoteConfigRepository,      // Ch 41
) {
    suspend fun currentState(): UpdateState =
        evaluator.evaluate(configRepo.versionPolicy())   // cached; refreshed in background

    /** Soft: flexible (background download, install when ready). */
    fun startFlexible(activity: Activity, info: AppUpdateInfo, launcher:
ActivityResultLauncher<IntentSenderRequest>) {
        if (info.isUpdateTypeAllowed(AppUpdateType.FLEXIBLE))
            appUpdateManager.startUpdateFlowForResult(info, launcher,
                AppUpdateOptions.newBuilder(AppUpdateType.FLEXIBLE).build())
        else openStoreListing()                          // fallback
    }

    /** Forced: immediate (full-screen blocking Play UI). */
    fun startImmediate(activity: Activity, info: AppUpdateInfo, launcher:
ActivityResultLauncher<IntentSenderRequest>) {
        if (info.isUpdateTypeAllowed(AppUpdateType.IMMEDIATE))
            appUpdateManager.startUpdateFlowForResult(info, launcher,
                AppUpdateOptions.newBuilder(AppUpdateType.IMMEDIATE).build())
        else openStoreListing()                          // staged rollout / not from Play ->
always an escape
    }

    fun openStoreListing() {
        val market = Intent(Intent.ACTION_VIEW, Uri.parse("market://details?
id=${ctx.packageName}"))
        val web = Intent(Intent.ACTION_VIEW,
Uri.parse("https://play.google.com/store/apps/details?id=${ctx.packageName}"))
        runCatching { ctx.startActivity(market.addFlags(Intent.FLAG_ACTIVITY_NEW_TASK)) }
            .onFailure { ctx.startActivity(web.addFlags(Intent.FLAG_ACTIVITY_NEW_TASK)) }
    }
}
```

54.7.3 Reactive 426 interceptor (Ch 16/2) → forced state

```
class UpgradeRequiredInterceptor @Inject constructor(
    private val updateState: MutableStateFlow<UpdateState>,   // app-global (Ch 39)
    private val configRepo: RemoteConfigRepository,
) : Interceptor {
    override fun intercept(chain: Interceptor.Chain): Response {
        val response = chain.proceed(chain.request())
        if (response.code == 426) {                           // Upgrade Required (server
enforcement, Ch 23)
            updateState.value = UpdateState.ForcedUpgrade(runBlocking {
configRepo.versionPolicy() })
        }
        return response
    }
}
```

54.7.4 Gate UI: forced (blocking) vs soft (dismissible), no loop

```
@Composable
fun UpdateGate(content: @Composable () -> Unit, vm: UpdateViewModel = hiltViewModel()) {
    val state by vm.state.collectAsStateWithLifecycle()
    when (val s = state) {
        is UpdateState.ForcedUpgrade -> ForcedUpgradeScreen(            // BLOCKS the whole app
            message = s.policy.message,
            onUpdate = { vm.startImmediateOrStore() },                  // always a working
action
            // No dismiss. Offline -> show retry, never crash. After update, re-eval -> no loop.
        )
        is UpdateState.SoftUpdate -> {
            content()                                                   // app usable
            SoftUpdateBanner(onUpdate = { vm.startFlexibleOrStore() }, onDismiss = { vm.snooze()
})
        }
        UpdateState.UpToDate -> content()
    }
}
```

54.7.5 Resume handling (install downloaded flexible update; avoid stuck state)

```
// On resume, if a flexible update finished downloading, prompt to complete; if an immediate
// update was interrupted, resume it (Play requires handling this).
override fun onResume() {
    super.onResume()
    appUpdateManager.appUpdateInfo.addOnSuccessListener { info ->
        if (info.installStatus() == InstallStatus.DOWNLOADED) promptInstall()       // flexible
finished
        if (info.updateAvailability() ==
UpdateAvailability.DEVELOPER_TRIGGERED_UPDATE_IN_PROGRESS)
            updateManager.startImmediate(this, info, launcher)                       // resume
interrupted immediate
    }
}
```

54.7.6 Module structure

```
:core:appupdate  VersionPolicy, UpdatePolicyEvaluator, UpdateManager,
UpgradeRequiredInterceptor, UpdateGate
:core:config     RemoteConfigRepository (Ch 41)  // version policy source
# 426 handling wired into the OkHttp stack (Ch 1/16). Server also enforces floor (Ch 23).
```

54.8 Concurrency and Race Conditions

Scenario	Risk	Handling
Stale cached policy re-gates after update	infinite loop	re-read live `versionCode`; evaluate against fresh policy on resume
426 during many parallel calls	repeated gate triggers	set forced state once (idempotent `MutableStateFlow`)
Flexible download completes in background	stuck "downloaded"	check `installStatus` on resume → prompt install
Immediate update interrupted	stuck mid-update	resume `IN_PROGRESS` on resume (Play requirement)
Config fetch fails at startup	wrong state	use last cached policy (Ch 41); fail open (don't force on no data)
Offline on forced screen	trapped/crash	show retry + store link; tolerate offline

- **No-loop is the subtle bug:** after a successful update the app restarts with a new `versionCode`; if you evaluate against a **stale cached policy** or don't re-read the version, you can re-gate immediately. Always compare the **live** `versionCode` to a freshly evaluated policy on resume.
- **Reactive 426 must be idempotent:** many in-flight requests can each see `426`; set the forced state on a single app-global `StateFlow` (Ch 39) so the gate appears once.

- **Fail open on missing policy:** if the policy can't be fetched (offline, backend down) and there's no cached value, **don't force-gate** on absence of data — that would trap users during a config outage; the server still enforces via `426` when it matters.

54.9 Failure Scenarios and Recovery

Failure	Detection	Response	Outcome
Old client breaks after backend change	support/ `426`	server-driven forced upgrade (Ch 16)	steered to update
Forced gate loops after update	user stuck	re-read live versionCode; fresh policy	no loop
Update not downloadable (staged)	Play API	store-link fallback + retry	recoverable
Not installed from Play	In-App API fails	store-link fallback	works
Offline on forced screen	no network	retry + explain; never crash	tolerated
Config outage force-gates everyone	spike	fail open on missing policy	no mass lockout
Modified client ignores gate	server logs	server rejects unsupported version (Ch 23)	enforced


54.9 Failure Scenarios and Recovery

> **Two failure modes to fear most:** trapping users (loops, offline crashes, config- outage mass-gating) and failing to actually enforce (client gate ignored by a modified app). Fix the first with always-an-escape + fail-open + no-loop; fix the second by enforcing the floor on the **server** — the client gate is UX, not security.

54.10 Scaling the Implementation

- **Level 1.** Server-driven policy (remote config, Ch 41); 3 states; store-link update.
- **Level 2.** Play In-App Updates (flexible soft, immediate forced); resume handling; no-loop.
- **Level 3 — production.** Reactive `426` (Ch 16); staged-rollout/offline/not-from-Play fallbacks; fail-open; server-side enforcement.
- **Level 4 — large.** Per-platform/region policies; phased floors (nudge → force over time); A/B of nudge copy; update-adoption analytics; security-driven emergency floors.
- **Level 5 — enterprise.** Version-support lifecycle governance (deprecation calendar tied to Ch 16 API versions), automated floor bumps on security fixes, adoption-curve dashboards, multi-store support (not just Play).

Avoid overengineering: most apps need a server-driven floor + soft/forced states + Play In-App Updates + store fallback. Don't hardcode min-versions, and don't build a custom updater when In-App Updates + store link suffice.

54.11 Alternative Approaches and Trade-offs

Dimension	Option A	Option B	When
Version floor	Server-driven (remote config/endpoint)	client constant	Server-driven always (reach non-updaters)
Update delivery	Play In-App Updates	store link only	In-App Updates (smooth) + store-link fallback
Forced flow	Immediate (Play blocking)	custom blocking screen + store link	Immediate where available; custom+link fallback
Soft flow	Flexible (background)	just a banner → store	Flexible (seamless); banner for non-Play
Enforcement	Server rejects old versions (426)	client gate only	Server (client gate is UX, bypassable)
Missing policy	Fail open	fail closed (force)	Fail open (avoid outage lockout)

Server-driven floor vs client constant: a hardcoded `MIN_VERSION` in the app can only be changed by shipping a new app — but the users who need to be forced off an old version are precisely those who won't install the new one, so the constant never reaches them. A **server-driven floor** (remote config/endpoint, Ch 41) is changeable instantly and reaches every running client. Always server-drive the policy.

Play In-App Updates vs store link: In-App Updates give a seamless, Google-managed flow (background download for flexible, blocking UI for immediate) and higher update rates — but only for **Play installs** and subject to staged-rollout availability. A plain **store link** always works as a fallback (including non-Play installs). Use In-App Updates as the primary path and the store link as the always-available escape; never ship a forced gate that can *only* use In-App Updates.

Client gate vs server enforcement: the client gate is a **UX** mechanism — a modified or old client can ignore it. Real enforcement (for breaking changes/security) must be on the **server** (reject unsupported versions with `426`, Ch 16/23). Do both: the gate gives users a good experience; the server guarantees incompatible/insecure clients can't transact.

54.12 Security Considerations

- **Forced upgrade as a security control (Ch 23):** when a client vulnerability is patched, raise the server floor to retire exploitable versions — but **enforce on the server** (reject old versions), since a tampered client ignores the gate.
- **Don't leak why in the message:** the forced-upgrade message shown to users shouldn't detail the vulnerability (Ch 28) — "please update to continue" suffices.
- **Validate the policy source:** the version policy comes over authed/trusted config (Ch 41/19) — a MITM that could force a downgrade or spoof a policy is a concern; fetch over TLS/pinning (Ch 23) and don't act on unauthenticated policy.
- **Store-link integrity:** open the official Play listing by package name; don't follow an arbitrary URL from config (open-redirect, Ch 52).
- **No bypass via deep links (Ch 52):** a deep link must not route *past* a forced gate; evaluate the gate before honoring deep-link navigation.

- Client vs backend: the **backend** enforces supported versions and emits `426`; the **client** provides the UX gate and update flow. Enforcement is server-side; convenience is client-side.

54.13 Performance and Resource Optimization

- **Cheap startup check:** use the **cached** policy (Ch 41) at startup (don't block the first frame on a network fetch, Ch 45); refresh in the background.
- **Flexible update downloads in the background** — doesn't interrupt the user; install on a natural restart.
- **Don't re-fetch policy excessively:** remote config caching (Ch 41) + background refresh; evaluate on resume, not continuously.
- **Lightweight gate check** (integer compare) — negligible cost.
- **Avoid over-gating:** too-aggressive soft nudges annoy; rate-limit/snooze.
- **Profiling:** update-adoption rate per version, forced-gate display rate, store-link vs In-App-Update conversion, time-on-old-version distribution.

54.14 Testing Strategy

Policy evaluation is pure logic (easy unit tests); Play flow via its test tracks / fakes.

```
class UpdatePolicyEvaluatorTest {
    private fun eval(installed: Int, min: Int, rec: Int, latest: Int) =
        UpdatePolicyEvaluator(BuildInfo(versionCode = installed)).evaluate(VersionPolicy(min,
rec, latest, ""))
    @Test fun `forced when below minSupported`() =
        assertTrue(eval(110, min = 120, rec = 125, latest = 130) is UpdateState.ForcedUpgrade)
    @Test fun `soft when between recommended and latest`() =
        assertTrue(eval(122, min = 120, rec = 125, latest = 130) is UpdateState.SoftUpdate)
    @Test fun `up to date when at or above recommended`() =
        assertEquals(UpdateState.UpToDate, eval(130, min = 120, rec = 125, latest = 130))
    @Test fun `no loop - fresh version evaluates up to date`() =
        assertEquals(UpdateState.UpToDate, eval(130, 120, 125, 130))   // post-update
}

class UpgradeInterceptorTest {
    @Test fun `426 sets forced state once`() { /* two parallel 426 -> single ForcedUpgrade */ }
}
// Play In-App Updates: use FakeAppUpdateManager (play core testing) to simulate
// available/immediate/flexible, download complete, staged-unavailable -> assert store fallback.
```

What to test: evaluator for all boundaries (forced/soft/up-to-date + no-loop post-update); `426` → forced (idempotent); flexible/immediate start + store fallback when not allowed; resume install-complete + resume-interrupted; fail-open on missing policy; offline on forced screen (retry, no crash). `FakeAppUpdateManager` for Play flows.

54.15 Production Observability

- **Metrics:** version-adoption distribution; forced-gate display + completion rate; soft-nudge show/accept/snooze; store-link vs In-App-Update conversion; `426` rate (old clients hitting the server); update-failure/cancel rate; time-to-adopt after a floor bump.
- **Logs:** `update{state, installed, min, latest, flow, outcome}` (no PII, Ch 28).
- **Debugging:** users stuck → loop (stale policy) / offline / staged-unavailable; low adoption → nudge ineffective / In-App Updates unavailable; mass lockout → failed fail-open; old clients still transacting → server not enforcing `426`.
- **Alerting:** forced-gate spike after a floor change (expected) vs unexpected (config bug); `426` from versions you didn't intend to gate; adoption stall.
- **Dashboards:** version adoption curve per release; floor-bump impact.

54.16 System Design Interview Preparation

> ≥25 questions.

Fundamentals

1. *Why an update strategy?* Old-version users break/are insecure; you must steer/force updates.
2. *Where does the version floor live?* On the **server** (remote config/endpoint, Ch 41) — never a client constant.
3. *Why not a client constant?* Non-updaters never get the build that changes it.
4. *Three states?* Up-to-date / soft (dismissible) / forced (blocking).
5. *Who enforces incompatibility?* The server (`426`, Ch 16); the client gate is UX.

Triggers

6. *Proactive check?* At startup/resume, compare `versionCode` to cached policy.
7. *Reactive signal?* `426 Upgrade Required` mid-session → forced.
8. *Why reactive matters?* Catches sessions predating a floor change.

Delivery

9. *Play In-App Updates flows?* Flexible (background) and immediate (blocking).
10. *Flexible for?* Soft updates.
11. *Immediate for?* Forced upgrades.
12. *Requirement?* Installed from Play.
13. *Fallback?* Open the Play Store listing (always available).

Resilience

14. *No-loop?* Re-read live `versionCode` + fresh policy after update.
15. *Staged rollout unavailable?* Store link + retry; don't claim unavailable update.
16. *Offline on forced screen?* Retry + explain; never crash/trap.

17. *Config outage?* Fail open (don't mass-gate on missing policy).
18. *Interrupted immediate update?* Resume on next launch (Play requirement).

Security

19. *Forced upgrade for security?* Yes — retire vulnerable clients; enforce server-side.
20. *Message content?* Don't leak the vuln (Ch 28).
21. *Policy source trust?* Authed/TLS-pinned config (Ch 23); don't act on spoofable policy.
22. *Deep-link bypass?* Evaluate gate before honoring deep links (Ch 52).

Testing/Production

23. *Test policy?* Pure unit tests at all boundaries + no-loop.
24. *Test Play flows?* `FakeAppUpdateManager`.
25. *Users stuck?* Loop / offline / staged-unavailable.
26. *Old clients still transacting?* Server not enforcing `426`.

Design-change challenges

1. **A backend change breaks clients below v120.** Raise server floor → forced upgrade (Ch 16); server rejects < v120 with `426`.
2. **Forced gate loops after users update.** Re-read live `versionCode` + fresh policy.
3. **Some users aren't on Play.** Store-link fallback.
4. **A security fix must retire old clients fast.** Emergency server floor bump + server enforcement.
5. **A config outage locked everyone out.** Fail open on missing policy.

Mock walkthrough (abridged)

Clarify (soft vs forced, security-driven?, Play-only?) → server-driven policy (Ch 41) + server enforcement (`426` , Ch 16) → 3 states → proactive (startup/resume) + reactive (`426`) triggers → Play In-App Updates (flexible/immediate) + store-link fallback → resilience (no-loop, offline, staged, fail-open) → security (server enforcement, message, policy trust) → observability (adoption, `426`).

54.17 Practical Exercises

1. **Beginner.** Implement `UpdatePolicyEvaluator` from a server-driven policy and render up-to-date/soft/forced states. *Eval:* correct boundaries; forced blocks.
2. **Intermediate.** Add Play In-App Updates (flexible for soft, immediate for forced) with a Play Store-link fallback. *Eval:* flows start; fallback when unavailable.
3. **Advanced.** Add a `426` interceptor that forces the gate mid-session (idempotent) and no-loop logic after update. *Eval:* `426` → forced once; no loop post-update.
4. **Production debugging.** Fix a forced-gate loop (stale cached policy) and an offline crash on the forced screen. *Eval:* no loop; offline tolerated.
5. **System design challenge.** Add fail-open on config outage and server-side version enforcement; build an adoption-curve dashboard. *Eval:* no mass lockout; server rejects old versions; adoption visible.

(Solutions withheld unless requested.)

54.18 Chapter Summary & Reference Sheet

Key decisions: keep the **version floor server-driven** (remote config/endpoint, Ch 41) so you can retire old clients **instantly** (a client constant never reaches non-updaters); derive **three states** — up-to-date / **soft** (dismissible nudge) / **forced** (blocking gate) — checked **proactively** at startup/resume and **reactively** on a `426 Upgrade Required` signal (Ch 16); deliver updates with **Play In-App Updates** (**flexible** for soft background downloads, **immediate** for forced blocking) with an **always-available Play Store-link fallback** (for staged-rollout/not-from-Play); make it **resilient** — **no loop** (re-read live `versionCode` + fresh policy after update), **offline-tolerant** (retry, never crash/trap), and **fail open** on missing policy (no outage lockout); and **enforce the floor on the server** (`426` , Ch 16/23) because the **client gate is UX, not security** (a tampered client ignores it). Use forced upgrades as a **security control** to retire vulnerable clients.

Concepts: server-driven version policy, three update states, proactive/reactive triggers, `426 Upgrade Required` , Play In-App Updates (flexible/immediate), store-link fallback, staged rollout, no-loop, fail-open, server-side enforcement.

Common mistakes: hardcoded min-version (can't reach non-updaters); client-only enforcement (bypassable); forced gate with no escape (In-App-Updates-only); loop after update (stale policy); offline crash on gate; mass lockout on config outage (fail-closed); leaking the vuln in the message; deep-link bypass.

Checklist:

- [ ] server-driven policy (Ch 41)
- [ ] 3 states (up-to-date/soft/forced)
- [ ] startup/resume + `426` triggers
- [ ] Play In-App Updates (flexible/immediate)
- [ ] store-link fallback (always an escape)
- [ ] no-loop (live versionCode + fresh policy)
- [ ] offline tolerant
- [ ] fail open on missing policy
- [ ] server enforces floor (`426` , Ch 16/23)
- [ ] non-leaky message
- [ ] no deep-link bypass.

Key APIs: `AppUpdateManager` / `appUpdateInfo` / `startUpdateFlowForResult` , `AppUpdateType.FLEXIBLE` / `IMMEDIATE` , `AppUpdateOptions` , `InstallStatus` / `UpdateAvailability` , `FakeAppUpdateManager` (test), `market://details?id=` / `https://play.google.com/store/apps/details?id=` , OkHttp `Interceptor` (426, Ch 1/16), remote config (Ch 41).

References:

- In-App Updates: https://developer.android.com/guide/playcore/in-app-updates
- Support in-app updates (Kotlin): https://developer.android.com/guide/playcore/in-app-updates/kotlin-java
- Test in-app updates: https://developer.android.com/guide/playcore/in-app-updates/test
- (composes) Ch 16 API Schema Evolution, Ch 41 Remote Config, Ch 23 Security, Ch 45 Startup, Ch 52 Deep Links

Chapter review (Phase 4)

- **Completeness:** all 18 sections; architecture/class/sequence/flow/failure diagrams; evaluator + UpdateManager (flexible/immediate/store) + 426 interceptor + gate UI + resume code; concurrency (no-loop, idempotent 426, fail-open); failure (trap vs enforcement); 5 levels; server-floor/In-App-Updates/enforcement trade-offs; security (server enforcement, message, policy trust); perf (cached startup check); evaluator + FakeAppUpdateManager tests; observability (adoption, 426); 26 Q&A + 5 challenges. ✅
- **Expand later:** API evolution (Ch 16), remote config (Ch 41), security (Ch 23), integrity (Ch 26).
- **Interview coverage:** exceeds ≥25 bar.