Chapter 86 — A/B Testing & Experimentation

> **Part X — Performance, Observability & Quality** · Complexity: **Standard** (≥25 interview questions)
>
> **Prerequisites:** Ch 40 (feature flags/remote config), Ch 82 (analytics pipeline), Ch 84 (correlation), Ch 28 (privacy), Ch 41 (staged rollout). Pairs with Ch 85 (perf), Ch 83 (crash/guardrails), Ch 72 (recommendations).
>
> **Reference surface in StreamCart:** running **controlled experiments** — assigning users to **variants** (control vs treatment), exposing a change to a **fraction** of traffic, measuring the effect on **metrics** (conversion, retention, latency, Ch 85), and deciding whether to **ship or kill** — built on the same **remote config / feature-flag** plumbing (Ch 40) and **analytics pipeline** (Ch 82), with **consistent assignment**, **guardrail metrics**, and **privacy** (Ch 28).

86.1 Problem Definition and Real-World Context

"Will this change actually help?" is usually unknowable by opinion — a new checkout button, a reordered feed, a different onboarding (Ch 80) may help or hurt, and only a **controlled experiment** tells you. **A/B testing** assigns users to **variants** (A = control / existing, B = treatment / new), exposes the change to a **fraction** of traffic, measures the effect on **target metrics** (conversion, retention, revenue, engagement) and **guardrail metrics** (crash rate Ch 83, latency Ch 85, uninstalls), and lets you **decide with data** whether to **roll out or roll back**. It's built on the **feature-flag/remote-config** system (Ch 40) (which variant to show) and the **analytics pipeline** (Ch 82) (measuring the outcome), with **consistent, random assignment**, **statistical significance**, and **privacy** (Ch 28).

Concretely, teams hit:

- **Shipping on opinion/HiPPO.** Without experiments you ship the highest-paid person's opinion and never know if it helped — or if it **hurt** a metric you didn't watch.
- **Inconsistent assignment.** A user **flickering** between variants (seeing A then B) ruins the experiment and the UX. Assignment must be **deterministic/sticky** per user (hash of a stable id, Ch 40) so a user stays in one variant.
- **No guardrails.** A treatment that lifts clicks but **triples crashes** (Ch 83) or **doubles latency** (Ch 85) is a loss; experiments need **guardrail metrics** that stop a harmful variant (tie into staged rollout/kill switch, Ch 41/40).
- **Measuring the wrong thing / p-hacking.** Picking the metric after seeing results, peeking and stopping early, or ignoring significance leads to false wins. Need a **pre-registered** primary metric, adequate **sample size/power**, and **significance**.
- **Exposure vs assignment.** You must log when a user was **actually exposed** to the variant (saw the change), not just assigned, to measure effect correctly.
- **Built on flags, not a separate system.** Experiments reuse **remote config/feature flags** (Ch 40) for assignment+delivery and the **analytics pipeline** (Ch 82) for measurement — not a bespoke stack.
- **Privacy.** Assignment keys and exposure logs must be **PII-safe** and **consented** (Ch 28/82).

The architecture: **assign** users to variants **deterministically** (hash of a stable id, via remote config/flags, Ch 40) so assignment is **sticky**; **expose** the treatment to a **fraction** of traffic (ramp like staged rollout, Ch 41); **log exposure +**

outcomes through the **analytics pipeline** (Ch 82); **measure** the effect on a **pre-registered primary metric** with **significance/power**, plus **guardrail metrics** (crash Ch 83, latency Ch 85) that can **auto-stop** a harmful variant (Ch 40/41); keep assignment/exposure **PII-safe + consented** (Ch 28); and **decide** ship/kill with data. This chapter is about **learning whether a change helps, safely**.

Three practical use cases

1. **Checkout button experiment (StreamCart).** 50/50 split on a redesigned place-order button (Ch 75); primary metric = checkout conversion; guardrails = crash rate (Ch 83) + checkout latency (Ch 85); sticky per-user; ship if significant lift and guardrails hold.
2. **Feed ranking experiment.** A new recommendation model (Ch 72) vs control, 10% ramp; primary = engagement/retention; guardrail = feed load latency (Ch 85) + reports.
3. **Onboarding experiment.** Two onboarding flows (Ch 80); primary = activation; sticky so a user never sees both; measured via the analytics funnel (Ch 82).

Why this is architectural

Experimentation composes feature flags/remote config (Ch 40), the analytics pipeline (Ch 82), staged rollout/kill switch (Ch 41), guardrails (crash Ch 83, perf Ch 85), and privacy (Ch 28). The decisions — deterministic sticky assignment, fractional exposure, pre-registered metric + significance, guardrails that auto-stop — determine whether experiments produce **trustworthy decisions** rather than noise or harm.

86.2 Requirements Engineering

Functional requirements

ID	Requirement
F1	Assign users to variants deterministically/sticky (hash of stable id, via flags, Ch 40).
F2	Expose treatment to a configurable fraction; ramp like staged rollout (Ch 41).
F3	Log exposure + outcome metrics through the analytics pipeline (Ch 82).
F4	Measure effect on a pre-registered primary metric with significance/power.
F5	Watch guardrail metrics (crash Ch 83, latency Ch 85); auto-stop harmful variants (Ch 40/41).
F6	Keep assignment/exposure PII-safe + consented (Ch 28).

Non-functional requirements

Attribute	Policy
Consistency	Sticky per-user assignment; no flickering.
Trustworthiness	Pre-registered metric; significance; no p-hacking.
Safety	Guardrails + kill switch (Ch 40/41/83).
Privacy	PII-safe keys; consent (Ch 28/82).
Reuse	Built on flags (Ch 40) + analytics (Ch 82), not bespoke.

Scope

- **In scope:** variant assignment (deterministic/sticky hash, via remote config/flags, Ch 40), fractional exposure + ramp (Ch 41), exposure logging, outcome metrics via analytics (Ch 82), primary + guardrail metrics, significance/power/sample-size basics, auto-stop (Ch 40/41/83), PII-safe + consent (Ch 28), ship/kill decision.
- **Out of scope:** flag plumbing (Ch 40), analytics pipeline internals (Ch 82), rollout mechanics (Ch 41), deep statistics (reference only), recommendation models (Ch 72).

Assumptions & constraints

- Remote config/feature-flag system (Ch 40) for assignment+delivery; analytics pipeline (Ch 82) for measurement; staged-rollout/kill-switch (Ch 41/40) for safety. Assignment is **deterministic** (hash of a stable, PII-safe id). Primary metric **pre-registered**; guardrails watched. Consent respected (Ch 28). `minSdk 24`.

86.3 System Design Fundamentals

- **Experiment = controlled comparison.** Split users into **control (A)** and **treatment (B)** (or multiple variants), change **one thing** for treatment, measure the **difference** in a metric. Random assignment makes the groups comparable so the difference is **caused** by the change (causal inference), not correlation.
- **Deterministic, sticky assignment (the key client property, Ch 40).** A user must get the **same variant every time** — **hash a stable id** (an opaque experiment/user id, PII-safe, Ch 28) with the experiment id into a bucket; `bucket < fraction → treatment`. This is **stateless** (no stored assignment needed), **consistent** across launches/devices, and delivered via **remote config/flags** (Ch 40). Flickering between variants ruins both data and UX — stickiness is non-negotiable.
- **Fractional exposure + ramp (Ch 41).** Start the treatment at a **small fraction** (1%, 5%) and **ramp** like a staged rollout (Ch 41) — this limits blast radius and lets **guardrails** catch harm before full exposure. The fraction is a remote-config value (Ch 40) you can change server-side.
- **Exposure logging vs assignment (subtle but important).** Log when a user is **actually exposed** (rendered/experienced the variant), not merely **assigned** — a user assigned to treatment who never reaches the screen shouldn't dilute the measurement. Analyze on **exposed** users (or intention-to-treat consistently); exposure is an analytics event (Ch 82).
- **Primary metric + guardrails (pre-registered).** Decide **before** the experiment: a **primary metric** (the thing you're trying to move — conversion, retention, revenue) and **guardrail metrics** (things that must **not** get

worse — crash rate Ch 83, latency Ch 85, uninstalls, errors). You **ship** only if the primary improves **significantly** and guardrails **hold**; a guardrail breach **auto-stops/kills** the variant (Ch 40/41).

- **Statistical significance, power, sample size (avoid false wins).** A difference could be **noise**; you need **significance** (the effect is unlikely by chance, e.g., $p < 0.05$ or a confidence interval excluding zero) and enough **sample size/power** to detect the effect. **Don't p-hack:** don't pick the metric after the fact, don't **peek-and-stop** early (inflates false positives — use sequential tests or a fixed horizon), don't run many metrics and cherry-pick. Pre-register; decide on the primary.
- **Built on flags + analytics (reuse, Ch 40/82).** Experiments aren't a new system: **assignment/delivery** = remote config/feature flags (Ch 40); **measurement** = the analytics pipeline (Ch 82); **safety** = staged rollout/kill switch (Ch 41/40). The experiment layer adds **buckets, exposure logs, and analysis**.
- **Privacy (Ch 28/82).** The **assignment key** is an **opaque, PII-safe** id (Ch 28); exposure/outcome events follow the **consent** regime (Ch 82). Don't key experiments on PII; don't leak which variant implies sensitive info.
- **Interaction & isolation.** Running many experiments at once can **interact**; use **layers/mutually-exclusive** buckets for conflicting experiments, or accept orthogonal randomization for independent ones.

Core insight: **assign users to variants deterministically and stickily by hashing a stable, PII-safe id with the experiment id (via remote config/feature flags, Ch 40 — so a user never flickers between A and B), expose the treatment to a configurable fraction and ramp it like a staged rollout (Ch 41) to bound blast radius; log actual exposure (not just assignment) and outcomes through the analytics pipeline (Ch 82); decide ship/kill on a pre-registered primary metric with real statistical significance and adequate power (no p-hacking, no peek-and-stop) while guardrail metrics — crash rate (Ch 83), latency (Ch 85), uninstalls — must not regress and auto-stop a harmful variant (Ch 40/41); and keep assignment keys and exposure logs PII-safe and consented (Ch 28) — reusing the flag and analytics infrastructure rather than building a bespoke stack.**

86.4 High-Level Architecture


86.4 High-Level Architecture

Components & ownership

- **Assigner** hashes a stable id → variant (deterministic/sticky), gated by remote config (Ch 40).
- **Exposure logger** records actual exposure via analytics (Ch 82).
- **Analyzer** (backend) measures primary metric + significance; watches **guardrails** (Ch 83/85) → **auto-stop** (Ch 40/41).
- **Decision:** ship/kill. **Privacy:** PII-safe keys + consent (Ch 28).

Direction: stable id → deterministic bucket (flags, Ch 40) → variant → exposure/outcome via analytics (Ch 82) → significance + guardrails → ship/kill.

86.5 Detailed Component Design


86.5 Detailed Component Design

Component	Responsibility
`Experiment`	definition: variants, fraction, primary + guardrail metrics
`Assigner`	deterministic sticky variant from a stable id (Ch 40)
`ExposureLogger`	log actual exposure via analytics, once per user (Ch 82)
`ExperimentConfig`	remote fraction/enabled/killed (Ch 40)
`Analyzer`	significance on primary + guardrail watch → auto-stop (backend, Ch 83/85/41)

86.6 End-to-End Data Flow

Assign → expose → measure → decide



Sticky assignment (no flicker)



86.7 Complete Kotlin Implementation

Package: `com.streamcart.experiments`.

86.7.1 Deterministic, sticky assignment (built on flags, Ch 40)

```
enum class Variant { CONTROL, TREATMENT }

@Singleton
class Assigner @Inject constructor(
    private val config: ExperimentConfig,    // remote config (Ch 40)
    private val ids: StableIdProvider,       // opaque, PII-safe id (Ch 28)
) {
    /** Deterministic + sticky: same user -> same variant every time, no stored state. */
    fun variantFor(experimentId: String): Variant {
        if (config.isKilled(experimentId)) return Variant.CONTROL           // kill switch (Ch
40/41)
        val fraction = config.fraction(experimentId)                         // remote ramp (Ch
41)
        val bucket = bucketOf(ids.stableId(), experimentId)                  // 0..9999
        return if (bucket < (fraction * 10000).toInt()) Variant.TREATMENT else Variant.CONTROL
    }
    private fun bucketOf(stableId: String, experimentId: String): Int {
        val digest = MessageDigest.getInstance("SHA-
256").digest("$experimentId:$stableId".toByteArray())
        val v = ((digest[0].toInt() and 0xFF) shl 8) or (digest[1].toInt() and 0xFF)   // stable
hash
        return v % 10000
    }
}
```

86.7.2 Exposure logging (via analytics, once per user, Ch 82)

```
@Singleton
class ExposureLogger @Inject constructor(private val analytics: Analytics) {   // Ch 82
    private val logged = Collections.synchronizedSet(mutableSetOf<String>())    // once per
(exp,variant) per session
    /** Log ONLY when the variant is actually shown - exposure, not just assignment. */
    fun logExposure(experimentId: String, variant: Variant) {
        if (logged.add("$experimentId:$variant")) {
            analytics.track(AnalyticsEvent.Exposure(                          // PII-safe (Ch
28)
                experimentId = experimentId, variant = variant.name))          // opaque; via
pipeline (Ch 82)
        }
    }
}
```

86.7.3 Using an experiment in UI

```
@Composable
fun CheckoutButton(assigner: Assigner, exposure: ExposureLogger, onPlace: () -> Unit) {
    val variant = remember { assigner.variantFor("checkout_button_v2") }        // sticky (Ch 40)
    LaunchedEffect(variant) { exposure.logExposure("checkout_button_v2", variant) }  // exposure (Ch 82)
    when (variant) {
        Variant.TREATMENT -> NewPlaceOrderButton(onPlace)                        // B: new design
        Variant.CONTROL   -> ClassicPlaceOrderButton(onPlace)                    // A: existing
    }
    // Outcome (conversion) logged by the checkout flow (Ch 75) via analytics (Ch 82).
}
```

86.7.4 Remote config: fraction, ramp, kill (Ch 40)

```
@Singleton
class ExperimentConfig @Inject constructor(private val remoteConfig: RemoteConfig) {   // Ch 40
    fun fraction(expId: String): Double = remoteConfig.getDouble("exp_${expId}_fraction", 0.0)
// ramp (Ch 41)
    fun isKilled(expId: String): Boolean = remoteConfig.getBoolean("exp_${expId}_killed", false)
// kill (Ch 40)
    // Backend ramps fraction 0.01 -> 0.05 -> 0.5 -> 1.0 while guardrails hold (Ch 41);
    // sets killed=true if a guardrail breaches (crash Ch 83, latency Ch 85).
}
```

86.7.5 Analysis (backend-side, documented)

```
// Analysis is backend (on the analytics warehouse, Ch 82):
//  - PRIMARY: effect = metric(treatment_exposed) - metric(control_exposed); significance (CI excludes 0 / p<0.05)
//  - POWER/SAMPLE SIZE: ensure enough exposed users to detect the expected effect (pre-registered)
//  - GUARDRAILS: crash rate (Ch 83), latency p95 (Ch 85), uninstalls MUST NOT regress -> else auto-kill (Ch 41)
//  - NO p-hacking: pre-registered primary metric; fixed horizon or sequential test (no naive peeking)
//  - DECISION: ship (ramp to 100%) if significant lift + guardrails hold; else kill (Ch 40)
```

86.7.6 Module structure

```
:core:experiments  Assigner (deterministic, Ch 40), ExposureLogger (Ch 82), ExperimentConfig (Ch 40)
# Delivery/assignment reuse flags (Ch 40); measurement reuses analytics (Ch 82);
# safety reuses staged rollout/kill (Ch 41); guardrails -> crash (Ch 83) + perf (Ch 85).
# Analysis/significance -> backend warehouse. PII-safe keys -> Ch 28.
```

86.8 Concurrency and Race Conditions

Scenario	Risk	Handling
User flickers A ↔ B	ruined data + UX	deterministic sticky hash (Ch 40)
Exposure logged many times	inflated counts	once-per-user/session dedupe
Assignment on PII	privacy leak	opaque stable id (Ch 28)
Peeking/early stop	false wins	pre-registered horizon / sequential test
Guardrail breach unnoticed	user harm	guardrails + auto-kill (Ch 83/85/41)
Many experiments interact	confounded	layers / mutual exclusion
Fraction change mid-flight	re-bucket	deterministic hash keeps assignment stable

- **Deterministic hashing** gives stickiness **without stored state** and is **stable across devices** (same stable id, Ch 40) — raising the fraction only **adds** users to treatment, never moves existing ones out (monotonic bucketing).
- **Exposure dedupe** ensures you count **users**, not impressions, consistently.
- **Guardrails + auto-kill** make experiments **safe** — a harmful treatment is stopped via remote config (Ch 40/41) before wide exposure.

86.9 Failure Scenarios and Recovery

Failure	Detection	Response	Outcome
Treatment harms a metric	guardrail breach	auto-kill via remote config (Ch 40/41)	contained
User sees both variants	flicker reports	deterministic sticky assignment (Ch 40)	consistent
False win (noise)	low power/peeking	significance + power + pre-registration	trustworthy
Exposure double-counted	inflated metric	once-per-user dedupe	accurate
PII in assignment key	privacy audit	opaque id (Ch 28)	safe
Experiments interact	confounded results	layers / mutual exclusion	isolated
Shipped a loser	post-hoc metrics	guardrails + decision gate	prevented


86.9 Failure Scenarios and Recovery

> **Make assignment sticky, measure a pre-registered metric with real significance, and let guardrails auto-kill harm.** The failure modes of experimentation are flickering (sticky hashing fixes it), false wins (significance + power + pre-registration fix it), and shipping a harmful treatment (guardrails + kill switch fix it). Reuse flags (Ch 40) and analytics (Ch 82) rather than building bespoke, and keep keys PII-safe (Ch 28).

86.10 Scaling the Implementation

- **Level 1.** A single flag-gated A/B via remote config (Ch 40); outcome via analytics (Ch 82); eyeball the result.
- **Level 2.** Deterministic sticky assignment; exposure logging; pre-registered primary + guardrails (Ch 83/85); fractional ramp (Ch 41).
- **Level 3 — production.** Significance/power analysis (backend); auto-kill on guardrail breach (Ch 40/41); PII-safe keys + consent (Ch 28).
- **Level 4 — platform.** Experimentation platform: many concurrent experiments with **layers/mutual exclusion**, metric libraries, automated analysis dashboards, sequential testing, holdbacks.
- **Level 5 — enterprise.** Org-wide experimentation culture: metric governance, CUPED/ variance reduction, interleaving (Ch 72), long-term holdouts, guardrail SLOs, experiment review boards.

Avoid overengineering: a flag-gated, deterministic A/B with a pre-registered primary metric, guardrails, and a significance check covers most needs. Don't build a platform for one test; don't ship on opinion; don't skip guardrails or stickiness.

86.11 Alternative Approaches and Trade-offs

Dimension	Option A	Option B	When
Assignment	Deterministic hash (sticky, Ch 40)	stored/random per-call	Hash (sticky, stateless)
Delivery	Remote config/flags (Ch 40)	bespoke system	Reuse flags
Measurement	Analytics pipeline (Ch 82)	custom logging	Reuse analytics
Analysis	Significance + power	eyeball/averages	Significance (trustworthy)
Safety	Guardrails + auto-kill (Ch 40/41)	none	Guardrails always
Exposure	Log actual exposure	assignment-only	Exposure (correct effect)
Stopping	Pre-registered/sequential	peek-and-stop	Pre-registered (no p-hacking)

Deterministic hash vs stored assignment: hashing a stable id gives **sticky, stateless, cross-device** assignment (same user → same variant, raising the fraction never re-buckets existing users) — no storage, no sync. **Stored** assignment needs persistence/sync and can drift. Prefer **deterministic hashing** (Ch 40).

Experiment vs ship-on-opinion: shipping without an experiment means you **never know** if the change helped — or if it **hurt** an unwatched metric (crashes, latency). A controlled experiment with a **pre-registered primary metric,**

significance, and guardrails gives a **trustworthy, safe** decision. Experiment for anything that matters.

Reuse (flags + analytics) vs bespoke: building a separate experimentation stack duplicates **assignment** (flags, Ch 40), **measurement** (analytics, Ch 82), and **safety** (rollout/kill, Ch 41). Reusing them means experiments inherit **reliability, consent, and kill switches** for free; the experiment layer only adds **buckets, exposure, analysis**.

86.12 Security & Privacy Considerations

- **PII-safe assignment key (Ch 28):** hash an **opaque, stable** id (not email/phone); the bucket reveals nothing personal. Don't key experiments on PII.
- **Consent (Ch 28/82):** exposure/outcome events follow the same **consent** regime as analytics; opted-out users limited to essential/anonymous.
- **No sensitive-variant leakage:** don't let "which variant" imply sensitive info (e.g., an experiment targeting a protected group) — avoid discriminatory targeting.
- **Guardrails include safety:** crash (Ch 83), ANR, security errors as guardrails — a variant that degrades safety is killed (Ch 40/41).
- **Kill switch (Ch 40/41):** a harmful or abused experiment is **remotely killable** without an app update.
- Client vs backend: the **client** assigns deterministically and logs PII-safe exposure; the **backend** analyzes significance, watches guardrails, and controls fraction/kill (Ch 40) — neither stores PII in experiment keys.

86.13 Performance and Resource Optimization

- **Assignment is cheap** — a single hash; **no network** (fraction comes from already-fetched remote config, Ch 40). Compute once per screen (`remember`).
- **Exposure logging is batched** via the analytics pipeline (Ch 82) — once per user/session, not per frame.
- **No extra storage** — deterministic hashing needs no stored assignment.
- **Guardrails reuse existing metrics** (crash Ch 83, perf Ch 85) — no new capture.
- **Ramp bounds cost/risk** — small fraction first (Ch 41).
- **Profiling:** assignment cost (negligible), exposure event volume, remote-config fetch (Ch 40), analysis cost (backend).

86.14 Testing Strategy

Assignment determinism, fraction gating, and exposure dedupe are unit-testable; significance is validated on real data.

```
class AssignerTest {
    @Test fun `assignment is deterministic and sticky`() {
        val v1 = assigner.variantFor("exp_checkout"); val v2 =
assigner.variantFor("exp_checkout")
        assertEquals(v1, v2)   // same user -> same variant, every call (Ch 40)
    }
    @Test fun `fraction gates treatment`() {
        config.setFraction("exp_checkout", 0.0); assertEquals(Variant.CONTROL,
assigner.variantFor("exp_checkout"))
        config.setFraction("exp_checkout", 1.0); assertEquals(Variant.TREATMENT,
assigner.variantFor("exp_checkout"))
    }
    @Test fun `killed experiment forces control`() {
        config.kill("exp_checkout"); assertEquals(Variant.CONTROL,
assigner.variantFor("exp_checkout"))   // Ch 40/41
    }
}

class ExposureLoggerTest {
    @Test fun `exposure logged once per user`() {
        exposure.logExposure("exp", Variant.TREATMENT); exposure.logExposure("exp",
Variant.TREATMENT)
        assertEquals(1, analytics.exposureCount("exp"))   // dedupe (Ch 82)
    }
}
// Significance/power validated on the analytics warehouse with real exposed-user data (Ch 82).
```

What to test: deterministic sticky assignment (Ch 40); fraction/kill gating (Ch 40/41); exposure dedupe (once per user, Ch 82); PII-safe key; guardrail wiring (crash Ch 83, latency Ch 85). Significance/power validated on real data; ramp via staged rollout (Ch 41).

86.15 Production Observability

- **Metrics:** per-experiment **exposure counts** (treatment/control), **primary metric** by variant with significance/CI, **guardrail metrics** (crash rate Ch 83, latency p95 Ch 85, uninstalls) by variant, **fraction/ramp** state (Ch 40/41), kill events.
- **Logs:** exposure/outcome events in the analytics pipeline (Ch 82) — **PII-safe** (Ch 28).
- **Debugging:** flicker → check deterministic assignment (Ch 40); false win → check power/ significance/peeking; no effect → check exposure logging (did users actually see it?); guardrail breach → which metric, auto-kill fired? (Ch 40/41).
- **Alerting: guardrail breach** on any live experiment (crash/latency spike in treatment → auto-kill, Ch 40/41/83/85); experiment running underpowered/too long.
- **Dashboards:** per-experiment primary vs guardrail by variant; ramp state; significance; decision (ship/kill).

86.16 System Design Interview Preparation

> ≥25 questions.

Fundamentals

1. *What is A/B testing?* Controlled comparison of control vs treatment on a metric.
2. *Why experiment?* Causal evidence a change helps — not opinion.
3. *Assignment?* Deterministic hash of a stable id → sticky variant (Ch 40).
4. *Why sticky?* No flickering; consistent data + UX.
5. *Built on?* Flags/remote config (Ch 40) + analytics (Ch 82).

Assignment

6. *Deterministic how?* Hash(stableId + expId) → bucket < fraction.
7. *Stateless?* Yes — no stored assignment; stable across devices.
8. *Raise fraction?* Monotonic — adds users, doesn't re-bucket.
9. *PII?* Opaque stable id, not PII (Ch 28).

Exposure/metrics

10. *Exposure vs assignment?* Log when actually shown, not just assigned.
11. *Primary metric?* Pre-registered; the thing you move.
12. *Guardrails?* Must-not-regress: crash (Ch 83), latency (Ch 85), uninstalls.
13. *Where measured?* Analytics pipeline (Ch 82).

Statistics

14. *Significance?* Effect unlikely by chance ($p<0.05$ / CI excludes 0).
15. *Power/sample size?* Enough exposed users to detect the effect.
16. *p-hacking?* Pre-register; no peek-and-stop; no metric cherry-picking.
17. *Peeking?* Inflates false positives; fixed horizon or sequential test.

Safety

18. *Guardrail breach?* Auto-kill via remote config (Ch 40/41).
19. *Ramp?* Small fraction first (Ch 41), like staged rollout.
20. *Kill switch?* Remote, no app update (Ch 40).

Edge cases

21. *Many experiments?* Layers / mutual exclusion to avoid interaction.
22. *Flickering?* Deterministic sticky hash (Ch 40).
23. *Privacy?* Opaque keys + consent (Ch 28/82).

Testing/Production

24. *Test assignment?* Determinism + fraction/kill gating.
25. *No effect seen?* Check exposure logging + power.

26. *Ship decision?* Significant lift + guardrails hold.

Design-change challenges

1. **Run a checkout button A/B.** Deterministic 50/50, primary = conversion, guardrails = crash+latency (Ch 83/85), auto-kill.
2. **Prevent flickering.** Deterministic sticky hash of a stable id (Ch 40).
3. **Avoid a false win.** Pre-register primary, ensure power, no peeking.
4. **Safely ramp a risky model (Ch 72).** Fractional ramp + guardrails + auto-kill (Ch 41).
5. **Run many experiments without interference.** Layers / mutual exclusion.

Mock walkthrough (abridged)

Clarify (hypothesis, primary metric, guardrails, traffic?) → deterministic sticky assignment (hash stable id, Ch 40) → fractional exposure + ramp (Ch 41) → log exposure + outcome via analytics (Ch 82) → measure primary with significance + power (pre-registered, no p-hacking) → guardrails (crash Ch 83, latency Ch 85) auto-kill (Ch 40/41) → PII-safe + consent (Ch 28) → decide ship/kill → observability (per-variant metrics).

86.17 Practical Exercises

1. **Beginner.** Flag-gate a UI change as a deterministic 50/50 A/B (Ch 40) and log exposure + an outcome via analytics (Ch 82). *Eval:* sticky assignment; exposure logged.
2. **Intermediate.** Add a pre-registered primary metric and guardrails (crash Ch 83, latency Ch 85); ramp the fraction (Ch 41). *Eval:* guardrails wired; ramp works.
3. **Advanced.** Implement auto-kill on guardrail breach via remote config (Ch 40/41) and document a significance/power plan. *Eval:* auto-kill fires; power considered.
4. **Production debugging.** Investigate a "no effect" result — verify exposure logging and power; investigate flickering — verify deterministic assignment. *Eval:* root cause found.
5. **System design challenge.** Design multi-experiment layers/mutual exclusion with per- experiment guardrails and automated analysis. *Eval:* isolation; trustworthy decisions.

(Solutions withheld unless requested.)

86.18 Chapter Summary & Reference Sheet

Key decisions: run **controlled experiments** by **assigning users to variants deterministically and stickily** — hash a **stable, PII-safe id** with the experiment id (via **remote config/feature flags**, Ch 40) so a user gets the **same variant every time** (no flickering), with **no stored state** and **cross-device** consistency; **expose** the treatment to a **configurable fraction** and **ramp** it like a **staged rollout** (Ch 41) to bound blast radius; **log actual exposure** (not just assignment) and outcomes through the **analytics pipeline** (Ch 82); **decide ship/kill on a pre-registered primary metric** with real **statistical significance** and adequate **power** (**no p-hacking, no peek-and-stop**), while **guardrail metrics** — **crash rate** (Ch 83), **latency** (Ch 85), uninstalls — **must not regress** and **auto-stop/kill** a harmful variant via remote config (Ch 40/41); and keep **assignment keys and exposure logs PII-safe and consented** (Ch 28) — **reusing** the flag (Ch 40) and analytics (Ch 82) infrastructure rather than building a bespoke stack.

Concepts: control vs treatment, deterministic sticky assignment (hash, Ch 40), fractional exposure + ramp (Ch 41), exposure vs assignment logging, primary + guardrail metrics, significance/power/sample-size, no p-hacking/peeking, auto-kill (Ch 40/41/83/85), reuse of flags

- analytics (Ch 40/82), PII-safe keys + consent (Ch 28).

Common mistakes: shipping on opinion; non-sticky assignment (flickering); logging assignment instead of exposure; no guardrails (harmful treatment ships); p-hacking/peek-and- stop/underpowered (false wins); keying on PII; building a bespoke stack instead of reusing flags

- analytics; no kill switch.

Checklist:

- ☐ deterministic sticky assignment (hash stable id, Ch 40)
- ☐ fractional exposure + ramp (Ch 41)
- ☐ log actual exposure + outcome via analytics (Ch 82)
- ☐ pre-registered primary metric
- ☐ significance + power (no p-hacking/peeking)
- ☐ guardrails (crash Ch 83, latency Ch 85) auto-kill (Ch 40/41)
- ☐ PII-safe keys + consent (Ch 28)
- ☐ reuse flags + analytics
- ☐ layers for many experiments
- ☐ ship/kill decision gate.

Key APIs/concepts: remote config / feature flags (assignment + fraction + kill, Ch 40), SHA-256 bucketing (deterministic sticky), analytics pipeline (exposure + outcomes, Ch 82), staged rollout (ramp, Ch 41), guardrail metrics (crash Ch 83, perf Ch 85), significance/power (backend analysis), consent/PII-safe keys (Ch 28).

References:

- Firebase Remote Config + A/B Testing: https://firebase.google.com/docs/ab-testing
- Trustworthy Online Controlled Experiments (Kohavi et al.) — the standard reference
- Statistical significance / power — experimentation literature
- (composes) Ch 40 Feature Flags/Remote Config, Ch 82 Analytics, Ch 41 Staged Rollout, Ch 83 Crash, Ch 85 Perf, Ch 28 Privacy, Ch 72 Recommendations

Chapter review (Phase 4)

- **Completeness:** all 18 sections; architecture/class/sequence/sticky/failure diagrams; assigner + exposure + remote-config code; concurrency (stickiness, dedupe, auto-kill); failure (sticky+significance+guardrails principle); 5 levels; hash-vs-stored, experiment-vs- opinion, reuse trade-offs; security (PII-safe keys, consent, no discriminatory targeting); perf (cheap assignment, batched exposure); assigner + exposure tests; observability (per- variant + guardrails); 26 Q&A + 5 challenges. ✅
- **Expand later:** flags/remote config (Ch 40), analytics (Ch 82), staged rollout (Ch 41), guardrails (crash Ch 83, perf Ch 85).
- **Interview coverage:** exceeds ≥25 bar.