

Makefile

```
# contest root Makefile; each problem dir's Makefile is just `include
  ../Makefile`
# in a problem dir: `make x` builds ./x from x.cpp (make's built-in
  %: %.cpp rule)
```

```
ROOT := $(dir $(abspath $(lastword $(MAKEFILE_LIST))))
```

```
CXX      = g++-13
CXXFLAGS = -std=c++20 -DLOCAL -Og -Wall -Wextra -D_GLIBCXX_DEBUG -
  fsanitize=address,undefined
CXXFLAGS += -I$(ROOT)headers
```

template.cpp

3cd55b

```
#include <bits/stdc++.h>
#ifdef LOCAL
#include "debug.h"
#else
#define debug(...) ((void)0)
#endif
```

```
#define all(x) begin(x), end(x)
#define sz(x) (int)(x).size()
#define pb push_back
#define fi first
#define se second
```

```
using namespace std;
```

```
using ll = long long;
using dd = double;
using ld = long double;
using pii = pair<int,int>;
using pll = pair<ll,ll>;
using vi = vector<int>;
using vll = vector<ll>;
```

```
void solve() {
```

```
}
```

```
signed main() {
  ios::sync_with_stdio(false);
  cin.tie(nullptr);
  int t = 1;
  // cin >> t;
  while (t--) {
    solve();
  }
  return 0;
}
```

headers/debug.h

635cef

```
#pragma once
#include <bits/stdc++.h>
using namespace std;
```

```
void pr(auto &&x) {
  int f = 0;
```

```
  if constexpr (ranges::range<decltype(x)> && !is_convertible_v<
    decltype(x), string_view>) {
    cerr << '{';
    for (auto &&i : x) cerr << (f++ ? ", " : ""), pr(i);
    cerr << '}';
  } else if constexpr (requires { get<0>(x); }) {
    cerr << '(';
    apply([&](auto &&...a) { ((cerr << (f++ ? ", " : ""), pr(a)),
      ...); }, x);
    cerr << ')';
  } else cerr << x;
}
```

```
#define debug(...) cerr << __LINE__ << ": [" << #__VA_ARGS__ << "]" ==
  , [](auto &&...a) { ((cerr << ' ', pr(a)), ...); cerr << '\n';
  })(__VA_ARGS__)
```