

miniRUEDI Symposium 18–20 Nov 2025

Eawag, Überlandstrasse 133, 8600 Dübendorf, Switzerland

Tentative/Draft Program

Tuesday, 18 Nov 2025

9:00 – 9:30	Coffee and snacks
9:30 – 9:40	Welcome
9:40 – 10:00	Introduction
10:00 – 10:40	Presentations
10:40 – 11:10	Break
11:10 – 12:10	Presentations
12:10 – 14:00	Lunch at Eawag
14:00 – 15:00	Presentations
15:00 – 15:30	Break
15:30 – 16:30	Presentations

Wednesday, 19 Nov 2025

9:00 – 9:30	Coffee and snacks
9:30 – 10:30	Presentations
10:30 – 11:00	Break
11:00 – 12:00	Presentations
12:00 – 14:00	Lunch at Eawag
14:00 – 15:00	Presentations
15:00 – 15:30	Break
15:30 – 16:30	Presentations
18:00	Group dinner (open end)

Thursday, 20 Nov 2025

9:00 – 9:30	Coffee and snacks
9:30 – 10:30	Presentations
10:30 – 11:00	Break
11:00 – 11:40	Presentations
12:00 – 14:00	Lunch at Eawag
14:00 – 15:00	miniRUEDI hands-on, lab tour

XY Nov 2025, HH:MM–HH:MM

Continuous miniRUEDI measurements reveal gas–seismic interactions at Lavey-les-Bains

Sébastien Giroud, Matthias Brennwald, Rolf Kipfer

Eawag

ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT
TEXT. ABSTRACT TEXT. ABSTRACT TEXT.

XY Nov 2025, HH:MM–HH:MM

Dissolved Gas Monitoring at the Bedretto Underground Laboratory: Responses to Seismic Stimulation

**Alexandra Lightfoot, Matthias Brennwald, Valentin Gischig, Alba Zappone,
Rolf Kipfer, Stefan Wiemer**

SED ETH Zürich

Gas Monitoring at the Bedretto Underground Laboratory: Responses to Seismic Stimulation In hydraulic stimulation experiments, such as those used in seismic and geothermal energy studies, monitoring dissolved reactive and noble gases in groundwater can provide key insights into fluid transport and redistribution. While tracers added to injection water reveal specific flow paths, dissolved gas monitoring in general captures a broader picture of how fluids are mobilised or redirected under pressure. At the Bedretto Underground Laboratory for Geosciences and Geoenergy (BULGG), we tested the geochemical response during an experiment designed to trigger a controlled magnitude-zero earthquake. High-pressure water (up to 20 MPa) was injected into borehole ST1, with krypton added as a tracer. A nearby borehole (ST2), 44 m away and discharging continuously, was equipped with a miniRuedi to measure dissolved He, Ar, Kr, N₂, O₂, and CO₂ in real time, complemented by parallel radon monitoring. This setup enabled us to track both immediate gas responses to pressure and delayed tracer migration. Dissolved gas signals at ST2 revealed a clear response once injection began. N₂ and Ar increased in terms of partial pressure, while He decreased, showing that injection resulted in mobilised or redirected younger, less radiogenic fluids toward ST2 well before the Kr tracer arrived. Radon activity increased only after tracer breakthrough, consistent with fracture opening and fluid movement under stress. These findings highlight dissolved gas monitoring as a sensitive tool for probing the interplay between stress, fractures, and fluids, particularly in the context of hydraulic stimulation.

XY Nov 2025, HH:MM–HH:MM

Investigating gasgeochemical production during the preparatory phase of dynamic brittle failure in Rotondo granite in the laboratory

**Paul Selvadurai, Claudio Madonna, Clement Roques, Hanna Ventura,
Matthias Brennwald, Rolf Kipfler, Benoit, Valley, Alexandra Lightfoot,
Laurent Marguet**

ETH Zurich

Laboratory geochemistry studies enhance our understanding of earthquake precursors. Controlled experimental conditions allow researchers to observe how microcracks, fluid flow, and mineral reactions influence geochemical signals, including gas emissions and isotope distributions. These experiments can identify specific geochemical changes, such as the release of radon or noble gases, associated with rock fracturing. Such insights are crucial for developing indicators of large events while calibrating geochemical signals, establishing links between these signals, stress states, and damage levels within rocks.

This study investigates the use of helium, argon, and CO₂ as real-time geochemical tracers for brittle deformation in crystalline rocks, focusing on Rotondo granite from the Bedretto Laboratory. These gases, stored in mineral lattices or fluid inclusions, are released during microstructural damage; however, their behavior during progressive rock failure remains poorly understood. Uniaxial compression experiments monitored gas variability with a miniRuedi quadrupole mass spectrometer, complemented by spatial strain measurements using Distributed Fibre Optic Strain (DFOS) sensing, acoustic emission (AE) monitoring, and post-mortem X-ray computed tomography (XRCT) of fracture networks. The experimental design aims to identify distinct deformation stages, from crack initiation to macroscopic failure, and link these to transient noble gas signals. Preliminary results reveal stage-specific fluctuations in helium and CO₂, supporting the hypothesis that gas emissions reflect structural damage evolution. This research advances the integration of mechanical and geochemical monitoring in rock mechanics, with important implications for underground stability assessment and early warning systems in geotechnical and seismic environments.

XY Nov 2025, HH:MM–HH:MM

A (very) portable Gas Equilibrium Membrane Sampling System (GEMSS)

Yama Tomonaga, Oliver S. Schilling

Eawag / University of Basel

The miniRUEDI has proved to be a valuable tool to monitor continuously and in real time the gas dynamics in environmental systems. While mid- and long-term observations imply generally fixed installations with a relatively constrained effort in terms of logistics, the spatial screening of the gas composition in surface waters and groundwater requires the transport of miniRUEDI with the respective GE-MIMS (and a power source, e.g. a generator) to the different sampling locations. This can be sometimes problematic, as the instrument weight of about 30 kg (not including pumps, generator ...) makes it "portable" only to a certain extent. To address this limitation, and to simultaneously improve on the long standing limitation of samples taken in copper tubes not being pre-screenable on the miniRUEDI prior to time-consuming noble gas isotope analyses, we developed a small portable Gas Equilibrium Sampling System (GEMSS aka "James") that can be taken to the field easily and allows for a sufficient amount of gas to be sampled for multiple analyses on a single sample. The system uses the same concept of gas equilibrium of the conventional GE-MIMS. However, instead of functioning as an inlet for miniRUEDI measurements, James allows acquisition of gas samples for subsequent analyses in reusable containers. James is relatively light and fits in a backpack, it not only allows replicate measurements on a miniRUEDI, but the respective samples can further be used also for other types of analyses (e.g., conventional noble gas isotope analyses on magnetic sector mass spectrometers).

XY Nov 2025, HH:MM–HH:MM

New tool for in-situ gas measurements in low flow porous media

C. Marion, C. Ebi, S. Bloem, M.S. Brennwald, R. Kipfer

Eawag

Dummy dummy to be improved and checked by co-authors: Gases, including noble gases, are powerful tracers in environmental science, widely used to study groundwater flow dynamics and surface–subsurface water interactions (Brennwald et al. 2022, Blanc et al. 2024, Schilling 2017, Schilling 2021, Peel 2022 & 2023). However, most applications focus on high-flow systems (L/min to L/s), while in-situ gas measurements in low-flow porous media (L/h), such as soil unsaturated and saturated zones or plant tissues, remain technically challenging—despite their critical role in the global hydrological cycle. We present a robust, field-deployable gas probe for long-term, in-situ gas monitoring in low-permeability or low-flow environments. The device consists of a gas-tight, 3D-printed body with an integrated pressure sensor and gas-permeable membranes that allow diffusion of target gases into the probe’s headspace for subsequent sampling and analysis. Originally developed for in-vivo gas monitoring in tree xylem (Marion et al., 2024), this method enables non-destructive, high-resolution measurements applicable to a variety of porous media, including soil, sediment, rock, and biological tissue.

**XY Nov 2025, HH:MM–HH:MM
?TBD?**

Diana Burghardt, Paul Fremdling
TU Dresden

TBD

XY Nov 2025, HH:MM–HH:MM
Noble gas laboratory installation

Benjamin Lefeuvre, Anne Battani

LFCR - UPPA

ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT
TEXT. ABSTRACT TEXT. ABSTRACT TEXT.

XY Nov 2025, HH:MM–HH:MM

Origin of fluid emissions along crustal to lithospheric faults in an extensional setting, Betic Cordillera, Spain

B  renice Cateland, Anne Battani, Matthais Brennwald, Benjamin Lefeuvre, Nicolas E. Beaudoin, Fr  d  ric Mouthereau, Rolando Burga, Jose Benavente, Magali Pujol

Universit   de Pau et des pays de l'Adour

The Betic Cordillera (SE Spain) has experienced a complex geodynamic history involving crustal thinning related to slab retreat. This deep lithospheric dynamic was accompanied by alkaline to calc-alkaline volcanism and the exhumation of metamorphic domes. These processes feed an active fluid system, the respective contributions of which remain poorly constrained. However, understanding and quantifying these deep fluid circulations has major implications for geothermal exploration and natural gas migration. Several crustal to lithospheric-scale faults in the Internal Betics have accommodated most of the deformation. These active structures (Lorca earthquake, Mw 5.2) are associated with significant hydrothermalism, as indicated by water temperatures reaching up to 65   C, and may act as preferential pathways for fluid and heat migration. We sampled fluids (water and gas when bubbles were present) from 14 thermal springs with temperatures ranging from 15 to 65   C. Gas species were measured in the field using a portable mass spectrometer (MiniRUEDI) along these strike-slip faults. The C  diz-Alicante Fault releases fluids rich in N₂ (86–96%), with CO₂ contents between 1 and 5%, and O₂ between 0.5 and 10%. Along the Alpujarras Fault, CO₂ dominates (63–91%) with lower amounts of N₂ (5–28%). The lithospheric Carboneras Fault emits fluids rich in N₂ (91%), with low proportions of O₂ (3%) and CO₂ (3%). Alhama de Murcia, the most active fault of the system, mainly releases CO₂ (52%) and N₂ (43%). This result helps us in discussing fluid origin in this extensive context.

XY Nov 2025, HH:MM–HH:MM
TBD

Stephanie Musy

University of Basel

I'll let you know as soon as I know, but it will be something about our continuous monitoring in Japan (+ some unsolicited but very funny jokes)

XY Nov 2025, HH:MM–HH:MM

Noble gas concentrations in a brazilian semiarid aquifer

Natália de Souza Arruda, Hannah Eckert, Bertram Graf von Reventlow, Edith Engelhardt, Jürgen Sültenfuß, Didier Gastmans, Werner Aeschbach

Heidelberg Universitat

He3/He4 as tracers to understand the groundwater flow model; Paleoclimate evidence; Excess Air; Sedimentary aquifer system.

. Keywords:

XY Nov 2025, HH:MM–HH:MM

Zimbabwe-Headwater Catchment Response to Extreme Rainfall Activities-Meeting on sampling of hydrological extreme events

Webster Gumindoga

University of Zimbabwe

Extreme rainfall events are becoming increasingly frequent across Zimbabwe, yet their effects on headwater catchment hydrology remain poorly quantified. Understanding rainfall–runoff–groundwater interactions under such events is essential for water resources planning, particularly in convective rainfall-dominated systems. This study assessed the hydrological and isotopic response of three representative headwater catchments—Domboshava (Mazowe), Marondera (Manyame), and the University of Zimbabwe (Gwebi)—during the 2023/2024 wet season. Stable isotopes of oxygen ($\delta^{18}\text{O}$) and hydrogen ($\delta^2\text{H}$) were analysed in rainfall, surface water, and groundwater, while Radon-222 (^{222}Rn) was used as a tracer of subsurface flow dynamics. Sampling was conducted at event and intra-event scales, with rainfall collected up to three times daily and groundwater monitored through logging wells. Early-season rainfall at the University of Zimbabwe site exhibited isotopic enrichment ($\delta^{18}\text{O} = 3.06\text{‰}$; $\delta^2\text{H} = 17.48\text{‰}$) and low d-excess (-7‰), indicating subcloud evaporation and limited recharge potential. Intra-event sampling revealed “ Λ -shaped” isotopic profiles, reflecting the temporal variability within convective storm systems. Distinct isotopic signatures were observed among rainfall, surface water, and groundwater, underscoring episodic recharge patterns. Variability in ^{222}Rn concentrations indicated contrasting subsurface flow paths and groundwater residence times across sites. The study highlights the heterogeneity of recharge processes in Zimbabwean headwater catchments and the influence of convective rainfall on water partitioning. Data limitations due to manual sampling and equipment gaps remain key challenges. Future work will focus on improved monitoring networks, recharge zone mapping, and long-term isotope-hydrology integration for water resource resilience under extreme rainfall conditions. Keywords: Stable isotopes, Convective rainfall, Groundwater recharge, Headwater catchment, Radon-222, Zimbabwe.

XY Nov 2025, HH:MM–HH:MM

Multi-Tracer Insights into Urban Catchment Dynamics and Wetland Support

Welham, A., van Rooyen, J., Watson, A., Chow, R., Roychoudhury, A.

Eawag

This contribution presents a multi-tracer study of an urbanized catchment in South Africa, combining isotopes ($\delta^{18}\text{O}$, $\delta^2\text{H}$), tritium, major ions, and dissolved natural gases to resolve interactions between rainwater, rivers, groundwater, and surface water transfer schemes. The results highlight how event-driven recharge, longer-residence groundwater, and managed surface flows jointly shape estuarine wetland resilience under climatic and anthropogenic pressures. (Will send the full abstract later today)

XY Nov 2025, HH:MM–HH:MM

Seasonality of Excess Air Signatures Under Varying Flow Conditions in a Sub-Alpine Fractured Bedrock Aquifer

Christoph E. West, Nicholas E. Thiros, Werner Aeschbach, W. Payton Gardner

Institute of Environmental Physics Heidelberg

We report on a tracer study to constrain groundwater dynamics in an alpine groundwater system near Crested Butte (Colorado, USA), dominated by snowmelt patterns. The hydrograph in this area, underlain by fractured shale, shows two flow periods: a base-flow period (BP) lasting from late summer to early spring, where no recharge occurs and the water level is 3-4 m below land surface; and a recharge period (RP) starting in late spring caused by snowmelt, leading to a rapid rise in water level by 1.5 m, which then declines until late summer. Dissolved noble gases were sampled at different times from a 10 m deep bedrock well at the bottom of a hillslope transect close to the East River. We observe different DeltaNe signatures during both flow periods: positive DeltaNe during RP and negative DeltaNe during BP. Our preliminary results suggest a link to (1) the hydrostatic pressure and (2) prevalent CO₂, N₂, and CH₄ subsurface production caused by bedrock weathering. Lower hydrostatic pressure during BP results in exsolution of oversaturated gases, which may be enhanced by continuous subsurface gas production. At higher hydrostatic pressure during RP, the positive DeltaNe from recharge may prevail. Our results highlight the complexity and seasonality of groundwater dynamics in snowmelt driven mountainous fractured bedrock aquifers, furthered by additional processes like subsurface gas production.

XY Nov 2025, HH:MM–HH:MM

On the hunt for freshwater under the oceanfloor (preliminary)

**Paul Moser Röggla, Alizè Longeau, Israela Musan, Alan Seltzer, David
Bekaert, Rolf Kipfer (preliminary)**

Eawag

Freshened Offshore Groundwater off the Coast of New England Mini Ruedi for dissolved gases in submarine aquifer (Preliminary)

XY Nov 2025, HH:MM–HH:MM

Impact river work entangled with gas data

Théo Blanc, Friederike Currle, Morgan Peel ...etc... Brunner Roki Schilling

Universiy of Neuchatel / Eawag

Entangle the travel time and mixing ratios from freshly infiltrating river water into groundwater. Use environmental gas tracers miniRuedi and Rad 7. Binary mixing models coupled with excess air model. The travel times change drastically because of river-work and high discharge event.

XY Nov 2025, HH:MM–HH:MM

Year-Long miniRUEDI Gas Time Series Reveal Shutdown-Driven Excess Air and Water-Quality Impacts

**Jared van Rooyen, Yama Tomonaga, Matthias S. Brennwald, Rolf Kipfer,
Oliver S. Schilling**

Eawag

Managed aquifer recharge (MAR) operations can unintentionally modulate subsurface gas dynamics, with consequences for redox conditions and groundwater quality. In this study, we deploy a portable mass spectrometer (miniRUEDI) in an observation well at the Hardwald MAR scheme near Basel, Switzerland, and acquire continuous noble- and reactive-gas records (He, Ar, Kr, N₂, O₂, CO₂) over a one-year period. The instrument enabled unattended, on-site measurements with percent-level precision and high temporal resolution, well-suited to capture transient events. During the study, MAR operations ceased eight times for periods ranging from hours to several days. Each cease produced a potential characteristic multiphase gas response: (i) rapid shifts in dissolved gas ratios consistent with bubble entrapment and dissolution upon re-wetting, i.e., formation of “excess air”; (ii) step-changes in O₂ and N₂ that propagated on operational time scales; and (iii) knock-on effects on redox-sensitive species (CO₂, CH₄) indicative of short-term biogeochemical reorganization. By combining noble-gas diagnostics of excess air with reactive-gas trends, we separate physical recharge effects from biogeochemical responses and quantify how shutdowns alter effective recharge signatures and residence-time proxies. These findings highlight portable mass spectrometry as a process-control tool for MAR, linking operational decisions to subsurface gas dynamics and water-quality outcomes in near-real time. Our results generalize established concepts of excess-air formation in porous media to the operational rhythms of MAR and provide actionable guidance for minimizing adverse water-quality swings during start/stop cycles.

XY Nov 2025, HH:MM–HH:MM

Noble gases – suitable tracers to optimize the productivity of a managed aquifer system?

JAKOB HELBING ET AL

AFFILIATIONS

The Hardhof groundwater field is essential for a secure drinking water supply in the city of Zurich. The city's urban infrastructure surrounds the groundwater field and thus limits its local extension. To increase the natural groundwater pumping capacity and guarantee safe drinking water supply at any time, the groundwater field is artificially managed. Riverbank-filtered Limmat water is pumped across the field and injected into the ground along the most vulnerable side towards heavy traffic infrastructure. To determine the necessary amount of water injected into the ground, a sophisticated real-time hydrological numerical model is employed. For an optimal performance, this model needs to be calibrated and evaluated. One possibility to do so is identifying real flow paths with tracer experiments and comparing these results with the output of the numerical model. In a groundwater protection zone however, nonhazardous tracers are vital. The groundwater field Hardhof offers a possibility to test the assumption, whether noble gases can be used as tracers in large scale managed aquifer recharge (MAR) systems. Approximately 100 boreholes within the groundwater field can be used both as injection points and measurement locations for noble-gas tracers. Therefore, different setups of distance and spread can be well tested. In our presentation, we will discuss experimental design and first estimations of this project.

XY Nov 2025, HH:MM–HH:MM

Noble gases as artificial tracers for routine hydrogeological investigations

Morgan PEEL, Kai SOLANKI, Daniel HUNKELER, Philip BRUNNER, Rolf KIPFER

Eawag

Noble gases are increasingly adopted as artificial tracers for hydro(geo)logical studies, thanks to advances in portable, high-resolution dissolved gas measurement technologies [1-3]. Their inert, non-toxic, and invisible nature makes them ideal for sensitive environments, such as rivers and drinking water catchment areas, where maintaining water quality and appearance is essential. The application of gases in aqueous environments poses unique challenges compared to traditional tracers, as potential degassing needs to be accounted for, and ideally avoided, during tracer injection. We present a straightforward method for preparing and injecting tracer solutions with accurately controlled dissolved gas concentrations, whilst avoiding tracer loss. A two-step degassing-pure gas saturation approach enables rapid preparation of high-concentration tracer solutions using readily available materials. We applied this method in a riverbank filtration setting to perform well-to-well tracer tests using helium-4 (He-4) and krypton-84 (Kr-84). Known quantities of both tracers were injected into observation wells upstream of a pumping well. A portable mass spectrometer ("miniRUEDI" GE-MIMS [3]) was used for continuous monitoring in the pumping well. Breakthrough curves of He-4 and Kr-84 enabled precise determination of groundwater flow velocities, travel times, and tracer recovery. These findings illustrate how noble gases complement traditional tracer methods in hydrogeological investigations. The method is adaptable to other gases (e.g., Ne, Kr, Xe, light hydrocarbons), significantly expanding the range of tracers available in groundwater management contexts. 1 : Brennwald et al., 2022, Front. Water (4) 2 : Blanc et al., 2024, Wat. Res. (254) 3 : Brennwald et al., 2016, Env. Sci. Techn. (50)

XY Nov 2025, HH:MM–HH:MM

Tracking CO₂ injection to an aquifer for CCS in Iceland

Matthias S. Brennwald, Jonas Simon Junker, Chuan Wang, Rolf Kipfer, Anne Obermann, Martin Voigt, and Alba Zappone

Eawag

Mineral sequestration of CO₂ in basalt aquifers is a promising pathway for permanent carbon storage. Within the DemoUpStorage R&D project, CO₂ was dissolved in saline groundwater and co-injected with helium as an inert tracer into a deep basalt aquifer at a pilot injection site near Helguvik, Iceland. We tested a combination of two novel geochemical and geophysical tools to monitor the subsurface CO₂ dynamics. Real-time, on-site monitoring of dissolved gases was conducted over one year using a gas-equilibrium membrane-inlet mass spectrometer (GE-MIMS). Electrical resistivity tomography (ERT) was used to track changes in aquifer resistivity before and after injection. GE-MIMS measurements revealed a clear increase in He concentrations downstream of the injection point, confirming fluid transport. However, no corresponding CO₂ increase was observed, indicating substantial CO₂ retardation relative to the fluid transport. No anomalies in He or CO₂ were detected in the overlying freshwater aquifer, indicating minimal upward migration. ERT data showed localized resistivity decreases suggesting basalt dissolution near the injection borehole. Together, GE-MIMS and ERT provided complementary, cost-effective insights into CO₂ transport, reaction, and storage processes in the basalt aquifer. These tools enhance monitoring and assessment capabilities, supporting the development of safe and effective geological CO₂ storage.

XY Nov 2025, HH:MM–HH:MM

Photosynthesis and productivity rates in the Eastern Tropical Pacific Ocean over the 2023-2025 El Niño cycle

Hedy M. Aardema, Hans A. Slagter, Lena Heins, Ralf Schiebel, Gerald H. Haug

AFFILIATIONS

DRAFT The El Niño-Southern Oscillation (ENSO) is a natural climate variability with strong fluctuations in the ocean environment that impact biota and productivity. This provides a natural laboratory for testing the response of productivity to rapid ocean warming. We conducted 4 expeditions in the Eastern Tropical Pacific to study the impact of this climatic variability on phytoplankton photophysiology and productivity. On the S/Y Eugen Seibold the underway set-up includes a LabSTAF active fluorometer (Chelsea, UK) and miniRUEDI mass spectrometer (Gasometrix, Switzerland) to measure photophysiological rates and net community productivity rates, respectively.

XY Nov 2025, HH:MM–HH:MM

Vermifiltration gas emissions and mass balances

Kayla Coppens

Eawag / University of Geneva

The miniRUEDI was used with a static flux chamber to quantify CO₂ and CH₄ emissions from 6 laboratory-scale vermifilters treating blackwater and brownwater at varying hydraulic loading rates. The gas emissions were further used to explore the impact of wastewater type and hydraulic loading on nitrogen and carbon mass balances.

XY Nov 2025, HH:MM–HH:MM

Evaluating the effects of multiple variable on the dissolution of CO₂

Mohammed Alshareef

University of Oxford

In a tube setup we simulate the injection of CO₂ through a column of water in order to assess the affects of bubble size and flux on the dossolution of CO₂. A review of the of data collected by the miniRUEDI through the headspace within the column is then used to identify the signature of CO₂ leakage.

**XY Nov 2025, HH:MM–HH:MM
TBD**

Alan Seltzer

University College Dublin

Not yet sure - either something about in-situ depth profile measurements in a stratified pond, or preliminary IODP exp 501 results, or volcanic gas measurements in Costa Rica or Eifel, Germany

XY Nov 2025, HH:MM–HH:MM
ABSTRACT TITLE

David Bekaert

CRPG

ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT
TEXT. ABSTRACT TEXT. ABSTRACT TEXT.

XY Nov 2025, HH:MM–HH:MM
ABSTRACT TITLE

Nicolette Bugher and Charles Harvey

AFFILIATIONS

ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT
TEXT. ABSTRACT TEXT. ABSTRACT TEXT.

XY Nov 2025, HH:MM–HH:MM

ABSTRACT TITLE

PRESENTING AUTORS

AFFILIATIONS

ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT
TEXT. ABSTRACT TEXT. ABSTRACT TEXT.

XY Nov 2025, HH:MM–HH:MM
ABSTRACT TITLE

Wil Mace

Universtiy of Utah

ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT TEXT. ABSTRACT
TEXT. ABSTRACT TEXT. ABSTRACT TEXT.

**XY Nov 2025, HH:MM–HH:MM
?TBD?**

Natalia Andrea Montoya Arévalo

Eawag

TBD