Name of Student: Minisha Singh	**PRN: 25070122292**
Semester: III	**Year : AY 2026-27**
Subject: Programming with Java	
ASSIGNMENT No : 4	
TITLE : Wrapper Classes in Java	

Problem Statement

Develop a Java application demonstrating the use of wrapper classes for conversion between primitive data types and objects, and performing basic operations on wrapped values.

Learning Objectives

To perform conversion between primitive data types and wrapper objects using Java wrapper classes.

Programme

```
public class WrapperDemo {


   public static void main(String args[]) {


      int a = 25;

      Integer objA = Integer.valueOf(a);

      System.out.println("Primitive to Object (Boxing): " + objA);


      Integer objB = 40;

      int b = objB.intValue();

      System.out.println("Object to Primitive (Unboxing): " + b);


      Integer objC = 15;
```

```
int c = objC;
System.out.println("Autoboxing/Autounboxing: " + c);

String str1 = "50";
int num1 = Integer.parseInt(str1);
System.out.println("String to int: " + num1);

String str2 = "12.75";
double num2 = Double.parseDouble(str2);
System.out.println("String to double: " + num2);

int num3 = 100;
String str3 = Integer.toString(num3);
System.out.println("int to String: " + str3);

Integer x = 10;
Integer y = 20;
int sum = x + y;
System.out.println("Sum using wrapper objects: " + sum);

Double p = 5.5;
Double q = 4.5;
double product = p * q;
System.out.println("Product using wrapper objects: " + product);

System.out.println("Max int value: " + Integer.MAX_VALUE);
System.out.println("Min int value: " + Integer.MIN_VALUE);
```

```
        Character ch = 'A';
        System.out.println("Is Letter: " + Character.isLetter(ch));
        System.out.println("Is Digit: " + Character.isDigit(ch));
    }
}
```

Output

```
Primitive to Object (Boxing): 25
Object to Primitive (Unboxing): 40
Autoboxing/Autounboxing: 15
String to int: 50
String to double: 12.75
int to String: 100
Sum using wrapper objects: 30
Product using wrapper objects: 24.75
Max int value: 2147483647
Min int value: -2147483648
Is Letter: true
Is Digit: false

=== Code Execution Successful ===
```

Conclusion

This program demonstrates the use of wrapper classes in Java for converting between primitive data types and objects. It shows boxing and unboxing (both manual and automatic), conversion between Strings and primitives using `parseInt()`, `parseDouble()`, and `toString()`, and basic arithmetic operations performed on wrapper objects. It also highlights useful wrapper class features like `MAX_VALUE`, `MIN_VALUE`, and character-checking methods such as `isLetter()` and `isDigit()`.