

# The `polyfit` Package for Quad-precision Orthogonal Polynomial Least Squares

Mark Hays

<https://github.com/minmus-9>

September 26, 2021

## Abstract

In this note I present the Python2, Python3, and C `polyfit` package that implements quad-precision [2, 6] least-squares polynomial fitting using orthogonal polynomials [5, 7, 8, 9]. Pure Python and C versions are provided; they are slower than the traditional approach (primarily due to being quad-precision), but are numerically more stable and accurate [1, 3, 10] than the traditional approach. A listing of the source code for the 250 SLOC Python reference implementation is included in appendix B. A much faster C version also ships with this package; there is a Python `ctypes`-based interface called `cpolyfit` that integrates this fast version into Python. Both Python interfaces support Python 2.7 and 3.6+.

## 1 TL;DR Quick Start

First, some rules of thumb:

- For the best results, always scale the  $x_i$  values to be  $O(1)$ . If this is not possible, it is best to use `polyfit` and not worry about  $x$  scaling.
- If you have to perform a higher order fit, it is best to use `polyfit`; however, your luck will run out sooner or later. Do not fear a 10<sup>th</sup> fit with `polyfit`.
- Although `polyfit` is slower than `numpy` by a factor of 2–4, it produces more accurate results.

This package consists of 3 modules:

- The 250 SLOC Python reference implementation in `polyfit.py`
- The C implementation for `libpolyfit.so` contained in `polyfit.c` and `polyfit.h`
- The `cpolyfit.py` Python `ctypes` interface to `libpolyfit.so`. This interface is identical to the one provided by the reference implementation except that it uses `array.array` objects instead of `float` objects.

Unlike `polyfit.py`, the C and `ctypes` APIs do not have any inline comments. The C version exactly follows the reference implementation and the comments in the reference implementation also apply to the C version. The `ctypes` version almost exclusively consists of glue code to `libpolyfit.so` and isn't interesting from an algorithmic viewpoint.

The full source code for the reference implementation, `polyfit.py`, accompanies this file and is also included in appendix B.

The `examples/` directory contains the following:

- `ex1.py` is the `polyfit.py` demo listed below
- `ex2.c` demonstrates the C language version of `polyfit` and is listed below
- `ex3.py` is a benchmark of `cpolyfit.py` versus a naïve but faster `numpy` least squares fit using Cholesky decomposition [4]
- `ex4.py` demonstrates the use of `cpolyfit.py`

The rest of this section contains the listings for `ex1.py` and `ex2.c` to get you going. Both examples do the same thing. The next section contains the `pydoc` and `polyfit.h` API documentation.

The following `demo()` function is a copy of `examples/ex1.py` and exercises the full `polyfit` API.

```
1  #!/usr/bin/env python3
2
3  "example usage of the polyfit api"
4
5  ## pylint: disable=invalid-name,bad-whitespace
6
7  import math
8  import sys
9
10 sys.path.insert(0, "..")
11
12 from polyfit import PolyfitPlan \
13     ## pylint: disable=wrong-import-position
14
15 def flist(l):
16     if not isinstance(l, list):
17         l = [l]
18     return " ".join("%.18e" % x for x in l)
19
20 def demo():
21     "demo of the api"
22     ## pylint: disable=unnecessary-comprehension
23
24     ## poly coefficients to fit, highest degree first
25     cv = [2, 1, -1, math.pi]
26     #cv = [1, -2, 1]
27
28     ## evaluate the polynomial above using horner's method
29     def pv(x):
30         "evaluate using cv"
31         r = 0.
32         for c in cv:
33             r *= x
34             r += c
35         return r
36
37     ## define the x and y values for the fit
```

```

38     N = 10000
39     xv = [x for x in range(N)]
40     yv = [pv(x) for x in xv]
41
42     ## weights:
43     ##     uniform to minimize the max residual
44     wv = [1. for _ in xv]
45
46     ##     relative to minimize the relative residual
47     ##     note that y is nonzero for this example
48     #wv = [y ** -2. for y in yv]
49
50     ## perform the fit
51     D = len(cv) - 1
52     plan = PolyfitPlan(D, xv, wv)
53     fit = plan.fit(yv)
54     ev = fit.evaluator()
55
56     ## print the fit stats
57     deg = plan.maxdeg()
58     print("maxdeg", deg)
59     print("points", plan.npoints())
60
61     ## print per-degree rms errors
62     print("erms ", flist(fit.rms_errors()))
63
64     ## print a few values
65     for i in range(4):
66         print("value %.1f %s" % (xv[i], flist(ev(xv[i], nder=-1))))
67
68     ## print value and all derivatives for all degrees
69     for i in range(D + 1):
70         print("deg %d %s" % (i, flist(ev(xv[0], deg=i, nder=-1))))
71
72     ## print coefficients for all degrees about (x - xv[0])
73     for i in range(D + 1):
74         print("coefs %d %s" % (i, flist(ev.coefs(xv[0], i))))
75
76     ## coefs halfway through
77     print("coefs ", flist(ev.coefs(xv[N >> 1], deg)))
78
79 if __name__ == "__main__":
80     demo()
81
82 ## EOF

```

---

Following is the C example `ex2.c` that corresponds to the Python `ex1.py`

```

1  /*****
2   * ex2.c - polyfit demo
3   */
4
5  #include <math.h>
6  #include <stdio.h>
7  #include <sys/time.h>
8

```

```

 9  #include "polyfit.h"
10
11  #ifndef M_PI
12  #define M_PI 0
13  #define USE_ACOS
14  #endif
15
16  #define N 10000
17  #define D 3
18  double xv[N], yv[N], wv[N];
19
20  /* poly coefficients to fit, highest degree first */
21  double cv[D + 1] = { 2, 1, -1, M_PI };
22
23  void init() {
24      double y;
25      int i, j;
26
27  #ifndef USE_ACOS
28      cv[D] = acos(-1);
29  #endif
30      for (i = 0; i < N; i++) {
31
32          /* evaluate the poly to fit using horner's method */
33          for (y = 0, j = 0; j <= D; j++) {
34              y *= i;
35              y += cv[j];
36          }
37          /* define xv[], yv[], and wv[] for the fit */
38          xv[i] = i;
39          yv[i] = y;
40  #if 1
41          wv[i] = 1;
42  #else
43          /* minimize relative residual */
44          wv[i] = 1. / (y * y); /* y != 0 for this example poly */
45  #endif
46      }
47  }
48
49  int main(int argc, char *argv[]) {
50      void *plan, *fit, *ev;
51      int i, j, n;
52      double coefs[D + 1], d[D + 1];
53      const double *t;
54
55      /* fill in xv, yv, and, wv */
56      init();
57
58      /* create the fit plan */
59      if ((plan = polyfit_plan(D, xv, wv, N)) == NULL) {
60          perror("polyfit_plan");
61          return 1;
62      }
63
64      /* compute the fit */

```

```

65     if ((fit = polyfit_fit(plan, yv)) == NULL) {
66         perror("polyfit_fit");
67         return 1;
68     }
69
70     /* make an evaluator */
71     if ((ev = polyfit_evaluator(fit)) == NULL) {
72         perror("polyfit_evaluator");
73         return 1;
74     }
75
76     /* print fit stats */
77     if ((n = polyfit_maxdeg(plan)) < 0) {
78         perror("polyfit_maxdeg");
79         return 1;
80     }
81     printf("maxdeg %d\n", n);
82     if ((n = polyfit_npoints(plan)) < 0) {
83         perror("polyfit_npoints");
84         return 1;
85     }
86     printf("points %d\n", n);
87
88     /* print per-degree rms errors */
89     if ((t = polyfit_rms_errs(fit, NULL)) == NULL) {
90         perror("polyfit_rms_errs");
91         return 1;
92     }
93     printf("erms  ");
94     for (i = 0; i <= D; i++) {
95         printf(" %.18e", t[i]);
96     }
97     printf("\n");
98
99     /* print a few values */
100    for (i = 0; i < 4; i++) {
101        if (polyfit_eval(ev, xv[i], D, d, D) < 0) {
102            perror("polyfit_eval");
103            return 1;
104        }
105        printf("value  %.1f", xv[i]);
106        for (j = 0; j <= D; j++) {
107            printf(" %.18e", d[j]);
108        }
109        printf("\n");
110    }
111
112    /* print value and all derivatives for all degrees */
113    for (i = 0; i <= D; i++) {
114        if (polyfit_eval(ev, xv[0], i, d, -1) < 0) {
115            perror("polyfit_eval");
116            return 1;
117        }
118        printf("deg    %d", i);
119        for (j = 0; j <= i; j++) {
120            printf(" %.18e", d[j]);

```

```

121     }
122     printf("\n");
123 }
124
125 /* print coefficients for all degrees about (x - xv[0]) */
126 for (i = 0; i <= D; i++) {
127     if (polyfit_coefs(ev, xv[0], i, coefs) < 0) {
128         perror("polyfit_coefs");
129         return 1;
130     }
131     printf("coefs  %d", i);
132     for (j = 0; j <= i; j++) {
133         printf(" %.18e", coefs[j]);
134     }
135     printf("\n");
136 }
137
138 /* coefs halfway through */
139 if (polyfit_coefs(ev, xv[N>>1], D, coefs) < 0) {
140     perror("polyfit_coefs");
141     return 1;
142 }
143 printf("coefs ");
144 for (i = 0; i <= D; i++) {
145     printf(" %.18e", coefs[i]);
146 }
147 printf("\n");
148
149 /* free the fit objects */
150 polyfit_free(ev);
151 polyfit_free(fit);
152 polyfit_free(plan);
153 return 0;
154 }
155
156 /* EOF */

```

## 2 API Documentation

Following is the pydoc documentation for the package's polyfit module.

### NAME

polyfit - quad precision orthogonal polynomial least squares fitting

### CLASSES

```

__builtin__.object
    PolyfitEvaluator
    PolyfitFit
    PolyfitPlan

```

```

class PolyfitEvaluator(__builtin__.object)
|   returned by PolyfitFit.evaluator(). this object evaluates
|   the fit polynomial and its derivatives, and also returns
|   its coefficients in powers of (x - x0) for given x0.
|

```

```

| Methods defined here:
|
| __call__(self, x, deg=-1, nder=0)
|     given a point x, a least squares fit degree deg,
|     and a desired number of derivatives to compute nder,
|     calculate and return the value of the polynomial and
|     any requested derivatives.
|
|     if deg is negative, use maxdeg instead. if nder is
|     negative, use the final value of deg; otherwise, compute
|     nder derivatives of the least squares polynomial of
|     degree deg.
|
|     returns a list whose first element is the value of the
|     least squares polynomial of degree deg at x. subsequent
|     elements are the requested derivatives. if zero
|     derivatives are requested, the scalar function value is
|     returned.
|
| __init__(self, doeval, docofs)
|
| coefs(self, x0, deg=-1)
|     return the coefficients of the fit polynomial of degree
|     deg about (x - x0). if deg is negative, use maxdeg
|     instead.
|
class PolyfitFit(__builtin__.object)
|     orthogonal polynomial fitter returned by PolyfitPlan.fit()
|
| Methods defined here:
|
| __init__(self, plan, yv)
|
| evaluator(self)
|     return a PolyfitEvaluator for this fit.
|
| residuals(self)
|     return the list of residuals for the maxdeg fit.
|
| rms_errors(self)
|     return a list of rms errors, one per fit degree. use them
|     to detect overfitting.
|
class PolyfitPlan(__builtin__.object)
|     orthogonal polynomial least squares planning class. you must
|     create one of these prior to fitting; it can be reused for
|     multiple fits of the same xv[] and wv[].
|
| Methods defined here:
|
| __init__(self, maxdeg, xv, wv)
|     given x values in xv[] and positive weights in wv[],
|     make a plan to perform least squares fitting up to
|     degree maxdeg.
|
|     this is code for "compute everything need to calculate

```

```

|         an expansion in xv- and wv-specific orthogonal
|         polynomials".
|
|     fit(self, yv)
|         given a set of y values in yv[], compute all least
|         squares fits to yv[] up to degree maxdeg. returns
|         a PolyfitFit object.
|
|     maxdeg(self)
|         return the maximum fit degree
|
|     npoints(self)
|         return the number of fit points

```

#### FUNCTIONS

```

polyfit_coefs(plan, ll_fit, x0=0.0, deg=-1)
    given a plan, a set of expansion coefficients generated
    by polyfit_fit, a center point x0, and a least squares
    fit degree, return the coefficients of powers of (x - x0)
    with the highest powers first. if deg is negative (the
    default), use maxdeg instead.

polyfit_eval(plan, a, x, deg=-1, nder=0)
    given a plan, a fit data object returned by
    polyfit_fit, a point x, a least squares fit degree deg,
    and a desired number of derivatives to compute nder,
    calculate and return the value of the polynomial and
    any requested derivatives.

    if deg is negative, use maxdeg instead. if nder is
    negative, use the final value of deg; otherwise, compute
    ndeg derivatives of the least squares polynomial of
    degree deg.

    returns a list whose first element is the value of the
    least squares polynomial of degree deg at x. subsequent
    elements are the requested derivatives. if zero
    derivatives are requested, the scalar function value is
    returned.

polyfit_fit(plan, yv)
    given a previously generated plan and a set of y values
    in yv[], compute all least squares fits to yv[] up to
    degree maxdeg.

    returns (resids, rms_errors, evaluator, coef_evaluator)
    where resids are the fit residuals at each point,
    rms_errors is a vector of rms fit errors for each possible
    degree, evaluator is a function to evaluate the fit
    polynomial, and coef_evaluator is a function to generate
    polynomial coefficients for the standard x_k basis.

polyfit_maxdeg(plan)
    return the maximum possible fit degree

polyfit_npoints(plan)

```



```

    return the number of data points being fit

polyfit_plan(maxdeg, xv, wv)
    given x values in xv[] and positive weights in wv[],
    make a plan to perform least squares fitting up to
    degree maxdeg.

    returns a plan object than can be json-serialized.

    this is code for "compute everything need to calculate
    an expansion in xv- and wv-specific orthogonal
    polynomials".

```

DATA

```
__all__ = ['PolyfitPlan', 'PolyfitFit', 'PolyfitEvaluator', 'polyfit_p...']
```

---

Following is the polyfit.h C API header.

```

1  /*****
2  * polyfit.h - quad-precision orthogonal polynomial least squares
3  */
4
5  #ifndef polyfit_h__
6  #define polyfit_h__
7
8  #ifdef __cplusplus
9  extern "C" {
10 #endif
11
12 /*****
13 * given x values in xv[] and positive weights in wv[],
14 * make a plan to perform least squares fitting up to
15 * degree maxdeg and return a plan object. returns NULL
16 * and sets errno on error.
17 */
18 extern void *polyfit_plan(
19     const int maxdeg,
20     const double * const xv,
21     const double * const wv,
22     const int npoints
23 );
24
25 /*****
26 * given a set of y values in yv[], compute all least
27 * squares fits to yv[] up to degree maxdeg and return
28 * a fit object. returns NULL and sets errno on error.
29 */
30 extern void *polyfit_fit(
31     const void * const plan,
32     const double * const yv
33 );
34
35 /*****
36 * given a fit, return an evaluator that can (a) compute the
37 * fit polynomial and its derivatives and (b) can compute
38 * coefficients of the polynomial about a given point x0.

```

```

39  * returns NULL and sets errno on error.
40  */
41  extern void *polyfit_evaluator(
42      const void * const fit
43  );
44
45  /*****
46   * given a point x, a least squares fit degree degree,
47   * and a desired number of derivatives to compute nderiv,
48   * calculate and return the value of the polynomial and
49   * any requested derivatives.
50   *
51   * if degree is negative, use maxdeg instead. if nderiv is
52   * negative, use the final value of deg; otherwise, compute
53   * nderiv derivatives of the least squares polynomial of
54   * degree deg.
55   *
56   * the derivatives array contains the polynomial value first,
57   * followed by any requested derivatives.
58   *
59   * returns 0 on success. on failure returns -1 and sets errno:
60   *   EINVAL - evaluator is not an evaluator.
61   *           - derivatives is NULL
62   */
63  extern int polyfit_eval(
64      void * const evaluator,
65      const double x,
66      const int degree,
67      double * const derivatives,
68      const int nderiv
69  );
70
71  /*****
72   * return the coefficients of the fit polynomial of degree
73   * degree about (x - x0). if degree is negative, use maxdeg
74   * instead.
75   *
76   * returns 0 on success. on failure returns -1 and sets errno:
77   *   EINVAL - evaluator is not an evaluator.
78   *           - coefs is NULL
79   */
80  extern int polyfit_coefs(
81      void * const evaluator,
82      const double x0,
83      const int degree,
84      double * const coefs
85  );
86
87  /*****
88   * return the maximum fit degree
89   *
90   * on failure returns -1 and sets errno:
91   *   EINVAL - plan object is not recognized
92   */
93  extern int polyfit_maxdeg(
94      const void * const plan

```

```

95 );
96
97 /*****
98  * return the number of fit points
99  *
100 * on failure returns -1 and sets errno:
101 *   EINVAL - plan object is not recognized
102 */
103 extern int polyfit_npoints(
104     const void * const plan
105 );
106
107 /*****
108  * return the list of residuals for the maxdeg fit.
109  *
110 * returns 0 on success. on failure returns -1 and sets errno:
111 *   EINVAL - fit is not a fit.
112 */
113 extern double *polyfit_resids(
114     const void * const fit,
115     double * const resids
116 );
117
118 /*****
119  * return a list of rms errors, one per fit degree. use them
120  * to detect overfitting.
121  *
122 * returns 0 on success. on failure returns -1 and sets errno:
123 *   EINVAL - fit is not a fit.
124 */
125 extern double *polyfit_rms_errs(
126     const void * const fit,
127     double * const errs
128 );
129
130 /*****
131  * free a plan, fit, or evaluator object
132  *
133 * returns 0 on success. on failure returns -1 and sets errno:
134 *   EINVAL - unrecognized object type.
135 *           - polyfit_object is NULL.
136 */
137 extern int polyfit_free(
138     void * const polyfit_object
139 );
140
141 #ifdef __cplusplus
142 };
143 #endif
144
145 #endif
146
147 /** EOF */

```

### 3 The Theory

Following the development in [5], suppose that we have  $N$  ordered pairs of data points

$$\{(x_i, y_i)\}_{i=1}^N \quad (1)$$

with  $x_i$  distinct and that we'd like to find the linear least-squares fit to a set of  $D + 1$  linearly independent functions  $\phi_j$ ,  $0 \leq j \leq D$

$$\hat{f}(x) = \sum_{k=0}^D a_k \phi_k(x) \quad (2)$$

so that

$$y_i \approx \hat{f}(x_i), \quad 1 \leq i \leq N \quad (3)$$

with  $D < N - 1$ . The functions  $\phi_k$  do not need to be linear; it is the dependence on the coefficients  $a_k$  that makes the problem linear. In the common polynomial case, you'd likely choose

$$\phi_k(x) = x^k. \quad (4)$$

To perform a least squares fit, we'll minimize the weighted error  $E$ :

$$E = \sum_{i=1}^N w_i \left( y_i - \sum_{k=0}^D a_k \phi_k(x_i) \right)^2 \quad (5)$$

for some given positive weights  $w_i$ ,  $1 \leq i \leq N$ , and for some unknown coefficients  $a_k$ ,  $0 \leq k \leq D$ . The quantity  $E$  is clearly a positive-definite quadratic form and so a minimum can be found by setting the gradient of  $E$  with respect to the  $a_j$  to zero:

$$\frac{\partial E}{\partial a_j} = 0, \quad j = 0 \leq D \quad (6)$$

Computing the partials from (5) and setting them to zero, we get

$$\begin{aligned} \frac{\partial E}{\partial a_j} &= -2 \sum_{i=1}^N w_i \left( y_i - \sum_{k=0}^D a_k \phi_k(x_i) \right) \phi_j(x_i) \\ &= 0. \end{aligned}$$

After a little rearrangement, this becomes

$$\sum_{i=1}^N w_i y_i \phi_j(x_i) = \sum_{k=0}^D a_k \sum_{i=1}^N w_i \phi_j(x_i) \phi_k(x_i). \quad (7)$$

The functional  $(\cdot, \cdot)$  defined by

$$(f, g) = \sum_{i=1}^N w_i f(x_i) g(x_i) \quad (8)$$

for arbitrary functions  $f$  and  $g$  defines an *inner product* on the *vector space* of functions defined on  $\{x_i\}$  and spanned by  $\{\phi_k\}$  because it is linear, symmetric, and positive definite (since the  $w_i$  are positive). In addition, this inner product is associative:

$$(f, g h) = (f g, h). \quad (9)$$

With this definition, we can rewrite (7) as

$$(y, \phi_j) = \sum_{k=0}^D a_k (\phi_j, \phi_k) \quad (10)$$

For the common polynomial case in (4), this reads

$$\sum_i w_i y_i x_i^j = \sum_k a_k \sum_i w_i x_i^{j+k}. \quad (11)$$

These two are called the *normal equations* and are the solution to the  $(D+1) \times (D+1)$  linear system

$$\begin{aligned} Aa &= B \\ A_{j,k} &= (\phi_j, \phi_k) \\ B_j &= (y, \phi_j) \end{aligned} \quad (12)$$

for the coefficient vector  $a$ . In the common case with  $w_i = 1$ , the matrix  $A$  is the Hilbert matrix, the poster-child for badly behaved linear systems, and the condition number of this matrix is exponential in  $D$ . You get roundoff error not only in computing the matrix elements, but also during the solution of the linear system. The number of points  $N$  and the fit degree  $D$  must be small in order to prevent catastrophic roundoff error. Using special linear solvers such as Cholesky decomposition, SVD, and friends [4] are strongly recommended for this approach.

In what follows, we will make a different choice for the  $\phi_k$  that will minimize roundoff errors. Suppose that the functions  $\phi_k$  are *orthogonal* with respect to the inner product so that

$$(\phi_j, \phi_k) = \delta_{jk} (\phi_k, \phi_k), \quad (13)$$

where the *Kronecker delta* is defined as

$$\delta_{jk} = \begin{cases} 1, & j = k \\ 0, & j \neq k \end{cases}. \quad (14)$$

Equation (7) now takes the simplified form

$$(y, \phi_k) = a_k (\phi_k, \phi_k) \quad (15)$$

$$(16)$$

so that

$$a_k = \frac{(y, \phi_k)}{(\phi_k, \phi_k)}. \quad (17)$$

For orthogonal functions, the matrix  $A$  for the normal equations is diagonal, making it trivial to obtain the values  $a_k$ . You still accumulate roundoff error computing the quantities on the right hand side, but only a single roundoff error solving for  $a_k$ .

What we will do below is use the  $w_i$  and  $x_i$  to construct a set of orthogonal polynomials  $\phi_k$ . Given  $y_i$ , we can then use (17) to compute the expansion (2).

First we will show that the  $\phi_k$  satisfy a three-term recurrence relation. Suppose that  $\phi_k(x)$  is monic and has degree exactly  $k$  so that its leading term is  $x^k$ . It is simple to show that [5]

$$x^k = \sum_{j=0}^k c_{jk} \phi_j(x) \quad (18)$$

for some set of  $c_{j,k}$ . Therefore we can write any polynomial as a weighted sum of the  $\phi_k$ . With this in mind, write

$$\phi_{k+1} - x\phi_k + b_k\phi_k + c_k\phi_{k-1} = \sum_{j=0}^{k-2} d_{jk}\phi_j \quad (19)$$

for some  $b_k$ ,  $c_k$ , and  $d_{jk}$  since  $\phi_{k+1} - x\phi_k$  is of degree  $k$  at most. Taking inner products with  $\phi_{k+1}$ ,  $\phi_k$ ,  $\phi_{k-1}$ , and  $\phi_j$ ,  $0 \leq j < k-1$  gives

$$\begin{aligned} (\phi_{k+1}, \phi_{k+1}) - (x\phi_k, \phi_{k+1}) &= 0 \\ -(x\phi_k, \phi_k) + b_k(\phi_k, \phi_k) &= 0 \\ -(x\phi_k, \phi_{k-1}) + c_k(\phi_{k-1}, \phi_{k-1}) &= 0 \\ 0 &= d_{jk} \end{aligned}$$

Since the inner product (8) is associative (9), we can rewrite these as

$$\begin{aligned} (\phi_{k+1}, \phi_{k+1}) &= (x\phi_k, \phi_{k+1}) \\ b_k &= \frac{(x\phi_k, \phi_k)}{(\phi_k, \phi_k)} \\ c_k &= \frac{(x\phi_{k-1}, \phi_k)}{(\phi_{k-1}, \phi_{k-1})} \end{aligned} \quad (20)$$

By setting  $k \rightarrow k-1$  in the first of these, we obtain the simple relations

$$b_k = \frac{(x\phi_k, \phi_k)}{(\phi_k, \phi_k)} \quad (21)$$

$$c_k = \frac{(\phi_k, \phi_k)}{(\phi_{k-1}, \phi_{k-1})} \quad (22)$$

To summarize,

$$\phi_{k+1} = (x - b_k)\phi_k - c_k\phi_{k-1}, \quad k < N. \quad (23)$$

$$\phi_0 = 1 \quad (24)$$

$$\phi_{i-1} = 0 \quad (25)$$

$$\begin{aligned}
b_k &= \frac{(x\phi_k, \phi_k)}{(\phi_k, \phi_k)} \\
c_k &= \frac{(\phi_k, \phi_k)}{(\phi_{k-1}, \phi_{k-1})}
\end{aligned}
\tag{26}$$

where  $b_k$  is given by (21) and  $c_k$  is given by (22). With the initial conditions on  $\phi_{-1}$  and  $\phi_0$ , it is clear that each  $\phi_k$  for  $k \geq 0$  is monic. Since  $d_{jk} = 0$ , the polynomials satisfy the three-term recurrence relation (23) as claimed. Armed with this recurrence, we can compute each  $\phi_k(x)$ , use (17) to get  $a_k$ , and build the final solution (2).

There are two things to note about (23). First,

$$\phi_N(x) = \prod_{i=1}^N (x - x_i) \tag{27}$$

vanishes on all of the  $x_i$  and would therefore contribute nothing if included in the fit (2). It can be shown [5] that the  $k$  zeros of  $\phi_k(x)$  are real, simple, and located in the interval spanned by the  $x_i$ . This fact is proven in appendix D. In particular, this means they are oscillatory over this interval and so care needs to be taken computing and summing them. The Python module is implemented in quadruple precision (using pairs of `double`) [2, 6]. The FORTRAN implementation of this algorithm is given in [7, 8, 9]; a Python2/Python3 implementation is included with this document. The evaluation procedure for (2) uses *Clenshaw's recurrence* [1, 3, 10] because of its numerical stability in computing the fit polynomial and its derivatives. This recurrence is covered in more detail in appendix C.

One advantage of using orthogonal polynomials to fit data is hidden in (17). Having computed a fit of order  $D$ , you immediately know *every* least squares fit of order less than  $D$  for *free*. Also, having computed a fit up to degree  $D$ , we can compute the fit of degree  $D+1$  by simply computing inner products with  $\phi_{k+1}$  in (17) using the recurrence (23) which is  $O(N)$  work.

The `Polyfit` class provides a special method `__call__` to evaluate the fit polynomial and, optionally, its derivatives at a given point, as well as a `coefs()` method to return the Taylor coefficients at a given point. It is important to note that the Taylor coefficients are less accurate than the  $a_k$ ; computing polynomial values using these coefficients will be less accurate (potentially far less accurate) than using `__call__()` directly. The `Polyfit` class also provides an `rms_err()` method that returns the RMS residual error for a given fit degree. This information can be used to prevent *over-fitting* via statistical tests; in fact, `dpolft` [7] optionally uses this information in a statistical F-test as a possible stopping criterion.

Appendix A compares `polyfit` to a naïve `numpy` implementation using the “standard” normal matrix for  $x^k$  using Cholesky decomposition [4] for stability. The key takeaways from the appendix are:

- For the best results, always scale the  $x$  and  $y$  values to be  $O(1)$ . If this is not possible, it is best to use `polyfit`.
- If you have to perform a higher order fit, it is best to use `polyfit`; however, your luck will run out sooner or later. Do not fear a  $10^{\text{th}}$  fit with `polyfit`.
- Although `polyfit` is slower than `numpy` by a factor of 2–4, it produces more accurate results.

## A Appendix: Performance Comparisons

Below is a table of examples comparing a naïve `numpy` polynomial fit with the  $x^k$  basis functions to `polyfit()`. This code for this test is available in `examples/ex3.py`. In the table,  $E_{\text{rms}}$  is the RMS residual for the fit and  $E_{\text{rel}}$  is the maximum relative error for the fit across all the  $x_i$ . The fit is for 100,000 points with the cubic polynomial

$$2x^3 + x^2 - x + \pi$$

There are 12 cases via 3 sets of criteria:

1. A cubic versus quartic versus 10th degree fit; all terms above cubic should be zero, of course
2. Whether or not the  $x$  values are scaled to the unit interval  $[-1, 1]$
3. Whether the weights are uniform or chosen to minimize relative error

The runtime for the two cases is also shown. The orthogonal polynomial case is slower primarily due to being implemented in quadruple precision (orthogonal polynomial fitting is inherently slower than directly computing moments).

Function	Order	X-scaling	Weights	Run time	$E_{\text{rms}}$	$E_{\text{rel}}$
<code>polyfit()</code>	3	unscaled	uniform	0.043	2.2e-2	4.8e-3
<code>numpy</code>	3	unscaled	uniform	0.022	2.4e+2	2.1e+2
<code>polyfit()</code>	3	unscaled	relative	0.044	4.4e-2	2.2e-16
<code>numpy</code>	3	unscaled	relative	0.020	3.5e+0	1.1e-11
<code>polyfit()</code>	3	scaled	uniform	0.043	1.9e-16	2.2e-16
<code>numpy</code>	3	scaled	uniform	0.015	2.6e-13	1.4e-13
<code>polyfit()</code>	3	scaled	relative	0.043	1.9e-16	2.2e-16
<code>numpy</code>	3	scaled	relative	0.012	1.8e-13	2.0e-13
<code>polyfit()</code>	4	unscaled	uniform	0.053	2.2e-2	2.1e-3
<code>numpy</code>	4	unscaled	uniform	0.021	1.5e+3	1.6e3
<code>polyfit()</code>	4	unscaled	relative	0.053	3.1e-2	2.2e-16
<code>numpy</code>	4	unscaled	relative	0.023	6.4e+4	1.0e-6
<code>polyfit()</code>	4	scaled	uniform	0.056	1.9e-16	2.2e-16
<code>numpy</code>	4	scaled	uniform	0.015	1.4e-12	1.4e-12
<code>polyfit()</code>	4	scaled	relative	0.053	1.9e-16	2.2e-16
<code>numpy</code>	4	scaled	relative	0.014	3.9e-13	5.1e-13
<code>polyfit()</code>	10	unscaled	uniform	0.11	1.4e-2	3.2e-3
<code>numpy</code>	10	unscaled	uniform	0.025	1.7e7	3.1e7
<code>polyfit()</code>	10	unscaled	relative	0.11	1.5e-2	2.2e-16
<code>numpy</code>	10	unscaled	relative	0.026	1.9e+9	3.3e-1
<code>polyfit()</code>	10	scaled	uniform	0.11	1.9e-16	2.2e-16
<code>numpy</code>	10	scaled	uniform	0.018	2.3e-8	4.2e-8
<code>polyfit()</code>	10	scaled	relative	0.11	1.9e-16	2.2e-16
<code>numpy</code>	10	scaled	relative	0.018	4.9e-9	1.0e-8

A number of things are apparent from this table:



- The C `polyfit` version is about 2–4 times slower than the `numpy` version implemented in C and FORTRAN.
- The RMS and relative errors for `polyfit` are about a thousand to a trillion times smaller than the `numpy` implementation.
- For unscaled  $x$  values in the range  $[0, 99999]$  the `numpy` fit is *awful*.
- For scaled  $x$  values in the range  $[0, 1]$  the `numpy` fit is much better, but the error is generally 1,000 times higher than for `polyfit`.
- Using relative weights decreases the relative error  $E_{\text{rel}}$  significantly. This should come as no surprise.
- Not shown, but for the 10th degree fit with `numpy`, the coefficients above degree 3 are not small; for `polyfit`, they are tiny in all cases.

## B Appendix: Source Code for the Python Reference Implementation

```

1  #!/usr/bin/env python3
2
3  "quad precision orthogonal polynomial least squares fitting"
4
5  ## {{{ prologue
6  from __future__ import print_function
7
8  ## pylint: disable=invalid-name,bad-whitespace
9  ## pylint: disable=useless-object-inheritance
10 ## pylint: disable=unnecessary-comprehension
11 ## XXX pylint: disable=missing-docstring
12
13 import math
14
15 __all__ = [
16     "PolyfitPlan", "PolyfitFit", "PolyfitEvaluator",
17     "polyfit_plan", "polyfit_fit", "polyfit_eval",
18     "polyfit_coefs", "polyfit_maxdeg", "polyfit_npoints"
19 ]
20 ## }}}
21 ## {{{ quad precision routines from ogita et al
22 def twosum(a, b):
23     "6 flops, algorithm 3.1 from ogita"
24     x = a + b
25     z = x - a
26     y = (a - (x - z)) + (b - z)
27     return x, y
28
29 def twodiff(a, b):
30     "6 flops, subtraction version of twosum()"
31     x = a - b
32     z = x - a
33     y = (a - (x - z)) - (b + z)

```

```

34     return x, y
35
36 def split(a, FACTOR = 1. + 2. ** 27):
37     "4 flops, algorithm 3.2 from ogita"
38     c = FACTOR * a
39     x = c - (c - a)
40     y = a - x
41     return x, y
42
43 def twoproduct(a, b):
44     "23 flops, algorithm 3.3 from ogita"
45     x      = a * b
46     a1, a2 = split(a)
47     b1, b2 = split(b)
48     y      = a2 * b2 - (x - a1 * b1 - a2 * b1 - a1 * b2)
49     return twosum(x, y)
50
51 def sum2s(p):
52     "7n-1 flops, algorithm 4.1 from ogita"
53     pi, sigma = p[0], 0.
54     for i in range(1, len(p)):
55         pi, q = twosum(pi, p[i])
56         sigma += q
57     return twosum(pi, sigma)
58
59 def vsum(p):
60     "6(n-1) flops, algorithm 4.3 from ogita"
61     im1 = 0
62     for i in range(1, len(p)):
63         p[i], p[im1] = twosum(p[i], p[im1])
64         im1 = i
65     return p
66
67 def sumkcore(p, K):
68     "6(K-1)(n-1) flops, algorithm 4.8 from ogita"
69     for _ in range(K - 1):
70         p = vsum(p)
71     return p
72
73 def sumk(p, K):
74     "(6K+1)(n-1)+6 flops, algorithm 4.8 from ogita"
75     p = sumkcore(p, K)
76     return sum2s(p)
77
78 def vectorsum(vec):
79     "19n-13 flops, sumk() with K=3"
80     return sumk(vec, K=3)
81 ## }}}
82 ## {{{ utility functions
83 def zero():
84     return (0., 0.)
85
86 def one():
87     return (1., 0.)
88
89 def vappend(vec, x):

```

```

90     "append quad to vector"
91     vec.extend(x)
92
93 def to_quad(x):
94     "float to quad"
95     return x if isinstance(x, tuple) else (float(x), 0.)
96
97 def to_float(x):
98     "quad to float"
99     return x[0] if isinstance(x, tuple) else float(x)
100 ## }}}
101 ## {{{ quad precision arithmetic
102 def add(x, y):
103     "14 flops"
104     x, xx = x
105     y, yy = y
106     z, zz = twosum(x, y)
107     return twosum(z, zz + xx + yy)
108
109 def sub(x, y):
110     "14 flops"
111     x, xx = x
112     y, yy = y
113     z, zz = twodiff(x, y)
114     return twosum(z, zz + xx - yy)
115
116 def mul(x, y):
117     "33 flops"
118     x, xx = x
119     y, yy = y
120     z, zz = twoproduct(x, y)
121     zz += xx * y + x * yy
122     return twosum(z, zz)
123
124 def div(x, y):
125     "36 flops, from dekker"
126     x, xx = x
127     y, yy = y
128     c = x / y
129     u, uu = twoproduct(c, y)
130     cc = (x - u - uu + xx - c * yy) / y
131     return twosum(c, cc)
132
133 def sqrt(x):
134     "35 flops, from dekker"
135     x, xx = x
136     if not (x or xx):
137         return zero()
138     c = math.sqrt(x)
139     u, uu = twoproduct(c, c)
140     cc = (x - u - uu + xx) * 0.5 / c
141     return twosum(c, cc)
142 ## }}}
143 ## {{{ polyfit_plan
144 def polyfit_plan(maxdeg, xv, wv):
145     """

```

```

146     given x values in xv[] and positive weights in wv[],
147     make a plan to perform least squares fitting up to
148     degree maxdeg.
149
150     returns a plan object than can be json-serialized.
151
152     this is code for "compute everything need to calculate
153     an expansion in xv- and wv-specific orthogonal
154     polynomials".
155     """
156     ## pylint: disable=too-many-locals
157
158     ## convert to quad
159     xv = [to_quad(x) for x in xv]
160     wv = [to_quad(w) for w in wv]
161     ## build workspaces and result object
162     N = len(xv)
163     b = [ ]          ## recurrence coefs b_k
164     c = [ ]          ## recurrence coefs c_k
165     g = [one()]      ## \gamma_k^2 \equiv (\phi_k, \phi_k)
166     r = {
167         "D": maxdeg,    ## max fit degree
168         "N": N,         ## number of data points
169         "b": b,         ## coefficients b_k
170         "c": c,         ## coefficients c_k
171         "g": g,         ## normalization factors g_k
172         "x": xv,        ## x values, needed for actual fit
173         "w": wv         ## y values, needed for actual fit
174     }
175     ## \phi_{k-1} and \phi_k
176     phi_km1 = [zero()] * N ## \phi_{-1}
177     phi_k = [one()] * N ## \phi_0
178
179     for k in range(maxdeg + 1):
180         bvec, gvec = [ ], [ ]
181         for i in range(N):
182             p = phi_k[i]
183             ## w_i \phi_k^2(x_i)
184             wp2 = mul(wv[i], mul(p, p))
185             ## w_i x_i \phi_k^2(x_i)
186             vappend(bvec, mul(xv[i], wp2))
187             ## w_i \phi_k^2(x_i)
188             vappend(gvec, wp2)
189         ## compute g_k = (\phi_k, \phi_k), b_k, and c_k
190         gk = vectorsum(gvec)
191         bk = div(vectorsum(bvec), gk)
192         ck = div(gk, g[k])
193         g.append(gk)
194         b.append(bk)
195         c.append(ck)
196         ## if we aren't done, update pk[] and pkm1[]
197         ## for the next round
198         if k == maxdeg:
199             break
200         for i in range(N):
201             ## \phi_{k+1}(x_i) = (x_i - b_k) \phi_k(x_i) -

```

```

202             ##                                c_k \phi_{k-1}(x_i)
203             phi_kp1 = sub(
204                 mul(sub(xv[i], bk), phi_k[i]),
205                 mul(ck, phi_kp1[i])
206             )
207             ## rotate the polys
208             phi_kp1[i] = phi_k[i]
209             phi_k[i] = phi_kp1
210             c.append(zero()) ## needed in polyfit_eval
211             return r
212     ## }}}
213     ## {{{ polyfit_fit
214     def polyfit_ll_fit(plan, yv):
215         """
216         internal: compute the fit to yv[]
217
218         given a previously generated plan and a set of y values
219         in yv[], compute all least squares fits to yv[] up to
220         degree maxdeg.
221
222         returns a json-serializable fit data object.
223         """
224         ## pylint: disable=too-many-locals
225         N, D = plan["N"], plan["D"]
226         b, c = plan["b"], plan["c"]
227         g = plan["g"]
228         wv = plan["w"]
229         xv = plan["x"]
230
231         a, e = [ ], [ ] ## fit coefs and rms errors
232         rv = [to_quad(y) for y in yv] ## residuals
233
234         ## \phi_{k-1} and \phi_k
235         phi_kp1 = [zero()] * N
236         phi_k = [one()] * N
237         for k in range(D + 1):
238             ## compute ak as (residual, \phi_k) / (\phi_k, \phi_k)
239             avec = [ ]
240             for i in range(N):
241                 vappend(avec, mul(wv[i], mul(rv[i], phi_k[i])))
242             ak = div(vectorsum(avec), g[k + 1])
243             a.append(ak)
244
245             ## remove the \phi_k component from the residual
246             ## compute rms error for this degree
247             evec = [ ]
248             for i in range(N):
249                 rv[i] = r = sub(rv[i], mul(ak, phi_k[i]))
250                 vappend(evec, mul(r, r))
251             e.append(sqrt(div(vectorsum(evec), to_quad(N))))
252
253             ## if we aren't done, update pk[] and pkp1[]
254             ## for the next round
255             if k == D:
256                 break

```

```

258     for i in range(N):
259         ## \phi_{k+1}(x_i) = (x_i - b_k) \phi_k(x_i) -
260         ##             c_k \phi_{k-1}(x_i)
261         phi_kp1 = sub(
262             mul(sub(xv[i], b[k]), phi_k[i]),
263             mul(c[k], phi_km1[i])
264         )
265         ## rotate the polys
266         phi_km1[i] = phi_k[i]
267         phi_k[i] = phi_kp1
268     ## return fit data
269     return {
270         "a": a,      ## orthogonal poly coefs
271         "e": e,      ## per-degree rms errors
272         "r": rv      ## per-point residuals
273     }
274
275 def polyfit_fit(plan, yv):
276     """
277     given a previously generated plan and a set of y values
278     in yv[], compute all least squares fits to yv[] up to
279     degree maxdeg.
280
281     returns (resids, rms_errors, evaluator, coef_evaluator)
282     where resids are the fit residuals at each point,
283     rms_errors is a vector of rms fit errors for each possible
284     degree, evaluator is a function to evaluate the fit
285     polynomial, and coef_evaluator is a function to generate
286     polynomial coefficients for the standard x_k basis.
287     """
288     ll_fit = polyfit_ll_fit(plan, yv)
289     ## get coefs, rms errors, and residuals
290     a, e, rv = ll_fit["a"], ll_fit["e"], ll_fit["r"]
291     ## return residuals, rms errors by degree, a poly
292     ## evaluator, and a coef evaluator
293     return (
294         [to_float(res) for res in rv],
295         [to_float(err) for err in e],
296         (lambda x, deg=-1, nder=0: \
297             polyfit_eval(plan, ll_fit, x, deg, nder)),
298         (lambda x, deg=-1: \
299             polyfit_coefs(plan, ll_fit, x, deg))
300     )
301     ## }}}
302     ## {{{ polyfit_eval
303 def _polyfit_eval(plan, ll_fit, x, deg=-1, nder=0):
304     """
305     internal: polyfit_eval in quad precision.
306     """
307     ## pylint: disable=too-many-locals
308     b, c, D = plan["b"], plan["c"], plan["D"]
309     a = ll_fit["a"]
310
311     if deg < 0:
312         deg = D
313     if nder < 0:

```

```

314         nder = deg
315
316     ##  $z_k^{\{(j-1)\}}$  and  $z_k^{\{(j)\}}$  for clenshaw's recurrence
317     zjm1 = a[:deg+1] + [zero(), zero()] ## init to  $a_{kj}$ 
318     zj   = [zero()] * (deg + 3)
319
320     fac = one()          ##  $j!$  factor
321     lim = min(deg, nder) ## max degree to compute
322     x   = to_quad(x)
323     ret = [ ]           ## return value
324     for j in range(lim + 1):
325         if j > 1:
326             fac = mul(fac, to_quad(j))
327             ## compute  $z_j^{\{(j)\}}$  using the recurrence
328             for k in range(deg, j - 1, -1):
329                 t = k - j
330                 ##  $z_k^{\{(j)\}} = z_k^{\{(j-1)\}} +$ 
331                 ##  $(x - b_t) z_{k+1}^{\{(j)\}} -$ 
332                 ##  $c_{t+1} z_{k+2}^{\{(j)\}}$ 
333                 tmp = sub(
334                     mul(sub(x, b[t]), zj[k + 1]),
335                     mul(c[t + 1], zj[k + 2])
336                 )
337                 zj[k] = add(zjm1[k], tmp)
338             ## save  $j!$   $z_j^{\{(j)\}}$ 
339             ret.append(mul(fac, zj[j]))
340             ## update z if we aren't done
341             if j == lim:
342                 break
343             ## update zjm1
344             zjm1[:] = zj
345             ## zj only needs last 2 elements cleared
346             zj[-2:] = [zero(), zero()]
347     if nder > deg:
348         ret += [zero()] * (nder - deg)
349     ## returns quad precision (for polyfit_coefs)
350     return ret
351
352 def polyfit_eval(plan, a, x, deg=-1, nder=0):
353     """
354     given a plan, a fit data object returned by
355     polyfit_fit, a point x, a least squares fit degree deg,
356     and a desired number of derivatives to compute nder,
357     calculate and return the value of the polynomial and
358     any requested derivatives.
359
360     if deg is negative, use maxdeg instead. if nder is
361     negative, use the final value of deg; otherwise, compute
362     nder derivatives of the least squares polynomial of
363     degree deg.
364
365     returns a list whose first element is the value of the
366     least squares polynomial of degree deg at x. subsequent
367     elements are the requested derivatives. if zero
368     derivatives are requested, the scalar function value is
369     returned.

```

```

370     """
371     ## get float values
372     r = _polyfit_eval_(plan, a, x, deg, nder)
373     r = [to_float(v) for v in r]
374     ## return scalar if no derivs
375     return r[0] if len(r) == 1 else r
376 ## }}}
377 ## {{{ polyfit_coefs
378 def polyfit_coefs(plan, ll_fit, x0=0., deg=-1):
379     """
380     given a plan, a set of expansion coefficients generated
381     by polyfit_fit, a center point x0, and a least squares
382     fit degree, return the coefficients of powers of (x - x0)
383     with the highest powers first. if deg is negative (the
384     default), use maxdeg instead.
385     """
386     ## get value and derivs, divide by j!
387     vals = _polyfit_eval_(plan, ll_fit, x0, deg, deg)
388     fac = one()
389     for j in range(2, len(vals)):
390         fac = div(fac, to_quad(j))
391         vals[j] = mul(vals[j], fac)
392     ## get highest power first and convert to float
393     vals.reverse()
394     return [to_float(v) for v in vals]
395 ## }}}
396 ## {{{ polyfit_maxdeg and polyfit_npoints
397 def polyfit_maxdeg(plan):
398     "return the maximum possible fit degree"
399     return plan["D"]
400
401 def polyfit_npoints(plan):
402     "return the number of data points being fit"
403     return plan["N"]
404 ## }}}
405 ## {{{ Polyfit classes
406 class PolyfitEvaluator(object):
407     """
408     returned by PolyfitFit.evaluator(). this object evaluates
409     the fit polynomial and its derivatives, and also returns
410     its coefficients in powers of (x - x0) for given x0.
411     """
412
413     def __init__(self, doeval, docofs):
414         self.eval, self.cofs = doeval, docofs
415
416     def __call__(self, x, deg=-1, nder=0):
417         """
418         given a point x, a least squares fit degree deg,
419         and a desired number of derivatives to compute nder,
420         calculate and return the value of the polynomial and
421         any requested derivatives.
422
423         if deg is negative, use maxdeg instead. if nder is
424         negative, use the final value of deg; otherwise, compute
425         nder derivatives of the least squares polynomial of

```



```

426         degree deg.
427
428         returns a list whose first element is the value of the
429         least squares polynomial of degree deg at x. subsequent
430         elements are the requested derivatives. if zero
431         derivatives are requested, the scalar function value is
432         returned.
433         """
434         return self.eval(x, deg, nder)
435
436     def coefs(self, x0, deg=-1):
437         """
438         return the coefficients of the fit polynomial of degree
439         deg about (x - x0). if deg is negative, use maxdeg
440         instead.
441         """
442         return self.cofs(x0, deg)
443
444 class PolyfitFit(object):
445     """
446     orthogonal polynomial fitter returned by PolyfitPlan.fit()
447     """
448
449     def __init__(self, plan, yv):
450         self.res, self.rms, self.eval, self.cofs = \
451             polyfit_fit(plan, yv)
452
453     def evaluator(self):
454         """
455         return a PolyfitEvaluator for this fit.
456         """
457         return PolyfitEvaluator(self.eval, self.cofs)
458
459     def residuals(self):
460         """
461         return the list of residuals for the maxdeg fit.
462         """
463         return self.res
464
465     def rms_errors(self):
466         """
467         return a list of rms errors, one per fit degree. use them
468         to detect overfitting.
469         """
470         return self.rms
471
472 class PolyfitPlan(object):
473     """
474     orthogonal polynomial least squares planning class. you must
475     create one of these prior to fitting; it can be reused for
476     multiple fits of the same xv[] and wv[].
477     """
478
479     def __init__(self, maxdeg, xv, wv):
480         """
481         given x values in xv[] and positive weights in wv[],

```

```

482         make a plan to perform least squares fitting up to
483         degree maxdeg.
484
485         this is code for "compute everything need to calculate
486         an expansion in xv- and wv-specific orthogonal
487         polynomials".
488         """
489         self.plan = polyfit_plan(maxdeg, xv, wv)
490
491     def fit(self, yv):
492         """
493         given a set of y values in yv[], compute all least
494         squares fits to yv[] up to degree maxdeg. returns
495         a PolyfitFit object.
496         """
497         return PolyfitFit(self.plan, yv)
498
499     def maxdeg(self):
500         "return the maximum fit degree"
501         return polyfit_maxdeg(self.plan)
502
503     def npoints(self):
504         "return the number of fit points"
505         return polyfit_npoints(self.plan)
506 ## }}}
507
508 ## EOF

```

## C Appendix: Clenshaw's Recurrence

Having determined all of the  $a_k$ ,  $b_k$ , and  $c_k$ , we would like to evaluate the fit polynomial and its derivatives. Recall that the fit polynomial is given by (2)

$$\hat{f}(x) = \sum_{k=0}^D a_k \phi_k(x).$$

Clenshaw's recurrence is a numerically stable method that yields the values of  $\hat{f}$  and its derivatives (optionally) at a given point  $x$ . The recurrence is given by

$$z_k = a_k + (x - b_k)z_{k+1} - c_{k+1}z_{k+2} \quad (28)$$

$$c_{D+1} = 0 \quad (29)$$

$$z_{D+1} = 0 \quad (30)$$

$$z_{D+2} = 0 \quad (31)$$

and is applied in the downward direction. Solving (28) for  $a_k$  and substituting into (23) gives

$$\hat{f}(x) = \sum_{k=0}^D \phi_k(x) [z_k - (x - b_k)z_{k+1} + c_{k+1}z_{k+2}] \quad (32)$$

$$= \sum_{k=0}^D z_k [\phi_k(x) - (x - b_{k-1})\phi_{k-1}(x) + c_{k-1}\phi_{k-2}(x)] \quad (33)$$

where the second step follows by grouping terms by  $z_k$ . Since

$$\phi_k(x) = (x - b_{k-1})\phi_{k-1}(x) - c_{k-1}\phi_{k-2}(x)$$

by (23), all of the terms vanish except for the  $k = 0$  term. Since  $\phi_0(x) = 1$ , we have

$$\hat{f}(x) = z_0. \quad (34)$$

Now on to the derivatives of  $\hat{f}$ . It is easy to show that

$$\phi_{k+1}^{(j)} = (x - b_k)\phi_k^{(j)} - c_k\phi_{k-1}^{(j)} + j\phi_k^{(j-1)}$$

where the superscript  $(j)$  denotes the derivative of order  $j$ . If we now define

$$z_k^{(j)} = z_k^{(j-1)} + (x - b_{k-j})z_{k+1}^{(j)} + c_{k-j+1}z_{k+2}^{(j)} \quad (35)$$

$$z_k^{(0)} = a_k, \quad (36)$$

then

$$\hat{f} = z_0^{(0)}.$$

To compute the  $j$ -th derivative of  $\hat{f}(x)$ , we invoke the recurrence (35) for  $j = 0$

$$\begin{aligned} \hat{f}^{(j)} &= \sum_{k=j}^D a_k \phi_k^{(j)} \\ &= \sum_{k=j}^D \phi_k^{(j)} \left[ z_k^{(0)} - (x - b_k)z_{k+1}^{(0)} + c_k z_{k+2}^{(0)} \right] \\ &= \sum_{k=j}^D z_k^{(0)} \left[ \phi_k^{(j)} - (x - b_{k-1})\phi_{k-1}^{(j)} + c_{k-1}\phi_{k-2}^{(j)} \right] \\ &= j \sum_{k=j}^D z_k^{(0)} \phi_{k-1}^{(j-1)} \end{aligned}$$

We can use (35) again after solving for  $z_k^{(0)}$ :

$$\begin{aligned} &= j \sum_{k=j}^D \phi_{k-1}^{(j-1)} \left[ z_k^{(1)} - (x - b_{k-1})z_{k+1}^{(1)} + c_k z_{k+2}^{(1)} \right] \\ &= j \sum_{k=j}^D z_k^{(1)} \left[ \phi_{k-1}^{(j-1)} - (x - b_{k-2})\phi_{k-2}^{(j-1)} + c_{k-2}\phi_{k-3}^{(j-1)} \right] \\ &= j(j-1) \sum_{k=j}^D z_k^{(1)} \phi_{k-2}^{(j-2)} \end{aligned}$$

Continuing this way, we finally arrive at

$$\hat{f}^{(j)} = j! \sum_{k=j}^D z_k^{(j-1)} \phi_{k-j}$$

$$\begin{aligned}
&= j! \sum_{k=j}^D \phi_{k-j} \left[ z_k^{(j)} - (x - b_{k-j}) z_{k+1}^{(j)} + c_{k-j+1} z_{k+2}^{(j)} \right] \\
&= j! \sum_{k=j}^D z_k^{(j)} [\phi_{k-j} - (x - b_{k-j-1}) \phi_{k-j-1} + c_{k-j-1} \phi_{k-j-2}] \\
&= j! z_j^{(j)}
\end{aligned}$$

since only the  $\phi_0$  term remains. Note that while computing the derivative of order  $j$ , we obtain all of the derivatives of order less than  $j$  for *free*.

## D Appendix: The Zeros of $\phi_k(x)$

Earlier it was claimed that

1. The zeros of  $\phi_k(x)$  are real
2. The zeros of  $\phi_k(x)$  are simple
3. The zeros of  $\phi_k(x)$  are lie in the interval spanned by the  $\{x_i\}$
4. The zeros of  $\phi_k(x)$  separate the zeros of  $\phi_{k+1}(x)$

We will prove these facts in this appendix; the development follows Hildebrand [5].

Define

$$a = \min_i x_i \tag{37}$$

$$b = \max_i x_i \tag{38}$$

and consider the sum

$$\sum_{i=1}^N w_i \phi_0(x_i) \phi_k(x_i) = 0, \quad k > 0. \tag{39}$$

Since  $k > 0$ , this sum always equals zero; however, since  $w_i \phi_0(x_i)$  does not change sign in  $[a, b]$ , it must be the case that  $\phi_k(x)$  has at least one root in  $[a, b]$ . Now let the roots of  $\phi_k(x)$  that lie in  $[a, b]$  and have odd multiplicity be denoted  $r_1, r_2, \dots, r_q$ . By definition the roots  $r_i$  are distinct. Define  $p(x)$  by

$$p(x) = (x - r_1)(x - r_2) \cdots (x - r_q). \tag{40}$$

Clearly  $q$  cannot exceed  $k$  since  $\phi_k(x)$  is of degree  $k$  and therefore can only have  $k$  (possibly complex) roots. Since the roots of  $p(x)$  are simple and distinct, the quantity  $p(x)\phi_k(x)$  cannot change sign in  $[a, b]$  and

$$\sum_{i=1}^N w_i p(x_i) \phi_k(x_i) > 0, \quad k > 0. \tag{41}$$

If we assume that  $q < k$ , we reach a contradiction because this sum must be zero since the degree of  $p(x)$  is less than  $k$  but  $\phi_k(x)$  is orthogonal to all polynomials of degree less than  $k$ . Therefore we must have  $q = k$  so that the roots of  $\phi_k(x)$  are real, simple, and lie in  $[a, b]$ .

To prove the zero-separation property, define  $\gamma_k$  by

$$\gamma_k^2 = (\phi_k, \phi_k) > 0 \quad (42)$$

since  $w_i > 0$  and rewrite (23) as

$$x \frac{\phi_k(x)}{\gamma_k^2} = \frac{\phi_{k+1}}{\gamma_k^2} + \frac{\phi_{k-1}}{\gamma_{k-1}^2} + b_k \frac{\phi_k(x)}{\gamma_k^2} \quad (43)$$

Multiplying this by  $\phi_k(y)$ , exchanging  $x$  and  $y$ , and subtracting the two eliminates the  $b_k$  term to give

$$(x - y) \frac{\phi_k(x)\phi_k(y)}{\gamma_k^2} = \frac{\phi_{k+1}(x)\phi_k(y) - \phi_k(x)\phi_{k+1}(y)}{\gamma_k^2} \quad (44)$$

$$- \frac{\phi_k(x)\phi_{k-1}(y) - \phi_{k-1}(x)\phi_k(y)}{\gamma_{k-1}^2} \quad (45)$$

Summing this from  $k = 0 \dots D$  telescopes to yield the *Christoffel-Darboux* identity

$$\sum_{k=0}^m \frac{\phi_k(x)\phi_k(y)}{\gamma_k^2} = \frac{\phi_{m+1}(x)\phi_m(y) - \phi_m(x)\phi_{m+1}(y)}{\gamma_m^2(x - y)}. \quad (46)$$

The confluent form (which will be important below) is obtained by letting  $y \rightarrow x$ :

$$\sum_{k=0}^m \frac{[\phi_k(x)]^2}{\gamma_k^2} = \frac{\phi'_{m+1}(x)\phi_m(x) - \phi'_m(x)\phi_{m+1}(x)}{\gamma_m^2}. \quad (47)$$

The Christoffel-Darboux identity may be used to prove the fact that the roots of  $\phi_k$  separate the roots of  $\phi_{k+1}$ . To see this, suppose that  $x_i$  and  $x_{i+1}$  are consecutive roots of  $\phi_{m+1}$ . Substituting these roots into (47), we see that the second term on the right hand side vanishes. The left hand side is strictly positive since  $\phi_0 = 1$ ; therefore,  $\phi'_{m+1}(x_i)\phi_m(x_i)$  and  $\phi'_{m+1}(x_{i+1})\phi_m(x_{i+1})$  are positive. Since the zeros of all the  $\phi_k$  are simple, it must be the case that  $\phi'_{m+1}(x_i)$  and  $\phi'_{m+1}(x_{i+1})$  have opposite sign. This means that  $\phi_m(x_i)$  and  $\phi_m(x_{i+1})$  have opposite sign; therefore,  $\phi_m$  must have a root between  $x_i$  and  $x_{i+1}$  as was to be shown.

## References

- [1] CW Clenshaw, "Curve Fitting with a Digital Computer," The Computer Journal, Volume 2, Issue 4, Pages 170–173, 1960. Online at <https://academic.oup.com/comjnl/article/2/4/170/470550>
- [2] TJ Dekker, "A Floating-Point Technique for Extending the Available Precision," Numer. Math. 18, 224–242, 1971.
- [3] GE Forsythe, "Generation and Use of Orthogonal Polynomials for Data-Fitting with a Digital Computer," Journal of the Society for Industrial and Applied Mathematics, vol 5, no 2 74–88, June 1957.

- [4] GH Golub and CF van Loan, Matrix Computations 2nd ed, Baltimore: Johns Hopkins University Press, 1989
- [5] FB Hildebrand, Introduction to Numerical Analysis, 2nd ed. Dover, 1974.
- [6] T Ogita, SM Rump, and S Oishi, “Accurate Sum and Dot Product,” Siam J Sci Comp, 26(6), 2005. Online at  
<https://www.tuhh.de/ti3/paper/rump/0gRu0i05.pdf>
- [7] LF Shampine, SM Davenport, and RE Huddleston, <https://netlib.org/slatec/src/dpolft.f> to compute a linear least-squares orthogonal polynomial fit. Written 6/1/1974, updated 5/27/1992.
- [8] LF Shampine, SM Davenport, and RE Huddleston, <https://netlib.org/slatec/src/dp1vlu.f> to evaluate the fit polynomial and its derivatives  $p^{(j)}(x)$  at a given point  $x$ . Written 6/1/1974, updated 5/1/1992.
- [9] LF Shampine, SM Davenport, and RE Huddleston, <https://netlib.org/slatec/src/dpcoef.f> To return the coefficients  $c_k$  of the polynomial as  $\sum_k c_k(x - x_0)^k$  at a given point  $x_0$ . Written 6/1/1974, updated 5/1/1992.
- [10] FJ Smith, “An Algorithm for Summing Orthogonal Polynomial Series and their Derivatives with Applications to Curve-Fitting and Interpolation,” Mathematics of Computation, vol 19, no 89 33-36, April 1965. Online at  
<https://www.ams.org/journals/mcom/1965-19-089/S0025-5718-1965-0172445-6/S0025-5718-1965-0172445-6.pdf>