


---

# INTRODUCTION TO JAVASCRIPT

## Lecture 18

---

# TODAY'S TOPICS



- Introduction to Sass
- **Exercise:** Sassy Shapes

---

# ANNOUNCEMENTS

- Sign-in Sheet




**QUESTIONS?**

**SASS**

---


# SASS



- Syntactically Awesome Stylesheets
- CSS Preprocess
- Sass introduced new concepts to CSS:
  - Variables
  - Nesting
  - Conditional Statements
  - Loops
  - Functions
  - Mixins

---


# SASS FILE EXTENSIONS



- Files must be saved with a Sass file extension
- The `.SCSS` extension uses a syntax that is a superset of CSS
- The `.sass` extension uses the original indented syntax

---

# SASS COMPILING




- Sass must be compiled into CSS
- Three implementation
  - Dart Sass
  - LibSass
  - Ruby Sass
- Live Sass Compiler Extension



# SASS VARIABLES

---

# SASS VARIABLES



- Sass variables are used hold values
- Sass variable names begin with a \$
- A colon (:) separate the name from the value
- Sass Variable can be used anywhere in the code


```
/* Sass */
$offwhite: #EEE8D6;
$darkblue: #022933;

body {
  color: $offwhite;
  background-color: $darkblue;
}
```

```
/* CSS */
body {
  color: #EEE8D6;
  background-color: #022933;
}
```

---

# CSS VARIABLES




- CSS variables are also used hold values
- CSS variables are set using the custom property notation
- CSS variables are access using the `var()` function

```
/* Sass */  
$offwhite: #EEE8D6;  
$darkblue: #022933;  
  
body {  
  color: $offwhite;  
  background-color: $darkblue;  
}
```

```
/* CSS */  
:root {  
  --offwhite: #EEE8D6;  
  --darkblue: #022933;  
}  
  
body {  
  color: var(--offwhite);  
  background-color: var(--darkblue);  
}
```

---

# SASS VARIABLES **VS** CSS VARIABLES



- **Sass variables** are read by Sass compiler
- **CSS variables** are read by the browser
- **Sass variable** can only hold one value at a time
- **CSS variables** can hold different values for different elements
- If a **Sass variable** value is changed, only future uses are affected
- If a **CSS variable** is changed, all uses are affected

# NESTING IN SASS

---

# NESTING IN SASS



- Nesting is a way for creating a visual hierarchy in CSS
- A child style is placed inside of the parent
- **WARNING!** Do not overuse nesting.



```
/* Sass */
ul {
  list-style: none;

  li {
    margin-bottom: 20px;
    border-top: 1px dotted red;
    font-size: 2.0rem;
  }

  p {
    margin: 0;
    font-size: 1.5rem;
  }
}
```

```
/* CSS */
ul {
  list-style: none;
}


ul li {
  margin-bottom: 20px;
  border-top: 1px dotted red;
  font-size: 2.0rem;
}

ul p {
  margin: 0;
  font-size: 1.5rem;
}
```

# SASS PARTIALS

---


# SASS PARTIALS



- **Partials** are Sass files that contain snippets of CSS and / or Sass
- **Partials** are included into other Sass files
- **Partials** are not directly compiled by Sass compiler
- **Partials** are used to modularized CSS
- **Partials** are created by adding an underscore (   ) at the beginning of the filename.

---

# INCLUDING PARTIALS




- **Partials** are adding to another Sass file using the `@import` rule
- The main file will have access to any variables, mixins, or functions in the included **partials**
- **NOTE:** The `@use` rule will **soon** be the preferred way to include partials

**HANDS-ON**

---

# NEXT TIME...



- Sass Mixins
- Sass @extend
- Sass Parent Selector
- **Review:** Boxes
- **Exercise:** Sassy Shapes