

Questions

1. Ansible accepts variable files in the YAML format only
 - a. True
 - b. False
2. Ansible by default hides the input characters when using the vars_prompt method
 - a. True
 - b. False
3. When using Ansible conditionals you still must quote the variables
 - a. True
 - b. False
4. The clause that is used to store command output in variables is called
 - a. Store
 - b. Declare
 - c. Register
 - d. Assign
5. Manual failure reporting is usually used with:
 - a. Yum and apt-get
 - b. MySQL related operations
 - c. File upload
 - d. Commands that falsely report an exit status of 0
6. When a command fails, the exit status it produces should not be 0
 - a. True
 - b. False
7. Manual change reporting is often used with third party package managers like composer and npm
 - a. True
 - b. False
8. If you run playbooks against localhost, Ansible will attempt to initiate SSH connection to localhost unless instructed otherwise
 - a. True
 - b. False
9. You can add variables to the inventory file directly
 - a. True
 - b. False
10. Ansible gathers facts about each host it connects to by default unless instructed otherwise
 - a. True
 - b. False
11. Ansible is bound to use its own Vault to store sensitive information. It cannot use other third party KMS products
 - a. True
 - b. False
12. Ansible Tags allow you to run parts of the playbook

- a. True
 - b. False
13. Exception handling in Ansible is done using blocks
- a. True
 - b. False
14. In addition to exception handling, Ansible can also be instructed to ignore errors altogether
- a. True
 - b. False

Answers

1. B – it can also accept JSON files
2. A
3. B – you should not quote variables when using the when clause
4. C
5. D
6. A
7. A
8. A
9. A
10. A
11. B
12. A
13. A
14. A