

Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks

NeurIPS 2015

Shaoqing Ren¹, Kaiming He², Ross Girshick³, Jian Sun²

¹**University of Science and Technology of China**

²**Visual Computing Group, Microsoft Research**

³**Facebook AI Research**


Part 1. Introduction

- **Object Detection**

- Recent advances
 - The success of region proposal methods (e.g., [4]) and region-based convolutional neural networks (RCNNs) [5]
- Region-based CNNs
 - Computationally expensive as originally developed in [5]
 - Their cost has been drastically reduced thanks to sharing convolutions across proposals
- Recent advances
 - The success of region proposal methods (e.g., [4]) and region-based convolutional neural networks (RCNNs) [5].

Part 1. Introduction

A single, unified network for object detection



• **FASTER R-CNN**

- The first module
 - A deep fully convolutional network that proposes regions
- The second module
 - The Fast R-CNN detector that uses the proposed regions
- The entire system is a single, unified network for object detection
- Using the recently popular terminology of neural networks with 'attention' mechanisms, the RPN module tells the Fast R-CNN module where to look.

Method: A Region Proposal Network (RPN)

- **A Region Proposal Network (RPN)**
 - Takes an image (of any size) as input and outputs a set of rectangular object proposals, each with an objectness score
 - Model this process with a fully convolutional network
 - Share computation with a Fast R-CNN object detection network
 - Assume that both nets share a common set of convolutional layers
 - Generate region proposals
 - Slide a small network over the convolutional feature map output by the last shared convolutional layer
 - Takes as input an $n \times n$ spatial window of the input convolutional feature map.
 - Each sliding window is mapped to a lower-dimensional feature
 - This feature is fed into two sibling fullyconnected layers—a box-regression layer (reg) and a box-classification layer (cls)

Method: A Region Proposal Network (RPN)

- **Anchors**

- At each sliding-window location, we simultaneously predict multiple region proposals
 - The number of maximum possible proposals for each location is denoted as k
- The reg layer has $4k$ outputs encoding the coordinates of k boxes
- The cls layer outputs $2k$ scores that estimate probability of object or not object for each proposal
- The k proposals are parameterized relative to k reference boxes, which we call anchors
- An anchor is centered at the sliding window in question
- An anchor is associated with a scale and aspect ratio
- Use 3 scales and 3 aspect ratios, yielding $k = 9$ anchors at each sliding position

Method: A Region Proposal Network (RPN)

- **Translation-Invariant Anchors**




- An important property of our approach is that it is translation invariant, both in terms of the anchors and the functions that compute proposals relative to the anchors
- The translation-invariant property also reduces the model size

Part 2. Method: A Region Proposal Network (RPN)

• Multi-Scale Anchors as Regression References

- Our design of anchors presents a novel scheme for addressing multiple scales size
- As a comparison, our anchor-based method is built on a pyramid of anchors, which is more cost-efficient
- Our method classifies and regresses bounding boxes with reference to anchor boxes of multiple scales and aspect ratios

Different schemes for addressing multiple scales and sizes



- (a) Pyramids of images and feature maps are built, and the classifier is run at all scales
- (b) Pyramids of filters with multiple scales/sizes are run on the feature map
- (c) We use pyramids of reference boxes in the regression functions

- **Loss Function**

- For training RPNs, we assign a binary class label to each anchor
 - (i) The anchor/anchors with the highest Intersection-over-Union (IoU) overlap with a ground-truth box
 - (ii) An anchor that has an IoU overlap higher than 0.7 with any ground-truth box
- A single ground-truth box may assign positive labels to multiple anchors
 - Adopt the first condition for the reason that in some rare cases the second condition may find no positive sample
- Assign a negative label to a non-positive anchor if its IoU ratio is lower than 0.3 for all ground-truth boxes
 - Anchors that are neither positive nor negative do not contribute to the training objective

The multi-task loss in Fast R-CNN

$$L(\{p_i\}, \{t_i\}) = \frac{1}{N_{cls}} \sum_i L_{cls}(p_i, p_i^*) + \lambda \frac{1}{N_{reg}} \sum_i p_i^* L_{reg}(t_i, t_i^*)$$