1.

*		* { margin:0; padding:0; }
		p { color:blue; }
	class	.box { border:1px solid #333; }
#	id	#main { background:yellow; }

2.

Α	В	A B( )	ul li { color:red; }
Α	> B	АВ	nav > ul { list - style:none; }
Α	+ B	A B	h1 + p { margin - top:0; }
Α	~ B	A B	h1 ~ p { color:gray; }

3.

[attr]		[title] { color:blue; }
[attr=value]	=	<pre>input[type=text] { width:200px; }</pre>
[attr^=val]	val	a[href^='https'] { color:green; }
[attr\$=val]	val	<pre>img[src\$='.png'] { border:1px solid #99 9; }</pre>
[attr*=val]	val	div[class*='card'] { padding:10px; }

## 4. 가

:hover		<pre>button:hover { background:red; }</pre>
:focus	( )	input:focus { outline:2px solid blue; }
:first - child		li:first - child { font - weight:bold; }
:last - child		li:last - child { color:orange; }
:nth - child(n)	n	li:nth - child(2) { color:green; }
:not(sel)	가	div:not(.active) { opacity:0.5; }

## 5. 가

::before	가	p::before { content:' '; }

::after	가	p::after { content:' '; }
::first - line		p::first-line { font-weight:bold; }
::selection		p::selection { background:yellow; }

## 6.

:has()	/	<pre>article:has(img) { border:2px solid gree n; }</pre>
:is()		:is(h1,h2,h3) { color:navy; }
:where()	0	:where(section p) { margin:0; }
:focus - visible		button:focus - visible { outline:2px solid blue; }