

Poincaré GloVe: Hyperbolic Word Embeddings

International Conference on Learning Representations 2019
ICLR 19 - (2019 NLP GROUP STUDY)

Data Mining & Information Systems Lab.
Department of Computer Science and Engineering,
College of Informatics, Korea University

이영걸



Alexandru Țifrea

[ETH Zurich](#)

Verified email at student.ethz.ch

[Machine learning](#) [Natural language understa...](#)

[FOLLOW](#)

[GET MY OWN PROFILE](#)

TITLE

CITED BY

YEAR

[Poincaré GloVe: Hyperbolic Word Embeddings](#)

A Țifrea, G Bécigneul, OE Ganea
arXiv preprint arXiv:1810.06546

23

2018

[Opinion Summarization for Hotel Reviews](#)

B Cristian, A Țifrea, MC Volmer, T Rebedea

Articles 1–2 [SHOW MORE](#)

Cited by

	All	Since 2014
Citations	23	23
h-index	1	1
i10-index	1	1



???



Gary Bécigneul

PHD Researcher at ETH, [MIT](#), MPI

Verified email at mit.edu - [Homepage](#)

[Geometric Machine Learning](#) [Hyperbolic Deep Learning](#)

[FOLLOW](#)

[GET MY OWN PROFILE](#)

TITLE

CITED BY

YEAR

[Mixed-curvature Variational Autoencoders](#)

O Skopek, OE Ganea, G Bécigneul
Under Review at ICLR 2020

2019

[Constant Curvature Graph Convolutional Networks](#)

G Bachmann*, G Bécigneul*, OE Ganea
Under Review at ICLR 2020

1

2019

[A Continuous-time Perspective for Modeling Acceleration in Riemannian Optimization](#)

F Alimisis, A Orvieto, G Bécigneul, A Lucchi
Under Review at AISTATS 2020

2019

[Breaking the Softmax Bottleneck via Learnable Monotonic Pointwise Non-linearities](#)

OE Ganea, S Gelly, G Bécigneul, A Severyn
ICML 2019: International Conference on Machine Learning

1

2019

[Poincaré GloVe: Hyperbolic Word Embeddings](#)

A Tifrea*, G Bécigneul*, OE Ganea*
ICLR 2019: International Conference on Learning Representations

23

2018

[Riemannian Adaptive Optimization Methods](#)

G Bécigneul, OE Ganea
ICLR 2019: International Conference on Learning Representations

21

2018

[Escaping Flat Areas via Function-Preserving Structural Network Modifications](#)

Y Kilcher*, G Bécigneul*, T Hofmann
Submitted at ICLR 2019

2018

[Hyperbolic Neural Networks](#)

OE Ganea*, G Bécigneul*, T Hofmann
NIPS 2018: Neural Information Processing Systems

32

2018

[Hyperbolic Entailment Cones for Learning Hierarchical Embeddings](#)

OE Ganea, G Bécigneul, T Hofmann
ICML 2018: International Conference on Machine Learning

47

2018

[Parametrizing filters of a CNN with a GAN](#)

Y Kilcher*, G Bécigneul*, T Hofmann
Submitted at ICLR 2017

1

2017

[On the effect of pooling on the geometry of representations](#)


G Bécigneul
Submitted at COLT 2017

2

2017

Cited by

	All	Since 2014
Citations	128	128
h-index	4	4
i10-index	4	4



Co-authors

	Octavian Ganea MIT	>
	Thomas Hofmann Professor of Computer Science, ...	>
	Alexandru Tifrea ETH Zurich	>
	Yannic Kilcher PhD Student, ETH Zurich	>
	Sylvain Gelly Google Brain Zurich	>
	Aliaksei Severyn Google	>
	Aurelien Lucchi ETH Zurich	>
	Ondrej Skopek Software Engineer, Google	>



Octavian Ganea


[FOLLOW](#)[MIT](#)Verified email at csail.mit.edu - [Homepage](#)[Machine Learning](#) [Representation Learning](#) [Graph Representation Learning](#) [Artificial Intelligence](#)

TITLE	CITED BY	YEAR
Mixed-curvature Variational Autoencoders O Skopek, OE Ganea, G Bécigneul ICLR'20: International Conference on Learning Representations		2020
Constant Curvature Graph Convolutional Networks G Bachmann, G Bécigneul, OE Ganea https://arxiv.org/pdf/1911.05076	1	2019
Breaking the Softmax Bottleneck via Learnable Monotonic Pointwise Non-linearities OE Ganea, S Gelly, G Bécigneul, A Severyn ICML'19: International Conference on Machine Learning	1	2019
Poincaré GloVe: Hyperbolic Word Embeddings A Tifrea*, G Bécigneul*, OE Ganea* ICLR'19: International Conference on Learning Representations	23	2019
Riemannian Adaptive Optimization Methods G Bécigneul, OE Ganea ICLR'19: International Conference on Learning Representations	21	2019
Hyperbolic Neural Networks OE Ganea, G Bécigneul, T Hofmann NeurIPS'18: Conference on Neural Information Processing Systems	32	2018
Hyperbolic Entailment Cones for Learning Hierarchical Embeddings OE Ganea, G Bécigneul, T Hofmann ICML'18: International Conference on Machine Learning	47	2018
Learning and Evaluating Sparse Interpretable Sentence Embeddings V Trifonov, OE Ganea, A Potapenko, T Hofmann EMNLP'18 Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks ...	2	2018
End-to-End Neural Entity Linking N Kolitsas*, OE Ganea*, T Hofmann CoNLL'18: Conference on Computational Natural Language Learning	21	2018
Web2Text: Deep Structured Boilerplate Removal T Vogels, OE Ganea, C Eickhoff ECIR'18: European Conference on Information Retrieval	7	2018
Deep Joint Entity Disambiguation with Local Neural Attention OE Ganea, T Hofmann EMNLP'17: Conference on Empirical Methods in Natural Language Processing	71	2017
Neural Multi-Step Reasoning for Question Answering on Semi-Structured Tables T Haug, OE Ganea, P Grnarova ECIR'18: European Conference on Information Retrieval	12	2017
Probabilistic Bag-of-Hyperlinks Model for Entity Linking OE Ganea, M Ganea, A Lucchi, C Eickhoff, T Hofmann	85	2016

[GET MY OWN PROFILE](#)

Cited by

	All	Since 2014
Citations	323	323
h-index	8	8
i10-index	8	8




Co-authors

	Thomas Hofmann Professor of Computer Science, ...	>
	Gary Bécigneul PHD Researcher at ETH, MIT, MPI	>
	Carsten Eickhoff Assistant Professor, Brown Univ...	>
	Aurelien Lucchi ETH Zurich	>
	Alexandru Tifrea ETH Zurich	>
	Paulina Grnarova ETH Zurich	>
	Thijs Vogels EPFL	>
	Anna Potapenko National Research University Hig...	>
	Sylvain Gelly Google Brain Zurich	>
	Aliaksei Severyn Google	>
	Ondrej Skopek Software Engineer, Google	>

– Recap

Characteristics(?) of tree structured graph



Suppose there are b branching factors on each nodes



At **level l** , there are $(b + 1)b^l$ nodes

There are $\frac{((b+1)b^{l-2})}{b-1}$ nodes on **a level less or equal than l**


Note: the # of nodes are exponentially increasing as level l (distance to the root of the tree) increases

– Recap


선 밖의 한 점을 지나 그 직선에 평행한 직선은 단 하나만 존재한다.^[1]



– Recap




사진출처: wikipedia




Poincaré disk with 3 **ultraparallel**
(hyperbolic) straight lines




– Recap



(a) Geodesics of the Poincaré disk



(b) Embedding of a tree in \mathcal{B}^2



(c) Growth of Poincaré distance

Figure 1: (a) Due to the negative curvature of \mathcal{B} , the distance of points increases exponentially (relative to their Euclidean distance) the closer they are to the boundary. (c) Growth of the Poincaré distance $d(u, v)$ relative to the Euclidean distance and the norm of v (for fixed $\|u\| = 0.9$). (b) Embedding of a regular tree in \mathcal{B}^2 such that all connected nodes are spaced equally far apart (i.e., all black line segments have identical hyperbolic length).

– Recap




Figure 2: Two-dimensional Poincaré embeddings of transitive closure of the WORDNET mammals subtree. Ground-truth is-a relations of the original WORDNET tree are indicated via blue edges. A Poincaré embedding with $d = 5$ achieves mean rank 1.26 and MAP 0.927 on this subtree.

– Hyperbolic spaces and their Cartesian product




Figure 1: Isometric deformation φ of \mathbb{D}^2 into \mathbb{H}^2 .

$$d_{\mathbb{D}^n}(x, y) = \cosh^{-1} \left(1 + \lambda_x \lambda_y \|x - y\|_2^2 / 2 \right)$$

$$\lambda_x := 2 / (1 - \|x\|_2^2)$$

$$d_{(\mathbb{D}^n)^p}(x, y)^2 = \sum_{i=1}^p d_{\mathbb{D}^n}(x_i, y_i)^2.$$

$$d_{\mathbb{H}^2}(x, y) = \cosh^{-1} \left(1 + \|x - y\|_2^2 / (2y_1 y_2) \right)$$

– Adapting GloVe

$$X_i = \sum_k X_{ik}; P_{ij} = \tilde{X}_{ij}/X_i$$

$$J = \sum_{i,j=1}^V f(X_{ij}) \left(w_i^T \tilde{w}_j + b_i + \tilde{b}_j - \log X_{ij} \right)^2,$$

$$J = \sum_{i,j=1}^V f(X_{ij}) \left(-h(d(w_i, \tilde{w}_j)) + b_i + \tilde{b}_j - \log X_{ij} \right)^2,$$

– Connecting Gaussian Embeddings & Hyperbolic Embeddings

$$d_F \left(\mathcal{N}(\mu, \sigma^2), \mathcal{N}(\mu', \sigma'^2) \right) = \sqrt{2} d_{\mathbb{H}^2} \left((\mu/\sqrt{2}, \sigma), (\mu'/\sqrt{2}, \sigma') \right).$$

$$d_F \left(\mathcal{N}(\mu, \Sigma), \mathcal{N}(\mu', \Sigma') \right) = \sqrt{\sum_{i=1}^n 2 d_{\mathbb{H}^2} \left((\mu_i/\sqrt{2}, \sigma_i), (\mu'_i/\sqrt{2}, \sigma'_i) \right)^2}.$$

