MAR MAC PREMIUM

WHEN YOU DEMAND THE BEST.

Premium Annealed Bar Tie Data Sheet

Standard Requirements:

Mar-Mac Wire Premium Annealed Bar Ties are produced from wire that is drawn, annealed, formed, and packaged in the USA. Premium Bar Ties meet "Buy American" standards. The wire used to produce Mar-Mac Wire Premium Annealed Bar Ties conforms to the ASTM A853 specification. Premium Bar Ties are produced in 14, 15, 16, 16.5, and 17 gauge wire sizes.

Chemical Requirements:

The wire used to produce Mar-Mac Premium Annealed Bar Ties is produced using a C1006 or C1008 grade of steel as specified in ASTM A510 and ASTM A1040.

Physical Requirements:

The wire used to produce the Premium Annealed Bar Ties is annealed in a "dead soft" annealing cycle. The wire used will be annealed to a tensile range of 40,000psi to 54,000psi.

Wire Diameter:

14 Gauge		15 Gauge		16 Gauge		16.5 Gauge		17 Gauge	
Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
.079"	.081"	.071"	.073"	.060"	.064"	.057"	.059"	.053"	.055"

Packaging Requirements:

Mar-Mac Wire Premium Annealed Bar Ties are supplied in poly fiber bags and in some cases can be supplied in boxes for 1,000 count products. Premium Annealed Bar Tie products are supplied in 5,000 count bundles, 2,500 count bundles, 4 X 1,000 count bundles, and 5 X 1,000 count bundles.

Mar-Mac Wire, Inc.

229 Mar-Mac Wire Road, McBee, SC 29101 (800) 541-2461 • FAX: (843) 335-6131