
Note) Slides and example codes are available:
https://github.com/mint-lab/3dv_tutorial




An Invitation to 3D Vision: Single-View Geometry


Sunglok Choi, Assistant Professor, Ph.D.
Dept. of Computer Science and Engineering, SEOULTECH
sunglok@seoultech.ac.kr | https://mint-lab.github.io/

Getting Started with 2D

- **Image coordinate** (unit: [pixel])



- **Camera coordinate** (unit: [meter])
  - Position: Focal point
  - X/Y direction: Image coordinate
  - Z direction: Right-hand rule



Getting Started with 2D

- **2D rotation matrix**
  - Rotational direction: Right-hand rule




$$\mathrm{R}(\theta) = \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix}$$

Properties of a rotation matrix

- $\mathrm{R}^{-1} = \mathrm{R}^{\mathrm{T}}$ (orthogonal matrix)
- $\det(\mathrm{R}) = 1$


- **3D rotation matrix**
  - Rotational direction: Right-hand rule




	Cameras	Vehicles	Airplanes	Telescopes
θ_x	Tilt	Pitch	Attitude	Elevation
θ_y	Pan	Yaw	Heading	Azimuth
θ_z	Roll	Roll	Bank	Horizon

Getting Started with 2D

- **3D rotation representation** (3 DOF)
  - **3D rotation matrix** (9 parameters)
    - Notation: 3x3 matrix
      - e.g. $\mathrm{R} = \mathrm{R}_z(\theta_z)\,\mathrm{R}_y(\theta_y)\,\mathrm{R}_x(\theta_x) = \begin{bmatrix} \cos\theta_z & -\sin\theta_z & 0 \\ \sin\theta_z & \cos\theta_z & 0 \\ 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} \cos\theta_y & 0 & \sin\theta_y \\ 0 & 1 & 0 \\ -\sin\theta_y & 0 & \cos\theta_y \end{bmatrix} \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos\theta_x & -\sin\theta_x \\ 0 & \sin\theta_x & \cos\theta_x \end{bmatrix}$
    - Properties: $\mathrm{R}^{-1} = \mathrm{R}^{\mathrm{T}}$ (orthogonal matrix), $\det(\mathrm{R}) = 1$
  - **Euler angle** (3 parameters)
    - Notation: $[\theta_x, \theta_y, \theta_z]$
    - Issues: Not unique, not continuous, Gimbal lock case (loss of degree-of-freedom)






"Gimber lock" case

Image: Wikipedia

Getting Started with 2D



- **3D rotation representation** (3 DOF)
  - **Axis-angle representation** (3 parameters; a.k.a. *rotation vector*, *Rodrigues notation*)
    - Notation: $\boldsymbol{\theta} = \theta \mathbf{e}$
      - e.g. Axis (unit vector): $\mathbf{e} = [0, 0, 1]$, angle: $\theta = \pi/2 \rightarrow \boldsymbol{\theta} = [0, 0, \pi/2]$
    - Properties: Log map of SO(3), dual ($-\mathbf{e}$ with $-\theta \rightarrow \boldsymbol{\theta}$), reverse angle ($-\boldsymbol{\theta}$)
    - Note) The standard notation in OpenCV with `cv.Rodrigues()` (R ↔ rvec)
  - (Unit) **Quaternion** (4 parameters)
    - Notation: $\mathbf{q} = [q_w, q_x, q_y, q_z]$ or $[q_x, q_y, q_z, q_w]$
      - Meaning: $\mathbf{q} = \cos\frac{\theta}{2} + (e_x\mathbf{i} + e_y\mathbf{j} + e_z\mathbf{k})\sin\frac{\theta}{2}$ where $\mathbf{i}^2 = \mathbf{j}^2 = \mathbf{k}^2 = \mathbf{ijk} = -1$
    - Property: ${q_x}^2 + {q_y}^2 + {q_z}^2 + {q_w}^2 = 1$, dual ($-\mathbf{q}$), reverse angle ($\bar{\mathbf{q}}$; conjugate)

- Note) 3D rotation conversion
  - Python: `scipy.spatial.transform.Rotation`
  - Web apps: NinjaCalc, Glowbuzzer, Andre Gaschler

Image: Wikipedia

Getting Started with 2D

- Example) **3D rotation conversion** [3d_rotation_conversion.py]

```python
import numpy as np
from scipy.spatial.transform import Rotation

# The given 3D rotation
euler = (45, 30, 60) # Unit: [deg] in the XYZ-order


# Generate 3D rotation object
robj = Rotation.from_euler('zyx', euler[::-1], degrees=True)

# Print other representations
print('\n## Euler Angle (ZYX)')
print(np.rad2deg (robj.as_euler('zyx'))) # [60, 30, 45] [deg] in the ZYX-order
print('\n## Rotation Matrix')
print(robj.as_matrix())
print('\n## Rotation Vector')
print(robj.as_rotvec())                  # [0.97, 0.05, 1.17]
print('\n## Quaternion (XYZW)')
print(robj.as_quat())                    # [0.44, 0.02, 0.53, 0.72]
```

Getting Started with 2D

- **Similarity**


$\frac{h}{H} = \frac{f}{Z}$ or $\frac{h}{f} = \frac{H}{Z} \rightarrow h = f\frac{H}{Z}$



Getting Started with 2D

- **Point translation**

$\mathbf{x}' = \mathbf{x} + \mathbf{t}$



Getting Started with 2D

- **Coordinate translation**

  Valid for the following point transformation?


  $\mathbf{x}' = \mathbf{x} + \mathbf{t}'$?


  No!

  The **inverse** of point translation

  $\mathbf{x} = \mathbf{x}' + \mathbf{t}'$

  $\mathbf{x}' = \mathbf{x} - \mathbf{t}'$






Getting Started with 2D

- **Point transformation**

$$\mathbf{x}' = R\mathbf{x} + \mathbf{t} = [R \mid \mathbf{t}] \begin{bmatrix} \mathbf{x} \\ 1 \end{bmatrix}$$




Getting Started with 2D

- **Coordinate transformation**

  Valid for the following point transformation?

  $\mathbf{x}' = \mathrm{R}'\mathbf{x} + \mathbf{t}'$?



Getting Started with 2D

- **Coordinate transformation**

  Valid for the following point transformation?

  $\mathbf{x}' = \mathrm{R}'\mathbf{x} + \mathbf{t}'$?

  No!

  The **inverse** of point transformation

  $\mathbf{x} = \mathrm{R}'\mathbf{x}' + \mathbf{t}'$

  $\downarrow \mathrm{R}'^{\mathsf{T}}(\mathbf{x} - \mathbf{t}') = \mathbf{x}'$

  $\mathbf{x}' = \mathrm{R}\mathbf{x} + \mathbf{t}$ ($\mathrm{R} = \mathrm{R}'^{\mathsf{T}}$ and $\mathbf{t} = -\mathrm{R}'^{\mathsf{T}}\mathbf{t}'$)





Table of Contents: Single-view Geometry

- **Getting Started with 2D**
  - Coordinate, rotation matrix, 3D rotation representation (rotation vector)
  - Similarity
  - Point transformation, coordinate transformation: inverse relationship
- **Camera Projection**
  - Pinhole camera model
  - Geometric distortion models
- **Camera Calibration**
- **Absolute Camera Pose Estimation**




The Cyclops, gouache and oil by Odilon Redon

Pinhole Camera Model

- **Pinhole camera model**



A large-scale camera obscura
at San Francisco, California



A modern-day camera obscura



An Image in a camera obscura
at Portslade, England





Image: Wikipedia, PNG EGG

Pinhole Camera Model

- **Real camera with a lens**
  - Q) Why does a camera use a lens? To acquire more light rays



- **Pinhole camera model**





Image: PNG EGG


Pinhole Camera Model

- **Pinhole camera model**
  - In conclusion (without lens distortion), $\mathbf{x} = \mathrm{P}\mathbf{X}$ $(\mathrm{P} = \mathrm{K}[\mathrm{R} \mid \mathbf{t}])$




Pinhole Camera Model

- [Pinhole camera model]




Pinhole Camera Model

- [Pinhole camera model]




Pinhole Camera Model

- Example) **Simple camera calibration**
  - Unknown: Focal length (f) of the camera (unit: [pixel])
  - Given: The observed object height (h) on the image plane (unit: [pixel])
  - Assumptions
    - The object height (H) and distance (Z) from the camera are known.
    - The object is aligned with the image plane.



Pinhole Camera Model

- Example) **Simple depth estimation** (object localization)
  - Unknown: Object distance (Z) from the camera (unit: [m])
  - Given: The observed object height (h) on the image plane (unit: [pixel])
  - Assumptions
    - The object height (H) and focal length (f) are known.
    - The object is aligned with the image plane.




$$\therefore Z = \frac{f}{h} H$$

Pinhole Camera Model

- Example) **Simple object measurement**
  - Unknown: Object height (H) (unit: [m])
  - Given: The observed object height (h) on the image plane (unit: [pixel])
  - Assumptions
    - The object distance (Z) from the camera and focal length (f) are known.
    - The object is aligned with the image plane.


$$\therefore H = \frac{h}{f} Z$$




Pinhole Camera Model



- **Vanishing points**
  - A point on the image plane where mutually parallel lines in 3D space
    - A vector to the vanishing point is parallel to the lines.
    - A vector to the vanishing point is parallel to the reference plane made by the lines.





Pinhole Camera Model



- **Vanishing points**
  - A point on the image plane where mutually parallel lines in 3D spac
    - A vector to the vanishing point is parallel to the lines.
    - A vector to the vanishing point is parallel to the reference plane made by the lines.






Image: Wikipedia

Pinhole Camera Model




- Example) **Simple camera pose estimation**
  - Unknown: Tilt angle (θ_x) of the camera w.r.t. the reference plane (unit: [rad])
  - Given: A vanishing point (x, y) from the reference plane
  - Assumptions
    - The focal length (f) is known.
    - The principal point (c_x, c_y) is known or set to the image center.
    - The camera has no roll, $\theta_z = 0$.
  - Note) The tilt angle in this page is defined as the opposite direction of the common notation.


$$\therefore \theta_x = \tan^{-1}\frac{c_y - y}{f}$$



Pinhole Camera Model



- Example) **Simple camera pose estimation**
  - Unknown: Tilt angle (θ_x) of the camera w.r.t. the reference plane (unit: [rad])
  - Given: A vanishing point (x, y) from the reference plane
  - Assumptions
    - The focal length (f) is known.
    - The principal point (c_x, c_y) is known or set to the image center.
    - The camera has no roll, $\theta_z = 0$.
  - Note) The pan angle (θ_y) with respect to the rail can be calculated similarly using x instead of y.




Pinhole Camera Model



- Example) **Object localization #1**
  - Unknown: Object position and height (unit: [m])
  - Given: The object's contact and head points on the image (unit: [pixel])
  - Assumptions
    - The focal length, principal points, and camera height are known.
    - The object is on the reference plane.
    - The camera is aligned to the reference plane.

$$\therefore Z = \frac{\bar{z}}{\bar{y}} L \qquad X = \frac{\bar{x}}{\bar{y}} L \qquad H = \left(\frac{\bar{y}}{\bar{z}} - \frac{\bar{y}'}{\bar{z}'} \right) Z$$

$$\begin{bmatrix} \bar{x} \\ \bar{y} \\ \bar{z} \end{bmatrix} = \begin{bmatrix} x - c_x \\ y - c_y \\ f \end{bmatrix}$$



Pinhole Camera Model




- Example) **Object localization #2**
  - Unknown: Object position and height (unit: [m])
  - Given: The object's contact and head points on the image (unit: [pixel])
  - Assumptions
    - The focal length, principal points, and camera height are known.
    - The object is on the reference plane.
    - ~~The camera is aligned to the reference plane.~~ The camera orientation (R) is known.

$$\therefore Z = \frac{\bar{z}}{\bar{y}} L \qquad X = \frac{\bar{x}}{\bar{y}} L \qquad H = \left(\frac{\bar{y}}{\bar{z}} - \frac{\bar{y}'}{\bar{z}'} \right) Z$$


$\because$ same camera center

$$\begin{bmatrix} \bar{x} \\ \bar{y} \\ \bar{z} \end{bmatrix} = \mathrm{R}^{\mathsf{T}} \begin{bmatrix} x - c_x \\ y - c_y \\ f \end{bmatrix}$$



Pinhole Camera Model

- Example) **Object localization #2** `[object_localization.py]`



Pinhole Camera Model

- Example) **Object localization #2** [object_localization.py]

```
if __name__ == '__main__':
    ...
    while True:
        img_copy = img.copy()
        if mouse_state['xy_e'][0] > 0 and mouse_state['xy_e'][1] > 0:
            # Calculate object location and height
            c = R.T @ [mouse_state['xy_s'][0] - cx, mouse_state['xy_s'][1] - cy, f]
            h = R.T @ [mouse_state['xy_e'][0] - cx, mouse_state['xy_e'][1] - cy, f]
            if c[1] < 1e-6: # Skip the degenerate case (beyond the horizon)
                continue
            X = c[0] / c[1] * L                 # Object location X [m]
            Z = c[2] / c[1] * L                 # Object location Z [m]
            H = (c[1] / c[2] - h[1] / h[2]) * Z # Object height [m]

            # Draw the head/contact points and location/height
            cv.line(img_copy, mouse_state['xy_s'], mouse_state['xy_e'], (0, 0, 255), 2)
            cv.circle(img_copy, mouse_state['xy_e'], 4, (255, 0, 0), -1) # Head point
            cv.circle(img_copy, mouse_state['xy_s'], 4, (0, 255, 0), -1) # Contact point
            info = f'X: {X:.3f}, Z: {Z:.3f}, H: {H:.3f}'
            cv.putText(img_copy, info, np.array(mouse_state['xy_s']) + (-20, 20), cv.FONT_HERSHEY_DUPLEX, 0.6, (0, 2

        cv.imshow('Object Localization and Measurement', img_copy)
        key = cv.waitKey(10)
        if key == 27: # ESC
            break
```

$$\begin{bmatrix}\bar{x}\\ \bar{y}\\ \bar{z}\end{bmatrix} = \mathrm{R}^{\mathrm{T}}\begin{bmatrix}x-c_x\\ y-c_y\\ f\end{bmatrix}$$

$$X = \frac{\bar{x}}{\bar{y}}L \quad Z = \frac{\bar{z}}{\bar{y}}L \quad H = \left(\frac{\bar{y}}{\bar{z}} - \frac{\bar{y}'}{\bar{z}'}\right)Z$$


Pinhole Camera Model

- **Camera matrix** K

$$\mathbf{x} = \begin{bmatrix} x \\ y \end{bmatrix} = f \begin{bmatrix} X/Z \\ Y/Z \end{bmatrix} + \begin{bmatrix} c_x \\ c_y \end{bmatrix} \rightarrow \mathbf{x} = \mathrm{K}\hat{\mathbf{x}} \text{ where } \mathrm{K} = \begin{bmatrix} f & 0 & c_x \\ 0 & f & c_y \\ 0 & 0 & 1 \end{bmatrix}, \ \mathbf{x} = \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}, \text{ and } \hat{\mathbf{x}} = \begin{bmatrix} X/Z \\ Y/Z \\ 1 \end{bmatrix}$$

Simplified as $\mathrm{K} = \begin{bmatrix} f & 0 & w/2 \\ 0 & f & h/2 \\ 0 & 0 & 1 \end{bmatrix}$ (w: image width, h: image height)


Generalized as $\mathrm{K} = \begin{bmatrix} f_x & s & c_x \\ 0 & f_y & c_y \\ 0 & 0 & 1 \end{bmatrix}$ (s: skew parameter)



Pinhole Camera Model

- **Homogeneous coordinates** (a.k.a. projective coordinates)
  - It describes an n-dimensional project space as $n+1$-dimensional coordinate system.
  - It has a non-conventional equivalence relationship: $(x_1, x_2, \ldots, x_{n+1}) \sim (\lambda x_1, \lambda x_2, \ldots, \lambda x_{n+1})$ such that $(0 \neq \lambda \in \mathbb{R})$.
    - e.g. (5, 12) is written as (5, 12, 1) which is also equal to (10, 24, 2) or (15, 36, 3) or …
  - On the previous slide, $\mathbf{x} = \mathrm{K}\hat{\mathbf{x}}$ where $\mathrm{K} = \begin{bmatrix} f & 0 & c_x \\ 0 & f & c_y \\ 0 & 0 & 1 \end{bmatrix}$, $\mathbf{x} = \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$, and $\hat{\mathbf{x}} = \begin{bmatrix} X/Z \\ Y/Z \\ 1 \end{bmatrix}$


$$\mathbf{x}' = \mathrm{K}\mathbf{X} \text{ where } \mathrm{K} = \begin{bmatrix} f & 0 & c_x \\ 0 & f & c_y \\ 0 & 0 & 1 \end{bmatrix}, \ \mathbf{x}' = \begin{bmatrix} x' \\ y' \\ w' \end{bmatrix}, \text{ and } \mathbf{X} = \begin{bmatrix} X \\ Y \\ Z \end{bmatrix} \quad (\text{Note: } \mathbf{x} = \tfrac{1}{w'}\mathbf{x}')$$




Pinhole Camera Model

- **Why homogeneous coordinates?**
  - An affine transformation ($\mathbf{y} = \mathbf{A}\mathbf{x} + \mathbf{b}$) is formulated by a single matrix multiplication.
  - A point at infinity (a.k.a. ideal point) is numerically represented by $w = 0$.
  - A point and line ($ax + by + c = 0$) can be beautifully described as like $\mathbf{l}^{\mathsf{T}}\mathbf{x} = 0$ or $\mathbf{x}^{\mathsf{T}}\mathbf{l} = 0$ ($\mathbf{l} = [a, b, c]^{\mathsf{T}}$).
    - Intersection of two lines: $\mathbf{x} = \mathbf{l}_1 \times \mathbf{l}_2$
    - A line by two points: $\mathbf{l} = \mathbf{x}_1 \times \mathbf{x}_2$

    } *Duality* of a point and line
  - A light ray (line at the camera center) is observed as a point on the image plane.
    - A plane at the camera center is observed as a line on the image plane.
    - A conic whose peak is at the camera center is observed as a conic section on the image plane.






Pinhole Camera Model

- **Projection matrix** P
  - A point $\mathbf{X}$ is not based on the camera coordinate so that it needs to be transformed into the camera coordinate.

$$\mathbf{X}' = \mathrm{R}\mathbf{X} + \mathbf{t} \;\rightarrow\; \mathbf{X}' = [\mathrm{R} \mid \mathbf{t}] \begin{bmatrix} \mathbf{X} \\ 1 \end{bmatrix}$$



  - The whole camera projection from the world coordinate to the image coordinate:

$$\mathbf{x} = \mathrm{K}\mathbf{X}' = \mathrm{K}(\mathrm{R}\mathbf{X} + \mathbf{t}) = \mathrm{K}\,[\mathrm{R} \mid \mathbf{t}] \begin{bmatrix} \mathbf{X} \\ 1 \end{bmatrix}$$


→ $\mathbf{x} = \mathrm{P}\mathbf{X}$ where $\mathrm{P} = \mathrm{K}\,[\mathrm{R} \mid \mathbf{t}]$ (3x4 matrix), $\mathbf{x}$ and $\mathbf{X}$ in homogeneous coordinates

  - Note) The camera pose (R^{T} and $-\mathrm{R}^{\mathrm{T}}\mathbf{t}$) can be derived from the inverse of point transformation (R and $\mathbf{t}$).


$$\mathrm{T}^{-1} = \begin{bmatrix} \mathrm{R} & \mathbf{t} \\ 0 & 1 \end{bmatrix}^{-1} = \begin{bmatrix} \mathrm{R}^{\mathrm{T}} & -\mathrm{R}^{\mathrm{T}}\mathbf{t} \\ 0 & 1 \end{bmatrix}$$


Pinhole Camera Model


A point cloud: `data/box.xyz`





- Example) **Image formation** `[image_formation.py]`











Pinhole Camera Model

- Example) **Image formation** [image_formation.py]

```python
from scipy.spatial.transform import Rotation

# The given camera configuration: Focal length, principal point, image resolution, position, and orientation
f, cx, cy, noise_std = 1000, 320, 240, 1
img_res = (640, 480)
cam_pos = [[0, 0, 0], [-2, -2, 0], [2, 2, 0], [-2, 2, 0], [2, -2, 0]]          # Unit: [m]
cam_ori = [[0, 0, 0], [-15 , 15, 0], [15, -15, 0], [15, 15, 0], [-15, -15, 0]] # Unit: [deg]

# Load a point cloud
X = np.loadtxt('../data/box.xyz') # Size: N x 3

# Generate images for each camera pose
K = np.array([[f, 0, cx], [0, f, cy], [0, 0, 1]])
for i, (pos, ori) in enumerate(zip(cam_pos, cam_ori)):
    # Derive 'R' and 't'
    Rc = Rotation.from_euler('zyx', ori[::-1], degrees=True).as_matrix()
    R = Rc.T
    t = -Rc.T @ pos

    # Project the points (Alternative: `cv.projectPoints()`)
    x = K @ (R @ X.T + t.reshape(-1, 1)) # Size: 3 x N
    x /= x[-1]

    # Add Gaussian noise
    noise = np.random.normal(scale=noise_std, size=(2, len(X)))
    x[0:2,:] += noise
```

$$\mathbf{K} = \begin{bmatrix} f & 0 & c_x \\ 0 & f & c_y \\ 0 & 0 & 1 \end{bmatrix}$$

$$\mathbf{R} = \mathrm{R}_c^{\mathrm{T}} \text{ and } \mathbf{t} = -\mathrm{R}_c^{\mathrm{T}}\mathbf{t}_c$$

$$\mathbf{x} = \mathrm{K}(\mathrm{R}\mathbf{X} + \mathbf{t})$$

$$\mathbf{x} = \begin{bmatrix} x/w \\ y/w \\ w/w \end{bmatrix}$$

Geometric Distortion Models



Q) How to represent such geometric distortion?

- A camera lens generates geometric distortion, which can be approximated as a nonlinear function f_d.
- Geometric distortion models f_d are mostly defined on the normalized image plane.
- Camera projection with geometric distortion: $\mathbf{x} = \mathrm{proj}(\mathbf{X}; \mathrm{K}, \mathrm{R}, \mathbf{t}, d)$ where d is a set of distortion coefficients.

Note) $\mathbf{x} = \mathrm{K}(\mathrm{R}\mathbf{X} + \mathbf{t})$ without distortion and normalization

$$\mathbf{X} = \begin{bmatrix} X \\ Y \\ Z \end{bmatrix} \longrightarrow \mathbf{X}' = \mathrm{R}\mathbf{X} + \mathbf{t} \longrightarrow \hat{\mathbf{x}} = \begin{bmatrix} \hat{x} \\ \hat{y} \end{bmatrix} = \begin{bmatrix} X'/Z' \\ Y'/Z' \end{bmatrix} \longrightarrow \hat{\mathbf{x}}_d = f_d(\hat{\mathbf{x}}) \longrightarrow \mathbf{x} = \begin{bmatrix} x \\ y \end{bmatrix} = \begin{bmatrix} f_x \hat{x}_d + c_x \\ f_y \hat{y}_d + c_y \end{bmatrix}$$

3D point (the world coordinate)	3D point (the camera coordinate)	2D point (the normalized image plane)	**geometric distortion**	pinhole camera projection

$$\mathbf{x} = \mathrm{proj}(\mathbf{X}; \mathrm{K}, \mathrm{R}, \mathbf{t}, d)$$

Image: Shawn Becker


Image: Camera Calibration Toolbox for MATLAB, Wikipedia, MathWorks

Geometric Distortion Models


- **Polynomial distortion model** (a.k.a. Brown-Conrady model; 1919)

$$\begin{bmatrix}\hat{x}_d \\ \hat{y}_d\end{bmatrix} = (1 + k_1 r^2 + k_2 r^4 + \cdots)\begin{bmatrix}\hat{x} \\ \hat{y}\end{bmatrix} + (1 + p_3 r^2 + p_4 r^4 + \cdots)\begin{bmatrix}2p_1\hat{x}\hat{y} + p_2(r^2 + 2\hat{x}^2) \\ 2p_2\hat{x}\hat{y} + p_1(r^2 + 2y^2)\end{bmatrix} \quad \text{where} \quad r^2 = \hat{x}^2 + \hat{y}^2$$


  - OpenCV (default): `cv.projectPoints()` ↔ `cv.undistortPoints()`



barrel dist. (-)




pincushion dist. (+)




mustache dist.

Radial distortion




Pixel error = [0.1174, 0.1159]
Focal Length = (657.303, 657.744) +/- [0.2849, 0.2894]
Principal Point = (302.717, 242.334) +/- [0.5912, 0.5571]
Skew = 0.0004198 +/- 0.0001905
Radial coefficients = (-0.2535, 0.1187, 0) +/- [0.00231, 0.009418, 0]
Tangential coefficients = (-0.0002789, 5.174e-005) +/- [0.0001217, 0.0001208]

Tangential distortion




Pixel error = [0.1174, 0.1159]
Focal Length = (657.303, 657.744) +/- [0.2849, 0.2894]
Principal Point = (302.717, 242.334) +/- [0.5912, 0.5571]
Skew = 0.0004198 +/- 0.0001905
Radial coefficients = (-0.2535, 0.1187, 0) +/- [0.00231, 0.009418, 0]
Tangential coefficients = (-0.0002789, 5.174e-005) +/- [0.0001217, 0.0001208]




Why?
Lens and sensor are not parallel.
(usually negligible)

Geometric Distortion Models

- Example) **Geometric distortion visualization** [distortion_visualization.py]





Geometric Distortion Models

- Example) **Geometric distortion visualization** [distortion_visualization.py]

```
# The initial camera configuration
img_w, img_h = (640, 480)
K = np.array([[800, 0, 320],
              [0, 800, 240],
              [0, 0, 1.]])
dist_coeff = np.array([-0.2, 0.1, 0, 0])
grid_x, grid_y, grid_z = (-18, 19), (-15, 16), 20

obj_pts = np.array([[x, y, grid_z] for y in range(*grid_y) for x in range(*grid_x)], dtype=np.float32)
while True:
    # Project 3D points with/without distortion
    dist_pts, _ = cv.projectPoints(obj_pts, np.zeros(3), np.zeros(3), K, dist_coeff)
    zero_pts, _ = cv.projectPoints(obj_pts, np.zeros(3), np.zeros(3), K, np.zeros(4))

    # Draw vectors
    img_vector = np.full((img_h, img_w, 3), 255, dtype=np.uint8)
    for zero_pt, dist_pt in zip(zero_pts, dist_pts):
        cv.line(img_vector, np.int32(zero_pt.flatten()), np.int32(dist_pt.flatten()), (255, 0, 0))
    for pt in dist_pts:
        cv.circle(img_vector, np.int32(pt.flatten()), 2, (0, 0, 255), -1)

    # Draw grids
    img_grid = np.full((img_h, img_w, 3), 255, dtype=np.uint8)
    dist_pts = dist_pts.reshape(len(range(*grid_y)), -1, 2)
    for pts in dist_pts:
        cv.polylines(img_grid, [np.int32(pts)], False, (0, 0, 255))
```

Geometric Distortion Models


- **Fisheye lens model** (a.k.a. Kannala-Brandt model; T-PAMI 2006)

$$\begin{bmatrix}\hat{x}_d \\ \hat{y}_d\end{bmatrix} = (1 + k_1\theta^2 + k_2\theta^4 + \cdots)\frac{\theta}{r}\begin{bmatrix}\hat{x} \\ \hat{y}\end{bmatrix} \quad \text{where} \quad r^2 = \hat{x}^2 + \hat{y}^2 \quad \text{and} \quad \theta = \tan^{-1} r$$


  - The fisheye lens model can describe strong barrel distortion especially around image boundaries.
  - OpenCV: `cv.fisheye.projectPoints()` ↔ `cv.fisheye.undistortPoints()`



Original fisheye image



Polynomial distortion model




Fisheye lens model

Image: OpenCV


Geometric Distortion Models

- More *parametric* distortion models


Brown-Conrady




Kannala-Brandt




Unified Camera



Field of View



Extended Unified Camera



Double Sphere




Image: Lochman et al., "BabelCalib: A Universal Approach to Calibrating Central Cameras", ICCV, 2021 Homepage

Geometric Distortion Models

- **Geometric distortion correction**
  - Input: The original image
  - Output: Its rectified image (without geometric distortion)
  - Given: Its camera matrix and distortion coefficients
  - Solutions for the polynomial distortion model
    - OpenCV `cv.undistort()` and `cv.undistortPoints()` (Note: included in `imgproc` module)
      ↔ `cv.projectPoints()` (Note: included in `calib3d` module)






Image: Shawn Becker

Geometric Distortion Models

- Example) **Geometric distortion correction** `[distortion_correction.py]`







Geometric Distortion Models

- Example) **Geometric distortion correction** [distortion_correction.py]

```
# The given video and calibration data
video_file = '../data/chessboard.avi'
K = np.array([[432.7390364738057, 0, 476.0614994349778],
              [0, 431.2395555913084, 288.7602152621297],
              [0, 0, 1]]) # Derived from `camera_calibration.py`
dist_coeff = np.array([-0.2852754904152874, 0.1016466459919075, -0.0004420196146339175, ...])

# Open a video
video = cv.VideoCapture(video_file)


# Run distortion correction
show_rectify = True
map1, map2 = None, None
while True:
    # Read an image from the video
    valid, img = video.read()
    ...

    # Rectify geometric distortion (Alternative: `cv.undistort()`)
    info = "Original"
    if show_rectify:
        if map1 is None or map2 is None:
            map1, map2 = cv.initUndistortRectifyMap(K, dist_coeff, None, None, (img.shape[1], img.shape[0]), cv.CV_3
        img = cv.remap(img, map1, map2, interpolation=cv.INTER_LINEAR)
        info = "Rectified"
    cv.putText(img, info, (10, 25), cv.FONT_HERSHEY_DUPLEX, 0.6, (0, 255, 0))
```


Image: Ishikawa Group Lab

Geometric Distortion Models


- Example) **Geometric distortion correction with virtual PTZ** `[fisheye_virtual_ptz.py]`



Fisheye camera
(Equidistance model)



Pinhole camera
(Perspective model)



+ **Z**oom (FOV)

Geometric Distortion Models

- Example) **Geometric distortion correction with virtual PTZ** [fisheye_virtual_ptz.py]

```
# The given fisheye image and camera model assumptions
fisheye_file = '../data/fisheye-blog-pics_09.jpg'
fisheye_fov_deg = 180.0

# Open a fisheye image
fisheye_img = cv.imread(fisheye_file)
...
fisheye_f = (img_w / 2) / np.deg2rad(fisheye_fov_deg / 2) # Equidistant model: f = r / theta
fisheye_K = np.array([[fisheye_f, 0, img_cx], [0, fisheye_f, img_cy], [0, 0, 1]], dtype=np.float64)
fisheye_D = np.zeros((4, 1), dtype=np.float64)
...

need_to_update = True
map1, map2 = None, None
while True:
     if need_to_update:
        # Generate the undistortion maps for the current parameters (Alternative: `cv.fisheye.undistortImage()`)
              undist_f = (img_w / 2) / np.tan(np.deg2rad(undist_fov_deg / 2)) # Perspective model: f = r / tan(theta
              undist_K = np.array([[undist_f, 0, img_cx], [0, undist_f, img_cy], [0, 0, 1]], dtype=np.float64)
              undist_R = Rotation.from_euler('zxy', [undist_roll_deg, undist_tilt_deg, undist_pan_deg], degrees=True
              map1, map2 = cv.fisheye.initUndistortRectifyMap(fisheye_K, fisheye_D, undist_R, undist_K, (img_w, img_
              need_to_update = False

    # Generate the undistorted image and show the image
     assert map1 is not None and map2 is not None
     undist_img = cv.remap(fisheye_img, map1, map2, interpolation=cv.INTER_LINEAR, borderMode=cv.BORDER_CONSTANT)
```

Camera Projection

Simplification *without* consideration of *geometric distortion*

- **Camera parameters**

$$\mathbf{x} = \text{proj}(\mathbf{X}; \mathrm{K}, \mathrm{R}, \mathbf{t}, d)$$

~ projection matrix P


~ $\mathbf{x} = \mathrm{P}\mathbf{X} = \mathrm{K}\,[\mathrm{R} \mid \mathbf{t}]\mathbf{X}$

~ camera matrix K

~ point transformation R and $\mathbf{t}$

  - **Intrinsic parameters**
    - e.g. Focal length, principal point, skew, *geometric distortion coefficient*, …
  - **Extrinsic parameters**
    - e.g. Rotation and translation

- A **camera projection model** *maps* a **3D point** (metric) in the 3D world *to* a **2D point** (pixel) on the image.



$$\mathbf{X}' = \mathrm{R}\mathbf{X} + \mathbf{t}$$


$$\mathbf{x} = \mathrm{K}\,\mathbf{X}'$$

$$\hat{\mathbf{x}}' = \mathrm{K}^{-1}\mathbf{x}$$

→ A **camera projection model** *interprets* a **pixel** on the image *as* its physical **ray** in the 3D world.

Camera Calibration


- **Camera calibration**
  - Unknown: Intrinsic + extrinsic parameters (5* + 6 DOF)
    - Note) The number of intrinsic parameters* can vary depending on user configuration.
  - Given: 3D points $\mathbf{X}_1$, $\mathbf{X}_2$, …, $\mathbf{X}_n$ and their projected points $\mathbf{x}_1$, $\mathbf{x}_2$, …, $\mathbf{x}_n$
  - Constraints: n x projection $\mathbf{x}_i = \mathrm{K}\,[\,\mathrm{R}\,|\,\mathbf{t}\,]\,\mathbf{X}_i$




Camera Calibration


- **Camera calibration**
  - Unknown: Intrinsic + m x extrinsic parameters (5* + m x 6 DOF)
  - Given: 3D points $\mathbf{X}_1$, $\mathbf{X}_2$, …, $\mathbf{X}_n$ and their projected points, $\mathbf{x}_i^j$, on the jth image
    - Note) m: the number of images, n: the number of 3D points
  - Constraints: m x n x projection $\mathbf{x}_i^j = \mathrm{proj}(\mathbf{X}_i; \mathrm{K}, \mathrm{R}_j, \mathbf{t}_j, d) \sim \mathrm{K}\left[\,\mathrm{R}_j \,|\, \mathbf{t}_j\,\right]\mathbf{X}_i$
  - Solutions [more]
    - OpenCV: `cv.calibrateCamera()` and `cv.initCameraMatrix2D()`
    - Kalibr: A ROS-based calibration tool for multi-camera, visual-inertia, and rolling shutter cameras
    - MINT Camera Calibration Toolbox: A generalized camera calibration with image/model selection
  - Note) How to get calibration boards

    → Print out the pattern and stick it on a hard board
    - Pattern Generator, calib.io
    - Calibration Checkerboard Collection, Mark Jones




Camera Calibration






- Tip) **How can we acquire good calibration images?**
  1. **The pattern board must be perfectly flat.**
     - Any curvature or bending introduces errors in a 3D point $\mathbf{X}_i$.
  2. **Keep the pattern board or camera stationary during image capture.**
     - Motion blur introduces observation noise to a 2D image point $\mathbf{x}_i^j$.
  3. **Take a sufficient numbers of images (>10-20) with diverse poses and coverage.**
     - Similarly to machine learning, more data and wider coverage will result in more accurate camera parameters.
     - If the number of images is limited, it is better to reduce the complexity of the camera model (e.g. setting the principal point at the image center).
  4. **Capture images where the pattern occupies a large portion of the image.**
     - Small pattern observation leads to insufficient coverage and ambiguity.
  5. **Do not capture images only* with the camera and board perfectly parallel.**
     - Intrinsic parameters are more accurately derived from perspective cues such as vanishing points.



Camera Calibration


- Example) **Camera calibration** [camera_calibration.py]



Note) **Field-of-view (FOV)** = focal length (w/o distortion)

- Horizontal: $2 \times \tan^{-1} \frac{w/2}{f_x} = 96°$

- Vertical: $2 \times \tan^{-1} \frac{h/2}{f_y} = 64°$




```
## Camera Calibration Results
* The number of selected images = 22
* RMS error = 0.473353
* Camera matrix (K) =
  [432.7390364738057, 0, 476.0614994349778]
  [0, 431.2395555913084, 288.7602152621297]
  [0, 0, 1]
* Distortion coefficient (k1, k2, p1, p2, k3, ...) =
  [-0.2852754904152874, 0.1016466459919075, -0.0004420196146339175, 0.0001149909868437517, -0.01803978785585194]
```

Note) Close to the center of the image, (480, 270)

Note) Close to zero (usually negligible)

Camera Calibration

- Example) **Camera calibration** [camera_calibration.py]

```
def select_img_from_video(video_file, board_pattern, select_all=False, wait_msec=10):
    # Open a video
    video = cv.VideoCapture(video_file)

    # Select images
    img_select = []
    ...
    return img_select

def calib_camera_from_chessboard(images, board_pattern, board_cellsize, K=None, dist_coeff=None, calib_flags=None):
    # Find 2D corner points from given images
    img_points = []
    for img in images:
        gray = cv.cvtColor(img, cv.COLOR_BGR2GRAY)
        complete, pts = cv.findChessboardCorners(gray, board_pattern)
        if complete:
            img_points.append(pts)
    assert len(img_points) > 0, 'There is no set of complete chessboard points!'

    # Prepare 3D points of the chess board
    obj_pts = [[c, r, 0] for r in range(board_pattern[1]) for c in range(board_pattern[0])]
    obj_points = [np.array(obj_pts, dtype=np.float32) * board_cellsize] * len(img_points) # Must be `np.float32`


    # Calibrate the camera
    return cv.calibrateCamera(obj_points, img_points, gray.shape[::-1], K, dist_coeff, flags=calib_flags)
```

$\mathbf{x}_i^j$

$\mathbf{X}_i$

Absolute Camera Pose Estimation

- **Absolute camera pose estimation** (perspective-n-point; PnP)
  - Unknown: Camera pose R and $\mathbf{t}$ (6 DOF)
  - Given: 3D points $\mathbf{X}_1$, $\mathbf{X}_2$, …, $\mathbf{X}_n$, their projected points $\mathbf{x}_1$, $\mathbf{x}_2$, …, $\mathbf{x}_n$, and camera matrix K
  - Constraints: n x projection $\mathbf{x}_i = \mathrm{K}\,[\,\mathrm{R}\,|\,\mathbf{t}\,]\,\mathbf{X}_i$
  - Solutions ($n \geq 3$) → 3-point algorithm
    - OpenCV: `cv.solvePnP()` and `cv.solvePnPRansac()`



Absolute Camera Pose Estimation

- Example) **Pose estimation (chessboard)** `[pose_estimation_chessboard.py]`

- Prepare a 3D box (AR model)
- Prepare 3D points (chessboard)

↓


- Grab an image
- Find a chessboard on the image

↓


[Camera pose estimation]
- Estimate camera pose using `cv.solvePnP()`

↓

[AR rendering]
- Draw the 3D box on the image using `cv.projectPoints()`



Absolute Camera Pose Estimation



- Example) **Pose estimation (chessboard)** [pose_estimation_chessboard.py]

```
# Open a video
video = cv.VideoCapture(video_file)

# Prepare a 3D box for simple AR
box_lower = board_cellsize * np.array([[4, 2,  0], [5, 2,  0], [5, 4,  0], [4, 4,  0]])
box_upper = board_cellsize * np.array([[4, 2, -1], [5, 2, -1], [5, 4, -1], [4, 4, -1]])

# Prepare 3D points on a chessboard
obj_points = board_cellsize * np.array([[c, r, 0] for r in range(board_pattern[1]) for c in range(board_pattern[0])]


# Run pose estimation
while True:
    # Read an image from the video
    valid, img = video.read()
    if not valid:
        break

    # Estimate the camera pose
    success, img_points = cv.findChessboardCorners(img, board_pattern, flags=board_criteria)
    if success:
        ret, rvec, tvec = cv.solvePnP(obj_points, img_points, K, dist_coeff)

        # Draw the box on the image
        ...

    # Show the image and process the key event
```

Absolute Camera Pose Estimation



- Example) **Pose estimation (chessboard)** [pose_estimation_chessboard.py]

```
# Open a video
# Prepare a 3D box for simple AR
# Prepare 3D points on a chessboard

# Run pose estimation
while True:
    # Read an image from the video


    # Estimate the camera pose
    success, img_points = cv.findChessboardCorners(img, board_pattern, flags=board_criteria)
    if success:
        ret, rvec, tvec = cv.solvePnP(obj_points, img_points, K, dist_coeff)

        # Draw the box on the image
        line_lower, _ = cv.projectPoints(box_lower, rvec, tvec, K, dist_coeff)
        line_upper, _ = cv.projectPoints(box_upper, rvec, tvec, K, dist_coeff)
        cv.polylines(img, [np.int32(line_lower)], True, (255, 0, 0), 2)
        cv.polylines(img, [np.int32(line_upper)], True, (0, 0, 255), 2)
        for b, t in zip(line_lower, line_upper):
            cv.line(img, np.int32(b.flatten()), np.int32(t.flatten()), (0, 255, 0), 2)

        # Print the camera position
        R, _ = cv.Rodrigues(rvec) # Alternative) `scipy.spatial.transform.Rotation`
        p = (-R.T @ tvec).flatten()
        info = f'XYZ: [{p[0]:.3f} {p[1]:.3f} {p[2]:.3f}]'
        cv.putText(img, info, (10, 25), cv.FONT_HERSHEY_DUPLEX, 0.6, (0, 255, 0))
```

Absolute Camera Pose Estimation

- Example) **Pose estimation (book)** `[pose_estimation_book1.py]`







(due to unknown and changing K; autofocus)

Absolute Camera Pose Estimation

- Example) **Pose estimation (book) + camera calibration** `[pose_estimation_book2.py]`



(due to wrong initial K)



Absolute Camera Pose Estimation

- Example) **Pose estimation (book) + camera calibration – initially given** K `[pose_estimation_book3.py]`

(due to wrong initial K)

- Load the cover image
- Extract ORB features
- Build **3D object points** $\mathbf{X}_1, \mathbf{X}_2, \ldots$

Pass tentative matches

- Grab an input image
- Extract **ORB features** $\mathbf{x}_1, \mathbf{x}_2, \ldots$
- Match them to the object features

[Outlier Rejection]
- Remove wrong matches using `cv::findHomography()`


(free from K)

Pass correct matches

[Camera Pose Estimation]
- Estimate camera parameters using `cv::calibrateCamera()`

[Camera Pose Update]
- Intrinsic: K (initially known)
- Extrinsic: R, $\mathbf{t}$

Draw the box using `cv::projectPoints()`



Summary) Single-view Geometry

- **Camera Projection Models:** $\mathbf{x} = \mathrm{proj}(\mathbf{X}; \mathrm{K}, \mathrm{R}, \mathbf{t}, d)$
  - **Pinhole camera model**: $\mathbf{x} = \mathrm{K}(\mathrm{R}\mathbf{X} + \mathbf{t})$
    - Note) Homogeneous coordinate
    - Example) Object localization / image formation
  - **Geometric distortion models**: $\hat{\mathbf{x}}_d = f_d(\hat{\mathbf{x}})$ on the normalized image plane $(\hat{\mathbf{x}};\ \hat{z} = 1)$
    - e.g. Polynomial distortion model: Radial distortion and tangential distortion
    - Example) Distortion visualization / distortion correction
- **Camera Calibration**
  - Problem) Finding camera intrinsic parameters (K, distortion coefficients) and extrinsic parameters (R and $\mathbf{t}$)
  - Example) Camera calibration
- **Absolute Camera Pose Estimation (PnP)**
  - Problem) Finding camera extrinsic parameters (R and $\mathbf{t}$) → camera pose (R^T and $-\mathrm{R}^\mathrm{T}\mathbf{t}$)
  - Example) Pose estimation (chessboard)
  - Example) Pose estimation (book) as three versions
    - Q) What is RANSAC? What is homography?

Beyond Classic Camera Models and Calibration

- Classic camera models: *Parametric* models
  - Pinhole camera projection + Polynomial lens distortion (a.k.a. Brown-Conrady model)
  - Pinhole camera projection + Fisheye lens distortion (a.k.a. Kannala-Brandt model)
- ***Non-parametric* representation**
  - Why non-parametric models (more parameters)?




Figure 1. Residual distortion patterns of fitting two parametric camera models (left, center) and a generic model (right) to a mobile phone camera. While the generic model shows mostly random noise, parametric models show strong systematic modeling errors.

How to represent the camera projection?




Figure 2. 2D sketch of the two generic camera models considered in this paper. (a) In image space (black rectangle), a grid of control points is defined that is aligned to the calibrated area (dashed pink rectangle) and extends beyond it by one cell. A point (red) is unprojected by B-Spline surface interpolation of the values stored for its surrounding 4x4 points (blue). Interpolation happens among directions (gray and blue arrows) starting from a projection center (black dot) for the central model (b), and among arbitrary lines (gray and blue arrows) for the non-central model (c).

Image: Schops et al., "Why Having 10,000 Parameters in Your Camera Model is Better Than Twelve", CVPR, 2020 CVF arXiv Github

Beyond Classic Camera Models and Calibration

- ***Neural* representation**
  - e.g. Perspective fields




Image: Jin et al., "Perspective Fields for Single Image Camera Calibration", CVPR, 2023 Homepage Github

Beyond Camera Pose Estimation with Feature Matching and PnP

- **Pose *regression***
  - e.g. PoseNet: Image → Absolute camera pose (position, quaternion; 7 DoF)




Image: Generated by Nano Banana 2

Reference: Kendall et al., "PoseNet: A Convolutional Network for Real-Time 6-DOF Camera Relocalization", ICCV, 2015 Github

Beyond Camera Pose Estimation with Feature Matching and PnP

- **Scene coordinate *regression* (SCR)**
  - e.g. ACE: Image → Absolute 3D positions of scene (~ pixels) + PnP/RANSAC




Image: Brachmann et al., "Accelerated Coordinate Encoding: Learning to Relocalize in Minutes using RGB and Poses", CVPR, 2023 Homepage