
Note) Slides and example codes are available:
https://github.com/mint-lab/prog_meets_math



Python Meets Mathematics:
Linear Algebra


Sunglok Choi, Assistant Professor, Ph.D.
Computer Science and Engineering Department, SEOULTECH
sunglok@seoultech.ac.kr | https://mint-lab.github.io/

Programming Meets Mathematics

- ~~Calculus~~ **Differentiation**
  - Visualization using Matplotlib
  - Differentiation
    - Meaning: The **slope** of a tangent line (~ linear approximation) of a function
    - Finding a **derivative** using rules, SymPy, and numerical differentiation
- **Linear Algebra**
- **Optimization**
- **Probability**
- **Information Theory**


Getting Started from Line Fitting

Q) How about finding a line from three points?



- Line representation: $y = ax + b$ $(y = -\frac{2}{3}x + \frac{14}{3})$
- Slope $a = \frac{2-4}{4-1} = -\frac{2}{3}$
- Y intercept $b = 4 - a \cdot 1 = \frac{14}{3}$

Getting Started from Line Fitting



- Line representation: $y = ax + b$ $(y = -\frac{2}{3}x + \frac{14}{3})$
- Slope $a = \frac{2-4}{4-1} = -\frac{2}{3}$
- Y intercept $b = 4 - a \cdot 1 = \frac{14}{3}$

Q) Can it represent a vertical line such as $x = 1$?

- Line representation: $ax + by + c = 0$


  $(2x + 3y - 14 = 0;\ 4x + 6y - 28 = 0)$

  → additional constraint $a^2 + b^2 = 1$
- Its shorter form: $\mathbf{n}^\intercal \mathbf{x} + c = 0$

  $(\mathbf{n} = \begin{bmatrix} a \\ b \end{bmatrix}$ and $\mathbf{x} = \begin{bmatrix} x \\ y \end{bmatrix})$

Linear Algebra


- **Algebra** is the study of mathematical objects and their rules of manipulation (e.g. arithmetic operations).
- **Linear algebra** is the mathematical branch for linear equations that are represented in vector spaces.
  - **Linear equations**
    - e.g. $ax + b = 0$ (one-variable), $ax + by + c = 0$ (two-variable), ..., $a_1x_1 + a_2x_2 + \cdots + a_nx_n + b = 0$ (n-variable)
    - Note) Nonlinear equations: $y = 0.1x^3 - 0.8x^2 - 1.5x + 5.4$, $y = \sin x$
  - **Vector space** (a.k.a. linear space): A set of vectors which can be 1) added together and 2) multiplied by scalars
    - Scalar: A single element
      - e.g. x (one-dimensional)
    - Vector: A finite ordered list of elements (a.k.a. tuple)
      - e.g. $[x, y]$ (two-dimensional row vector), ..., $[x_1, x_2, \ldots, x_n]^\intercal$ (n-dimensional column vector)
    - Matrix: A rectangular array (table) of elements arranged in rows and columns (a.k.a. tensor)
      - e.g. $m \times n$ matrix



$$\begin{array}{c} \\ 1 \\ 2 \\ 3 \\ \vdots \\ m \end{array} \begin{array}{c} \begin{array}{cccc} 1 & 2 & \ldots & n \end{array} \\ \begin{bmatrix} a_{11} & a_{12} & \ldots & a_{1n} \\ a_{21} & a_{22} & \ldots & a_{2n} \\ a_{31} & a_{32} & \ldots & a_{3n} \\ \vdots & \vdots & \vdots & \vdots \\ a_{m1} & a_{m2} & \ldots & a_{mn} \end{bmatrix} \end{array}$$

Image: Wikipedia (vector space, matrix)

Vector


- **Why a vector?**
  - To represent physical quantities
    - e.g. Speed (magnitude; 속력 in Korean) vs. velocity (magnitude+*direction*; 속도 in Korean)
  - To represent data and models
    - e.g. A point $[1, 4]$, a line $2x + 3y - 14 = 0 \rightarrow [2, 3, -14]$, and its normal vector $[2, 3]$ or $[0.554 \ldots, 0.882 \ldots]$
    - e.g. Sound data 

- **Vector operations**
  - Vector addition (subtraction): $\mathbf{a} + \mathbf{b}$
  - Scalar multiplication (division): $a\,\mathbf{b}$
  - Vector multiplication
    - Dot product (a.k.a. scalar product): $\mathbf{a} \cdot \mathbf{b} = \sum_{i=1}^{n} a_i b_i = a_1 b_1 + a_2 b_2 + \cdots + a_n b_n$ or $\mathbf{a} \cdot \mathbf{b} = \|\mathbf{a}\|\,\|\mathbf{b}\|\cos\theta$
    - Cross product (a.k.a. vector product): $\mathbf{a} \times \mathbf{b} = \|\mathbf{a}\|\,\|\mathbf{b}\|\sin\theta\ \mathbf{n}$

Image: Toward Data Science (an article by Kartik Chaudhary)

Vector

- **Norm** is a function from a vector space to the non-negative real numbers that behaves like the distance from the origin (a.k.a. magnitude).
  - Notation: $\|\mathbf{a}\|$ for a vector $\mathbf{a}$
  - Properties
    - Triangle inequality: $\|\mathbf{x}+\mathbf{y}\| \leq \|\mathbf{x}\| + \|\mathbf{y}\|$
    - Absolute homogeneity: $\|a\,\mathbf{x}\| = |a|\,\|\mathbf{x}\|$
    - Positive definiteness: If $\|\mathbf{x}\| = 0$, then $\mathbf{x} = \mathbf{0}$



  - Examples
    - **Absolute-value norm**: A norm on 1-dimensional vector spaces

$$\|\mathbf{x}\| = |x_1|$$

    - **Euclidean norm** (a.k.a. L^2-norm): The most common norm in n-dimensional Euclidean spaces

$$\|\mathbf{x}\|_2 = \sqrt{x_1^2 + x_2^2 + \cdots + x_n^2}$$


    - **Manhattan norm** (a.k.a. L^1-norm)

$$\|\mathbf{x}\|_1 = |x_1| + |x_2| + \cdots + |x_n|$$

    - Note) A norm can be defined for a matrix.

Image: Wikipedia

Vector



- **Vector operations** (cont'd)
  - Vector multiplication
    - **Dot product** (a.k.a. scalar product, inner product)
      - Geometric definition: $\mathbf{a} \cdot \mathbf{b} = \|\mathbf{a}\| \, \|\mathbf{b}\| \cos\theta$
      - Algebraic definition: $\mathbf{a} \cdot \mathbf{b} = \sum_{i=1}^{n} a_i b_i = a_1 b_1 + a_2 b_2 + \cdots + a_n b_n$
        - As matrix multiplication: $\mathbf{a} \cdot \mathbf{b} = \mathbf{a}^{\mathsf{T}}\mathbf{b}$ where $\mathbf{a}$ and $\mathbf{b}$ are column vectors.

          $\mathbf{a} \cdot \mathbf{b} = \mathbf{a}\mathbf{b}^{\mathsf{T}}$ where $\mathbf{a}$ and $\mathbf{b}$ are row vectors.
        - e.g. $[3, 2] \cdot [5, 1] = 17$
        - e.g. $[3, 2, 9] \cdot [5, 1, -2] = -1$
      - Applications
        - Scalar projection
        - (Angular) similarity of two vectors (cosine similarity)

$$\cos\theta = \frac{\mathbf{a} \cdot \mathbf{b}}{\|\mathbf{a}\| \, \|\mathbf{b}\|}$$

Image: Wikipedia

Vector

- **Vector operations** (cont'd)
  - Vector multiplication
    - **Cross product** (a.k.a. vector product) is only defined in a three-dimensional space.
      - Definition: $\mathbf{a} \times \mathbf{b} = \|\mathbf{a}\| \, \|\mathbf{b}\| \sin\theta \, \hat{\mathbf{n}}$


        where $\hat{\mathbf{n}}$ is a unit vector orthogonal (수직 in Korean) to a plane containing $\mathbf{a}$ and $\mathbf{b}$

      - Computing (using matrix determinant)

$$\mathbf{a} \times \mathbf{b} = \begin{vmatrix} \mathbf{i} & \mathbf{j} & \mathbf{k} \\ a_1 & a_2 & a_3 \\ b_1 & b_2 & b_3 \end{vmatrix} = (a_2 b_3 - a_3 b_2)\mathbf{i} - (a_1 b_3 - a_3 b_1)\mathbf{j} + (a_1 b_2 - a_2 b_1)\mathbf{k}$$

        - e.g. $[1, 4, 1] \times [4, 2, 1] = [2, 3, -14]$

      - Applications
        - Relationship of angular velocity, angular momentum, and torque in a 3D space
        - Area of the parallelogram (평행사변형 in Korean) made by two vectors
        - More applications in computational geometry






Image: Wikipedia


Vector

- **Vector operations** (cont'd)
  - Vector multiplication
    - **Cross product** (a.k.a. vector product) is defined only in a three-dimensional space
      - Definition: $\mathbf{a} \times \mathbf{b} = \|\mathbf{a}\| \, \|\mathbf{b}\| \, \sin\theta \, \hat{\mathbf{n}}$

        where $\hat{\mathbf{n}}$ is a unit vector orthogonal (수직 in Korean) to a plane containing $\mathbf{a}$ and $\mathbf{b}$
      - Computing (using matrix determinant)


$$\mathbf{a} \times \mathbf{b} = \begin{vmatrix} \mathbf{i} & \mathbf{j} & \mathbf{k} \\ a_1 & a_2 & a_3 \\ b_1 & b_2 & b_3 \end{vmatrix} = (a_2 b_3 - a_3 b_2)\mathbf{i} - (a_1 b_3 - a_3 b_1)\mathbf{j} + (a_1 b_2 - a_2 b_1)\mathbf{k}$$

      - e.g. $[1, 4, 1] \times [4, 2, 1] = [2, 3, -14]$
      - Applications
        - Relationship of angular velocity, angular momentum, and moment of inertia
        - Area of the parallelogram (평행사변형 in Korean) made by two vectors
        - More applications in computational geometry



- Line representation: $ax + by + c = 0$

  $(2x + 3y - 14 = 0)$



- Area of the parallelogram made by two vectors
- Line from two points
- Intersection point from two lines
- Distance between two *skew* lines
- Volume of the parallelepiped made by three vectors


$(1, 4)$

$(4, 2)$


Image: Wikipedia

Matrix

- **Why a matrix?**
  - To represent physical quantities
    - e.g. Moment of inertia in the 3D space (a.k.a. inertia tensor)
  - To represent data and models
    - e.g. Images, multiple sounds
    - e.g. State-space representation (control theory), camera projection
  - To represent geometric transformation
    - e.g. Rotation matrix $\mathrm{R}(\theta) = \begin{bmatrix} \cos\theta & -\sin\theta \\ \sin\theta & \cos\theta \end{bmatrix}$
    - e.g. Rigid transformation, camera projection
  - To solve a system of linear equations (선형연립방정식 in Korean)
    - e.g. A system of equations for a line from (1, 4) and (4, 2)
      - Line representation: $y = ax + b$
      - A system of equations: $a \cdot 1 + b = 4$, $a \cdot 4 + b = 2$ $\longrightarrow$ $\begin{bmatrix} 1 & 1 \\ 4 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \end{bmatrix} = \begin{bmatrix} 4 \\ 2 \end{bmatrix}$ $(\mathbf{Ax} = \mathbf{b})$



$$I = \begin{bmatrix} \frac{1}{12}m(3r^2+h^2) & 0 & 0 \\ 0 & \frac{1}{12}m(3r^2+h^2) & 0 \\ 0 & 0 & \frac{1}{2}mr^2 \end{bmatrix}$$






Image: Wikipedia and ResearchGate (a paper by Smits and Wevers).

Matrix

- **Matrix operations**
  - Matrix addition (subtraction): $A + B$
  - Scalar multiplication (division): $a\,B$
  - **Matrix multiplication** (a.k.a. matrix product): AB
    - Not commutative (교환법칙 in Korean): $AB \neq BA$
      - Example) ~~Proof~~ Verification using SymPy

```
import sympy as sp

a11, a12, a21, a22 = sp.symbols('a11 a12 a21 a22')
b11, b12, b21, b22 = sp.symbols('b11 b12 b21 b22')
A = sp.Matrix([[a11, a12], [a21, a22]])
B = sp.Matrix([[b11, b12], [b21, b22]])

print(A+B == B+A) # True
print(A*B == B*A) # False
print(A*B - B*A)  # Check their difference
```




Image: Wikipedia

Matrix

- **Matrix operations** (cont'd)
  - **Matrix inverse** ($\mathrm{A}\mathrm{A}^{-1} = \mathrm{A}^{-1}\mathrm{A} = \mathrm{I}$; ~ 역수 in Korean)
    - Invertible matrix (a.k.a. non-singular matrix, non-degenerate matrix) if A is
      - Square (A: $n \times n$ matrix)
      - Linearly independent rows/columns
        - Full rank ($\mathrm{rank}(\mathrm{A}) = n$)
        - Non-zero determinant ($\det(\mathrm{A}) \neq 0$ or $|\mathrm{A}| \neq 0$)
  - **Pseudo-inverse** (~ a generalized matrix inverse)
    - **Not necessarily square** (A: $m \times n$ matrix, $\mathrm{A}^{\dagger}$: $n \times m$ matrix)
    - Left inverse ($\mathrm{A}^{\dagger}\mathrm{A} = \mathrm{I}_n$): $\mathrm{A}^{\dagger} = (\mathrm{A}^{\intercal}\mathrm{A})^{-1}\mathrm{A}^{\intercal}$
      - If A has linearly independent columns ($\mathrm{rank}(\mathrm{A}) = n$)
    - Right inverse ($\mathrm{A}\mathrm{A}^{\dagger} = \mathrm{I}_m$): $\mathrm{A}^{\dagger} = \mathrm{A}^{\intercal}(\mathrm{A}\mathrm{A}^{\intercal})^{-1}$
      - If A has linearly independent rows ($\mathrm{rank}(\mathrm{A}) = m$)

Matrix

- **Matrix operations** (cont'd)
  - **Matrix inverse**
    - Example) Line fitting from two points, $(1,4)$ and $(4,2)$
      - Line representation: $y = ax + b$
      - A system of equations: $a \cdot 1 + b = 4$

$$a \cdot 4 + b = 2$$

$$\downarrow$$

$$\begin{bmatrix} 1 & 1 \\ 4 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \end{bmatrix} = \begin{bmatrix} 4 \\ 2 \end{bmatrix} \longrightarrow \mathbf{x} = \mathrm{A}^{-1}\mathbf{b}$$

$$(\mathrm{A}\mathbf{x} = \mathbf{b})$$

  - **Pseudo-inverse**
    - Example) Line fitting from more than two points such as $(1,4)$, $(4,2)$, and $(7,1)$
      - $\mathrm{A} = \begin{bmatrix} 1 & 1 \\ 4 & 1 \\ 7 & 1 \end{bmatrix}$ and $\mathbf{b} = \begin{bmatrix} 4 \\ 2 \\ 1 \end{bmatrix}$

NumPy: A Matrix Library in Python

- NumPy supports multi-dimensional arrays and matrices with their high-level mathematical functions.
  - It is fundamental for scientific and numerical computing in Python.
- References: Documentation, Tutorials/Books/Talks, and **Cheatsheet** (created by DataCamp)

Quantum Computing	Statistical Computing	Signal Processing	Image Processing	Graphs and Networks	Astronomy Processes	Cognitive Psychology
QuTiP PyQuil Qiskit	Pandas statsmodels Xarray Seaborn	SciPy PyWavelets python-control	Scikit-image OpenCV Mahotas	NetworkX graph-tool igraph PyGSP	AstroPy SunPy SpacePy	PsychoPy

Bioinformatics	Bayesian Inference	Mathematical Analysis	Chemistry	Geoscience	Geographic Processing	Architecture & Engineering
BioPython Scikit-Bio PyEnsembl ETE	PyStan PyMC3 ArviZ emcee	SciPy SymPy cvxpy FEniCS	Cantera MDAnalysis RDKit	Pangeo Simpeg ObsPy Fatiando a Terra	Shapely GeoPandas Folium	COMPAS City Energy Analyst Sverchok

Image: NumPy (retrieved at October 14th, 2021)

NumPy:

- NumPy
  - It is
- Referen

Python For Data Science *Cheat Sheet*

NumPy Basics

Learn Python for Data Science Interactively at www.DataCamp.com


NumPy

The **NumPy** library is the core library for scientific computing in Python. It provides a high-performance multidimensional array object, and tools for working with these arrays.

Use the following import convention:

```
>>> import numpy as np
```

NumPy Arrays



Creating Arrays

```
>>> a = np.array([1,2,3])
>>> b = np.array([(1.5,2,3), (4,5,6)], dtype = float)
>>> c = np.array([[(1.5,2,3), (4,5,6)], [(3,2,1), (4,5,6)]],
                 dtype = float)
```

Initial Placeholders

```
>>> np.zeros((3,4))                    Create an array of zeros
>>> np.ones((2,3,4),dtype=np.int16)    Create an array of ones
>>> d = np.arange(10,25,5)             Create an array of evenly
                                       spaced values (step value)
>>> np.linspace(0,2,9)                 Create an array of evenly
                                       spaced values (number of samples)
>>> e = np.full((2,2),7)               Create a constant array
>>> f = np.eye(2)                      Create a 2X2 identity matrix
>>> np.random.random((2,2))            Create an array with random values
>>> np.empty((3,2))                    Create an empty array
```

I/O

Saving & Loading On Disk

```
>>> np.save('my_array', a)
>>> np.savez('array.npz', a, b)
>>> np.load('my_array.npy')
```

Saving & Loading Text Files

```
>>> np.loadtxt("myfile.txt")
>>> np.genfromtxt("my_file.csv", delimiter=',')
>>> np.savetxt("myarray.txt", a, delimiter=" ")
```

Data Types

```
>>> np.int64       Signed 64-bit integer types
>>> np.float32     Standard double-precision floating point
>>> np.complex     Complex numbers represented by 128 floats
>>> np.bool        Boolean type storing TRUE and FALSE values
>>> np.object      Python object type
>>> np.string_     Fixed-length string type
>>> np.unicode_    Fixed-length unicode type
```

Inspecting Your Array

```
>>> a.shape          Array dimensions
>>> len(a)           Length of array
>>> b.ndim           Number of array dimensions
>>> e.size           Number of array elements
>>> b.dtype          Data type of array elements
>>> b.dtype.name     Name of data type
>>> b.astype(int)    Convert an array to a different type
```

Asking For Help

```
>>> np.info(np.ndarray.dtype)
```

Array Mathematics

Arithmetic Operations

```
>>> g = a - b                          Subtraction
 array([[-0.5,  0. ,  0. ],
        [-3. , -3. , -3. ]])
>>> np.subtract(a,b)                   Subtraction
>>> b + a                              Addition
 array([[ 2.5,  4. ,  6. ],
        [ 5. ,  7. ,  9. ]])
>>> np.add(b,a)                        Addition
>>> a / b                              Division
 array([[ 0.66666667,  1.        ,  1.        ],
        [ 0.25      ,  0.4       ,  0.5       ]])
>>> np.divide(a,b)                     Division
>>> a * b                              Multiplication
 array([[  1.5,   4. ,   9. ],
        [  4. ,  10. ,  18. ]])
>>> np.multiply(a,b)                   Multiplication
>>> np.exp(b)                          Exponentiation
>>> np.sqrt(b)                         Square root
>>> np.sin(a)                          Print sines of an array
>>> np.cos(b)                          Element-wise cosine
>>> np.log(a)                          Element-wise natural logarithm
>>> e.dot(f)                           Dot product
 array([[ 7.,  7.],
        [ 7.,  7.]])
```

Comparison

```
>>> a == b                             Element-wise comparison
 array([[False,  True,  True],
        [False, False, False]], dtype=bool)
>>> a < 2                              Element-wise comparison
 array([True, False, False], dtype=bool)
>>> np.array_equal(a, b)               Array-wise comparison
```

Aggregate Functions

```
>>> a.sum()                  Array-wise sum
>>> a.min()                  Array-wise minimum value
>>> b.max(axis=0)            Maximum value of an array row
>>> b.cumsum(axis=1)         Cumulative sum of the elements
>>> a.mean()                 Mean
>>> b.median()               Median
>>> a.corrcoef()             Correlation coefficient
>>> np.std(b)                Standard deviation
```

Copying Arrays

```
>>> h = a.view()             Create a view of the array with the same data
>>> np.copy(a)               Create a copy of the array
>>> h = a.copy()             Create a deep copy of the array
```

Sorting Arrays

```
>>> a.sort()                 Sort an array
>>> c.sort(axis=0)           Sort the elements of an array's axis
```

Subsetting, Slicing, Indexing

Also see Lists

Subsetting

```
>>> a[2]                     Select the element at the 2nd index
  3
>>> b[1,2]                   Select the element at row 1 column 2
  6.0                        (equivalent to b[1][2])
```

Slicing

```
>>> a[0:2]                   Select items at index 0 and 1
  array([1, 2])
>>> b[0:2,1]                 Select items at rows 0 and 1 in column 1
  array([ 2.,  5.])
>>> b[:1]                    Select all items at row 0
  array([[1.5, 2., 3.]])     (equivalent to b[0:1, :])
>>> c[1,...]                 Same as [1,:,:]
  array([[[ 3.,  2.,  1.],
          [ 4.,  5.,  6.]]])
>>> a[ : :-1]                Reversed array a
  array([3, 2, 1])
```

Boolean Indexing

```
>>> a[a<2]                   Select elements from a less than 2
  array([1])
```

Fancy Indexing

```
>>> b[[1, 0, 1, 0],[0, 1, 2, 0]]   Select elements (1,0),(0,1),(1,2) and (0,0)
  array([ 4. , 2. , 6. , 1.5])
>>> b[[1, 0, 1, 0]][:,[0,1,2,0]]   Select a subset of the matrix's rows
  array([[ 4. ,5. , 6. , 4. ],     and columns
         [ 1.5, 2. , 3. , 1.5],
         [ 4. , 5. , 6. , 4. ],
         [ 1.5, 2. , 3. , 1.5]])
```

Array Manipulation

Transposing Array

```
>>> i = np.transpose(b)      Permute array dimensions
>>> i.T                      Permute array dimensions
```

Changing Array Shape

```
>>> b.ravel()                Flatten the array
>>> g.reshape(3,-2)          Reshape, but don't change data
```

Adding/Removing Elements

```
>>> h.resize((2,6))          Return a new array with shape (2,6)
>>> np.append(h,g)           Append items to an array
>>> np.insert(a, 1, 5)       Insert items in an array
>>> np.delete(a,[1])         Delete items from an array
```

Combining Arrays

```
>>> np.concatenate((a,d),axis=0)   Concatenate arrays
  array([ 1,  2,  3, 10, 15, 20])
>>> np.vstack((a,b))               Stack arrays vertically (row-wise)
  array([[ 1. ,  2. ,  3. ],
         [ 1.5,  2. ,  3. ],
         [ 4. ,  5. ,  6. ]])
>>> np.r_[e,f]                     Stack arrays vertically (row-wise)
>>> np.hstack((e,f))               Stack arrays horizontally (column-wise)
  array([[ 7.,  7.,  1.,  0.],
         [ 7.,  7.,  0.,  1.]])
>>> np.column_stack((a,d))         Create stacked column-wise arrays
  array([[ 1, 10],
         [ 2, 15],
         [ 3, 20]])
>>> np.c_[a,d]                     Create stacked column-wise arrays
```

Splitting Arrays

```
>>> np.hsplit(a,3)           Split the array horizontally at the 3rd
  [array([1]),array([2]),array([3])]   index
>>> np.vsplit(c,2)           Split the array vertically at the 2nd index
[array([[[ 1.5,  2. ,  1. ],
         [ 4. ,  5. ,  6. ]]]),
 array([[[ 3.,  2.,  3.],
         [ 4.,  5.,  6.]]])]
```

DataCamp
Learn Python for Data Science Interactively

Image: DataCamp

NumPy: A Matrix Library in Python

- Usage example) Creating n-dimensional arrays (1/2)
  - `numpy.array` can contain a **homogeneous** (~ same) data type. (vs. `list` and `tuple`)

```
import numpy as np

# 1. Create an array from composite data (list or tuple, not set and dictionary)
A = np.array([3, 29, 82])
B = np.array(((3., 29, 82), (10, 18, 84)))
C = np.array([[3, 29, 82], [10, 18, 84]], dtype=float)
D = np.array([3, 29, 'Choi'])
E = np.array([[3], [29], [82]])
print(A.ndim, A.size, A.shape, A.dtype) # 1 3 (3,) int32
                                       # Note) np.array_equal(A, A.T) == True
print(B.ndim, B.size, B.shape, B.dtype) # 2 6 (2, 3) float64
print(C.ndim, C.size, C.shape, C.dtype) # 2 6 (2, 3) float64
print(D.ndim, D.size, D.shape, D.dtype) # 1 3 (3,) <U11 (Unicode)
                                       # Note) array(['3', '29', 'Choi'])
print(E.ndim, E.size, E.shape, E.dtype) # 2 3 (3,1) int32
                                       # Note) np.array_equal(E, E.T) == False
                                       #       because E.T == array([[3, 29, 82]])
```

NumPy: A Matrix Library in Python

- Usage example) Creating n-dimensional arrays (2/2)
  - `numpy.array` can contain a **homogeneous** (~ same) data type. (vs. `list` and `tuple`)

```
import numpy as np

# 2. Create an array using initializers
F = np.zeros((3, 2))             # Create a 3x2 array filled with 0 (default: float64)
G = np.ones((3, 2))              # Create a 2x3 array filled with 1
H = np.eye(3, dtype=np.float32) # Create a 3x3 identity matrix (single-precision)
I = np.empty((3, 2))             # == np.zeros((3, 2))
J = np.empty((0, 9))             # [ ] with size of (0, 9)
K = np.arange(0, 1, 0.2)         # Step 0.2: array([0., 0.2, 0.4, 0.6, 0.8])
L = np.linspace(0, 1, 5)         # Number 5: array([0., 0.25, 0.50, 0.75, 1.])
M = np.random.random((3, 2))     # == np.random.uniform(size=(3, 2))
                                 # Note) np.random.normal()
```

NumPy: A Matrix Library in Python

- Usage example) Indexing and slicing
  - `numpy.array` can access elements of a n-dim array not only with `[r][c]` but also with **`[r,c]`**.
  - `numpy.array` can access elements with a Boolean array (called **logical indexing**).

	0	1	2
0	3	29	82
1	10	18	84

```
import numpy as np
A = np.array(((3., 29, 82), (10, 18, 84)))

# 1. Indexing and slicing
A[1][1]                  # 18.0
A[1, 1]                  # 18.0  Note) list[1, 1] does not work!
A[1,1:2]                 # array([18.])
A[1,:]                   # Get a row:       array([10., 18., 84.])
A[:,2]                   # Get a column:    array([82., 84.])
A[0:2,0:2]               # Get a submatrix: array([[3., 29.], [10., 18.]])

# 2. Logical indexing
A > 80                   # array([[False, False, True], [False, False, True]])
A[A > 80]                # array([82., 84.])
A[A > 80] = 80           # Masked operations are possible!

# 3. Fancy indexing
A[(1, 0, 0), (1, 0, 2)] # array([18., 3., 82.])
                         # Get items at (1, 1), (0, 0), (0, 2)
```

Image: Jake VanderPlas's book

NumPy: A Matrix Library in Python


- Usage example) Arithmetic operations (vs. `list` and `tuple`)

```
import numpy as np
A = np.array([[1, 2], [3, 4]])
B = np.array([[5, 6], [7, 8]])

# 1. Element-wise arithmetic operations
print(A + B)                    # np.add(A, B)
print(A - B)                    # np.subtract(A, B)
print(A * B)                    # np.multiply(A, B)
print(A / B)                    # np.divide(A, B)

# 2. Matrix operations
print(A.T)                      # A.transpose()
print(A @ B)                    # np.matmul(A, B)
print(np.linalg.norm(A))        # 5.48 (default: L2-norm)
print(np.linalg.matrix_rank(A)) #  2, full rank
print(np.linalg.det(A))         # -2, non-zero determinant
print(np.linalg.inv(A))         # Matrix inverse
print(np.linalg.pinv(A))        # Matrix pseudo-inverse

# 3. Broadcasting
print(A + 1)                    # [[2, 3], [4, 5]]
print(A + [0, -1])              # [[1, 1], [3, 3]]
print(A + [[1], [-1]])          # [[2, 3], [2, 3]]
```



Matrix

- Example) Line fitting from two points, $(1, 4)$ and $(4, 2)$
  - Line representation: $y = ax + b$
  - A system of equations: $a \cdot 1 + b = 4$

$$a \cdot 4 + b = 2$$

$$\downarrow$$

$$\begin{bmatrix} 1 & 1 \\ 4 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \end{bmatrix} = \begin{bmatrix} 4 \\ 2 \end{bmatrix} \longrightarrow \mathbf{x} = \mathrm{A}^{-1}\mathbf{b}$$

$$(\mathrm{A}\mathbf{x} = \mathbf{b})$$

- Example) Line fitting from two points, $(1, 4)$ and $(4, 2)$, using NumPy

```
import numpy as np

A = np.array([[1., 1.], [4., 1.]])
b = np.array([[4.], [2.]])
A_inv = np.linalg.inv(A)
print(A_inv * b) # [[-1.33333333  1.33333333]
                 #  [ 2.66666667 -0.66666667]]  Note) broadcast
print(A_inv @ b) # [[-0.66666667]
                 #  [ 4.66666667]]
```

Matrix

- Example) Line fitting from two points, $(1, 4)$ and $(4, 2)$, using NumPy

```
import numpy as np

A = np.array([[1., 1.], [4., 1.]])
b = np.array([[4.], [2.]])
A_inv = np.linalg.inv(A)
print(A_inv @ b) # [[-0.66666667]
                 #  [ 4.66666667]]
```


- Example) Line fitting from more than two points such as $(1, 4)$, $(4, 2)$, and $(7, 1)$ using NumPy
  - $\mathrm{A} = \begin{bmatrix} 1 & 1 \\ 4 & 1 \\ 7 & 1 \end{bmatrix}$ and $\mathbf{b} = \begin{bmatrix} 4 \\ 2 \\ 1 \end{bmatrix}$

```
import numpy as np


A = np.array([[1., 1.], [4., 1.], [7., 1.]])
b = np.array([[4.], [2.], [1.]])
A_inv = np.linalg.pinv(A) # Left inverse
print(A_inv @ b) # [[-0.5]
                 #  [ 4.33333333]]
```

Matrix

- Example) Line fitting with noisy but more data (1/2)
  - `data_num = 2`



  - `data_num = 100`



Matrix

- Example) Line fitting with noisy but more data (2/2)

```python
import numpy as np
import matplotlib.pyplot as plt

true_line = lambda x: -2/3*x + 14/3
data_range = np.array([-4, 12])
data_num = 100
noise_std = 0.5

# Generate the true data
x = np.random.uniform(data_range[0], data_range[1], size=data_num)
y = true_line(x) # y = -2/3*x + 10/3

# Add Gaussian noise
xn = x + np.random.normal(scale=noise_std, size=x.shape)
yn = y + np.random.normal(scale=noise_std, size=y.shape)

# Solve the system of equations
A = np.vstack((xn, np.ones(xn.shape))).T
b = yn
line = np.linalg.pinv(A) @ b


# Plot the data and result
plt.title(f'Line: y={line[0]:.3f}*x + {line[1]:.3f} ')
plt.plot(data_range, true_line(data_range), 'r-', label='The true line')
plt.plot(xn, yn, 'b.', label='Noisy data')
plt.plot(data_range, line[0]*data_range + line[1], 'g-', label='Estimate')
plt.xlim(data_range)
plt.legend()
plt.show()
```

$$\begin{bmatrix} x_1 & x_2 & \cdots & x_n \\ 1 & 1 & \cdots & 1 \end{bmatrix} \xrightarrow{\text{transpose}} \begin{bmatrix} x_1 & 1 \\ x_2 & 1 \\ \vdots & \vdots \\ x_n & 1 \end{bmatrix} \begin{bmatrix} a \\ b \end{bmatrix} = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{bmatrix}$$

$$(\mathbf{Ax} = \mathbf{b})$$

Matrix

- Example) Curve fitting (1/2)
  - Curve representation: $y = ax^3 + bx^2 + cx + d$ (a 3rd-order polynomial equation)
    - e.g. $y = 0.1x^3 - 0.8x^2 - 1.5x + 5.4$



$$\begin{bmatrix} x_1^3 & x_1^2 & x_1 & 1 \\ x_2^3 & x_2^2 & x_2 & 1 \\ \vdots & \vdots & \vdots & \vdots \\ x_n^3 & x_n^2 & x_n & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \\ d \end{bmatrix} = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{bmatrix}$$

$$(\mathbf{Ax} = \mathbf{b})$$

Matrix

- Example) Curve fitting (2/2)

```
import numpy as np
import matplotlib.pyplot as plt

true_curve = lambda x: 0.1*x**3 - 0.8*x**2 - 1.5*x + 5.4
data_range = (-6, 12)
data_num = 100
noise_std = 0.5

# Generate the true data
x = np.random.uniform(data_range[0], data_range[1], size=data_num)
y = true_curve(x)

# Add Gaussian noise
xn = x + np.random.normal(scale=noise_std, size=x.shape)
yn = y + np.random.normal(scale=noise_std, size=y.shape)

# Solve the system of equations
A = np.vstack((xn**3, xn**2, xn, np.ones(xn.shape))).T
b = yn
curve = np.linalg.pinv(A) @ b

# Plot the data and result
plt.title(f'Curve: y={curve[0]:.3f}*$x^3$ + {curve[1]:.3f}*$x^2$ + {curve[2]:.3f}*$x$ + {curve[3]:.3f}')
xc = np.linspace(*data_range, 100)
plt.plot(xc, true_curve(xc), 'r-', label='The true curve')
plt.plot(xn, yn, 'b.', label='Noisy data')
plt.plot(xc, curve[0]*xc**3 + curve[1]*xc**2 + curve[2]*xc + curve[3], 'g-', label='Estimate')
plt.xlim(data_range)
plt.legend()
plt.show()
```

$$\begin{bmatrix} x_1^3 & x_1^2 & x_1 & 1 \\ x_2^3 & x_2^2 & x_2 & 1 \\ \vdots & \vdots & \vdots & \vdots \\ x_n^3 & x_n^2 & x_n & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \\ d \end{bmatrix} = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{bmatrix}$$


$$(\mathrm{A}\mathbf{x} = \mathbf{b})$$

Matrix

$$\begin{bmatrix} x_1^r & x_1^{r-1} & \cdots & x_1^2 & x_1 & 1 \\ x_2^r & x_2^{r-1} & \cdots & x_2^2 & x_2 & 1 \\ \vdots & \vdots & \vdots & \vdots & \vdots & \vdots \\ x_n^r & x_n^{r-1} & \cdots & x_n^2 & x_n & 1 \end{bmatrix} \begin{bmatrix} c_r \\ c_{r-1} \\ \vdots \\ c_2 \\ c_1 \\ c_0 \end{bmatrix} = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{bmatrix}$$

$(\mathbf{Ax} = \mathbf{b})$

- Example) Curve fitting with model selection (1/2)



• • •

```python
import numpy as np
import matplotlib.pyplot as plt

def buildA(order, xs):
    A = np.empty((0, len(xs)))
    for i in range(order + 1):
        A = np.vstack((xs**i, A))
    return A.T

true_coeff = [0.1, -0.8, -1.5, 5.4]
poly_order = 3 # Try other integer (>= 0)
data_range = (-6, 12)
data_num = 100
noise_std = 1

# Generate the true data
x = np.random.uniform(data_range[0], data_range[1], size=data_num)
y = buildA(len(true_coeff) - 1, x) @ true_coeff

# Add Gaussian noise
xn = x + np.random.normal(scale=noise_std, size=x.shape)
yn = y + np.random.normal(scale=noise_std, size=y.shape)

# Solve the system of equations
A = buildA(poly_order, xn)
b = yn
coeff = np.linalg.pinv(A) @ b

# Plot the data and result
plt.title(f'Order: {poly_order}, Coeff: ' + np.array2string(coeff, precision=2, suppress_small=True))
xc = np.linspace(*data_range, 100)
plt.plot(xc, np.matmul(buildA(len(true_coeff) - 1, xc), true_coeff), 'k-', label='The true curve', alpha=0.2)
plt.plot(xn, yn, 'b.', label='Noisy data')
plt.plot(xc, np.matmul(buildA(poly_order, xc), coeff), 'g-', label='Estimate')
plt.xlim(data_range)
plt.legend()
plt.show()
```

$$\begin{bmatrix} x_1^r & x_1^{r-1} & \cdots & x_1^2 & x_1 & 1 \\ x_2^r & x_2^{r-1} & \cdots & x_2^2 & x_2 & 1 \\ \vdots & \vdots & & \vdots & \vdots & \vdots \\ x_n^r & x_n^{r-1} & \cdots & x_n^2 & x_n & 1 \end{bmatrix} \begin{bmatrix} c_r \\ c_{r-1} \\ \vdots \\ c_2 \\ c_1 \\ c_0 \end{bmatrix} = \begin{bmatrix} y_1 \\ y_2 \\ \vdots \\ y_n \end{bmatrix}$$

$$(\mathbf{Ax} = \mathbf{b})$$

Matrix

- Example) Line fitting from two points, $(1, 4)$ and $(1, 2)$
  - Line representation: $y = ax + b$
  - A system of equations: $a \cdot 1 + b = 4$

$$a \cdot 1 + b = 2$$

$$\downarrow$$

$$\begin{bmatrix} 1 & 1 \\ 1 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \end{bmatrix} = \begin{bmatrix} 4 \\ 2 \end{bmatrix} \longrightarrow \mathbf{x} = \mathrm{A}^{-1}\mathbf{b}$$

$$(\mathrm{A}\mathbf{x} = \mathbf{b})$$

- Example) Line fitting from two points, $(1, 4)$ and $(1, 2)$, using NumPy

```
import numpy as np

A = np.array([[1., 1.], [1., 1.]])
b = np.array([[4.], [2.]])
A_inv = np.linalg.inv(A) # Error! (singular matrix)
print(A_inv @ b)
```

Matrix

- **Null space** (a.k.a. kernel)
  - A set of vectors which map A (m-by-n matrix) to the zero vector

    $N(\mathrm{A}) = \{\, \mathbf{v} \in K^n \mid \mathrm{A}\mathbf{v} = \mathbf{0} \,\}$
  - Rank-nullity theorem: $\mathrm{rank}(\mathrm{A}) + \mathrm{nullity}(\mathrm{A}) = n$
  - Application) Solving a **homogenous** system of linear equations, $\mathrm{A}\mathbf{x} = \mathbf{0}$

- Practice) Line fitting from two points, $(1, 4)$ and $(1, 2)$, using NumPy
  - Line representation: $ax + by + c = 0$
  - In a matrix form, $\begin{bmatrix} 1 & 4 & 1 \\ 1 & 2 & 1 \end{bmatrix} \begin{bmatrix} a \\ b \\ c \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \end{bmatrix}$

How about $(1, 4)$ and $(4, 2)$?

```
import numpy as np
from scipy import linalg

A = np.array([[1., 4., 1.], [1., 2., 1.]])
x = linalg.null_space(A)
print(x / x[0]) # [[1.], [0.], [-1.]]  Note) Line: x - 1 = 0
```

Summary

- NumPy: N-dimensional array representation and numerical analysis (수치해석 in Korean)
  - `numpy.array` vs. `list/tuple`
    - Homogeneous data type
    + Indexing/slicing and arithmetic operations
- ~~Linear algebra~~ **Vector**
  - Why? 1) To represent physical quantities / 2) To represent data and models
  - Vector operations
    - Note) Norm (~ the distance from the origin, magnitude)
    - Vector multiplication
      - Dot product: $\mathbf{a} \cdot \mathbf{b} = \|\mathbf{a}\| \, \|\mathbf{b}\| \, \cos\theta$
        - Applications: Cosine similarity
      - Cross product: $\mathbf{a} \times \mathbf{b} = \|\mathbf{a}\| \, \|\mathbf{b}\| \, \sin\theta \, \hat{\mathbf{n}}$ ($\hat{\mathbf{n}}$: the unit orthogonal vector of $\mathbf{a}$ and $\mathbf{b}$) defined in 3D spaces
        - Applications: Physics in a 3D space, …, computational geometry

Summary

- ~~Linear algebra~~ **Matrix**
  - Why? + 3) To represent geometric transformation / 4) **To solve a system of linear equations**
  - Matrix operations
    - Matrix multiplication (not commutative)
    - Matrix inverse (square + full rank), pseudo-inverse
  - Examples) **Line and curve fitting** (regression analysis; 회귀분석 in Korean)
    - What is a model and its parameters?
      - e.g. Line: $y = ax + b$ (or $ax + by + c = 0$)
      - e.g. Curve: nth-order polynomial equations (e.g. $y = ax^3 + bx^2 + cx + d$)
    - How to formulate the problem using matrices: $\mathbf{Ax} = \mathbf{b}$ (or $\mathbf{Ax} = \mathbf{0}$)
    - How to solve the equations using matrix operations: Pseudo-inverse (or finding null vectors)
    - Lesson #1) **More (over-constrained) data is beneficial.**
      - The estimation result from *more data* becomes *more robust* (~ strong) against noise.
    - Lesson #2) **Model complexity can lead underfitting and overfitting.**
      - *Too complex (flexible) models* can be too sensitive to noise, which can cause *overfitting*.