

Enter password:

Welcome to the MariaDB monitor. Commands end with ; or \g.

Your MySQL connection id is 8

Server version: 5.7.12 MySQL Community Server (GPL)

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MySQL [(none)]> use university;

Reading table information for completion of table and column names

You can turn off this feature to get a quicker startup with -A

Database changed

MySQL [university]> SELECT TEACHER.NAME, COURSE.COURSE_ID, COURSE.COURSE_NAME
-> FROM TEACHER JOIN COURSE ON TEACHER.TEACHER_ID = COURSE.TEACHER_ID;

NAME	COURSE_ID	COURSE_NAME
UNUBOLD	1	CLOUD COMPUTING
UNUBOLD	2	React
UNUBOLD	3	Angular
ASAAD	3	Angular

4 rows in set (0.02 sec)

MySQL [university]>

```
MySQL [(none)]> show databases;
```

```
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| performance_schema |
| sys |
+-----+
```

```
4 rows in set (0.00 sec)
```

```
MySQL [(none)]> create database university;
```

```
Query OK, 1 row affected (0.01 sec)
```

```
MySQL [(none)]> show databases;
```

```
+-----+
| Database |
+-----+
| information_schema |
| mysql |
| performance_schema |
| sys |
| university |
+-----+
```

```
5 rows in set (0.00 sec)
```

```
MySQL [(none)]> use university;
```

```
Database changed
```

```
MySQL [university]> CREATE TABLE TEACHER (
```

```
-> TEACHER_ID int,
-> NAME varchar(255)
-> );
```

```
Query OK, 0 rows affected (0.02 sec)
```

```
MySQL [university]> CREATE TABLE COURSE (
```

```
-> COURSE_ID int,
-> COURSE_CODE varchar(255),
-> COURSE_NAME varchar(255),
-> TEACHER_ID int
-> );
```

```
Query OK, 0 rows affected (0.02 sec)
```

```
MySQL [university]> show tables;
```

```
+-----+
| Tables_in_university |
+-----+
| COURSE |
| TEACHER |
+-----+
```

```
2 rows in set (0.00 sec)
```

```
MySQL [university]> INSERT INTO TEACHER (TEACHER_ID, NAME)
```