




NPM & Modules

npm & packages Intro



What is npm?

- ▶ **npm** is the standard package manager for Node.js. It also manages downloads of dependencies of your project.
- ▶ www.npmjs.com hosts thousands of free packages to download and use.
- ▶ The NPM program is installed on your computer when you install Node.js.
 - ▶ `npm -v` // will print npm version
- ▶ What is a package?
 - ▶ A package in Node.js contains all the files you need for a module.
 - ▶ Modules are JavaScript libraries you can include in your project.
- ▶ A package contains:
 - ▶ JS files
 - ▶ `package.json` (manifest)
 - ▶ `package-lock.json` (maybe)


Create & use a new package

```
npm init // will create package.json
```

```
npm install moment --save
```

```
// moment is a package that parse, validate, manipulate and display dates
```

- ▶ When we install a package:
 - ▶ Notice dependencies changes in `package.json`
 - ▶ notice folder: `node_modules`
 - ▶ This structure separate our app code to the dependencies. Later when we share/deploy our application, there's no need to copy `node_modules`, run: `npm install` will read all dependencies and install them locally.



```
momentdemo.js
var moment = require('moment');
console.log(moment().format("LLLL")); //Sunday, June 13,
2021 6:24 PM
```


package.json Manifest

- ▶ The `package.json` file is kind of a manifest for your project.
 - ▶ It can do a lot of things, completely unrelated.
 - ▶ It's a central repository of configuration for installed packages.
 - ▶ The only requirement is that it respects the JSON format.
-
- ▶ `version`: indicates the current version
 - ▶ `name`: the application/package name
 - ▶ `description`: a brief description of the app/package
 - ▶ `main`: the entry point for the application
 - ▶ `scripts`: defines a set of node scripts you can run
 - ▶ `dependencies`: sets a list of npm packages installed as dependencies
 - ▶ `devDependencies`: sets a list of npm packages installed as development dependencies

```
{  
  "name": "package_demo",  
  "version": "1.0.0",  
  "description": "",  
  "main": "index.js",  
  "scripts": {  
    "start": "node momentdemo.js"  
  },  
  "author": "Rujuan Xing",  
  "license": "ISC",  
  "dependencies": {  
    "moment": "^2.29.1"  
  },  
  "devDependencies": {  
    "eslint": "^7.28.0"  
  }  
}
```

Semantic Versioning

- ▶ The Semantic Versioning concept is simple:
all versions have 3 digits: $x.y.z$.
 - ▶ the first digit is the major version
 - ▶ the second digit is the minor version
 - ▶ the third digit is the patch version
- ▶ When you make a new release, you don't just up a number as you please, but you have rules:
 - ▶ you up the **major** version when you make incompatible API changes
 - ▶ you up the **minor** version when you add functionality in a backward-compatible manner
 - ▶ you up the **patch** version when you make backward-compatible bug fixes



More details about Semantic Versioning

- ▶ Why is that so important?

- ▶ Because `npm` set some rules we can use in the `package.json` file to choose which versions it can update our packages to, when we run `npm update`.

- ▶ The rules use those symbols:

- ▶ `^`: it's ok to automatically update to anything within this major release. If you write `^0.13.0`, when running `npm update`, it can update to `0.13.1`, `0.14.2`, and so on, but not to `1.14.0` or above.
 - ▶ `~`: if you write `~0.13.0` when running `npm update` it can update to patch releases: `0.13.1` is ok, but `0.14.0` is not.
 - ▶ `>`: you accept any version higher than the one you specify

package-lock.json

- ▶ Introduced by NPM version 5 to capture the exact dependency tree installed at any point in time.
- ▶ Describes the exact tree
- ▶ Guarantee the dependencies on all environments.
- ▶ Use `npm ci` if you want to use dependencies in package-lock.json file
- ▶ Don't modify this file manually.
- ▶ Always use npm CLI to change dependencies, it'll automatically update package-lock.json

```
{
  "name": "lesson03-demo",
  "version": "1.0.0",
  "lockfileVersion": 1,
  "requires": true,
  "dependencies": {
    "moment": {
      "version": "2.24.0",
      "resolved": "https://registry.npmjs.org/moment/-/moment-2.24.0.tgz",
      "integrity": "sha512-bV7f+6l2QigeBBZSM/6yTNq4P2fNpSWj/0e7jQcy87A8e7o2nAfP/34/2ky5Vw4B9S446EtIhodAzkFCcR4dQg=="
    }
  }
}
```


More About Packages

- ▶ **Development Dependencies:** Needed only while I'm developing the app. It's not needed for running the app.

- ▶ `npm install mocha --save-dev`
`// notice devDependencies entry now in package.json`

- ▶ **Global Dependencies:** Available to all applications

- ▶ `npm install -g nodemon`
 - ▶ `nodemon app.js` `//auto detects changes and restarts your project`

More npm CLI Commands

```
npm -v // will print npm version
npm init // will create package.json
npm install <package> --S // download & install the code from last commit of git repo
                        // "--save" option will update package.json automatically
                        // other options are: --save-dev (-D) --save-optional (-O)
npm i <package> -g // download & install a package globally
npm i <package> --dry-run
npm ls -g --depth=0 // show all global packages in your system
npm update // check versions in package.json and update
npm i npm -g // update npm
npm outdated -g // show all outdated global packages
npm prune // if a package is installed without --save then delete and clean

npm config list // display the default npm settings
npm config set init-author-name "Josh Edward"
npm config delete init-author-name
npm config set save true // automatically --save (-S)

npm search lint // search online for package with lint in the name
npm home <package> // open browser to package homepage
npm repo <package> // open browser to package repository
```



More about HTTP

Understanding Request & Response

- ▶ A request message from a client to a server includes, within the first line of that message, the method to be applied to the resource, the identifier of the resource, and the protocol version in use.
- ▶ After receiving and interpreting a request message, a server responds with an HTTP response message.

```
const http = require('http');
http.createServer((req, res) => {
  console.log(req.url, req.method, req.headers);

  res.setHeader('Content-Type', 'text/html');
  res.write('<html>');
  res.write('<head><title>My First Page</title></head>');
  res.write('<body><h1>Hello From Node.js</h1></body>');
  res.write('</html>');
  res.end();
}).listen(3000);
```

HTTP Request: Reading Get and Post Data

- ▶ Handling basic GET & POST requests is relatively simple with Node.js.
- ▶ We use the `url` module to parse and read information from the URL.
- ▶ The `url` module uses the WHATWG URL Standard (<https://url.spec.whatwg.org/>)

href												
protocol		auth		host		path		hash				
				hostname	port	pathname	search					
								query				
" https:	//	user	:	pass	@	sub.host.com	:	8080	/p/a/t/h	?	query=string	#hash
protocol		username		password		hostname		port				
origin						host						
origin						origin		pathname		search		hash
href												

Using URL Module

► Parsing the URL string using the WHATWG API:

```
const url = require('url');  
const myURL =  
    new URL('https://user:pass@sub.host.com:8080/p/a/t/h?course1=nodejs&course2=angular#hash');  
console.log(myURL);
```

```
URL {  
  href: 'https://user:pass@sub.host.com:8080/p/a/t/h?course1=nodejs&course2=angular#hash',  
  origin: 'https://sub.host.com:8080',  
  protocol: 'https:',  
  username: 'user',  
  password: 'pass',  
  host: 'sub.host.com:8080',  
  hostname: 'sub.host.com',  
  port: '8080',  
  pathname: '/p/a/t/h',  
  search: '?course1=nodejs&course2=angular',  
  searchParams: URLSearchParams { 'course1' => 'nodejs', 'course2' => 'angular' },  
  hash: '#hash'
```


Parsing the Query String

```
const url = require('url');
const myURL =
    new URL('https://user:pass@sub.host.com:8080/p/a/t/h?course1=nodejs&course2=angular#hash');
let params = myURL.searchParams;
console.log(params);
console.log(params.get('course1'), params.get('course2'));
```

```
URLSearchParams { 'course1' => 'nodejs', 'course2' => 'angular' }
nodejs angular
```

HTTPS and Secure Communication

- ▶ HTTPS stands for Hyper Text Transfer Protocol Secure. It is a protocol for securing the communication between two systems e.g. the browser and the web server.
- ▶ The following figure illustrates the difference between communication over http and https:




Generating Keys

- ▶ OpenSSL Windows installer is here
<http://slproweb.com/products/Win32OpenSSL.html>
- ▶ Navigate to the OpenSSL bin directory.
 - ▶ C:\openssl_X64\bin in our example. You can also add openssl.exe as Path environment variable, then you can use command “openssl” under all direcotries.
- ▶ Right-click the **openssl.exe** file and select **Run as administrator**.
- ▶ Enter the following command to begin generating a certificate and private key:
 - ▶ **req -x509 -sha256 -nodes -days 365 -newkey rsa:2048 -keyout privateKey.key -out certificate.crt**
- ▶ For production environment / deploying to a production server you need to get the keys and certificate from a certification authority (CA) e.g., Verisign, Thawte

<https://helpcenter.gsx.com/hc/en-us/articles/115015960428-How-to-Generate-a-Self-Signed-Certificate-and-Private-Key-using-OpenSSL>

```
OpenSSL> req -x509 -sha256 -nodes -days 365 -newkey rsa:2048 -keyout privateKey.key -out certificate.crt
Loading 'screen' into random state - done
Generating a 2048 bit RSA private key
.....+++
.....+++
writing new private key to 'privateKey.key'
-----
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [AU]:US
State or Province Name (full name) [Some-State]:Iowa
Locality Name (eg, city) []:Fairfield
Organization Name (eg, company) [Internet Widgits Pty Ltd]:MIU
Organizational Unit Name (eg, section) []:MSD
Common Name (eg, YOUR name) []:Rujuan Xing
Email Address []:rxing@miu.edu
```



Create HTTPS Server

```
const fs = require('fs');

var options = {
  key: fs.readFileSync('./privateKey.key'),
  cert: fs.readFileSync('./certificate.crt')
};

const server = require('https')
  .createServer(options);

server.on('request', (req, res) => {
  res.writeHead(200, { 'content-type': 'text/plain' });
  res.end('Hello from my HTTPS Web server!!!\n');
});

server.listen(443);
```

Try this link if the previous slides doesn't work for you:
<https://nodejs.org/en/knowledge/HTTP/servers/how-to-create-a-HTTPS-server/>

Resources

▶ Node and NPM

- ▶ [Nodejs.org](https://nodejs.org)
- ▶ [Npmjs.com](https://npmjs.com)
- ▶ [Node API Documentation](https://nodejs.org/en/docs/api/)
- ▶ [NPM Documentation](https://docs.npmjs.com/)

▶ HTTPS

- ▶ [HTTPS \(Wikipedia\)](https://en.wikipedia.org/wiki/HTTPS)
- ▶ [Public Key Cryptography](#)
- ▶ [Transport Layer Security](#)
- ▶ [Node HTTPS Server](#)
- ▶ [Kurose, James F., and Keith W. Ross. Computer networking: a top-down approach. Pearson, 2017, ISBN-10: 0134522206 • ISBN-13: 9780134522203.](#)

▶ Other Resources

- ▶ [Howto: Make Your Own Cert With OpenSSL on Windows](#)
- ▶ [OpenSSL for Windows](#)
- ▶ [How to Use SSL/TLS with Node.js](#)
- ▶ [Adding HTTPS \(SSL\) to Express 4.X Applications](#)
- ▶ [How does HTTPS actually work?](#)