

Source Table (used for all examples)

Source coding (smoking) : 1 = No , 2 = Yes

age	smoking	SBP	Weight	Height
65	2	135	80	1.80
...	...	...	...	...

Cross-table transfer



Same source - target pair
for all examples

Target Table (used for all examples)

Target coding (Smoking) : 0 = No , 1= Yes

age	smoking	SBP	Weight	Height
63	1	132	78	176
...	...	...	...	...

	Intended	Bad omission / naive reference	Admissible reference
1 Measurement interpret coding / Value meaning	Source : smoking 1 2 ... decode source code → Target : smoking 0 1 ... Decode source codes to target - compatible values.	Source : smoking — — ... Target : smoking — — ... Removes predictive information (from source smoking)	Source : smoking 1 2 ... Target : smoking 0 1 ... Remove decoding only ; preserve raw values
2 Correspondence Match variables across schemas	Source : SBP 135 121 ... specified pairing ↔ Target : systolic_BP 132 119 ... Align SBP and Systolic BP as the same concept (shared representation)	Source : SBP — — ... Target : systolic_BP — — ... changes available information / representation (drops transferred BP information)	Source : SBP 135 121 ... Target : systolic_BP 132 119 ... preserve values ; remove pairing only (keep domain - local columns)
3 Relation Specify structural relation	Age + → declared deriction SBP Specify a direcctional relation (e.g. positive)	Age → × SBP Removes more than the relation (e.g , delets inputs or changes the relation)	Age ← unconstraint → SBP Remove constraint only (keep the variables and interface)

Removes predictive information
(from source smoking)