

# Using the MiPal Whiteboard Classgenerator

Mick Hawkins

30 October 2015

## Contents

|                                                               |          |
|---------------------------------------------------------------|----------|
| <b>1 Introduction .....</b>                                   | <b>2</b> |
| 1.1 Supported Operating Systems .....                         | 2        |
| <b>2 Creating an input file .....</b>                         | <b>2</b> |
| 2.1 File type and filename .....                              | 2        |
| 2.2 Specifying your name .....                                | 2        |
| 2.3 Specifying an alias .....                                 | 3        |
| 2.4 Specifying simple variables .....                         | 3        |
| 2.4.1 Specifying arrays .....                                 | 3        |
| 2.5 Specifying the struct comment .....                       | 4        |
| <b>3 Installing the classgenerator executable file .....</b>  | <b>4</b> |
| <b>4 Running the program .....</b>                            | <b>4</b> |
| <b>5 Supported data types .....</b>                           | <b>6</b> |
| <b>6 Output from the generated files .....</b>                | <b>7</b> |
| <b>7 Using fromString() with the Whiteboard Monitor .....</b> | <b>7</b> |

# 1 Introduction

The Classgenerator is a command line tool used to generate classes for use with the MiPal Whiteboard. It reads input from a text file and generates Whiteboard .c and .h class files, and a C++ wrapper.

It is assumed the user has general skills in use of the `bash` shell.

## 1.1 Supported Operating Systems

The Classgenerator requires MacOS X 10.9 and later. Linux support is not yet available.

## 2 Creating an input file

An input file must be created before using the Classgenerator. The input file specifies the variables types used in the generated classes.

### 2.1 File type and filename

The input file must be a plain-text `.txt` file. The `.txt` file extension must be used.

To correctly generate C and C++ class names:

- The filename should use lowercase letters
- The filename must begin with a lowercase letter
- The filename should use underscores between words
- Numbers may be used
- Other than in the `.txt` file extension, periods/fullstops must not be used

If the input file's name includes uppercase letters:

- These capital letters will be kept and used in the C++ filename/class (which is in camel case)
- These capital letters will be converted to lowercase for the `wb_` files

These are some examples of *suitable* filenames:

```
ball_colour.txt
oculus_prime_interface.txt
vision_goals.txt
point2D.txt
point_2D.txt
```

These are examples of *unsuitable* filenames:

```
BallColour.txt
goal.doc
WALK.txt
vision_goals
```

A sample text file `sample_input.txt` can be found in the `GUNao/posix/classgenerator/classgenerator` folder.

### 2.2 Specifying your name

As the author you may, as an option, specify your name in the input file. Your name is used in the comment at the top of each file:

- As the creator of the file
- In the copyright clause
- In the GNU license

**If you not specify your name in the input file, the system username will be used.**

Specify your name in the first line of the input file using the following format:

```
author /tab Your Name
```

- `author` must be in lowercase
- There must be a single `tab` between `author` and your name
- Your name must be written exactly how you want it to appear (as a suggestion, capitalised with a space between parts of the name)

Hyphenated names, and multi-word names will work as expected.

Examples of how to specify names:

```
author Captain Spaulding
```

```
author Otis B. Driftwood
```

## 2.3 Specifying an alias

To allow compatibility with existing, pre-classgenerator code, you may specify an alias class using the following format:

```
alias /tab alias_filename
```

## 2.4 Specifying simple variables

To specify variables, use the following format:

```
datatype /tab variable_name=default /tab comment
```

- Each variable must include a datatype, variable name and comment
- The data type must be written as specified in section 5 *Supported Data Types*
- There must be a single `tab` between each of the datatype, variable name/default, and comment
- Variable names should be written exactly how you want them to appear
- Specifying a default value is optional (see below\*)
- The comment may be specified by “// ” to aide in readability

Currently supported data types are listed in section 5 *Supported Data Types*. Strings and objects to be added shortly.

Example of specifying variables in an input file:

```
int16_t    pointX=5           // pointX is the X coordinate
int16_t    pointY             // pointY is the Y coordinate
bool       is_red=false       is_red is true if the colour is red
```

In this example, `pointY` does not have a default value specified

Note: depending on the `tab` setting of your text file editor, things may not line up perfectly.

\*If default values are not specified, the following defaults will be used:

- Boolean: `false`
- Numerical types: `0`

### 2.4.1 Specifying arrays

To specify arrays, use the following format:

```
datatype /tab variable_name[array_size]=default /tab comment
```

The specifications in 2.4 also apply to arrays. In addition:

- Default values for arrays may be specified between curly braces and separated by commas
- If default values are not specified, the array will be filled with the default value of the variable type (as specified in 2.4)

- An array size must be specified
- If a string is specified as an array of `char`, the array size must allow for the null termination character

Example of specifying arrays in an input file:

```
int16_t    my_values[4]={1,1,2,3}    // my_values has default values
int16_t    your_values[3]            // no default specified
```

In this example, `your_values` does not have a default value specified

Note: C Strings may be specified as an array of type `char`. When doing so the size of the array must allow for a null termination character.

## 2.5 Specifying the struct comment

To specify a comment for the struct, leave a blank line after the variables, and enter the comment lines at the end of the text file. An example of an input text file with a struct comment is:

```
int16_t    pointX=5                // pointX is the X coordinate
int16_t    pointY                  // pointY is the Y coordinate
/return <- this is a blank line
```

This is the first line of a comment for the struct.

This is the second line.

This comment will appear above the struct in the `wb_` header file and the C++ and Swift wrappers

## 3 Installing the classgenerator executable file

The classgenerator executable is located in the `GUNao/posix/classgenerator/classgenerator` folder. It is called `classgenerator`.

To allow the executable to be run from any directory, copy it to the `usr/local/bin` directory under MacintoshHD. This directory is hidden. To open it, go to the Finder and, under the “Go” menu, use “Go to folder”.

If you do not have a `usr/local/bin` directory, enter the following in the Terminal:

```
sudo mkdir -p /usr/local/bin
cd /usr/local/bin
open .
```

...this will create and open the directory. Copy the executable into this folder.

## 4 Running the program

With the program installed in the `usr/local/bin` directory, it can be run from any location.

In the Terminal, change to the directory that you would like your generated files to be located. Put your input file in this directory also.

The name of the input file must be entered as a command line argument. For example:

```
classgenerator ball_colour.txt
```

This will run the generator using the file `ball_colour.txt` as input and will generate the Whiteboard classes:

```
wb_ball_colour.h
wb_ball_colour.c
```

To also generate a C++ wrapper for these files, use the command line argument `c` or `-c`

```
classgenerator ball_colour.txt c
```

This will generate the Whiteboard classes and a C++ wrapper:

```
wb_ball_colour.h
wb_ball_colour.c
BallColour.h
```

To also generate a Swift wrapper and Bridging Header for these files, use the command line argument `s` or `-s`

```
classgenerator ball_colour.txt s
```

This will generate the Whiteboard classes and a Swift wrapper and Bridging Header:

```
wb_ball_colour.h
wb_ball_colour.c
BallColour.swift
BallColour-Bridging-Header.h
```

To generate both the C++ and Swift wrappers use the command line arguments `c/-c` and `s/-s` together:

```
c s
s c
sc
cs
-c -s
-s -c
-sc
-cs
```

will all work to produce both wrappers.

The command line arguments may be entered in any order. These variations will produce the same result:

```
classgenerator ball_colour.txt c
classgenerator ball_colour.txt -c
classgenerator c ball_colour.txt
classgenerator -c ball_colour.txt
```

## 5 Supported data types

Strings, arrays and object types to be supported shortly. The currently supported data types are:

bool

char

signed char

unsigned char

int

signed int

unsigned

unsigned int

int8\_t

uint8\_t

int16\_t

uint16\_t

int32\_t

uint32\_t

int64\_t

uint64\_t

short

short int

signed short

signed short int

unsigned short

unsigned short int

long

long int

signed long

signed long int

unsigned long

unsigned long int

long long

long long int

signed long long

signed long long int

unsigned long long

unsigned long long int

long64\_t

float

float\_t

double

double\_t

long double

double double

Note: C Strings may be specified as an array of type `char`. When doing so the size of the array must allow for a null termination character.

## 6 Output from the generated files

The `toString()` and `description()` methods return strings that are formatted as follows.

For a struct of variables with values:

```
Type: bool  
Name: pressed  
Value: true
```

```
Type: int_16 array  
Name: point2D  
Value: {1, 3}
```

The `description()` function will return this string:

```
pressed=true, point2D={1, 3}
```

The `toString()` function will return this string:

```
true, {1, 3}
```

## 7 Using `fromString()` with the Whiteboard Monitor

When using the Whiteboard Monitor, strings can be tested at the command line. When using classes generated by the Classgenerator, these strings should be formatted similarly to the strings described in *6 Output from the generated files*. Either format can be read by the `fromString()` function

The use of spaces is optional, and additional spaces may be used. For example, the `fromString()` function treats the following strings in the same way:

```
pressed=true,point2D={1,3}  
pressed = true, point2D= {1 , 3}  
true,{ 1 , 3 }  
true ,{1, 3}
```