

INTERACTION DESIGN AND EVALUATION. SESSION 1

Dept. Computer Science – UPC

2

MOTIVATION

- Interaction Design and Evaluation:
 - Design User Interfaces
 - Measure/Predict performance
 - Design interaction

3

OBJECTIVES

- Understanding the fundamentals of basic interaction in UI
 - Hick-Hyman Law: Choice-Reaction Time
 - Fitts' Law: Pointing Time
 - Crossing and Steering Laws: Continuous Gestures
 - Guidelines for UI design and evaluation
 - Experiments to assess/evaluate interaction theories

4

OUTLINE – SESSION 1

- Background
- Hick-Hyman Law: Measuring choice-reaction time
- Fitts Law: Measuring Pointing Time

5

OUTLINE – SESSION 1

- **Background:**
 - Basics
 - Information Measures
- Hick-Hyman Law: Measuring choice-reaction time
- Fitts Law: Measuring Pointing Time

6


BACKGROUND. BASICS

- **Information Theory:**
 - Due to Claude E. Shannon
 - *A Mathematical Theory of Communication* (1948)
 - Based on previous works by Nyquist and Hartley
 - Analysis of transmission of electrical signals for telegraphic communication
 - Shannon Entropy measures:
 - The amount of information to be transmitted by a message*

7

BACKGROUND. BASICS

- Information Theory. Elements (telegraph):



8

BACKGROUND. BASICS

- Information Theory. Elements (telegraph):

- **Information source:** The element that produces a message or sequences of message.
- **Transmitter:** Operates on the message to make it transmissible through a medium.
- **Channel:** The medium that transmits the message.
- **Receiver:** The element that reconstruct the message to the destination.

9

BACKGROUND. INFORMATION MEASURES

- Let d be a device that produces symbols A, B, and C with the same probability
 - $M = 3$ is the total number of symbols
 - Each time a symbol is produced we are uncertain on which symbol is going to be generated
 - This uncertainty is not so big, since there are only three possibilities
 - The probability of a symbol to appear is $1/M : 1/3$
 - The **uncertainty** is measured by $\log_2(3)$

10

BACKGROUND. INFORMATION MEASURES

- The **uncertainty** we have depends on the number M of symbols $\rightarrow \log_2(M)$.
 - 3 symbols \rightarrow uncertainty of $\log_2(3)$.
 - 2 symbols \rightarrow uncertainty of $\log_2(2)$.
- Logarithms are commonly taken in base 2, and the units are bits.

11

BACKGROUND. INFORMATION MEASURES

- Let d be a device that produces one single symbol: C
 - $M = 1$ is the total number of symbols
 - We have **no uncertainty** and $\log_2(1) = 0$
 - The probability of getting the symbol C is 1
 - We previously know which symbol will appear!

12

BACKGROUND. INFORMATION MEASURES

- We have two devices, one with outputs A, B, C, and the second with outputs 1, 2.
- We combine *words* by concatenating one symbol of device 1 and one with device 2.
- We will have 6 different words: A1, A2, B1, B2, C1, C2
 - 6 symbols \rightarrow uncertainty of $\log_2(6) \rightarrow \log_2(2) + \log_2(3) = \log_2(6)$.

13

BACKGROUND. INFORMATION MEASURES

- M symbols with equal probability → each symbol has probability $P=1/M$

- **Rewriting the uncertainty**

$$\log_2(M) = \log_2\left(\left(\frac{1}{M}\right)^{-1}\right) = \log_2(P^{-1}) = -\log_2(P)$$

- $-\log_2(P)$ is called the **surprise** or *surprisal* of finding a certain symbol
- We will use p_i from now on for the probability of a symbol i
- For M symbols that have different probabilities, we may have a different p_i for each, provided that
$$\sum_{i=1}^M p_i = 1$$

14

BACKGROUND. INFORMATION MEASURES

- **Information is the reduction of uncertainty or average surprise of a set of symbols**

- Measuring the surprise for an *infinite* set of symbols (produced by a device) → the frequency of each symbol transforms to the probability.
- Shannon Entropy measures the amount of information:

$$H = \sum_{i=1}^N p_i \log_2\left(\frac{1}{p_i}\right) = -\sum_{i=1}^N p_i \log_2 p_i$$

- N is the number of alternatives
- p_i is the probability of the i th alternative.
- **H is the entropy of the message that is to be transmitted, the amount of information expected to be received (no noise).**

15

BACKGROUND. INFORMATION MEASURES

- Information Theory. Shannon entropy:
 - There is interference: Not all information will reach the receiver
 - **Average information faithfully transmitted (R):**

$$R = H(x) - H_y(x)$$

- **$H_y(x)$ is the equivocation** or conditional entropy of x when y is known

16

BACKGROUND. INFORMATION MEASURES

- Applications of Shannon entropy:
 - All types of signal transmission and storage:
 - Measuring information
 - Dictionary creation for compression
 - ...

17


OUTLINE

- *Background*
- **Hick-Hyman Law: Measuring choice-reaction time**
 - Hick-Hyman Law
 - Experimental assessment
- Fitts Law: Measuring Pointing Time
- Typing & Keyboards

18

HICK-HYMAN LAW

- Hick-Hyman Law:
 - Initially stated by William E. Hick (1951)
 - Describes human decision time as a function of the information content conveyed by a visual stimulus
 - It takes longer to respond to a stimulus when it belongs to a large set as opposed to a smaller set of stimuli
 - Extended by Ray Hyman (1952)



19

HICK-HYMAN LAW

- **Time to make a decision (Reaction Time):**

$$RT = a + bH_T$$

- a, b constants
- H_T **transmitted information**

20

HICK-HYMAN LAW

- Hick-Hyman Law:
 - H_T : **Transmitted information:**

$$H_T = \log_2(n+1)$$

- n are the equiprobable alternatives
- original formulation did not have the "+1"
attends for the uncertainty whether to respond or not
- **Time to answer is the Reaction Time:**

$$RT = a + b \log_2(n+1)$$


21

HICK-HYMAN LAW. EXPERIMENTAL ASSESSMENT

- Hick's initial experiment:
 - 10 pea lamps are arranged in an irregular circle
 - One random lamp is lit every 5 seconds
 - User has to press the correct key corresponding to the lamp that is lit
 - Stimulus and response encoded in a moving paper in binary code



22



23

HICK-HYMAN LAW. EXPERIMENTAL ASSESSMENT

- Time to answer. Reaction Time:

$$RT = a + b \log_2(n+1)$$

- Reaction Time is a linear function of stimulus information
- Hyman [Hyman53] found that it also holds for not equiprobable alternatives
- Experiment:
 - 8 lights (whose names were *Bun, Boo, Bee, Bore, By, Bix, Bev, and Bate*)
 - The users had to name the one lit
 - A microphone attached to the throat detected the voice and stopped the timer
 - First with equal probabilities
 - Then, with varying probabilities

24

HICK-HYMAN LAW. EVIDENCES

- **Evidences of Hick-Hyman Law**
 - Performance in hierarchical full-screen menu selections is well described by Hick-Hyman [Landauer85]
 - Selection times decay logarithmically with menu length for frequently selected items, but linearly with infrequent ones [Sears94].
 - Learnt locations (most frequent) fit Hick-Hyman decision times
 - Non-learnt locations fit a linear search
 - Novice users search linearly while experts decide upon item location and fit a Hick-Hyman curve [Cockburn2008]

25


OUTLINE

- *Background*
- *Hick-Hyman Law: Measuring choice-reaction time*
- **Fitts Law: Measuring Pointing Time**
 - Original formulation
 - Variants
 - Experimental evidences
 - Extensions: 2D and Precision Pointing
 - Discussion
 - Assessed Results
- Typing & Keyboards

26

FITTS' LAW. ORIGINAL FORMULATION

- States a **linear relationship between task difficulty and movement time (MT)**
- Formulation is also based on Information Theory
 - Amplitude of movement is the *signal*
 - Human motor system is the communication *channel*
 - Target width is the *noise*



27

FITTS' LAW. ORIGINAL FORMULATION

- **Task difficulty:**

$$ID = \log_2 \left(\frac{2A}{W} \right)$$

- *ID*: Index of difficulty
- *A*: Amplitude of movement
- *W*: Target width


28

FITTS' LAW. ORIGINAL FORMULATION

- **Task difficulty:**

$$ID = \log_2 \left(\frac{2A}{W} \right)$$

- The larger the amplitude the higher the difficulty
- The larger the target the lower the difficulty



29

FITTS' LAW. ORIGINAL FORMULATION

- **Movement Time:** Time to point a certain objective (target)

$$MT = a + bID$$

- a start/stop times in seconds
- b inherent speed of the device

30

FITTS LAW. EXPERIMENTAL EVIDENCES

Fitts Law. Original experiments:

- Experiment 1. Reciprocal tapping:
 - Participants used a metal-tipped stylus:
 - Two experiments with two different stylus: ~ 28.35 gr and 453.6 gr
 - Tap two strips of metallic targets of width from ~ 0.635 to 5.08 cm
 - At distance 5.08 to 40.64 cm
 - **Yes, original data is in ounces and inches!!!** 😊
 - Participants instructed to be accurate!

31

FITTS LAW. EXPERIMENTAL EVIDENCES


Fitts Law. Original experiments:

- Experiment 2: Disk transfer
 - Participants had to transfer stack round plastic disks (with holes drilled through the middle) from one pin to another
 - Holes of different sizes and pins of different diameters used
- Experiment 3: Pin transfer
 - Participants had to transfer pins of different diameters from a set of holes to another set of holes

32

FITTS LAW. EXPERIMENTAL EVIDENCES

- Fitts Law. Results. Curve fitted: $MT = 12.8 + 94.7 ID$



33

FITTS LAW. EXPERIMENTAL EVIDENCES

- Fitts Law. Results:
 - Experiment 1:
 - Average error negligible
 - *Most difficult condition: Smaller W and largest A*
 - Results show that there is a linear relationship between MT and ID

34

FITTS' LAW. VARIANTS

- Original formulation fits well to the original experiments
 - But it might fit better
- Other researchers have found different formulations that better model the experimental data
 - Including the experimental data by Fitts
- Welford [Welford68]:

$$MT = a + b \log_2 \left(\frac{D + 0.5W}{W} \right)$$

- D is the distance of movement
- W is the width of the target

35

FITTS' LAW. VARIANTS

- **MacKenzie's** approach [MacKenzie92] is one of the most accepted:


$$MT = a + b \log_2 \left(\frac{D}{W} + 1 \right)$$

- D is the distance of movement
- W is the width of the target

36

FITTS' LAW. VARIANTS

- Vertical and horizontal movements can be treated equally



37


FITTS LAW. EXTENSIONS

- Main application of Fitts in HCI is evaluation/design of UI and interaction
- Today's interfaces are much more complex
 - Variety of sizes
 - 2D movements
 - Use of fingers

38

FITTS LAW. EXTENSIONS

- Use in UI design or evaluation:




- D is the distance the pointer (mouse) covers to reach the target (button)
- W is the width of the target (button)

39

FITTS LAW. EXTENSIONS. 2D

- Vertical and horizontal movements can be treated equally... or not!



40

FITTS LAW. EXTENSIONS. 2D

- Fitts' Law is designed for 1D movements
 - BUT...most movements in a UI are 2D
- Several extensions deal with 2D movements
 - Mimicking Fitts' Law, but changing some of the parameters
 - [Crossman83]: $MT = a + b \log_2 \left(\frac{2D}{W} \right) + c \log_2 \left(\frac{2D}{H} \right)$
 - [Accot97]: $MT = a + b \log_2 \left(\sqrt{\left(\frac{D}{W} \right)^2 + \eta \left(\frac{D}{H} \right)^2} + 1 \right)$

41

FITTS LAW. EXTENSIONS. PRECISION POINTING

- Fitts Law does not model properly very small targets:
 - Extra time devoted to fine adjustment
 - Increase of errors
 - ...
- Very small targets yield a lower fit of the regression curve of the MT function
- Touchscreens also modifies the timing we require to point targets.

42

FITTS LAW. EXTENSIONS. PRECISION POINTING

Extension of Fitts' Law by analyzing the behavior both in tactile screens and small targets ([Sears91]):

- Named FFitts (**Finger Fitts**), also PPMT (Precision Pointing Movement Time) by some other authors :

$$FFits = a + bID + dID_2$$

$$FFits = a + b \left[\log_2 \left(\frac{cD}{W} \right) \right] + d \left[\log_2 \left(\frac{e}{W} \right) \right]$$

43

FITTS LAW. EXTENSIONS. PRECISION POINTING

- FFitts:

$$FFitts = a + b \left[\log_2 \left(\frac{cD}{W} \right) \right] + d \left[\log_2 \left(\frac{e}{W} \right) \right]$$

- the first logarithmic factor measures *the time to place the finger on the screen initially*
- the second factor measures *the time to position the cursor*
- D is the distance, measured in three dimensions, from the original hand location to the location of first contact
- W is some measurement of target size
- a , b , c , d , and e must be determined for each specific case

44

FITTS LAW. EXTENSIONS. PRECISION POINTING

- FFitts:


$$FFitts = a + b \left[\log_2 \left(\frac{cD}{W} \right) \right] + d \left[\log_2 \left(\frac{e}{W} \right) \right]$$

- If the task consists of iteratively clicking targets: D is the distance from one target to the next one

45

FITTS LAW EXTENSIONS. PRECISION POINTING

- FFitts' experiments:
 - Date from 1989!
 - Tactile screens of lower resolution than mouse interaction
 - Required on purpose stabilization software



46

FITTS LAW. DISCUSSION

Fitting regression curves:

- Validation of Fitts' Law may not extrapolate to outside values
 - Only valid for the experiments carried out
 - Has been demonstrated that very small values of ID do not fit properly
 - Limited number of target sizes (four in original Fitts' work)
 - The lack of precise distance measurements (from the user's hand to the target) makes analysis difficult
- The higher number of freedom degrees, the easier to fit in a regression curve
 - Note that this sort of proves are partially done *a posteriori*
- Validity Fitts => Experimentation

49

FITTS LAW. DISCUSSION

Speed vs accuracy tradeoff:

- Users can be *guided* through the experimentation:
 - Ask them to be precise
 - Showing error rates enforces correction
 - Ask them to be fast
- We may skew the experiment depending on what we say, e.g.:
 - “This experiment is to demonstrate that larger targets are acquired easier than small targets”
 - Users might want to satisfy you!
 - ...Or not!

51

FITTS LAW. ASSESSED RESULTS

- **Fitts’ Law has shown its validity in multiple setups and devices:**
 - Mouse, joystick, finger, stylus...
 - Different screen types of varying sizes...
 - But the results cannot be extrapolate to data outside the experiment
- **Precued targets lead to more efficient and precise pointing movements than for non-precued targets [Hertzum2013].**
 - Most common case: we know the buttons’ positions in advance.
 - The benefit of precuing is larger for the mouse than the touchpad
 - Maybe movement preparation is more effective if the device is more demanding
- **The index finger alone does not perform as well as the wrist or forearm in pointing tasks**
 - But the thumb and index fingers in coordination outperform all above cases [Balakrishnan97]

5. Donades les constants $a = 400$ ms, $b = 200$ ms/bit i un objectiu de mida 2.1 cm a una distància de 10.5 cm. Marca la resposta correcta assumint que fem els càlculs amb la versió de McKenzie de la llei de Fitts.

- a. $ID \approx 3.4$.
- b. $2 < ID < 3$.
- c. $ID \approx 4.3$.
- d. MT està entre 1100 i 1200 ms.

6. La llei de Hick-Hyman:

- a. Modela el temps de decisió com una funció de la informació transmesa.
- b. Modela el temps de selecció d'un element com a funció de la distància a recórrer i la mida de l'element.
- c. Modela el temps de decisió com una funció de la distància a recórrer i l'entropia dels elements a seleccionar.
- d. Utilitza l'entropia de Shannon per a mesurar la distància del recorregut mínim.