

Fast Track fit

First results with accumulative method


L. Mirabito

IPN Lyon, UCB Lyon, IN2P3, CNRS

October 29, 2014


Accumulation

- Put all stubs in conformal space ($x' = \frac{x}{r^2}, y' = \frac{y}{r^2}$)
- Calculate all possible combination of 2 layers hits, excluding the inner most one.
- Fill an histogram in (a, b) space of found combinations
- Select bins with ≥ 3 entries (or 4 if more than 150 stubs)



Accumulation numbers

nacu_vs_nstub



Adding hits

For all candidates

Loop on all layers

- 1 Skip if layers already touched
- 2 Extrapolate the candidate to the layer $y_{ext} = a_{cand} \times x + b_{cand}$
- 3 Calculate distance and add nearby hits

Adding hits

For all candidates

Loop on all layers

- 1 Skip if layers already touched
- 2 Extrapolate the candidate to the layer $y_{ext} = a_{cand} \times x + b_{cand}$
- 3 Calculate distance and add nearby hits

Fit

- Requires at least 4 hits in (x,y) and 2 hits in (R,z) selected
- Linear regression in the 2 planes
- Reject low pt candidates

Sample & Results

140 Pile-up + 4 tops

- File AMana_4TPU140_d01pt2.root
- 295 events
- 1314 MC tracks with $P_t > 2\text{GeV}$


Sample & Results

140 Pile-up + 4 tops


- File AMana_4TPU140_d01pt2.root
- 295 events
- 1314 MC tracks with $P_t > 2\text{GeV}$

Sector	N Track MC	Ntrack Reco	Efficiency	Fake rate
16	1314	1736	90.64	10.05


Candidates track statistic




Pt resolution




ϕ resolution



η resolution



z resolution



Summary

Method

Only the first step is quadratic in stub numbers (without the inner most layer ones) so the performances should be comparable to the Hough transform approach.

The final steps are linear in number of stubs and limited (≤ 64) in parallel blocks.

Summary

Method

Only the first step is quadratic in stub numbers (without the inner most layer ones) so the performances should be comparable to the Hough transform approach.

The final steps are linear in number of stubs and limited (≤ 64) in parallel blocks.

First results

In a barrel sector, high efficiency and relatively low fake rate are achieved. Detail tuning of the algorithm are still to be done and should improve those already good results.

Summary

Method

Only the first step is quadratic in stub numbers (without the inner most layer ones) so the performances should be comparable to the Hough transform approach.

The final steps are linear in number of stubs and limited (≤ 64) in parallel blocks.

First results

In a barrel sector, high efficiency and relatively low fake rate are achieved. Detail tuning of the algorithm are still to be done and should improve those already good results.

Futur

- Cuts tuning
- Sector tuning
- GPU & FPGA implementation