

# TODO

## **\*) Interpreter prompt.**

```
|0:commonadmin@morgan)-(12:15:33.31)|
|[-/core/infrastructure/ubiquitous_bash]
|1) > c "1+1" ; _clc "1+1" ; c "solve(x == y + 1, y)"
2
2
x - 1
|0:commonadmin@morgan)-(12:15:41.31)|
|[-/core/infrastructure/ubiquitous_bash]
|2) > ./ubiquitous_bash.sh _python
Python 3.7.3 (default, Jan 22 2021, 20:04:44)
[GCC 8.3.0] on linux
Type "help", "copyright", "credits" or "license" for more information.
(InteractiveConsole)
|#:commonadmin@morgan)-(python-0x30703f0)|
|[-/core/infrastructure/ubiquitous_bash]
|1) > print(_getScriptAbsoluteFolder())
/home/commonadmin/core/infrastructure/ubiquitous_bash
|#:commonadmin@morgan)-(python-0x30703f0)|
|[-/core/infrastructure/ubiquitous_bash]
|2) > c("1+1")
'2'
|#:commonadmin@morgan)-(python-0x30703f0)|
|[-/core/infrastructure/ubiquitous_bash]
|3) > _bash("-i")
|0:commonadmin@morgan)-(12:17:15.31)|
|[-/core/infrastructure/ubiquitous_bash]
|1) > exit
exit
(None, 0)
|#:commonadmin@morgan)-(python-0x30703f0)|
|[-/core/infrastructure/ubiquitous_bash]
|4) > exit()
|0:commonadmin@morgan)-(12:17:20.31)|
|[-/core/infrastructure/ubiquitous_bash]
|3) > false
|1:commonadmin@morgan)-(12:18:50.31)|
|[-/core/infrastructure/ubiquitous_bash]
|4) > █
```

Similar for 'ghci' Haskell interpreter desired (to install with '\_setupUbiquitous' to either '.ghci' or a hook there to include another file in '.ubcorerc').

## **+ ) Environment variables - scriptAbsoluteFolder .**

Haskell programs will need 'scriptAbsoluteFolder' or similar to include Haskell files in adjacent directories, even from the 'ghci' interpreter.

```
System.Environment.getEnv "scriptAbsoluteFolder"
```

## **\*) Shell commands with Haskell variables or at least environment variables.**

Several commands apparently do not work as might be expected.

```
scriptAbsoluteFolder=System.Environment.getEnv "scriptAbsoluteFolder"
scriptAbsoluteFolder
:cd scriptAbsoluteFolder
:! cd scriptAbsoluteFolder
```

Must not fail due to misquoting of spaces or other possible characters in filenames.

## **\*) Run haskell programs from files in directory relative to a script in a related directory.**

```
:load scriptAbsoluteFolder /_example/Main
```

# Environment Variables

```
System.Directory.getCurrentDirectory
```

```
System.Environment.getEnv "scriptAbsoluteFolder"
```

```
:cd dir
:load _example/Main
```

# Dependencies

```
if [[ -e /etc/issue ]] && cat /etc/issue | grep 'Debian' > /dev/null 2>&1
then
    _wantGetDep '/usr/share/doc/haskell-platform/README.Debian'
fi

_wantGetDep alex
_wantGetDep cabal
_wantGetDep happy
_wantGetDep HsColour
_wantGetDep hscolour

_wantGetDep ghc
_wantGetDep ghci
! type -p 'ghc' && echo 'warn: missing: ghc'
! type -p 'ghci' && echo 'warn: missing: ghci'

_tryExec "_test_haskell"
```

## Reference

[https://downloads.haskell.org/~ghc/7.4.1/docs/html/users\\_guide/loading-source-files.html](https://downloads.haskell.org/~ghc/7.4.1/docs/html/users_guide/loading-source-files.html)

```
'Prelude> :cd dir'
      System.Directory.getCurrentDirectory
'save Main.hs'
```

[https://wiki.haskell.org/GHCi\\_in\\_colour](https://wiki.haskell.org/GHCi_in_colour)

<https://stackoverflow.com/questions/11250262/how-to-see-the-current-working-directory-in-winghci>

```
'System.Directory.getCurrentDirectory'
'A poor man's solution to set the ghci prompt to the current working directory would be putting'
'let cur fill = do { cwd <- System.Directory.getCurrentDirectory; return (":set prompt \"" ++ cwd ++ fill ++ "
\""); }

: def doprompt (\_ -> cur ">")
: def mycd (\dir -> System.Directory.setCurrentDirectory dir >> cur ">")
: doprompt'
'.ghci
':! allows shell commands'
```

[https://downloads.haskell.org/~ghc/5.04.1/docs/html/users\\_guide/ghci.html](https://downloads.haskell.org/~ghc/5.04.1/docs/html/users_guide/ghci.html)

<https://stackoverflow.com/questions/42311688/haskell-cant-load-a-file-in-ghci-changeworkingdirectory-does-not-exist>

```
'ghci -ignore-dot-ghci'
```

<https://hackage.haskell.org/package/base-4.16.0.0/docs/System-Environment.html>

```
'getEnv'
... "$scriptAbsoluteFolder"
exec(open(os.environ['scriptAbsoluteFolder']+'lean.py').read())
```

<https://gitlab.haskell.org/ghc/ghc/-/issues/10920>