Parsing 16/09/15 16:39

# **Parser**

This assignment is based on the project described in *Modern Compiler Implementation in ML*, section **PROGRAM**, pages 81-82 and pages 100-101. The source code mentioned in this section (as being available from \$Tiger/chap3 and \$Tiger/chap4) should be taken from the Documents (https://bb.au.dk/webapps/blackboard/content/listContent.jsp? course\_id=\_43271\_1&content\_id=\_355480\_1&mode=reset) part of this website, stored in the tar archive part3.tgz. This archive should be unpacked and used for an initial test as follows (where myPrompt stands for your command line prompt, such as dovs@linux-en0j:~, and it is assumed that you downloaded part3.tgz to your home directory, /home/dovs):

```
myPrompt> cd ~/dovs
myPrompt> tar xzf ~/part3.tgz
myPrompt> cd part3
myPrompt> make sa
...
myPrompt> ./compiletests
...
```

In order to obtain a working lexer you need to copy the contents of your tiger.lex from part2 to part3/tiger.lex. You cannot simply copy the file tiger.lex into part3, because you need to use a type svalue, type token, type lexresult, and %header directive as specified in part3/tiger.lex, but the rest should be directly reusable in part3. The file rescue—tiger.lex.sml contains the ML-Lex output from a working lexer; you may use this in case your own lexer does not fully work.

The Makefile contains several goals that you may use (to use goal X, execute make X). Compared to part2, the goal sa has been added to the Makefile as a shorthand for the goal standalone, which will generate a stand-alone binary compiler that is executed by the script tigerc. For an interactive session ('REPL'), use the goal ia, or the long form interact. A new goal rs, short for rescue, has been added. This goal will generate a binary compiler using the lexer implementation in rescue—tiger.lex.sml. You may inspect the Makefile and the script forcetigerc to see how this is done; the main point is that touch is used on tiger.lex.sml to ensure that it is used as-is, rather than being overwritten (if it is older than tiger.lex then the compilation manager will run ML-Lex and it will then generate a new tiger.lex.sml based on your tiger.lex, which will prevent the use of the rescue lexer).

# **Parser requirements**

The parser should parse the Tiger language as specified in the appendix, extended with the exponentiation expression *exp* ^ *exp*. Exponentiation operator has the second-highest precedence after unary minus, i.e., it binds tighter than \* or /, but weaker than unary minus.

The parser should use the semantic actions to construct an abstract syntax tree for the program. Note that the initial source code provided for this project is ready for the construction of a parser that does not return anything, corresponding to a set of empty semantic actions. It is recommended that you construct such a "check only" parser first, and only implement the semantic actions when the grammar works correctly. Note that the parser return type must then be adjusted in several locations in the source code.

### **Parsing conflicts**

Parsing 16/09/15 16:39

The parser should not have reduce/reduce conflicts or shift/reduce conflicts. If you have a small number of shift/reduce conflicts, then they should be described in your report, explaining why they are benign. It is possible to create the parser without shift/reduce conflicts so this should be your goal.

#### **Test cases**

You should also create 5 small Tiger programs containing syntax errors, and describe how your parser reacts to them in your report. Make sure that your implementation works on the provided test files

../testcases/test{0,1,2}?.tig, which should all parse without errors. You should deliver the source code in an archive:

```
myPrompt> cd ~/dovsproject
myPrompt> zip -r ~/part3.zip part3
```

### Report

The project should be documented by a short report, only a handful of pages. It may be formatted using LaTeX or other document processing systems and delivered as a PDF file, or it may be a plain ASCII file. The report must briefly describe your approach, especially insofar as it differs from the project description due to, e.g., problems making it work, or interesting experiments. Use the report template provided for this hand-in as a starting point.

### **Deliverables**

• part3.zip This is a zip archive file that will contain your solution. This file can be obtained by running the command

```
myPrompt> cd ~/dovsproject
myPrompt> zip -r ~/part3.zip part3
```

This file should include the source code to your solution.

- part3-tests.zip This is a zip file (created in a similar manner as above) that should contain the five test cases that you created.
- *Project report* as a PDF file. See the section of the site for a template, and description above for what to include in the report.

## **Submission instructions**

Upload three file: part3.zip, part3-tests.zip, and part3-report.pdf using the course submission system (http://dovs.cs.au.dk/).

## **Deadline**

Wednesday, September 23rd, 14:00.

Content on this page is maintained by Aslan Askarov.