

Sensitivity analysis of climate change risk assessment

Study of parameters variation in hazard indicators

Marco Casari

Supervisors

Prof.ssa Elisa Palazzi

Prof. Alberto Viglione


University of Turin

Midterm discussion, 4 July 2024

- ▶ Risk: potential for adverse consequences for human or ecological systems [...]

Introduction

- ▶ Risk: potential for adverse consequences for human or ecological systems [...]
- ▶ Climate Change Risk Assessment (CCRA)



The problem

- ▶ The choice of indicators is arbitrary

The problem

- ▶ The choice of indicators is arbitrary
- ▶ Analysis of the sensitivity of indicators to a change in value of their parameters, for drivers within the hazard determinant

► Torino Airport

Case study

- ▶ Torino Airport
- ▶ Hazard drivers: heat wave, heavy precipitation

- ▶ Climatological baseline: ERA5
- ▶ Climate projections: NEX-GDDP-CMIP6

- ▶ Organisation: European Centre for Medium-Range Weather Forecasts
- ▶ Data type: reanalysis
- ▶ Spatial coverage: global
- ▶ Spatial resolution: $0.25^\circ \times 0.25^\circ$
- ▶ Temporal coverage: 1940-present
- ▶ Temporal resolution: hour

- ▶ Organisation: NASA Earth Exchange
- ▶ Data type: statistically downscaled bias-corrected climate projections
- ▶ Spatial coverage: global
- ▶ Spatial resolution: $0.25^{\circ} \times 0.25^{\circ}$
- ▶ Temporal coverage: 1950-2100
- ▶ Temporal resolution: day
- ▶ Historical period 1950-2014, projection period 2015-2100
- ▶ Model: EC-Earth3
- ▶ Scenario: SSP1-2.6, SSP2-4.5, SSP5-8.5

- ▶ Box of 3×3 grid points centred at the coordinates of the airport

Temporal domain

- ▶ Baseline period: 1994-2023
- ▶ Time horizons: 2021-2040, 2051-2070, 2081-2100

- ▶ Indicators: heat wave frequency, maximum n -days precipitation
- ▶ Fixed exposure and vulnerability from literature


- ▶ Indicators: heat wave frequency, maximum n -days precipitation
- ▶ Fixed exposure and vulnerability from literature
- ▶ Evaluate risk following the guidelines

Preprocessing

1. Regrid ERA5
2. Aggregate ERA5 at daily frequency
3. Align NEX-GDDP-CMIP6 timestamps




Preprocessing

1. Regrid ERA5
2. Aggregate ERA5 at daily frequency
3. Align NEX-GDDP-CMIP6 timestamps
4. Bias adjustment





Preprocessing

1. Regrid ERA5
2. Aggregate ERA5 at daily frequency
3. Align NEX-GDDP-CMIP6 timestamps
4. Bias adjustment



Evaluation of hazard indicators

1. Define intervals of parameter values



Evaluation of hazard indicators

1. Define intervals of parameter values
2. Spatial aggregation


Evaluation of hazard indicators

1. Define intervals of parameter values
2. Spatial aggregation
3. Temporal aggregation


Evaluation of hazard indicators

1. Define intervals of parameter values
2. Spatial aggregation
3. Temporal aggregation
4. Risk evaluation

Heat wave frequency



Maximum n -days precipitation



Next steps

- ▶ Extend analysis to other indicators for same hazard drivers
- ▶ Extend analysis to Bologna's and Ciampino's airports
- ▶ Sample intervals specifically for the location of interest
- ▶ Evaluate uncertainty
- ▶ Evaluate risk with non-linear relations among hazard indicators and among determinants