





# Introduction

- Predictive coding model of Rao and Ballard.
- Free-energy model of Friston.

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Introduction

└ Introduction

1. Prior predictions are compared to stimuli and the model parameters are updated considering prediction errors, features corresponding to receptive fields in the the primary sensory cortex are learned.
2. Weight stimuli by their noise, learn features using their covariance, implement attentional modulation changing the variance of attended features.

- Predictive coding model of Rao and Ballard.
- Free-energy model of Friston.

# Introduction

- Predictive coding model of Rao and Ballard.
- Free-energy model of Friston.
- Hebbian plasticity.

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Introduction

└ Introduction

1. Prior predictions are compared to stimuli and the model parameters are updated considering prediction errors, features corresponding to receptive fields in the the primary sensory cortex are learned.
2. Weight stimuli by their noise, learn features using their covariance, implement attentional modulation changing the variance of attended features.
3. Synaptic strenght is changed proportionally to activities of pre-synaptic and post-synaptic neurons.

- Predictive coding model of Rao and Ballard.
- Free-energy model of Friston.
- Hebbian plasticity.

# Introduction

- Predictive coding model of Rao and Ballard.
- Free-energy model of Friston.
- Hebbian plasticity.
- Free energy minimization.

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

## └ Introduction

### └ Introduction

1. Prior predictions are compared to stimuli and the model parameters are updated considering prediction errors, features corresponding to receptive fields in the the primary sensory cortex are learned.
2. Weight stimuli by their noise, learn features using their covariance, implement attentional modulation changing the variance of attended features.
3. Synaptic strenght is changed proportionally to activities of pre-synaptic and post-synaptic neurons.
4. Minimization of free energy can be seen as the base of many theories of perception.

- Predictive coding model of Rao and Ballard.
- Free-energy model of Friston.
- Hebbian plasticity.
- Free energy minimization.

# Working hypotheses

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Introduction

└ Working hypotheses

1. The state of a neuron is determined only by the synaptic weight and the state of its input neurons.

1 Local computation.

## Working hypotheses

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Introduction

└ Working hypotheses

1. The state of a neuron is determined only by the synaptic weight and the state of its input neurons.
2. Synaptic plasticity depends only on the activities of pre-synaptic and post-synaptic neurons.

- Local computation.
- Local plasticity.

1. The state of a neuron is determined only by the synaptic weight and the state of its input neurons.
2. Synaptic plasticity depends only on the activities of pre-synaptic and post-synaptic neurons.
3. The state of a neuron is the result of the application of a monotonic function to the linear combination of states and synaptic weights of input neurons.



- Feature is a scalar variable  $v \in \Omega_v$ .
- Stimulus is a scalar variable  $u \in \Omega_u$ .

- Feature is a scalar variable  $v \in \Omega_v$ .
- Stimulus is a scalar variable  $u \in \Omega_u$ .
- Relation between feature and stimulus is a differentiable function  $g : \Omega_v \rightarrow \Omega_u$ .

- Feature is a scalar variable  $v \in \Omega_v$ .
- Stimulus is a scalar variable  $u \in \Omega_u$ .
- Relation between feature and stimulus is a differentiable function  $g : \Omega_v \rightarrow \Omega_u$ .



- ◀ ◻ ▶ ◀ ◻ ▶ ◀ ≡ ▶ ◀ ≡ ▶ ≡ ↺ 🔍 ↻

# Exact solution to the inference problem

- Bayes theorem:

$$p(v|u) = \frac{p(v)p(u|v)}{p(u)} \quad (1)$$

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Single variable model

└ Exact solution to the inference problem

1. Knowledge of feature depending on a given stimulus is the posterior. Prior knowledge on the feature is the prior, distribution of stimulus is the likelihood.

• Bayes theorem:  $p(v|u) = \frac{p(v)p(u|v)}{p(u)}$  . (1)

# Exact solution to the inference problem

- Bayes theorem:

$$p(v|u) = \frac{p(v)p(u|v)}{p(u)} \quad . \quad (1)$$

- Marginal likelihood of stimuli:

$$p(u) = \int_{\Omega_v} p(v)p(u|v) dv \quad . \quad (2)$$

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Single variable model

└ Exact solution to the inference problem

1. Knowledge of feature depending on a given stimulus is the posterior. Prior knowledge on the feature is the prior, distribution of stimulus is the likelihood.
2. In general, marginal likelihood is difficult to evaluate.

- Bayes theorem:  $p(v|u) = \frac{p(v)p(u|v)}{p(u)} \quad . \quad (1)$

- Marginal likelihood of stimuli:  $p(u) = \int_{\Omega_v} p(v)p(u|v) dv \quad . \quad (2)$



# Approximate solution to the inference problem

- Most likely value of the feature is a scalar variable  $\phi \in \Omega_v$ .

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Single variable model

└ Approximate solution to the inference problem

1. Evaluating the mode of the posterior instead of the whole function is more biologically plausible.

- Most likely value of the feature is a scalar variable  $\phi \in \Omega_v$ .



$$F(v, u) = \ln(p(v)p(u|v)) \quad (3)$$



# Neural implementation




Fig. 3 from article: network implementation of the dynamical system

$$\begin{cases} \dot{\phi} = \varepsilon_u g'(\phi) - \varepsilon_p \\ \dot{\varepsilon}_p = \phi - v_p - \Sigma_p \varepsilon_p \\ \dot{\varepsilon}_u = u - g(\phi) - \Sigma_u \varepsilon_u \end{cases} . \quad (6)$$

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Single variable model

└ Neural implementation

- Note that hypotheses are satisfied.



Fig. 3 from article: network implementation of the dynamical system

$$\begin{cases} \dot{\phi} = \varepsilon_u g'(\phi) - \varepsilon_p \\ \dot{\varepsilon}_p = \phi - v_p - \Sigma_p \varepsilon_p \\ \dot{\varepsilon}_u = u - g(\phi) - \Sigma_u \varepsilon_u \end{cases} . \quad (6)$$

- Choose model parameters to maximize  $p(u)$ .

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

- Single variable model

- Learning model parameters

1. Model parameters are mean and variance of variables.

- Choose model parameters to maximize  $p(u)$ .

# Learning model parameters

- Choose model parameters to maximize  $p(u)$ .
- Equivalent to maximize negative free energy with respect to parameters:

$$\frac{\partial F}{\partial v_p} = \frac{\phi - v_p}{\Sigma_p} \quad , \quad (7)$$

$$\frac{\partial F}{\partial \Sigma_p} = \frac{1}{2} \left( \frac{(\phi - v_p)^2}{\Sigma_p^2} - \frac{1}{\Sigma_p} \right) \quad , \quad (8)$$

$$\frac{\partial F}{\partial \Sigma_u} = \frac{1}{2} \left( \frac{(u - g(\phi))^2}{\Sigma_u^2} - \frac{1}{\Sigma_u} \right) \quad . \quad (9)$$

2023-12-12

## Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Single variable model

└ Learning model parameters

- Model parameters are mean and variance of variables.
- The fixed point of this dynamical system exists only as sample mean over the occurred events of perception, where most likely feature value and stimulus are known.

- Choose model parameters to maximize  $p(u)$ .
- Equivalent to maximize negative free energy with respect to parameters:

$$\frac{\partial F}{\partial v_p} = \frac{\phi - v_p}{\Sigma_p} \quad , \quad (7)$$

$$\frac{\partial F}{\partial \Sigma_p} = \frac{1}{2} \left( \frac{(\phi - v_p)^2}{\Sigma_p^2} - \frac{1}{\Sigma_p} \right) \quad , \quad (8)$$

$$\frac{\partial F}{\partial \Sigma_u} = \frac{1}{2} \left( \frac{(u - g(\phi))^2}{\Sigma_u^2} - \frac{1}{\Sigma_u} \right) \quad . \quad (9)$$

# Learning model parameters

- Choose model parameters to maximize  $p(u)$ .
- Equivalent to maximize negative free energy with respect to parameters:

$$\frac{\partial F}{\partial v_p} = \frac{\phi - v_p}{\Sigma_p} \quad , \quad (7)$$

$$\frac{\partial F}{\partial \Sigma_p} = \frac{1}{2} \left( \frac{(\phi - v_p)^2}{\Sigma_p^2} - \frac{1}{\Sigma_p} \right) \quad , \quad (8)$$

$$\frac{\partial F}{\partial \Sigma_u} = \frac{1}{2} \left( \frac{(u - g(\phi))^2}{\Sigma_u^2} - \frac{1}{\Sigma_u} \right) \quad . \quad (9)$$

- Hebbian plasticity is satisfied using prediction errors.

2023-12-12

## Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Single variable model

└ Learning model parameters

- Model parameters are mean and variance of variables.
- The fixed point of this dynamical system exists only as sample mean over the occurred events of perception, where most likely feature value and stimulus are known.
- Without prediction errors, the computation is still local.

- Choose model parameters to maximize  $p(u)$ .
- Equivalent to maximize negative free energy with respect to parameters:

$$\frac{\partial F}{\partial v_p} = \frac{\phi - v_p}{\Sigma_p} \quad , \quad (7)$$

$$\frac{\partial F}{\partial \Sigma_p} = \frac{1}{2} \left( \frac{(\phi - v_p)^2}{\Sigma_p^2} - \frac{1}{\Sigma_p} \right) \quad , \quad (8)$$

$$\frac{\partial F}{\partial \Sigma_u} = \frac{1}{2} \left( \frac{(u - g(\phi))^2}{\Sigma_u^2} - \frac{1}{\Sigma_u} \right) \quad . \quad (9)$$

- Hebbian plasticity is satisfied using prediction errors.

# Learning relation parameter

- Linear relation:

$$g(v, \theta) = \theta v \quad . \quad (10)$$

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Single variable model

└ Learning relation parameter

1. Only one parameter is considered without loss of generality.









# Free energy framework

- Minimization of Kullback-Leibler divergence:

$$KL(q(v)||p(v|u)) = \int_{\Omega_v} q(v) \ln \left( \frac{q(v)}{p(v|u)} \right) dv \quad . \quad (13)$$

- Definition of negative free energy:

$$F(v, u) = \int_{\Omega_v} q(v) \ln \left( \frac{p(v, u)}{q(v)} \right) dv \quad . \quad (14)$$

2023-12-12

## Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Single variable model

└ Free energy framework

- In general, the posterior is approximated by a simpler probability distribution and the divergence between the two is minimized.
- Minimize KL divergence or maximize negative free energy to learn most likely model value, maximize marginal likelihood or maximize negative free energy to learn model parameters.

- Minimization of Kullback-Leibler divergence:

$$KL(q(v)||p(v|u)) = \int_{\Omega_v} q(v) \ln \left( \frac{q(v)}{p(v|u)} \right) dv \quad . \quad (13)$$

- Definition of negative free energy:

$$F(v, u) = \int_{\Omega_v} q(v) \ln \left( \frac{p(v, u)}{q(v)} \right) dv \quad . \quad (14)$$

# Free energy framework

- Minimization of Kullback-Leibler divergence:

$$KL(q(v)||p(v|u)) = \int_{\Omega_v} q(v) \ln \left( \frac{q(v)}{p(v|u)} \right) dv \quad . \quad (13)$$

- Definition of negative free energy:

$$F(v, u) = \int_{\Omega_v} q(v) \ln \left( \frac{p(v, u)}{q(v)} \right) dv \quad . \quad (14)$$

- For the models discussed in the paper:  $q(v) = \delta(v - \phi)$ .

2023-12-12

## Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Single variable model

└ Free energy framework

- In general, the posterior is approximated by a simpler probability distribution and the divergence between the two is minimized.
- Minimize KL divergence or maximize negative free energy to learn most likely model value, maximize marginal likelihood or maximize negative free energy to learn model parameters.
- Equation (3) is recovered using delta function centered in the most likely feature value as probability distribution.

- Minimization of Kullback-Leibler divergence:

$$KL(q(v)||p(v|u)) = \int_{\Omega_v} q(v) \ln \left( \frac{q(v)}{p(v|u)} \right) dv \quad . \quad (13)$$

- Definition of negative free energy:

$$F(v, u) = \int_{\Omega_v} q(v) \ln \left( \frac{p(v, u)}{q(v)} \right) dv \quad . \quad (14)$$

- For the models discussed in the paper:  $q(v) = \delta(v - \phi)$ .



# Hierarchical structure implementation

- Parallel to structure of cortical areas.

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Multiple variables model

└ Hierarchical structure implementation

1. Information is used and travels in different layers of the cortex.

# Hierarchical structure implementation

- Parallel to structure of cortical areas.
- Generalized equations for the inference task:

$$\dot{\vec{\phi}}_i = -\vec{\varepsilon}_i + h'(\vec{\phi}_i) \times \mathbf{\Theta}_{i-1}^\top \vec{\varepsilon}_{i-1} \quad , \quad (15)$$

$$\dot{\vec{\varepsilon}}_i = \vec{\phi}_i - \mathbf{\Theta}_i h(\vec{\phi}_{i+1}) - \mathbf{\Sigma}_i \vec{\varepsilon}_i \quad . \quad (16)$$

- Generalized equations for the learning task:

$$\frac{\partial F}{\partial \mathbf{\Sigma}_i} = \frac{1}{2}(\vec{\varepsilon}_i \vec{\varepsilon}_i^\top - \mathbf{\Sigma}_i^{-1}) \quad , \quad (17)$$

$$\frac{\partial F}{\partial \mathbf{\Theta}_i} = \vec{\varepsilon}_i h(\vec{\phi}_{i+1})^\top \quad . \quad (18)$$

2023-12-12

## Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

- └ Multiple variables model
  - └ Hierarchical structure implementation

1. Information is used and travels in different layers of the cortex.
2. Note the elementwise product and matrices of model and relation parameters.

Hierarchical structure implementation

- Parallel to structure of cortical areas.
- Generalized equations for the inference task:
 
$$\dot{\vec{\phi}}_i = -\vec{\varepsilon}_i + h'(\vec{\phi}_i) \times \mathbf{\Theta}_{i-1}^\top \vec{\varepsilon}_{i-1} \quad , \quad (15)$$

$$\dot{\vec{\varepsilon}}_i = \vec{\phi}_i - \mathbf{\Theta}_i h(\vec{\phi}_{i+1}) - \mathbf{\Sigma}_i \vec{\varepsilon}_i \quad . \quad (16)$$
- Generalized equations for the learning task:
 
$$\frac{\partial F}{\partial \mathbf{\Sigma}_i} = \frac{1}{2}(\vec{\varepsilon}_i \vec{\varepsilon}_i^\top - \mathbf{\Sigma}_i^{-1}) \quad , \quad (17)$$

$$\frac{\partial F}{\partial \mathbf{\Theta}_i} = \vec{\varepsilon}_i h(\vec{\phi}_{i+1})^\top \quad . \quad (18)$$

## Recover local plasticity




Fig. 7 from article: networks satisfying local plasticity for (a) single variable model and (b) multiple variables model. They implement the generalized dynamical system

$$\begin{cases} \dot{\vec{\varepsilon}}_i = \vec{\phi}_i - g_i(\vec{\phi}_{i+1}) - \vec{\varepsilon}_i \\ \dot{\vec{e}}_i = \mathbf{\Sigma}_i \vec{\varepsilon}_i - \vec{e}_i \end{cases} . \quad (19)$$

2023-12-12

## Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└ Multiple variables model

└ Recover local plasticity

- The update rule for the model parameters is Hebbian and contains the learning rate as hyperparameter of the model.
- Convergence of prediction errors to the sample variances is guaranteed if the most likely feature values change at slower time scales.



Fig. 7 from article: networks satisfying local plasticity for (a) single variable model and (b) multiple variables model. They implement the generalized dynamical system

$$\begin{cases} \dot{\vec{\varepsilon}}_i = \vec{\phi}_i - g_i(\vec{\phi}_{i+1}) - \vec{\varepsilon}_i \\ \dot{\vec{e}}_i = \mathbf{\Sigma}_i \vec{\varepsilon}_i - \vec{e}_i \end{cases} . \quad (19)$$



# Conclusion

- Stimuli weighted by noise.
- Learn covariance of stimuli.
- Attentional modulation.

2023-12-12

Summary of *A tutorial on the free-energy framework for modelling perception and learning* by Rafal Bogacz

└─ Conclusion

└─ Conclusion

- Stimuli weighted by noise.
- Learn covariance of stimuli.
- Attentional modulation.