

DoGoodie Paired Testing Lab

Pilot Handoff and Demo Guide

Audience: pilot owners, administrators, coordinators, testers, reviewers, viewers, and deployment maintainers

Document status: current-build operating guide

Last updated: 12 August 2026

Production URL: <https://pairedtesting-lab.vercel.app/>

System of record: the deployed application, its linked Supabase project, and the release commit recorded in the technical handoff

This system organizes controlled paired pricing observations. It does not, by itself, prove discrimination, causation, intent, liability, statistical significance, scientific validity, or legal admissibility. Qualified methodology and legal reviewers remain responsible for study design and interpretation.

1. Quick Start

Use this section during a pilot. Use the later sections for preparation, training, and troubleshooting.

Before collection

- ☐ The study owner approved the research question, isolated variable, A/B conditions, controls, tolerances, evidence, exclusions, and target.
- ☐ The coordinator verified the country, pickup and destination pins, timezone, currency, provider, and service/tier for both sides.
- ☐ The protocol and study are active.
- ☐ Every participant has an individual active account and active study membership.
- ☐ Testers completed Device Profile and confirmed device, app, recording, location, connectivity, and availability.
- ☐ Assignments use the intended timezone and testing windows.
- ☐ A secure escalation channel, export location, incident contact, and retention owner are known.

Go/no-go rule: Do not begin collection if any required item above is unresolved.

Run one paired assignment

1. Each tester opens **Assigned Studies**, selects the study, opens the featured **Next assignment**, and verifies the locked route, service/tier, condition, instructions, and window.
2. Each tester completes the readiness checklist and selects **Confirm ready**.
3. During the allowed window, each tester selects **Start test**. Synchronized assignments require both testers to be ready.

4. Each tester follows the in-app capture procedure, acknowledges every capture-checklist item, and unlocks evidence upload.
5. Each tester uploads the screenshot first. Google Cloud Vision processes it asynchronously; the tester confirms the correct detected ride card, fare, and status-bar time, then uploads the required recording.
6. After both testers' evidence sets are complete, each tester completes the remaining observation details, saves the latest changes, reviews the record, and selects **Submit and lock** independently. The application then shows a read-only submission receipt.
7. After both sides submit, the system creates one matched pair and runs technical validation.
8. A reviewer examines both observations, validation results, and evidence before recording a decision.

Close the pilot

- [] Every assignment is completed, cancelled, expired, or has a named next action.
- [] Every matched pair has a final review or is explicitly listed as pending.
- [] Invalid, warning, incomplete, and replacement outcomes are explained.
- [] Dashboard, pair table, exports, and report counts reconcile.
- [] Evidence and metadata were spot-checked by an authorized reviewer.
- [] PDF output was checked for clipping and page breaks.
- [] Access was removed for people who no longer need it.
- [] Product bugs, training issues, protocol issues, and methodology questions were separated in the debrief.

2. System Model

A complete test unit follows this lifecycle:

Study -> Active protocol -> Assignment -> Two observations -> Matched pair -> Technical validation -> Human review -> Report/export

Terms that must remain distinct

Term	Meaning
Technical validation	Deterministic checks against the locked assignment and protocol.
Human review	A documented decision about whether the pair is usable.
Price difference	A descriptive comparison, not a finding of causation or liability.
Accepted usable pair	A pair included under the configured report rules and counted toward the study target.
Directional difference	$\text{Tester B fare} - \text{Tester A fare}$. Positive means B was higher.
Percentage difference	$(B - A) / A \times 100$. Not calculated when A is zero.

Technical statuses

Status	Operational meaning	Required action
Valid	Required technical rules passed.	Send for human review.
Warning	A preferred/advisory tolerance was exceeded.	Review the affected rule and evidence.
Invalid	At least one required rule failed.	Reject or use an authorized, documented exception.
Incomplete	Partner response or required data/evidence is missing.	Resolve or schedule a replacement.
Pending	Pair creation or validation is not finished.	Check both tester submissions and processing state.

Technical status and human review status are separate. A reviewer decision must never rewrite the underlying technical result.

3. Roles and Ownership

Use one named account per person and grant the minimum required role. Global role alone does not grant study access; active study membership is also required.

Role	Primary responsibilities	Must not do
Administrator	Invite accounts, manage global roles, oversee access and deployment ownership.	Share credentials or grant broad access for convenience.
Coordinator	Configure studies and protocols, manage membership, schedule assignments, monitor collection, and prepare outputs.	Alter an active protocol to repair collected data.
Tester	Use Assigned Studies to find current work, verify the assignment, coordinate timing with the named partner, execute the assigned condition, capture evidence, and submit an accurate observation.	Coordinate or disclose observed prices, edit evidence, book a ride, or use another person's account.
Expert reviewer	Inspect observations, rule results, and evidence; accept, accept with exception, reject, or clear a decision.	Treat technical validation as a legal or causal conclusion.
Law-firm viewer	Read released completed/archived assigned outputs.	Open raw evidence or export data unless separately authorized.
Deployment maintainer	Manage Vercel/Supabase configuration, migrations, backups, monitoring, and incident response.	Put secrets in source control, documents, screenshots, or chat.

For demonstrations and QA, use separate browser profiles for separate users so sessions and permissions are not mixed.

Navigation and data scope

The current interface separates portfolio-level pages from one-study workspaces:

- **Dashboard** opens the portfolio dashboard for authorized non-tester roles. Use the scope selector in the page header to switch between **All studies** and one accessible study.

- **Study Management**, **Assigned Studies**, **Review Studies**, and **Released Studies** are role-specific study libraries. Selecting a study opens its dedicated workspace.
- A study workspace has role-filtered tabs: **Overview**, **Protocol**, **Assignments**, **Matched Pairs**, **Evidence**, and **Activity Log**. Testers see only Overview and Assignments; other tabs appear only when the role permits them.
- **Reports** opens a report library across accessible studies. Reports can be filtered as interim or final and opened without changing a hidden global study selection.
- **Activity Log** at the main-navigation level is a portfolio activity view. The Activity Log inside a study workspace is scoped to that study.

The application now uses clean public paths such as `/dashboard`, `/studies`, `/tester-studies`, and `/reports`. Older `/paired-testing-demo/...` links redirect to the corresponding clean path.

4. Readiness Gates

Gate A: Environment ready

Owner: deployment maintainer

Pass when:

- The intended Vercel deployment is healthy.
- Production environment variables point to the intended Supabase project and production site URL.
- Required migrations are applied.
- Public registration is disabled.
- Invitation and password-recovery links work on the deployed domain.
- Private evidence storage policies and size limits are confirmed.
- Google Cloud Vision is enabled and `OCR_PROVIDER=google` plus the three server-only Google credential variables are configured.
- A sanitized test screenshot completes OCR and opens the candidate-confirmation screen.
- Backup, retention, monitoring, incident response, and key-rotation ownership are assigned.

Gate B: Study design ready

Owner: study/methodology owner

Pass when:

- Research question and descriptive purpose are approved.
- Country, exact route pins, timezone, currency, provider, and services are correct.
- Isolated variable and A/B labels are unambiguous.
- Fixed controls, tolerances, evidence, observation fields, exclusions, and target are approved.
- Any external randomization or counterbalancing allocation is preserved.

Gate C: People ready

Owner: coordinator

Pass when:

- Required accounts are active with correct global roles and study membership.
- Testers completed Device Profile and device/browser checks.
- Participants received the same operational instructions and escalation contact.
- Backup testers and replacement capacity are available.

Gate D: Assignment ready

Owner: coordinator and assigned testers

Pass when:

- The active assignment locks the intended protocol, route, side-specific service/tier, conditions, currency, timezone, and schedule.
 - The schedule is inside the study period and displayed in the intended timezone.
 - Tester A and Tester B are distinct eligible accounts.
 - Required capture and recording tools are ready.
-

5. Configuration Guide

Create the study

1. Open **Studies -> Create study**.
2. Enter the study name, purpose, owner, and target accepted-pair count.
3. Select the country before setting the route.
4. Search and pin both pickup and destination. Verify the map pins and written addresses visually.
5. Review the derived timezone and currency.
6. Select the provider and exact service/tier for Tester A and Tester B.
7. Enable side-specific operating-system restrictions only when the protocol requires them.
8. Set the testing date range and review the summary.
9. Create the draft study, then add testers, reviewers, viewers, and coordinators through **Membership**.

Geocoding is an operational aid, not a legal determination of jurisdiction.

Configure the protocol

Complete and review:

1. Study question and protocol details.
2. Isolated variable and exact Tester A/Tester B values.
3. Matching controls.
4. Validation thresholds.

5. Evidence and observation requirements.
6. Exclusion conditions and final preview.

Activate only after approval. An active protocol version is locked. Later methodology changes require a new documented version and must not silently alter prior assignments.

Pairing and allocation

The coordinator currently selects Tester A and Tester B manually. The application does not implement study randomization, side allocation, counterbalancing, route allocation, or time-block randomization.

When random allocation is required:

1. Use an approved external reproducible procedure.
 2. Preserve its method, seed, allocation sheet, and author.
 3. Enter the resulting assignments without changing the allocation.
 4. Record deviations factually.
-

6. Collection Procedures

Coordinator: create assignments

1. Open **Assignments** -> **Create assignment**.
2. Select the active protocol and route.
3. Confirm the locked side-specific provider and service/tier.
4. Choose synchronized or asynchronous testing when available.
5. Set the date and windows in the displayed study timezone.
6. Set the number of paired sessions and select distinct eligible testers.
7. Add operational instructions that clarify execution without changing the protocol.
8. Review and create the assignments.

For asynchronous work, Tester B must begin at or after Tester A's window ends. The request-time synchronization rule is not applicable, but other configured controls remain active.

Tester: prepare

Before test day:

- Open **Assigned Studies**, select the study, and use its Overview to see assigned, actionable, and submitted sessions. The featured card identifies the next assignment and links to the full assignment list.
- Update **Device profile** with accurate stable device information.
- Confirm the assigned condition and service/tier.
- Verify location permission, connectivity, battery, storage, and screen recording.
- Disable notification previews and remove unrelated personal content from view.
- Use the partner name and email shown on the assignment only for operational coordination. The paired roster may also show the partner's assigned protocol condition.

- Coordinating readiness and the start cue is allowed; disclosing or comparing observed quotes before both submissions are locked is not allowed.

Tester: capture and submit

1. Open **Assigned Studies**, select the study, then open the featured assignment or the **Assignments** tab. Read the locked route, condition, service/tier, window, and coordinator instructions.
2. Complete all readiness items and select **Confirm ready**.
3. Select **Start test** only within the allowed tester-side window.
4. Follow the countdown or independent-start instruction.
5. Follow the displayed capture steps or open the video tutorial. Start screen recording, use the exact locked route and service/tier, capture the quote without booking, take the full-screen screenshot, then stop and save the recording.
6. Complete every **Confirm before uploading** item and select **Unlock evidence upload**.
7. Upload the screenshot first. While Google Cloud Vision is working, the page shows **waiting for OCR** or **Processing screenshot OCR**; the job is retried automatically after temporary failures.
8. When candidate review opens, select the complete ride card, the fare inside that card, and the device time in the status bar. Replace both evidence files when the correct values are unavailable or the attempt must be repeated.
9. Upload the required screen recording. When your evidence is complete, the application may show **Waiting for [partner]'s evidence**.
10. After both evidence sets are ready, capture the current location and complete only the observation fields required by the active protocol, such as app version, network category, battery percentage, or notes.
11. Select **Save draft**, then **Review and submit**, verify the confirmation checklist, and select **Submit and lock**.
12. Confirm the read-only submission receipt shows the assignment, condition, fare, evidence count, route, and submission time. Return to the study assignment list; no further editing is available unless the record is formally reopened.

Submission locks the observation. Do not repeatedly resubmit after an error; record the exact error and escalate.

7. Review and Reporting

Reviewer decision path

1. Open **Review Studies**, select the study, then select the study workspace's **Matched Pairs** tab.
2. Filter to pending work and open a pair. The study workspace remains the navigation context while the pair detail is open.
3. Compare both fares, timestamps, locations, assigned conditions, and service/tier.
4. Review every technical rule and both evidence records/files.
5. Select one outcome:

Outcome	Use when	Documentation
Accept pair	Complete evidence and acceptable technical result.	Select the applicable reason and factual note.
Accept with technical exception	An authorized reviewer deliberately includes a documented technical problem.	Detailed justification of at least 20 characters; use sparingly.
Reject pair	Pair must be excluded and normally replaced.	Factual reason and note of at least 10 characters.
Clear decision	Reassessment is required.	Explain why the decision returned to pending.

Report classification

- **Included:** expert accepted, evidence complete, and technically valid/warning; or accepted with a documented authorized exception.
- **Pending:** no final expert decision.
- **Excluded:** rejected or fails inclusion requirements.

Before distribution:

1. Open **Dashboard** and use the scope selector to choose the study. Do not reconcile a single-study report against the **All studies** portfolio totals.
2. Reconcile accepted usable counts across the study-scoped Dashboard, the study workspace's **Matched Pairs** tab, and the report.
3. Open **Reports**, search for the study name/code, confirm whether it is marked **Interim** or **Final**, and select **Open report**.
4. Open CSV/JSON exports and confirm expected columns and row counts.
5. Preview the report and use browser **Print / Save PDF**.
6. Check Letter page breaks, clipped tables, charts, date/timezone labels, and included/pending/excluded counts.
7. Store exports only in the approved secure location.

Use the main **Activity Log** to inspect events across accessible studies. Use **Study Management/Review Studies -> select study -> Activity Log** when investigating a single study. Filters are category-scoped so actor, object, action, and date choices remain relevant to the selected activity scope.

8. Failure and Repeat Rules

Never repair a failed test by editing evidence, coordinating fares, or changing an active protocol retroactively.

Situation	Action
Tester cannot start	Verify readiness, partner readiness for synchronized work, and tester-side window.
Evidence uploads remain locked	Complete all six capture acknowledgements and select Unlock evidence upload .
Screenshot shows queued/processing	Keep the page open or return later; the persisted OCR job is retried automatically. Record the assignment and evidence identifiers if it does not progress.
OCR fails after three attempts	Replace the screenshot only when the file is invalid; otherwise record the error and escalate so provider configuration and the job can be inspected.
Tester is waiting after completing evidence	The workflow intentionally waits for the partner's complete screenshot confirmation and recording before opening final session details.
Observation cannot save	Verify Device Profile, required fields, and timestamp/window.
Observation cannot submit	Verify confirmed screenshot, correct service, latest saved changes, and all required evidence.
Pair does not appear	Confirm both tester slots show submitted; capture codes and exact error before escalating.
Evidence is unreadable/mismatched	Replace it before submission; do not force an incorrect OCR confirmation.
Required rule fails	Preserve the original attempt and send it for review; schedule a replacement when directed.
Tester or device becomes unavailable	Cancel/expire with a documented reason and create a new assignment.
Protocol problem is discovered	Pause collection, preserve existing records, and create/approve a new protocol version.

Record the environment, study/assignment/pair code, role, local timestamp and timezone, browser/device, exact steps, exact error, and a sanitized screenshot. Never include passwords, tokens, or secrets.

9. Privacy and Security

Do not enter, upload, or share:

- Passwords, invitation/recovery links, API keys, database credentials, or access tokens.
- Payment details or provider login credentials.
- Government IDs, health information, unrelated chats, contacts, or private photos.
- Real passenger trip details, precise home addresses, or unnecessary third-party personal data.
- Cropped or edited evidence presented as original evidence.

Operational requirements:

- Use individual accounts and minimum permissions; never share logins.
- Use approved pilot identities and provider accounts.
- Assigned testers can see the paired partner's display name, email address, and assigned protocol condition for coordination. Use this information only for the assigned session and do not forward it. Testers do not

receive the partner's submission data through the roster.

- Law-firm viewers do not receive partner email addresses through the assignment roster.
 - Treat evidence and exports as sensitive even when storage is private.
 - Report lost devices, wrong-recipient access, account sharing, or exposed credentials immediately.
 - Agree retention and deletion rules before collecting real data.
 - Treat the activity log as operational history, not a cryptographically immutable chain of custody.
-

10. Recommended First Shakedown

This is an operational test, not a sample-size or statistical recommendation.

- One country and one short, unambiguous route.
- One provider and the same normalized service/tier on both sides.
- One approved isolated variable with clear A/B labels.
- Two primary testers and two backups.
- One coordinator, one reviewer, and one read-only viewer.
- Synchronized testing first; avoid cross-platform and asynchronous work in round one.
- Six planned matched pairs plus two replacement assignments.
- Stop after pair 1 for a process check, pair 3 for a data-quality check, and pair 6 for report/export QA.

Suggested operational success criteria:

- All users see only permitted studies and actions.
 - At least five of six planned pairs reach review without operator intervention.
 - Required evidence opens for authorized users and has complete metadata.
 - Invalid/incomplete attempts have traceable reasons and replacement decisions.
 - Report classification can be explained from underlying pairs.
 - Dashboard, CSV, JSON, and PDF counts reconcile.
-

11. Demo Run Sheet (20 Minutes)

Use a clearly labeled training study and approved demonstration evidence. Do not create fabricated records in a real pilot study.

Time	Area	Show	Key message
2 min	Portfolio Dashboard	All-studies totals, study scope selector, and descriptive boundary	Select the correct scope before interpreting or reconciling metrics.
3 min	Study workspace and Protocol	Select a study; show Overview tabs, route, services, A/B conditions, controls, tolerances, evidence, and locked version	Each study has a stable workspace; assignments inherit an approved version.
3 min	Membership and Assignment	Role-scoped tabs, partner roster, and one future assignment	Global role and study membership both matter; pairing is manual.
5 min	Tester journey	Assigned Studies overview, next assignment, Device Profile, partner contact, readiness, start, screenshot/OCR, recording, observation, submit, and receipt	Evidence-first workflow, permitted timing coordination, and locked submission.
3 min	Pair and validation	Directional difference and rule-level results	Technical status is deterministic and separate from review.
2 min	Expert review	Accept, exception, reject, clear	Exceptions require explicit human justification.
2 min	Reports and activity	Report library, interim/final stage, study report, global/study activity, exports, and PDF preview	Outputs remain descriptive, scoped, and subject to QA.

Demo recovery plan

- If two live tester accounts are unavailable, show a completed training pair.
- If external geocoding is unavailable, use an already configured training route.
- If email delivery is delayed, use previously activated training accounts; never share passwords.
- If evidence upload is unavailable, explain the expected flow and show existing approved training evidence.
- If an unexpected error occurs, stop the action, capture the sanitized error, and continue with a prepared completed record.

12. Technical Handoff

Environment ownership

The receiving operator needs these non-secret references:

- Production URL (<https://pairedtesting-lab.vercel.app/>) and any preview application URLs.
- Supabase project name/reference and owner.
- Vercel project and deployment owner.
- Migration maintainer.
- Monitoring/incident contact.
- Secure evidence export location and retention owner.
- Issue tracker and escalation channel.

Secrets must be delivered through the approved secret manager, never inside this guide or source control.

Required application variables

```
NEXT_PUBLIC_SUPABASE_URL
NEXT_PUBLIC_SUPABASE_PUBLISHABLE_KEY
NEXT_PUBLIC_SITE_URL
SUPABASE_SECRET_KEY
OCR_PROVIDER
GOOGLE_CLOUD_PROJECT_ID
GOOGLE_CLOUD_CLIENT_EMAIL
GOOGLE_CLOUD_PRIVATE_KEY
```

`SUPABASE_SECRET_KEY`, `GOOGLE_CLOUD_CLIENT_EMAIL`, and `GOOGLE_CLOUD_PRIVATE_KEY` are server-only and must never use the `NEXT_PUBLIC_` prefix. Production uses `OCR_PROVIDER=google`; Tesseract is an explicit controlled fallback and is never selected silently.

Developer verification

```
npm install
npm run typecheck
npm run lint
npm run test:run
npm run build
```

For local development, create an untracked `.env.local`, run `npm run dev`, and open `http://localhost:3000`. Routine testers, reviewers, viewers, and most developers do not need migration privileges, database passwords, or server secret keys.

Never run a linked database reset against a shared or production project.

Release record

Complete this table for every pilot release:

Item	Value
Application deployment URL	
Git commit	
Deployment date/time and timezone	
Supabase project reference	
Latest applied migration	
Pilot owner	
Coordinator	
Incident contact	
Approved export location	
Retention owner/policy reference	
Known limitations accepted by	

Post-update smoke checks

Run these checks after deploying the current navigation/study-workspace update:

- ☐ Old bookmarked `/paired-testing-demo/...` URLs redirect to their clean equivalents without losing the intended destination.
 - ☐ Administrator/coordinator navigation shows Dashboard, Study Management, Activity Log, and Reports.
 - ☐ Tester navigation shows Assigned Studies and the selected study overview identifies the next actionable assignment.
 - ☐ Reviewer navigation shows Review Studies; selecting one exposes the permitted Protocol, Matched Pairs, Evidence, and Activity Log tabs.
 - ☐ Viewer navigation shows only released studies and permitted read-only workspace tabs.
 - ☐ The Dashboard scope selector changes between portfolio and one-study computations without mixing totals.
 - ☐ The Reports library filters interim/final reports and opens the correct study report.
 - ☐ A tester sees only their paired roster's name, email, and protocol condition—not partner submission data.
 - ☐ Capture acknowledgement unlocks evidence upload, Google Vision OCR progresses through queued/processing/completed states, and correct detected boxes can be confirmed.
 - ☐ A tester with complete evidence sees the partner-waiting state until both evidence sets are ready.
 - ☐ Protocol-configured observation requirements control which final fields are mandatory.
 - ☐ A submitted tester sees a read-only receipt and can return to the study assignment history.
 - ☐ Global and study-scoped Activity Logs show the intended category-filtered events.
-

13. Current Limitations

- No live rideshare API, scraping, automated quote request, booking, or provider notification.
- No built-in randomization or counterbalancing engine.
- Google Cloud Vision OCR may misread fare, service, or time and requires tester confirmation; external API availability and billing configuration are production dependencies.
- Geocoding is not a jurisdictional authority.
- Thresholds, controls, exclusions, sample size, and interpretation require independent approval.
- Reminders, exception escalation, and replacement scheduling remain partly manual.
- Partner coordination occurs outside the application using the displayed contact information; the application does not provide chat, start-cue synchronization, or automated reminders.
- Activity history is not tamper-proof forensic chain-of-custody infrastructure.
- Browser-generated PDF output requires visual QA.
- Backups, monitoring, retention, incident response, and production operations remain environment-owner responsibilities.
- Provider/service availability must be confirmed in the actual environment before each pilot.

Treat unexpected behavior as a pilot finding. Preserve the record, document the context, and avoid undocumented workarounds.