`yacoub`: a Python package for Simulating Generalized Fading Channels

José V. de M. Cardoso, Paulo R. Lins Júnior,
Wamberto J. L. Queiroz, and Marcelo S. Alencar, *IEEE Senior Member*
Universidade Federal de Campina Grande
Instituto Federal de Educação, Ciencia, e Tecnologia da Paraíba
Campina Grande, Paraíba, Brasil
{josevinicius,paulo,wamberto,malencar}@iecom.org.br

***Abstract*—We present a well tested Python-based library for simulating and computing generalized fading channels, named `yacoub`. We describe the applicability of `yacoub` using examples in recent communications systems challenges, namely: cooperative spectrum sensing, bit error rate computation in generalized fading channel, and parameter estimation in free space optics. The development of `yacoub` open source and its code is avaliable at `http://github.com/mirca/yacoub`.**

I. Introduction

A. Note on notation

Scalars and random variables are denoted as *italic* small-case letters *e.g.* x; vectors and random vectors are denoted as *italic*, boldface, small-case letters *e.g.* $\boldsymbol{x}$. The $n-$th component of a vector $\boldsymbol{x}$ is denoted as x_n. A complex vector of length n is defined as $\boldsymbol{x} \in \mathbb{C}^{n\times 1}$. All vectors are column vectors. Matrices are denoted as *italic*, boldface, capital letters as in $\boldsymbol{X}$; the identity matrix of order n is denoted as $\boldsymbol{I}_n$. We define a discrete-time circularly symmetric Gaussian process $\boldsymbol{z}$ as any (finite or infinite) collection of random varibles $\boldsymbol{z} = \boldsymbol{x} + j\boldsymbol{y}$, $j \triangleq \sqrt{-1}$, such that $\boldsymbol{x}$ and $\boldsymbol{y}$ are iid jointly Gaussian with zero mean vector and covariance matrix given by $\mathbb{E}\left[\boldsymbol{z}\boldsymbol{z}^{\dagger}\right]$, in which $\boldsymbol{z}^{\dagger}$ means the conjugate transpose of $\boldsymbol{z}$ and $\mathbb{E}$ denotes the expected value. The probability of an event A is denoted as $\mathbb{P}(A)$.

II. The Acceptance-Rejection sampler in log-space

III. Examples

A. Spectrum Sensing in Complex Generalized Fading Channels

The spectrum sensing problem consists in deciding whether or not a given channel frequency band is being occupied by a licensed (primary) user and, in case that such frequency band is available, how to opportuniscally allocate secondary users such that the interference on the primary user is negligible.

From a probabilistic point of view, the spectrum sensing problem may be framed as a decision theory problem, as follows

$$H_0:\ \boldsymbol{y} = \boldsymbol{w}, \tag{1}$$
$$H_1:\ \boldsymbol{y} = h\boldsymbol{s} + \boldsymbol{w}, \tag{2}$$

in which $\boldsymbol{y} \in \mathbb{C}^{n\times 1}$ is the decoded received vector signal, $\boldsymbol{w} \in \mathbb{C}^{n\times 1}$ is complex Gaussian noise process with zero mean vector and covariance matrix given as $\sigma^2\boldsymbol{I}_n$, and h is the channel gain.

In [**?**], the authors have shown that the probability distribution of the energy statistic $\tilde{y} \triangleq \boldsymbol{y}^{\dagger}\boldsymbol{y}$ conditioned on the knowledge of h, in case that $\boldsymbol{s}$ is an M-PSK signal such that every symbol has the same probability of occurrence, $\mathbb{P}(s_n = s) = \frac{1}{M}$, is given as

$$p(\tilde{y}|h, H_1) = 1 - Q_n\left(\sqrt{\frac{2n|h|^2E_s}{\sigma^2}}, \sqrt{\frac{2\tilde{y}}{\sigma^2}}\right), \tag{3}$$

in which Q_n is the Marcum-Q function and E_s is the energy per symbol.

The pdf of $\tilde{y}$ can be written using the Law of Total Expectation

$$p(\tilde{y}|H_1) = \mathbb{E}\left[p(\tilde{y}|h, H_1)\right] = \int_{-\infty}^{+\infty} p(\tilde{y}|h, H_1)p(h)\ \mathrm{d}h. \tag{4}$$

Recall that the energy detection rule can be expressed as

$$d_\delta(\tilde{y}) = \begin{cases} 1, & \tilde{y} \geq \delta, \\ 0, & \tilde{y} < \delta, \end{cases} \tag{5}$$

in which δ is a strictly positive real number known as energy threshold, and $d_\delta(\tilde{y}) = j,\ j \in \{0, 1\}$ means that the detector has decided in favor of the hypothesis H_j.

As a result, the probabilities of false alarm and detection can be written as

$$p_f = 1 - p() \tag{6}$$
$$p_d = \tag{7}$$

B. Parameter Estimation in Free Space Optics

C. BER in Complex $\alpha - \mu$ Fading

IV. Conclusions

Acknowledgement

The authors would like to thank the Federal University of Campina Grande (UFCG) and the Institute for Advanced Studies in Communications (Iecom) for supporting this research.